



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'fpurge.3'

\$ man fpurge.3

FPURGE(3)

Linux Programmer's Manual

FPURGE(3)

NAME

fpurge, __fpurge - purge a stream

SYNOPSIS

```
/* unsupported */

#include <stdio.h>

int fpurge(FILE *stream);

/* supported */

#include <stdio.h>

#include <stdio_ext.h>

void __fpurge(FILE *stream);
```

DESCRIPTION

The function fpurge() clears the buffers of the given stream. For output streams this discards any unwritten output. For input streams this discards any input read from the underlying object but not yet obtained via getc(3); this includes any text pushed back via ungetc(3). See also fflush(3).

The function __fpurge() does precisely the same, but without returning a value.

RETURN VALUE

Upon successful completion fpurge() returns 0. On error, it returns -1 and sets errno appropriately.

ERRORS

EBADF stream is not an open stream.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?__fpurge() ? Thread safety ? MT-Safe race:stream ?

??

CONFORMING TO

These functions are nonstandard and not portable. The function fpurge() was introduced in 4.4BSD and is not available under Linux. The function __fpurge() was introduced in Solaris, and is present in glibc 2.1.95 and later.

NOTES

Usually it is a mistake to want to discard input buffers.

SEE ALSO

fflush(3), setbuf(3), stdio_ext(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

2017-09-15

FPURGE(3)