



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'gamemode-simulate-game.1'

\$ man gamemode-simulate-game.1

gamemode-simulate-game(1) gamemode-simulate-game man page gamemode-simulate-game(1)

NAME

gamemode-simulate-game - simulate a game using gamemode

SYNOPSIS

gamemode-simulate-game

DESCRIPTION

GameMode is a daemon/lib combo for Linux that allows games to request a set of optimizations be temporarily applied to the host OS.

The design has a clear cut abstraction between the host daemon and library (gamemode and libgamemode), and the client loaders (libgamemodeauto and gamemode_client.h) that allows for safe usage without worrying about whether the daemon is installed or running. This design also means that while the host library currently relies on systemd for exchanging messages with the daemon, it's entirely possible to implement other internals that still work with the same clients.

GameMode was designed primarily as a stop-gap solution to problems with the Intel and AMD CPU powersave or ondemand governors, but is intended to be expanded beyond just CPU governor states, as there are a wealth of automation tasks one might want to apply.

USAGE

The executable starts gamemode, sleeps for 10 seconds and stops it. It will exit with zero if everything works fine, else it will print an error and exit with one.

To use this with a CI you might need to start a dbus session by hand. This can be done with:

dbus-run-session -- gamemode-simulate-game

Note that this might output to stderr, even if it exits with zero.

SEE ALSO

gamemode(8), gamemode-run(1), dbus-run-session(1)

ABOUT

GameMode source can be found at <https://github.com/FeralInteractive/gamemode.git>

AUTHOR

Feral Interactive (linux-contact@feralinteractive.com)

1.6.1

26 May 2020

gamemode-simulate-game(1)