



Linux Ubuntu 22.4.5 Manual Pages on command 'gitlab-api-v4.1p'

\$ man gitlab-api-v4.1p

GITLAB-API-V4(1p) User Contributed Perl Documentation GITLAB-API-V4(1p)

NAME

gitlab-api-v4 - Command line interface to the GitLab API v4.

SYNOPSIS

Generally:

```
gitlab-api-v4 [<options>] <method> [<arg> ...] [<param>:<value> ...]
```

List all groups:

```
gitlab-api-v4 groups
```

List information about a project:

```
gitlab-api-v4 project <project_id>
```

Create an admin user:

```
gitlab-api-v4 create-user \  
  username:foo \  
  password:xxxxxxx \  
  email:user@example.com \  
  "name:Foo Smith" \  
  admin:1
```

CONFIGURING

You may configure this module with environment variables, command line options, and a configuration file. To setup the configuration file run:

```
gitlab-api-v4 configure
```

This will ask several interactive questions to help you configure this script. The

information, which may include GitLab authentication tokens, is stored in

"~/gitlab-api-v4.json".

Read more at [GitLab::API::v4::Config](#).

OPTIONS

url

--url=<url>

Sets "url" in [GitLab::API::v4](#).

access-token

--access-token=<token>

Sets "access_token" in [GitLab::API::v4](#).

private-token

--private-token=<token>

Sets "private_token" in [GitLab::API::v4](#).

retries

--retries=<count>

Sets "retries" in [GitLab::API::v4](#).

all

--all

-a

Retrieves all results when the results would normally be paged. See "all" in

[GitLab::API::v4::Paginator](#) for details.

pretty

--pretty

-p

Enables the "pretty" in JSON feature.

canonical

--canonical

-c

Enables the "canonical" in JSON feature.

API METHOD

<method>

The API method to call - one of the methods documented in "API METHODS" in

[GitLab::API::v4](#).

API ARGUMENTS

<arg> ...

Any arguments that the "API METHOD" requires.

API PARAMETERS

<param>:<value> ...

Any parameters that the "API METHOD" accepts.

access-level

access-level:guest

access-level:reporter

access-level:developer

access-level:master

access-level:owner

There are mappings setup for the various "access-level" parameters so that you can, for example, specify "access-level:guest" and it will be automatically converted to "access-level:10".

SUPPORT

See "SUPPORT" in GitLab::API::v4.

AUTHORS

See "AUTHORS" in GitLab::API::v4.

COPYRIGHT AND LICENSE

See "COPYRIGHT AND LICENSE" in GitLab::API::v4.

perl v5.30.0

2020-02-13

GITLAB-API-V4(1p)