



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

*Rocky Enterprise Linux 9.2 Manual Pages on command 'globfree.3'*

**\$ man globfree.3**

GLO

**glob, globfree - find pathnames matching a pattern, free memory from glob()**

## SYNOPSIS

```
#include <glob.h>

int glob(const char *pattern, int flags,
         int (*errfunc) (const char *epath, int eerrno),
         glob_t *pglob);

void globfree(glob_t *pglob);
```

## DESCRIPTION

The `glob()` function searches for all the pathnames matching pattern according to the rules used by the shell (see `glob(7)`). No tilde expansion or parameter substitution is done; if you want these, use `wordexp(3)`.

The `globfree()` function frees the dynamically allocated storage from an earlier call to `glob()`.

The results of a `glob()` call are stored in the structure pointed to by `pglob`. This structure is of type `glob_t` (declared in `<glob.h>`) and includes the following elements defined by POSIX.2 (more may be present as an extension):

```
typedef struct {  
    size_t gl_pathc; /* Count of paths matched so far */  
    char **gl_pathv; /* List of matched pathnames. */  
    size_t gl_offs; /* Slots to reserve in gl_pathv. */  
} glob_t;
```

Results are stored in dynamically allocated storage.

The argument flags is made up of the bitwise OR of zero or more the following symbolic constants, which modify the behavior of glob():

#### GLOB\_ERR

Return upon a read error (because a directory does not have read permission, for example). By default, glob() attempts carry on despite errors, reading all of the directories that it can.

#### GLOB\_MARK

Append a slash to each path which corresponds to a directory.

#### GLOB\_NOSORT

Don't sort the returned pathnames. The only reason to do this is to save process? ing time. By default, the returned pathnames are sorted.

#### GLOB\_DOOFFS

Reserve pglob->gl\_offs slots at the beginning of the list of strings in pglob->pathv. The reserved slots contain null pointers.

#### GLOB\_NOCHECK

If no pattern matches, return the original pattern. By default, glob() returns GLOB\_NOMATCH if there are no matches.

#### GLOB\_APPEND

Append the results of this call to the vector of results returned by a previous call to glob(). Do not set this flag on the first invocation of glob().

#### GLOB\_NOESCAPE

Don't allow backslash ('\') to be used as an escape character. Normally, a back? slash can be used to quote the following character, providing a mechanism to turn off the special meaning metacharacters.

flags may also include any of the following, which are GNU extensions and not defined by

POSIX.2:

#### GLOB\_PERIOD

Allow a leading period to be matched by metacharacters. By default, metacharacters can't match a leading period.

#### GLOB\_ALTDIRFUNC

Use alternative functions pglob->gl\_closedir, pglob->gl\_readdir, pglob->gl\_opendir, pglob->gl\_lstat, and pglob->gl\_stat for filesystem access instead of the normal li?

brary functions.

## GLOB\_BRACE

Expand csh(1) style brace expressions of the form {a,b}. Brace expressions can be nested. Thus, for example, specifying the pattern "{foo/{,cat,dog},bar}" would re? turn the same results as four separate glob() calls using the strings: "foo/", "foo/cat", "foo/dog", and "bar".

## GLOB\_NOMAGIC

If the pattern contains no metacharacters, then it should be returned as the sole matching word, even if there is no file with that name.

## GLOB\_TILDE

Carry out tilde expansion. If a tilde ('~') is the only character in the pattern, or an initial tilde is followed immediately by a slash ('/'), then the home directory of the caller is substituted for the tilde. If an initial tilde is followed by a username (e.g., "~andrea/bin"), then the tilde and username are substituted by the home directory of that user. If the username is invalid, or the home directory cannot be determined, then no substitution is performed.

## GLOB\_TILDE\_CHECK

This provides behavior similar to that of GLOB\_TILDE. The difference is that if the username is invalid, or the home directory cannot be determined, then instead of using the pattern itself as the name, glob() returns GLOB\_NOMATCH to indicate an error.

## GLOB\_ONLYDIR

This is a hint to glob() that the caller is interested only in directories that match the pattern. If the implementation can easily determine file-type information, then nondirectory files are not returned to the caller. However, the caller must still check that returned files are directories. (The purpose of this flag is merely to optimize performance when the caller is interested only in directories.)

If errfunc is not NULL, it will be called in case of an error with the arguments epath, a pointer to the path which failed, and errno, the value of errno as returned from one of the calls to opendir(3), readdir(3), or stat(2). If errfunc returns nonzero, or if GLOB\_ERR is set, glob() will terminate after the call to errfunc.

Upon successful return, pglob->gl\_pathc contains the number of matched pathnames and pglob->gl\_pathv contains a pointer to the list of pointers to matched pathnames. The list

of pointers is terminated by a null pointer.

It is possible to call `glob()` several times. In that case, the `GLOB_APPEND` flag has to be set in `flags` on the second and later invocations.

As a GNU extension, `pglob->gl_flags` is set to the flags specified, ored with `GLOB_MAGCHAR` if any metacharacters were found.

## RETURN VALUE

On successful completion, `glob()` returns zero. Other possible returns are:

## GLOB\_NOSPACE

for running out of memory,

## GLOB ABORTED

for a read error, and

GLOB NOMATCH

for no found matches.

## ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

?Interface ? Attribute ? Value ?

?glob() ? Thread safety ? MT-Unsafe race:utent env ?

? ? ? sig·AI RM timer locale ?

?globfree() ? Thread safety ? MT-Safe ?

In the above table, `utent` in `race:utent` signifies that if any of the functions set up

tent(3), getutent(3), or endutent(3) are used in parallel in different threads of a pro?

gram, then data races could occur. `glob()` calls those functions, so we use `race:utent` to

remind users

## INFORMING TO

POS

The structure elements `gl_pathc` and `gl_offs` are declared as `size_t` in glibc 2.1, as they

The `glob()` function may fail due to failure of underlying function calls, such as `mal?`  
`loc(3)` or `opendir(3)`. These will store their error code in `errno`.

## EXAMPLES

One example of use is the following code, which simulates typing

```
ls -l *.c ../*.c
```

in the shell:

```
glob_t globbuf;  
  
globbuf.gl_offs = 2;  
  
glob("*.c", GLOB_DOOFFS, NULL, &globbuf);  
  
glob("../*.c", GLOB_DOOFFS | GLOB_APPEND, NULL, &globbuf);  
  
globbuf.gl_pathv[0] = "ls";  
  
globbuf.gl_pathv[1] = "-l";  
  
execvp("ls", &globbuf.gl_pathv[0]);
```

## SEE ALSO

`ls(1)`, `sh(1)`, `stat(2)`, `exec(3)`, `fnmatch(3)`, `malloc(3)`, `opendir(3)`, `readdir(3)`, `wordexp(3)`,  
`glob(7)`

## COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.