



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'jnl.3'

\$ man jnl.3

J0(3)

Linux Programmer's Manual

J0(3)

NAME

j0, j0f, j0l, j1, j1f, j1l, jn, jnf, jnl - Bessel functions of the first kind

SYNOPSIS

```
#include <math.h>

double j0(double x);

double j1(double x);

double jn(int n, double x);

float j0f(float x);

float j1f(float x);

float jnf(int n, float x);

long double j0l(long double x);

long double j1l(long double x);
```

Link with -Im

Feature Test Macro Requirements for glibc (see [feature_test_macros\(7\)](#)):

i0(), i1(), in();

XOPEN SOURCE

/* Since glibc 2.19: */ DEFAULT_SOURCE

|| /* Glibc versions <= 2.19: */ SVID_SOURCE || BSD_SOURCE

`i0f(), i0l(), i1f(), i1l(), inf(), inl()`:

XOPEN SOURCE >= 600

|| (ISOC99 SOURCE && XOPEN SOURCE)

```
|| /* Since glibc 2.19: */ _DEFAULT_SOURCE
|| /* Glibc versions <= 2.19: */ _SVID_SOURCE || _BSD_SOURCE
```

DESCRIPTION

The `j0()` and `j1()` functions return Bessel functions of `x` of the first kind of orders 0 and 1, respectively. The `jn()` function returns the Bessel function of `x` of the first kind of order `n`.

The `j0f()`, `j1f()`, and `jnf()`, functions are versions that take and return float values.

The `j0l()`, `j1l()`, and `jnl()` functions are versions that take and return long double values.

RETURN VALUE

On success, these functions return the appropriate Bessel value of the first kind for `x`.

If `x` is a NaN, a NaN is returned.

If `x` is too large in magnitude, or the result underflows, a range error occurs, and the return value is 0.

ERRORS

See `math_error(7)` for information on how to determine whether an error has occurred when calling these functions.

The following errors can occur:

Range error: result underflow, or `x` is too large in magnitude
errno is set to ERANGE.

These functions do not raise exceptions for `fetestexcept(3)`.

ATTRIBUTES

For an explanation of the terms used in this section, see `attributes(7)`.

??

?Interface ? Attribute ? Value ?

??

?`j0()`, `j0f()`, `j0l()` ? Thread safety ? MT-Safe ?

??

?`j1()`, `j1f()`, `j1l()` ? Thread safety ? MT-Safe ?

??

?`jn()`, `jnf()`, `jnl()` ? Thread safety ? MT-Safe ?

??

The functions returning double conform to SVr4, 4.3BSD, POSIX.1-2001, and POSIX.1-2008.

The others are nonstandard functions that also exist on the BSDs.

BUGS

There are errors of up to 2e-16 in the values returned by `j0()`, `j1()`, and `jn()` for values of `x` between -8 and 8.

SEE ALSO

`y0(3)`

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

2020-12-21

`J0(3)`