



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'l2ping.1'

\$ man l2ping.1

L2PING(1)

Linux System Administration

L2PING(1)

NAME

I2ping - Send L2CAP echo request and receive answer

SYNOPSIS

l2ping [OPTIONS] bd_addr

DESCRIPTION

`l2ping(1)` sends a L2CAP echo request to the Bluetooth MAC address `bd_addr` given in dotted hex notation.

OPTIONS

-i <hciX>

The command is applied to device hciX, which must be the name of an installed Bluetooth device (X = 0, 1, 2, ...). If not specified, the command will be sent to the first available Bluetooth device.

-s size

The size of the data packets to be sent.

-c count

Send count number of packets then exit.

-t timeout

Wait timeout seconds for the response.

-d delay

Wait delay seconds between pings.

-f Kind of flood ping. Use with care! It reduces the delay time between packets to 0.

-r Reverse ping (gnip?). Send echo response instead of echo request.

-v Verify response payload is identical to request payload. It is not required for remote stacks to return the request payload, but most stacks do (including Bluez).

bd_addr

The Bluetooth MAC address to be pinged in dotted hex notation like
01:02:03:ab:cd:ef or 01:EF:cd:aB:02:03

RESOURCES

<http://www.bluez.org>

REPORTING BUGS

linux-bluetooth@vger.kernel.org

AUTHOR

Maxim Krasnyansky <maxk@qualcomm.com>, Marcel Holtmann <marcel@holtmann.org>, Nils Faerber <nils@kernelconcepts.de>, Adam Laurie <adam@algroup.co.uk>.

COPYRIGHT

Free use of this software is granted under the terms of the GNU Lesser General Public License (LGPL).

BlueZ

Jan 22, 2002

L2PING(1)