



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'make-first-existing-target.1'

\$ man make-first-existing-target.1

MAKE-FIRST-EXISTING-TARGET(1) User Contributed Perl Documentation MAKE-FIRST-EXISTING-TARGET(1)

NAME

make-first-existing-target - runs make on one of several targets

SYNOPSIS

make-first-existing-target [-c cmd] target1 [target2 ...] -- [make-options]

DESCRIPTION

The design of make(1) causes difficulty when you know that a Makefile probably has one of several standardized target names, and want build machinery to run exactly one of them, propagating any errors. make(1) will exit 2 if a target does not exist, but an existing target may also exit 2 due to some other failure. Makefiles cannot be reliably parsed to find targets by anything less Turing-complete than make, and make itself does not provide a way to enumerate the targets in a Makefile. It may not even be possible to enumerate the targets in a Makefile without executing part of it. (Proof of this is left as an exercise for the reader.)

This program avoids the problems described above, by attempting to call each specified target in turn, until it observes make actually doing something for one of them.

OPTIONS

-c cmd

This can be used to specify the make command to run. Default is "make".

EXIT STATUS

The exit status is 0 if at least one target existed and was successfully run, and nonzero otherwise.

AUTHOR

Joey Hess <joey@kitenet.net>

LICENSE

Same as GNU make.

SEE ALSO

make(1)

perl v5.18.2

2014-05-13

MAKE-FIRST-EXISTING-TARGET(1)