

MKDIR(1)

User Commands

MKDIR(1)

NAME

mkdir - make directories

SYNOPSIS

mkdir [OPTION]... DIRECTORY...

DESCRIPTION

Create the DIRECTORY(ies), if they do not already exist.

Mandatory arguments to long options are mandatory for short options too.

-m, --mode=MODE

set file mode (as in chmod), not a=rwx - umask

-p, --parents

no error if existing, make parent directories as needed, with their file modes unaffected by any -m option.

-v, --verbose

print a message for each created directory

default type

--context[=CTX]

like **-Z**, or if **CTX** is specified then set the **SELinux** or **SMACK** security context to **CTX**

--help display this help and exit

--version

output version information and exit

AUTHOR

Written by David MacKenzie.

REPORTING BUGS

GNU coreutils online help: [<https://www.gnu.org/software/coreutils/>](https://www.gnu.org/software/coreutils/)

Report any translation bugs to [<https://translationproject.org/team/>](https://translationproject.org/team/)

COPYRIGHT

Copyright ? 2023 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later [<https://gnu.org/licenses/gpl.html>](https://gnu.org/licenses/gpl.html).

This is free software: you are free to change and redistribute it.

There is NO WARRANTY, to the extent permitted by law.

Linux UBUNTU Manual Pages

mkdir(2)

Full documentation <<https://www.gnu.org/software/coreutils/mkdir>>

or available locally via: info '(coreutils) mkdir invocation'

GNU coreutils 9.4

June 2025

MKDIR(1)