



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'msgrcv.2'

\$ man msgrcv.2

MSGOP(2)

Linux Programmer's Manual

MSGOP(2)

NAME

msgrcv, msgsnd - System V message queue operations

SYNOPSIS

```
#include <sys/types.h>
#include <sys/ipc.h>
#include <sys/msg.h>
int msgsnd(int msqid, const void *msgp, size_t msgsz, int msgflg);
ssize_t msgrcv(int msqid, void *msgp, size_t msgsz, long msgtyp,
               int msgflg);
```

DESCRIPTION

The msgsnd() and msgrcv() system calls are used to send messages to, and receive messages from, a System V message queue. The calling process must have write permission on the message queue in order to send a message, and read permission to receive a message.

The msgp argument is a pointer to a caller-defined structure of the following general form:

```
struct msghdr {
    long mtype;    /* message type, must be > 0 */
    char mtext[1]; /* message data */
};
```

The mtext field is an array (or other structure) whose size is specified by msgsz, a non-negative integer value. Messages of zero length (i.e., no mtext field) are permitted.

The mtype field must have a strictly positive integer value. This value can be used by

the receiving process for message selection (see the description of `msgrecv()` below).

`msgsnd()`

The `msgsnd()` system call appends a copy of the message pointed to by `msgp` to the message queue whose identifier is specified by `msqid`.

If sufficient space is available in the queue, `msgsnd()` succeeds immediately. The queue capacity is governed by the `msg_qbytes` field in the associated data structure for the message queue. During queue creation this field is initialized to `MSGMNB` bytes, but this limit can be modified using `msgctl(2)`. A message queue is considered to be full if either of the following conditions is true:

- ? Adding a new message to the queue would cause the total number of bytes in the queue to exceed the queue's maximum size (the `msg_qbytes` field).

- ? Adding another message to the queue would cause the total number of messages in the queue to exceed the queue's maximum size (the `msg_qbytes` field). This check is necessary to prevent an unlimited number of zero-length messages being placed on the queue. Although such messages contain no data, they nevertheless consume (locked) kernel memory.

If insufficient space is available in the queue, then the default behavior of `msgsnd()` is to block until space becomes available. If `IPC_NOWAIT` is specified in `msgflg`, then the call instead fails with the error `EAGAIN`.

A blocked `msgsnd()` call may also fail if:

- ? the queue is removed, in which case the system call fails with `errno` set to `EIDRM`; or
- ? a signal is caught, in which case the system call fails with `errno` set to `EINTR`; see `signal(7)`. (`msgsnd()` is never automatically restarted after being interrupted by a signal handler, regardless of the setting of the `SA_RESTART` flag when establishing a signal handler.)

Upon successful completion the message queue data structure is updated as follows:

- ? `msg_lspid` is set to the process ID of the calling process.
- ? `msg_qnum` is incremented by 1.
- ? `msg_stime` is set to the current time.

`msgrecv()`

The `msgrecv()` system call removes a message from the queue specified by `msqid` and places it in the buffer pointed to by `msgp`.

The argument `msgsz` specifies the maximum size in bytes for the member `mtext` of the struc?

ture pointed to by the `msgp` argument. If the message text has length greater than `msgsz`, then the behavior depends on whether `MSG_NOERROR` is specified in `msgflg`. If `MSG_NOERROR` is specified, then the message text will be truncated (and the truncated part will be lost); if `MSG_NOERROR` is not specified, then the message isn't removed from the queue and the system call fails returning -1 with `errno` set to `E2BIG`.

Unless `MSG_COPY` is specified in `msgflg` (see below), the `msgtyp` argument specifies the type of message requested, as follows:

? If `msgtyp` is 0, then the first message in the queue is read.

? If `msgtyp` is greater than 0, then the first message in the queue of type `msgtyp` is read, unless `MSG_EXCEPT` was specified in `msgflg`, in which case the first message in the queue of type not equal to `msgtyp` will be read.

? If `msgtyp` is less than 0, then the first message in the queue with the lowest type less than or equal to the absolute value of `msgtyp` will be read.

The `msgflg` argument is a bit mask constructed by ORing together zero or more of the following flags:

`IPC_NOWAIT`

Return immediately if no message of the requested type is in the queue. The system call fails with `errno` set to `ENOMSG`.

`MSG_COPY` (since Linux 3.8)

Nondestructively fetch a copy of the message at the ordinal position in the queue specified by `msgtyp` (messages are considered to be numbered starting at 0).

This flag must be specified in conjunction with `IPC_NOWAIT`, with the result that, if there is no message available at the given position, the call fails immediately with the error `ENOMSG`. Because they alter the meaning of `msgtyp` in orthogonal ways, `MSG_COPY` and `MSG_EXCEPT` may not both be specified in `msgflg`.

The `MSG_COPY` flag was added for the implementation of the kernel checkpoint-restore facility and is available only if the kernel was built with the `CONFIG_CHECKPOINT_RESTORE` option.

`MSG_EXCEPT`

Used with `msgtyp` greater than 0 to read the first message in the queue with message type that differs from `msgtyp`.

`MSG_NOERROR`

To truncate the message text if longer than `msgsz` bytes.

If no message of the requested type is available and IPC_NOWAIT isn't specified in msgflg, the calling process is blocked until one of the following conditions occurs:

- ? A message of the desired type is placed in the queue.
- ? The message queue is removed from the system. In this case, the system call fails with errno set to EIDRM.
- ? The calling process catches a signal. In this case, the system call fails with errno set to EINTR. (msgrecv() is never automatically restarted after being interrupted by a signal handler, regardless of the setting of the SA_RESTART flag when establishing a signal handler.)

Upon successful completion the message queue data structure is updated as follows:

msg_lpid is set to the process ID of the calling process.

msg_qnum is decremented by 1.

msg_rtime is set to the current time.

RETURN VALUE

On failure both functions return -1 with errno indicating the error, otherwise msgsnd() returns 0 and msgrecv() returns the number of bytes actually copied into the mtext array.

ERRORS

When msgsnd() fails, errno will be set to one among the following values:

EACCES The calling process does not have write permission on the message queue, and does not have the CAP_IPC_OWNER capability in the user namespace that governs its IPC namespace.

EAGAIN The message can't be sent due to the msg_qbytes limit for the queue and IPC_NOWAIT was specified in msgflg.

EFAULT The address pointed to by msgp isn't accessible.

EIDRM The message queue was removed.

EINTR Sleeping on a full message queue condition, the process caught a signal.

EINVAL Invalid msqid value, or nonpositive mtype value, or invalid msgsqsz value (less than 0 or greater than the system value MSGMAX).

ENOMEM The system does not have enough memory to make a copy of the message pointed to by msgp.

When msgrecv() fails, errno will be set to one among the following values:

E2BIG The message text length is greater than msgsqsz and MSG_NOERROR isn't specified in msgflg.

EACCES The calling process does not have read permission on the message queue, and does not have the CAP_IPC_OWNER capability in the user namespace that governs its IPC namespace.

EFAULT The address pointed to by msgp isn't accessible.

EIDRM While the process was sleeping to receive a message, the message queue was removed.

EINTR While the process was sleeping to receive a message, the process caught a signal; see signal(7).

EINVAL msqid was invalid, or msgsz was less than 0.

EINVAL (since Linux 3.14)

msgflg specified MSG_COPY, but not IPC_NOWAIT.

EINVAL (since Linux 3.14)

msgflg specified both MSG_COPY and MSG_EXCEPT.

ENOMSG IPC_NOWAIT was specified in msgflg and no message of the requested type existed on the message queue.

ENOMSG IPC_NOWAIT and MSG_COPY were specified in msgflg and the queue contains less than msgtyp messages.

ENOSYS (since Linux 3.8)

Both MSG_COPY and IPC_NOWAIT were specified in msgflg, and this kernel was config? ured without CONFIG_CHECKPOINT_RESTORE.

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, SVr4.

The MSG_EXCEPT and MSG_COPY flags are Linux-specific; their definitions can be obtained by defining the _GNU_SOURCE feature test macro.

NOTES

The inclusion of <sys/types.h> and <sys/ipc.h> isn't required on Linux or by any version of POSIX. However, some old implementations required the inclusion of these header files, and the SVID also documented their inclusion. Applications intended to be portable to such old systems may need to include these header files.

The msgp argument is declared as struct msbuf * in glibc 2.0 and 2.1. It is declared as void * in glibc 2.2 and later, as required by SUSv2 and SUSv3.

The following limits on message queue resources affect the msgsnd() call:

MSGMAX Maximum size of a message text, in bytes (default value: 8192 bytes). On Linux, this limit can be read and modified via /proc/sys/kernel/msgmax.

MSGMNB Maximum number of bytes that can be held in a message queue (default value: 16384

bytes). On Linux, this limit can be read and modified via /proc/sys/kernel/msgmnb.

A privileged process (Linux: a process with the CAP_SYS_RESOURCE capability) can increase the size of a message queue beyond MSGMNB using the msgctl(2) IPC_SET op? eration.

The implementation has no intrinsic system-wide limits on the number of message headers

(MSGTQL) and the number of bytes in the message pool (MSGPOOL).

BUGS

In Linux 3.13 and earlier, if msgrcv() was called with the MSG_COPY flag, but without IPC_NOWAIT, and the message queue contained less than msqtyp messages, then the call would block until the next message is written to the queue. At that point, the call would re? turn a copy of the message, regardless of whether that message was at the ordinal position msqtyp. This bug is fixed in Linux 3.14.

Specifying both MSG_COPY and MSC_EXCEPT in msgflg is a logical error (since these flags impose different interpretations on msqtyp). In Linux 3.13 and earlier, this error was not diagnosed by msgrcv(). This bug is fixed in Linux 3.14.

EXAMPLES

The program below demonstrates the use of msgsnd() and msgrcv().

The example program is first run with the -s option to send a message and then run again with the -r option to receive a message.

The following shell session shows a sample run of the program:

```
$ ./a.out -s
sent: a message at Wed Mar 4 16:25:45 2015
$ ./a.out -r
message received: a message at Wed Mar 4 16:25:45 2015
```

Program source

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <time.h>
#include <unistd.h>
#include <errno.h>
#include <sys/types.h>
```

```

#include <sys/ipc.h>
#include <sys/msg.h>

struct msgbuf {
    long mtype;
    char mtext[80];
};

static void
usage(char *prog_name, char *msg)
{
    if (msg != NULL)
        fputs(msg, stderr);

    fprintf(stderr, "Usage: %s [options]\n", prog_name);
    fprintf(stderr, "Options are:\n");
    fprintf(stderr, "-s      send message using msgsnd()\n");
    fprintf(stderr, "-r      read message using msgrcv()\n");
    fprintf(stderr, "-t      message type (default is 1)\n");
    fprintf(stderr, "-k      message queue key (default is 1234)\n");
    exit(EXIT_FAILURE);
}

static void
send_msg(int qid, int msgtype)
{
    struct msgbuf msg;
    time_t t;

    msg.mtype = msgtype;
    time(&t);
    snprintf(msg.mtext, sizeof(msg.mtext), "a message at %s",
             ctime(&t));
    if (msgsnd(qid, &msg, sizeof(msg.mtext),
               IPC_NOWAIT) == -1) {
        perror("msgsnd error");
        exit(EXIT_FAILURE);
    }
}

```

```

printf("sent: %s\n", msg.mtext);

}

static void
get_msg(int qid, int msgtype)
{
    struct msgbuf msg;

    if (msgrecv(qid, &msg, sizeof(msg.mtext), msgtype,
                MSG_NOERROR | IPC_NOWAIT) == -1) {
        if (errno != ENOMSG) {
            perror("msgrecv");
            exit(EXIT_FAILURE);
        }
        printf("No message available for msgrecv()\n");
    } else
        printf("message received: %s\n", msg.mtext);
}

int
main(int argc, char *argv[])
{
    int qid, opt;

    int mode = 0;          /* 1 = send, 2 = receive */

    int msgtype = 1;

    int msgkey = 1234;

    while ((opt = getopt(argc, argv, "srt:k:")) != -1) {
        switch (opt) {
            case 's':
                mode = 1;
                break;
            case 'r':
                mode = 2;
                break;
            case 't':
                msgtype = atoi(optarg);
        }
    }
}

```

```

if (msgtype <= 0)
    usage(argv[0], "-t option must be greater than 0\n");
break;

case 'k':
    msgkey = atoi(optarg);
break;

default:
    usage(argv[0], "Unrecognized option\n");
}

}

if (mode == 0)
    usage(argv[0], "must use either -s or -r option\n");

qid = msgget(msgkey, IPC_CREAT | 0666);

if (qid == -1) {
    perror("msgget");
    exit(EXIT_FAILURE);
}

if (mode == 2)
    get_msg(qid, msgtype);
else
    send_msg(qid, msgtype);
exit(EXIT_SUCCESS);
}

```

SEE ALSO

`msgctl(2)`, `msgget(2)`, `capabilities(7)`, `mq_overview(7)`, `sysvipc(7)`

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.