



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'newuidmap.1'

\$ man newuidmap.1

NEWUIDMAP(1)

User Commands

NEWUIDMAP(1)

NAME

newuidmap - set the uid mapping of a user namespace

SYNOPSIS

newuidmap pid uid loweruid count [uid loweruid count [...]]

DESCRIPTION

The newuidmap sets /proc/[pid]/uid_map based on its command line arguments and the uids allowed in /etc/subuid. Note that the root user is not exempted from the requirement for a valid /etc/subuid entry.

After the pid argument, newuidmap expects sets of 3 integers:

uid

Beginning of the range of UIDs inside the user namespace.

loweruid

Beginning of the range of UIDs outside the user namespace.

count

Length of the ranges (both inside and outside the user namespace).

newuidmap verifies that the caller is the owner of the process indicated by pid and that for each of the above sets, each of the UIDs in the range [loweruid, loweruid+count] is allowed to the caller according to /etc/subuid before setting /proc/[pid]/uid_map.

Note that newuidmap may be used only once for a given process.

OPTIONS

There currently are no options to the newuidmap command.

FILES

/etc/subuid

List of user's subordinate user IDs.

/proc/[pid]/uid_map

Mapping of uids from one between user namespaces.

SEE ALSO

login.defs(5), newusers(8), subuid(5), useradd(8), usermod(8), userdel(8).

shadow-utils 4.8.1

02/06/2024

NEWUIDMAP(1)