Rocky Enterprise Linux 9.2 Manual Pages on command 'npm-edit.1'

$ man npm-edit.1

NPM-EDIT(1)   NPM-EDIT(1)

NAME

   npm-edit - Edit an installed package

 Synopsis

    npm edit <pkg>

   Note: This command is unaware of workspaces.

 Description

   Selects a dependency in the current project and opens the package folder in the default

   editor (or whatever you've configured as the npm editor config -- see npm-config npm-con?

   fig).

   After it has been edited, the package is rebuilt so as to pick up any changes in compiled

   packages.

   For instance, you can do npm install connect to install connect into your package, and

   then npm edit connect to make a few changes to your locally installed copy.

 Configuration

   <!-- AUTOGENERATED CONFIG DESCRIPTIONS START --> <!-- automatically generated, do not edit

   manually --> <!-- see lib/utils/config/definitions.js -->

 editor

   ? Default: The EDITOR or VISUAL environment variables, or 'notepad.exe' on Windows, or

    'vim' on Unix systems

   ? Type: String

   The command to run for npm edit and npm config edit. <!-- automatically generated, do not

   edit manually --> <!-- see lib/utils/config/definitions.js -->

<!-- AUTOGENERATED CONFIG DESCRIPTIONS END -->

See Also

- ? npm help folders

- ? npm help explore

- ? npm help install

- ? npm help config

- ? npm help npmrc

undefined NaN   NPM-EDIT(1)