



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'npm-install-ci-test.1'***

**\$ man npm-install-ci-test.1**

NPM-INSTALL-CI-TEST(1)

NPM-INSTALL-CI-TEST(1)

### NAME

npm-install-ci-test - Install a project with a clean slate and run tests

### Synopsis

npm install-ci-test

alias: npm cit

### Description

This command runs npm ci followed immediately by npm test.

### Configuration

<!-- AUTOGENERATED CONFIG DESCRIPTIONS START --> <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

#### audit

? Default: true

? Type: Boolean

When "true" submit audit reports alongside the current npm command to the default registry

and all registries configured for scopes. See the documentation for npm help audit for de?

tails on what is submitted. <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

#### ignore-scripts

? Default: false

? Type: Boolean

If true, npm does not run scripts specified in package.json files.

Note that commands explicitly intended to run a particular script, such as npm start, npm

stop, npm restart, npm test, and npm run-script will still run their intended script if ignore-scripts is set, but they will not run any pre- or post-scripts. <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js --> script-shell

? Default: '/bin/sh' on POSIX systems, 'cmd.exe' on Windows

? Type: null or String

The shell to use for scripts run with the npm exec, npm run and npm init <pkg> commands.

<!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

<!-- AUTOGENERATED CONFIG DESCRIPTIONS END -->

## See Also

? npm help install-test

? npm help ci

? npm help test

undefined NaN

NPM-INSTALL-CI-TEST(1)