



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'npm-org.1'

\$ man npm-org.1

NPM-ORG(1)

NPM-ORG(1)

NAME

npm-org - Manage orgs

Synopsis

npm org set <orgname> <username> [developer | admin | owner]

npm org rm <orgname> <username>

npm org ls <orgname> [<username>]

Note: This command is unaware of workspaces.

Example

Add a new developer to an org:

\$ npm org set my-org @mx-smith

Add a new admin to an org (or change a developer to an admin):

\$ npm org set my-org @mx-santos admin

Remove a user from an org:

\$ npm org rm my-org mx-santos

List all users in an org:

\$ npm org ls my-org

List all users in JSON format:

\$ npm org ls my-org --json

See what role a user has in an org:

\$ npm org ls my-org @mx-santos

Description

You can use the npm org commands to manage and view users of an organization. It supports

adding and removing users, changing their roles, listing them, and finding specific ones and their roles.

Configuration

<!-- AUTOGENERATED CONFIG DESCRIPTIONS START --> <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

registry

? Default: "https://registry.npmjs.org/"

? Type: URL

The base URL of the npm registry. <!-- automatically generated, do not edit manually -->

<!-- see lib/utils/config/definitions.js -->

otp

? Default: null

? Type: null or String

This is a one-time password from a two-factor authenticator. It's needed when publishing or changing package permissions with npm access.

If not set, and a registry response fails with a challenge for a one-time password, npm will prompt on the command line for one. <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

json

? Default: false

? Type: Boolean

Whether or not to output JSON data, rather than the normal output.

? In npm pkg set it enables parsing set values with JSON.parse() before saving them to your package.json.

Not supported by all npm commands. <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

parseable

? Default: false

? Type: Boolean

Output parseable results from commands that write to standard output. For npm search, this will be tab-separated table format. <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

<!-- AUTOGENERATED CONFIG DESCRIPTIONS END -->

See Also

? npm help using orgs

? Documentation on npm Orgs <https://docs.npmjs.com/orgs/>

undefined NaN

NPM-ORG(1)