



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'npm-profile.1'

\$ man npm-profile.1

NPM-PROFILE(1)

NPM-PROFILE(1)

NAME

npm-profile - Change settings on your registry profile

Synopsis

npm profile get [--json|--parseable] [<property>]

npm profile set [--json|--parseable] <property> <value>

npm profile set password

npm profile enable-2fa [auth-and-writes|auth-only]

npm profile disable-2fa

Note: This command is unaware of workspaces.

Description

Change your profile information on the registry. Note that this command depends on the registry implementation, so third-party registries may not support this interface.

? npm profile get [<property>]: Display all of the properties of your profile, or one or more specific properties. It looks like:

+-----+-----+

| name | example |

+-----+-----+

| email | me@example.com (verified) |

+-----+-----+

| two factor auth | auth-and-writes |

+-----+-----+

| fullname | Example User |

```

+-----+
| homepage      |           |
+-----+
| freenode      |           |
+-----+
| twitter       |           |
+-----+
| github         |           |
+-----+
| created        | 2015-02-26T01:38:35.892Z |
+-----+
| updated        | 2017-10-02T21:29:45.922Z |
+-----+

```

? npm profile set <property> <value>: Set the value of a profile property. You can set the following properties this way: email, fullname, homepage, freenode, twitter, github

? npm profile set password: Change your password. This is interactive, you'll be prompted for your current password and a new password. You'll also be prompted for an OTP if you have two-factor authentication enabled.

? npm profile enable-2fa [auth-and-writes|auth-only]: Enables two-factor authentication.

Defaults to auth-and-writes mode. Modes are:

? auth-only: Require an OTP when logging in or making changes to your account's authentication. The OTP will be required on both the website and the command line.

? auth-and-writes: Requires an OTP at all the times auth-only does, and also requires one when publishing a module, setting the latest dist-tag, or changing access via npm access and npm owner.

? npm profile disable-2fa: Disables two-factor authentication.

Details

Some of these commands may not be available on non npmjs.com registries.

Configuration

```
<!-- AUTOGENERATED CONFIG DESCRIPTIONS START --> <!-- automatically generated, do not edit
manually --> <!-- see lib/utils/config/definitions.js -->
registry
```

? Default: "https://registry.npmjs.org/"

? Type: URL

The base URL of the npm registry. <!-- automatically generated, do not edit manually -->

<!-- see lib/utils/config/definitions.js -->

json

? Default: false

? Type: Boolean

Whether or not to output JSON data, rather than the normal output.

? In npm pkg set it enables parsing set values with JSON.parse() before saving them to your package.json.

Not supported by all npm commands. <!-- automatically generated, do not edit manually -->

<!-- see lib/utils/config/definitions.js -->

parseable

? Default: false

? Type: Boolean

Output parseable results from commands that write to standard output. For npm search, this

will be tab-separated table format. <!-- automatically generated, do not edit manually -->

--> <!-- see lib/utils/config/definitions.js -->

otp

? Default: null

? Type: null or String

This is a one-time password from a two-factor authenticator. It's needed when publishing or changing package permissions with npm access.

If not set, and a registry response fails with a challenge for a one-time password, npm will prompt on the command line for one. <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

<!-- AUTOGENERATED CONFIG DESCRIPTIONS END -->

See Also

? npm help adduser

? npm help registry

? npm help config

? npm help npmrc

? npm help owner

? npm help whoami

? npm help token

undefined NaN

NPM-PROFILE(1)