



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'npm-restart.1'

\$ man npm-restart.1

NPM-RESTART(1)

NPM-RESTART(1)

NAME

npm-restart - Restart a package

Synopsis

npm restart [-- <args>]

Description

This restarts a project. It is equivalent to running npm run-script restart.

If the current project has a "restart" script specified in package.json, then the following scripts will be run:

1. prerestart
2. restart
3. postrestart

If it does not have a "restart" script specified, but it does have stop and/or start scripts, then the following scripts will be run:

1. prerestart
2. prestop
3. stop
4. poststop
5. prestart
6. start
7. poststart
8. postrestart

<!-- AUTOGENERATED CONFIG DESCRIPTIONS START --> <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

ignore-scripts

? Default: false

? Type: Boolean

If true, npm does not run scripts specified in package.json files.

Note that commands explicitly intended to run a particular script, such as npm start, npm stop, npm restart, npm test, and npm run-script will still run their intended script if ignore-scripts is set, but they will not run any pre- or post-scripts. <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

script-shell

? Default: '/bin/sh' on POSIX systems, 'cmd.exe' on Windows

? Type: null or String

The shell to use for scripts run with the npm exec, npm run and npm init <pkg> commands.

<!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

<!-- AUTOGENERATED CONFIG DESCRIPTIONS END -->

See Also

? npm help run-script

? npm help scripts

? npm help test

? npm help start

? npm help stop

? npm help restart

undefined NaN

NPM-RESTART(1)