



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'openssl-srp.1ssl'

\$ man openssl-srp.1ssl

OPENSSL-SRP(1SSL) OpenSSL OPENSSL-SRP(1SSL)

NAME

openssl-srp - maintain SRP password file

SYNOPSIS

openssl srp [-help] [-verbose] [-add] [-modify] [-delete] [-list] [-name section]
[-srpfile file] [-gn identifier] [-userinfo text] [-passin arg] [-passout arg] [-engine
id] [-rand files] [-writerand file] [-provider name] [-provider-path path] [-propquery
propq] [-config configfile] [user ...]

DESCRIPTION

This command is deprecated. It is used to maintain an SRP (secure remote password) file.

At most one of the -add, -modify, -delete, and -list options can be specified. These options take zero or more usernames as parameters and perform the appropriate operation on the SRP file. For -list, if no user is given then all users are displayed.

The configuration file to use, and the section within the file, can be specified with the -config and -name flags, respectively.

OPTIONS

-help

Display an option summary.

-verbose

Generate verbose output while processing.

-add

Add a user and SRP verifier.

-modify

Modify the SRP verifier of an existing user.

-delete

Delete user from verifier file.

-list

List users.

-name

The particular SRP definition to use.

-srpvfile file

If the config file is not specified, -srpvfile can be used to specify the file to operate on.

-gn Specifies the g and N values, using one of the strengths defined in IETF RFC 5054.

-userinfo

specifies additional information to add when adding or modifying a user.

-passin arg, -passout arg

The password source for the input and output file. For more information about the format of arg see openssl-passphrase-options(1).

-engine id

See "Engine Options" in openssl(1). This option is deprecated.

-rand files, -writerand file

See "Random State Options" in openssl(1) for details.

-provider name

-provider-path path

-propquery propq

See "Provider Options" in openssl(1), provider(7), and property(7).

-config configfile

See "Configuration Option" in openssl(1).

[-rand files] [-writerand file]

HISTORY

The -engine option was deprecated in OpenSSL 3.0.

COPYRIGHT

Copyright 2017-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source

distribution or at <<https://www.openssl.org/source/license.html>>.

3.0.2

2024-02-16

OPENSSL-SRP(1SSL)