



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'padsp.1'***

**\$ man padsp.1**

padsp(1) General Commands Manual padsp(1)

#### **NAME**

padsp - PulseAudio OSS Wrapper

#### **SYNOPSIS**

padsp [options] PROGRAM [ARGUMENTS ...]

padsp -h

#### **DESCRIPTION**

padsp starts the specified program and redirects its access to OSS compatible audio devices (/dev/dsp and auxiliary devices) to a PulseAudio sound server.

padsp uses the \$LD\_PRELOAD environment variable that is interpreted by ld.so(8) and thus does not work for SUID binaries and statically built executables.

Equivalent to using padsp is starting an application with \$LD\_PRELOAD set to libpulsedsp.so

#### **OPTIONS**

**-h | --help**

Show help.

**-s SERVER**

Set the PulseAudio server to connect to.

**-n NAME**

The client application name that shall be passed to the server when connecting.

**-m NAME**

The stream name that shall be passed to the server when creating a stream.

**-M** Disable /dev/mixer emulation.

**-S** Disable /dev/sndstat emulation.

**-D** Disable /dev/dsp emulation.

**-d** Enable debug output.

## AUTHORS

The PulseAudio Developers <pulseaudio-discuss (at) lists (dot) freedesktop (dot) org>;

PulseAudio is available from <http://pulseaudio.org/>

## SEE ALSO

[pulseaudio\(1\)](#), [pasuspender\(1\)](#), [ld.so\(8\)](#)

Manuals

User

[padsp\(1\)](#)