



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'papersize.5'

\$ man *pagesize.5*

PAPER SIZE(5)

File Formats Manual

PAPER SIZE(5)

NAME

pagesize - specify preferred paper size

SYNOPSIS

/etc/paper size

DESCRIPTION

The *pagesize* file is used to specify the preferred paper size to use by available commands and programs generating documents.

The format of this file is extremely simple: whitespace and anything starting with `#' is ignored, and the name of the paper is the first string found; the case in the name of the paper does not import (see CAVEATS section however).

PAPER NAMES

The following names are commonly understood by programs: a3, a4, a5, b5, letter, legal, executive, note and 11x17.

Additional paper names that one may encounter are: a0, a1, a2, a6, a7, a8, a9, a10, b0, b1, b2, b3, b4, tabloid, statement, note, halfletter, halfexecutive, folio, quarto, ledger, archA, archB, archC, archD, archE, flsa, flse, csheet, dsheet, esheet and 10x14.

The value of the *pagesize* file can be overridden by looking in order at the PAPER SIZE environment variable, then at the contents of the file specified by the PAPER CONF environment variable. If the *pagesize* file does not exist, programs using the paper library default to using letter as a fall-back value

CAVEATS

This manual page documents the format of the *pagesize* file that is read by the libpaper

library. Some programs that read this file do not yet use the library and may have trouble ignoring whitespace and comments in the file; they may also require that the paper names use a specific capitalization.

DOCUMENTATION

Yves Arrouye <arrouye@debian.org>

SEE ALSO

paperconf(1)

paperconfig(8)

PAPERSIZE(5)