



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'pdfdetach.1'***

**\$ man pdfdetach.1**

pdfdetach(1)

General Commands Manual

pdfdetach(1)

#### **NAME**

pdfdetach - Portable Document Format (PDF) document embedded file extractor (version 3.03)

#### **SYNOPSIS**

pdfdetach [options] [PDF-file]

#### **DESCRIPTION**

Pdfdetach lists or extracts embedded files (attachments) from a Portable Document Format (PDF) file.

#### **OPTIONS**

Some of the following options can be set with configuration file commands. These are listed in square brackets with the description of the corresponding command line option.

**-list** List all of the embedded files in the PDF file. File names are converted to the text encoding specified by the "-enc" switch.

**-save number**

Save the specified embedded file. By default, this uses the file name associated with the embedded file (as printed by the "-list" switch); the file name can be changed with the "-o" switch.

**-savefile filename**

Save the specified embedded file. By default, this uses the file name associated with the embedded file (as printed by the "-list" switch); the file name can be changed with the "-o" switch.

**-saveall**

Save all of the embedded files. This uses the file names associated with the em?

bedded files (as printed by the "-list" switch). By default, the files are saved in the current directory; this can be changed with the "-o" switch.

#### **-o path**

Set the file name used when saving an embedded file with the "-save" switch, or the directory used by "-saveall".

#### **-enc encoding-name**

Sets the encoding to use for text output (embedded file names). This defaults to "UTF-8".

#### **-opw password**

Specify the owner password for the PDF file. Providing this will bypass all security restrictions.

#### **-upw password**

Specify the user password for the PDF file.

**-v** Print copyright and version information.

**-h** Print usage information. (-help and --help are equivalent.)

## **EXIT CODES**

The Xpdf tools use the following exit codes:

0 No error.

1 Error opening a PDF file.

2 Error opening an output file.

3 Error related to PDF permissions.

99 Other error.

## **AUTHOR**

The pdfinfo software and documentation are copyright 1996-2011 Glyph & Cog, LLC.

## **SEE ALSO**

[pdffonts\(1\)](#), [pdfimages\(1\)](#), [pdfinfo\(1\)](#), [pdftocairo\(1\)](#), [pdftohtml\(1\)](#), [pdftoppm\(1\)](#),

[pdftops\(1\)](#), [pdftotext\(1\)](#) [pdfseparate\(1\)](#), [pdfsig\(1\)](#), [pdfunite\(1\)](#)