



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'podman-network-exists.1'***

**\$ man podman-network-exists.1**

podman-network-exists(1)()

podman-network-exists(1)()

#### **NAME**

podman-network-exists - Check if the given network exists

#### **SYNOPSIS**

podman network exists network

#### **DESCRIPTION**

podman network exists checks if a network exists. The Name or ID of the network may be used as input. Podman will return an exit code of 0 when the network is found. A 1 will be returned otherwise. An exit code of 125 indicates there was another issue.

#### **OPTIONS**

--help, -h

Print usage statement

#### **EXAMPLE**

Check if a network called net1 exists (the network does actually exist).

```
$ podman network exists net1
```

```
$ echo $?
```

```
0
```

```
$
```

Check if an network called webbackend exists (the network does not actually exist).

```
$ podman network exists webbackend
```

```
$ echo $?
```

```
1
```

```
$
```

## SEE ALSO

`podman(1)`, `podman-network-create(1)`, `podman-network-rm(1)`

## HISTORY

January 2021, Originally compiled by Paul Holzinger <paul.holzinger@web.de>

`podman-network-exists(1)()`