



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'podman-network-inspect.1'

\$ man podman-network-inspect.1

podman-network-inspect(1)() podman-network-inspect(1)()

NAME

podman-network-inspect - Displays the raw CNI network configuration for one or more net?
works

SYNOPSIS

podman network inspect [options] [network ...]

DESCRIPTION

Display the raw (JSON format) network configuration.

OPTIONS

--format, -f

Pretty-print networks to JSON or using a Go template.

EXAMPLE

Inspect the default podman network

```
# podman network inspect podman
```

```
[{  
  "cniVersion": "0.3.0",  
  "name": "podman",  
  "plugins": [  
    {  
      "type": "bridge",  
      "bridge": "cni0",  
      "isGateway": true,  
      "ipMasq": true,
```

```

    "ipam": {
      "type": "host-local",
      "subnet": "10.88.1.0/24",
      "routes": [
        { "dst": "0.0.0.0/0" }
      ]
    }
  },
  {
    "type": "portmap",
    "capabilities": {
      "portMappings": true
    }
  }
]
}
]

# podman network inspect podman --format '{{(index .plugins 0).ipam.ranges}}'
[[map[gateway:10.88.0.1 subnet:10.88.0.0/16]]

```

SEE ALSO

podman(1), podman-network(1), podman-network-ls(1)

HISTORY

August 2019, Originally compiled by Brent Baude bbaude@redhat.com [?mailto:bbaude@redhat.com?](mailto:bbaude@redhat.com)

podman-network-inspect(1)