



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'regerror.3'

\$ man regerror.3

REGEX(3) Linux Programmer's Manual

REGEX(3)

NAME

`regcomp`, `regexec`, `regerror`, `regfree` - POSIX regex functions

SYNOPSIS

```
#include <regex.h>

int regcomp(regex_t *preg, const char *regex, int cflags);

int regexec(const regex_t *preg, const char *string, size_t nmatch,
            regmatch_t pmatch[], int eflags);

size_t regerror(int errcode, const regex_t *preg, char *errbuf,
                size_t errbuf_size);

void regfree(regex_t *preg);
```

DESCRIPTION

POSIX regex compiling

`regcomp()` is used to compile a regular expression into a form that is suitable for subsequent `regexec()` searches.

`regcomp()` is supplied with `preg`, a pointer to a pattern buffer storage area; `regex`, a pointer to the null-terminated string and `cflags`, flags used to determine the type of compilation.

All regular expression searching must be done via a compiled pattern buffer, thus `regexec()` must always be supplied with the address of a `regcomp()` initialized pattern buffer.

cflags is the bitwise-or of zero or more of the following:

Use POSIX Extended Regular Expression syntax when interpreting regex. If not set, POSIX Basic Regular Expression syntax is used.

REG_ICASE

Do not differentiate case. Subsequent `regexec()` searches using this pattern buffer will be case insensitive.

REG_NOSUB

Do not report position of matches. The `nmatch` and `pmatch` arguments to `regexec()` are ignored if the pattern buffer supplied was compiled with this flag set.

REG_NEWLINE

Match-any-character operators don't match a newline.

A nonmatching list (`[^...]`) not containing a newline does not match a newline.

Match-beginning-of-line operator (`^`) matches the empty string immediately after a newline, regardless of whether `eflags`, the execution flags of `regexec()`, contains

`REG_NOTBOL`.

Match-end-of-line operator (`$`) matches the empty string immediately before a new? line, regardless of whether `eflags` contains `REG_NOTEOL`.

POSIX regex matching

`regexec()` is used to match a null-terminated string against the precompiled pattern `buf`? `fer`, `preg`. `nmatch` and `pmatch` are used to provide information regarding the location of any matches. `eflags` is the bitwise-or of zero or more of the following flags:

REG_NOTBOL

The match-beginning-of-line operator always fails to match (but see the compilation flag `REG_NEWLINE` above). This flag may be used when different portions of a string are passed to `regexec()` and the beginning of the string should not be interpreted as the beginning of the line.

REG_NOTEOL

The match-end-of-line operator always fails to match (but see the compilation flag `REG_NEWLINE` above).

REG_STARTEND

Use `pmatch[0]` on the input string, starting at byte `pmatch[0].rm_so` and ending be? fore byte `pmatch[0].rm_eo`. This allows matching embedded NUL bytes and avoids a `strlen(3)` on large strings. It does not use `nmatch` on input, and does not change `REG_NOTBOL` or `REG_NEWLINE` processing. This flag is a BSD extension, not present in

POSIX.

Byte offsets

Unless REG_NOSUB was set for the compilation of the pattern buffer, it is possible to obtain match addressing information. pmatch must be dimensioned to have at least nmatch elements. These are filled in by regexec() with substring match addresses. The offsets of the subexpression starting at the *i*th open parenthesis are stored in pmatch[i]. The entire regular expression's match addresses are stored in pmatch[0]. (Note that to return the offsets of *N* subexpression matches, nmatch must be at least *N*+1.) Any unused structure elements will contain the value -1.

The regmatch_t structure which is the type of pmatch is defined in <regex.h>.

```
typedef struct {  
    regoff_t rm_so;  
    regoff_t rm_eo;  
} regmatch_t;
```

Each rm_so element that is not -1 indicates the start offset of the next largest substring match within the string. The relative rm_eo element indicates the end offset of the match, which is the offset of the first character after the matching text.

POSIX error reporting

regerror() is used to turn the error codes that can be returned by both regcomp() and regexec() into error message strings.

regerror() is passed the error code, errcode, the pattern buffer, preg, a pointer to a character string buffer, errbuf, and the size of the string buffer, errbuf_size. It returns the size of the errbuf required to contain the null-terminated error message string.

If both errbuf and errbuf_size are nonzero, errbuf is filled in with the first errbuf_size - 1 characters of the error message and a terminating null byte ('\0').

POSIX pattern buffer freeing

Supplying regfree() with a precompiled pattern buffer, preg will free the memory allocated to the pattern buffer by the compiling process, regcomp().

RETURN VALUE

regcomp() returns zero for a successful compilation or an error code for failure.

regexec() returns zero for a successful match or REG_NOMATCH for failure.

ERRORS

The following errors can be returned by regcomp():

?Interface	? Attribute	? Value	?
??			
?regcomp(), regexec() ? Thread safety ? MT-Safe locale ?			
??			
?regerror()	? Thread safety	? MT-Safe env	?
??			
?regfree()	? Thread safety	? MT-Safe	?
??			

CONFORMING TO

POSIX.1-2001, POSIX.1-2008.

EXAMPLES

```
#include <stdint.h>
#include <stdio.h>
#include <stdlib.h>
#include <regex.h>

#define ARRAY_SIZE(arr) (sizeof((arr)) / sizeof((arr)[0]))

static const char *const str =
    "1) John Driverhacker;\n2) John Doe;\n3) John Foo;\n";

static const char *const re = "John.*o";

int main(void)
{
    static const char *s = str;
    regex_t regex;
    regmatch_t pmatch[1];
    regoff_t off, len;
    if (regcomp(&regex, re, REG_NEWLINE))
        exit(EXIT_FAILURE);
    printf("String = \"%s\"\n", str);
    printf("Matches:\n");
    for (int i = 0; ; i++) {
        if (regexec(&regex, s, ARRAY_SIZE(pmatch), pmatch, 0))
            break;
        off = pmatch[0].rm_so + (s - str);
        if (off <= len)
            printf("%.*s\n", off, s);
    }
}
```

```
len = pmatch[0].rm_eo - pmatch[0].rm_so;
printf("#%d:\n", i);
printf("offset = %jd; length = %jd\n", (intmax_t) off,
(intmax_t) len);
printf("substring = \"%.*s\"\n", len, s + pmatch[0].rm_so);
s += pmatch[0].rm_eo;
}
exit(EXIT_SUCCESS);
}
```

SEE ALSO

grep(1), regex(7)

The glibc manual section, Regular Expressions

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

GNU

2020-08-13

REGEX(3)