



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'rpc_gss_set_defaults.3t'

\$ man rpc_gss_set_defaults.3t

RPC_GSS_SET_DEFAULTS(3) BSD Library Functions Manual RPC_GSS_SET_DEFAULTS(3)

NAME

rpc_gss_set_defaults ? set service and quality of protection

SYNOPSIS

```
#include <rpc/rpcsec_gss.h>
```

```
bool_t
```

```
rpc_gss_set_defaults(AUTH *auth, rpc_gss_service_t service, const char *qop);
```

DESCRIPTION

Set the service and quality of protection to be used for RPC requests. The new values apply for the rest of the lifetime of the context (unless changed again with this function).

PARAMETERS

service The service type to use for subsequent RPC requests

qop The quality of protection to use or NULL for the default

RETURN VALUES

Returns TRUE if the values were set

AVAILABILITY

The `rpc_gss_set_defaults()` function is part of `libtirpc`.

SEE ALSO

`rpc(3)`, `gssapi(3)`, `rpcsec_gss(3)`

AUTHORS

This manual page was written by Doug Rabson <dfr@FreeBSD.org>.