



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'setsid.1'***

**\$ man setsid.1**

SETSID(1)

User Commands

SETSID(1)

#### NAME

setsid - run a program in a new session

#### SYNOPSIS

setsid [options] program [arguments]

#### DESCRIPTION

setsid runs a program in a new session. The command calls fork(2) if already a process group leader. Otherwise, it executes a program in the current process. This default behavior is possible to override by the --fork option.

#### OPTIONS

-c, --ctty

Set the controlling terminal to the current one.

-f, --fork

Always create a new process.

-w, --wait

Wait for the execution of the program to end, and return the exit status of this program as the exit status of setsid.

-V, --version

Display version information and exit.

-h, --help

Display help text and exit.

#### AUTHORS

Rick Sladkey <jrs@world.std.com>

Page 1/2

## SEE ALSO

[setsid\(2\)](#)

## REPORTING BUGS

For bug reports, use the issue tracker at <https://github.com/karelzak/util-linux/issues>.

## AVAILABILITY

The setsid command is part of the util-linux package which can be downloaded from Linux

Kernel Archive <<https://www.kernel.org/pub/linux/utils/util-linux/>>.

util-linux 2.37.2

2021-06-02

SETSID(1)