

SUDO(8)

System Manager's Manual

SUDO(8)

## NAME

**sudo, sudoedit** ? execute a command as another user

## SYNOPSIS

**sudo -h | -K | -k | -V**

**sudo -v [-ABkNnS] [-g group] [-h host] [-p prompt] [-u user]**

**sudo -l [-ABkNnS] [-g group] [-h host] [-p prompt] [-U user] [-u user]**

**[command [arg ...]]**

**sudo [-ABbEHnPS] [-C num] [-D directory] [-g group] [-h host]**

**[-p prompt] [-R directory] [-r role] [-t type] [-T timeout]**

**[-u user] [VAR=value] [-i | -s] [command [arg ...]]**

**sudoedit [-ABkNnS] [-C num] [-D directory] [-g group] [-h host]**

**[-p prompt] [-R directory] [-r role] [-t type] [-T timeout]**

**[-u user] file ...**

## DESCRIPTION

**sudo** allows a permitted user to execute a command as the **superuser** or another user, as specified by the security policy. The invoking user's **real** (not **effective**) **user-ID** is used to determine the user name with which to query the security policy.

**sudo** supports a plugin architecture for **security policies**, **auditing**,

their own plugins to work seamlessly with the sudo front-end. The default security policy is sudoers, which is configured via the file /etc/sudoers, or via LDAP. See the ?Plugins? section for more information.

The security policy determines what privileges, if any, a user has to run sudo. The policy may require that users authenticate themselves with a password or another authentication mechanism. If authentication is required, sudo will exit if the user's password is not entered within a configurable time limit. This limit is policy-specific; the default password prompt timeout for the sudoers security policy is 0 minutes.

Security policies may support credential caching to allow the user to run sudo again for a period of time without requiring authentication. By default, the sudoers policy caches credentials on a per-terminal basis for 15 minutes. See the timestamp\_type and timestamp\_timeout options in sudoers(5) for more information. By running sudo with the -v option, a user can update the cached credentials without running a command.

On systems where sudo is the primary method of gaining superuser privileges, it is imperative to avoid syntax errors in the security policy configuration files. For the default security policy, sudoers(5),

utility which will ensure that no syntax errors are introduced.

When invoked as `sudoedit`, the `-e` option (described below), is implied.

Security policies and audit plugins may log successful and failed attempts to run `sudo`. If an I/O plugin is configured, the running command's input and output may be logged as well.

The options are as follows:

## `-A, --askpass`

Normally, if `sudo` requires a password, it will read it from the user's terminal. If the `-A` (`askpass`) option is specified, a (possibly graphical) helper program is executed to read the user's password and output the password to the standard output. If the `SUDO_ASKPASS` environment variable is set, it specifies the path to the helper program. Otherwise, if `sudo.conf(5)` contains a line specifying the `askpass` program, that value will be used. For example:

```
# Path to askpass helper program
Path askpass /usr/X11R6/bin/ssh-askpass
```

If no `askpass` program is available, `sudo` will exit with an error.

## **-B, --bell**

Ring the bell as part of the password prompt when a terminal is present. This option has no effect if an `askpass` program is used.

## **-b, --background**

Run the given command in the background. It is not possible to use shell job control to manipulate background processes started by `sudo`. Most interactive commands will fail to work properly in background mode.

## **-C num, --close-from=num**

Close all file descriptors greater than or equal to `num` before executing a command. Values less than three are not permitted. By default, `sudo` will close all open file descriptors other than standard input, standard output, and standard error when executing a command. The security policy may restrict the user's ability to use this option. The `sudoers` policy only permits use of the `-C` option when the administrator has enabled the `closefrom_override` option.

## **-D directory, --chdir=directory**

Run the command in the specified directory instead of the `cur?`

ror if the user does not have permission to specify the working directory.

## **-E, --preserve-env**

Indicates to the security policy that the user wishes to preserve their existing environment variables. The security policy may return an error if the user does not have permission to preserve the environment.

## **--preserve-env=list**

Indicates to the security policy that the user wishes to add the comma-separated list of environment variables to those preserved from the user's environment. The security policy may return an error if the user does not have permission to preserve the environment. This option may be specified multiple times.

## **-e, --edit**

Edit one or more files instead of running a command. In lieu of a path name, the string "sudoedit" is used when consulting the security policy. If the user is authorized by the policy, the following steps are taken:

1. Temporary copies are made of the files to be edited with

2. The editor specified by the policy is run to edit the temporary files. The sudoers policy uses the SUDO\_EDITOR, VISUAL and EDITOR environment variables (in that order). If none of SUDO\_EDITOR, VISUAL or EDITOR are set, the first program listed in the editor sudoers(5) option is used.
  
3. If they have been modified, the temporary files are copied back to their original location and the temporary versions are removed.

To help prevent the editing of unauthorized files, the following restrictions are enforced unless explicitly allowed by the security policy:

- ? Symbolic links may not be edited (version 1.8.15 and higher).
  
- ? Symbolic links along the path to be edited are not followed when the parent directory is writable by the invoking user unless that user is root (version 1.8.16 and higher).
  
- ? Files located in a directory that is writable by the invoking user may not be edited.

sion 1.8.16 and higher).

Users are never allowed to edit device special files.

If the specified file does not exist, it will be created. Unlike most commands run by sudo, the editor is run with the invoking user's environment unmodified. If the temporary file becomes empty after editing, the user will be prompted before it is installed. If, for some reason, sudo is unable to update a file with its edited version, the user will receive a warning and the edited copy will remain in a temporary file.

**-g group, --group=group**

Run the command with the primary group set to group instead of the primary group specified by the target user's password database entry. The group may be either a group name or a numeric group-ID (GID) prefixed with the `#` character (e.g., `#0` for GID 0). When running a command as a GID, many shells require that the `#` be escaped with a backslash (`\#`). If no `-u` option is specified, the command will be run as the invoking user. In either case, the primary group will be set to group. The sudoers policy permits any of the target user's groups to be specified via the `-g` option as long as the `-P` option is not in use.

## **-H, --set-home**

Request that the security policy set the HOME environment variable to the home directory specified by the target user's password database entry. Depending on the policy, this may be the default behavior.

## **-h, --help**

Display a short help message to the standard output and exit.

## **-h host, --host=host**

Run the command on the specified host if the security policy plugin supports remote commands. The sudoers plugin does not currently support running remote commands. This may also be used in conjunction with the -l option to list a user's privileges for the remote host.

## **-i, --login**

Run the shell specified by the target user's password database entry as a login shell. This means that login-specific resource files such as .profile, .bash\_profile, or .login will be read by the shell. If a command is specified, it is passed to the shell as a simple command using the -c option. The command and any args are concatenated, separated by spaces, after escaping each character (including white space) with a backslash

lar signs. If no command is specified, an interactive shell is executed. `sudo` attempts to change to that user's home directory before running the shell. The command is run with an environment similar to the one a user would receive at log in. Most shells behave differently when a command is specified as compared to an interactive session; consult the shell's manual for details. The Command environment section in the `sudoers(5)` manual documents how the `-i` option affects the environment in which a command is run when the `sudoers` policy is in use.

## **-K, --remove-timestamp**

Similar to the `-k` option, except that it removes every cached credential for the user, regardless of the terminal or parent process ID. The next time `sudo` is run, a password must be entered if the security policy requires authentication. It is not possible to use the `-K` option in conjunction with a command or other option. This option does not require a password. Not all security policies support credential caching.

## **-k, --reset-timestamp**

When used without a command, invalidates the user's cached credentials for the current session. The next time `sudo` is run in the session, a password must be entered if the security policy requires authentication. By default, the `sudoers` policy uses a

parent process ID if no terminal is present). This prevents the `-k` option from interfering with sudo commands run in a different terminal session. See the `timestamp_type` option in `sudoers(5)` for more information. This option does not require a password, and was added to allow a user to revoke sudo permissions from a `.logout` file.

When used in conjunction with a command or an option that may require a password, this option will cause sudo to ignore the user's cached credentials. As a result, sudo will prompt for a password (if one is required by the security policy) and will not update the user's cached credentials.

Not all security policies support credential caching.

## `-l, --list`

If no command is specified, list the privileges for the invoking user (or the user specified by the `-U` option) on the current host. A longer list format is used if this option is specified multiple times and the security policy supports a verbose output format.

If a command is specified and is permitted by the security policy for the invoking user (or the, user specified by the `-U` op?

command is displayed along with any args. If `-l` is specified more than once (and the security policy supports it), the matching rule is displayed in a verbose format along with the command. If a command is specified but not allowed by the policy, `sudo` will exit with a status value of 1.

## `-N, --no-update`

Do not update the user's cached credentials, even if the user successfully authenticates. Unlike the `-k` flag, existing cached credentials are used if they are valid. To detect when the user's cached credentials are valid (or when no authentication is required), the following can be used:

```
sudo -Nnv
```

Not all security policies support credential caching.

## `-n, --non-interactive`

Avoid prompting the user for input of any kind. If a password is required for the command to run, `sudo` will display an error message and exit.

## `-P, --preserve-groups`

Preserve the invoking user's group vector unaltered. By de?

the list of groups the target user is a member of. The real and effective group-IDs, however, are still set to match the target user.

**-p prompt, --prompt=prompt**

Use a custom password prompt with optional escape sequences. The following percent (?%?) escape sequences are supported by the sudoers policy:

**%H** expanded to the host name including the domain name (only if the machine's host name is fully qualified or the `fqdn` option is set in `sudoers(5)`)

**%h** expanded to the local host name without the domain name

**%p** expanded to the name of the user whose password is being requested (respects the `rootpw`, `targetpw`, and `runaspw` flags in `sudoers(5)`)

**%U** expanded to the login name of the user the command will be run as (defaults to root unless the `-u` option is also specified)

**%u** expanded to the invoking user's login name

**%%** two consecutive **??** characters are collapsed into a single **??** character

The custom prompt will override the default prompt specified by either the security policy or the `SUDO_PROMPT` environment variable. On systems that use PAM, the custom prompt will also override the prompt specified by a PAM module unless the `passprompt_override` flag is disabled in `sudoers`.

**-R directory, --chroot=directory**

Change to the specified root directory (see `chroot(8)`) before running the command. The security policy may return an error if the user does not have permission to specify the root directory.

**-r role, --role=role**

Run the command with an SELinux security context that includes the specified role.

**-S, --stdin**

Write the prompt to the standard error and read the password from the standard input instead of using the terminal device.

**-s, --shell**

is set or the shell specified by the invoking user's password database entry. If a command is specified, it is passed to the shell as a simple command using the `-c` option. The command and any args are concatenated, separated by spaces, after escaping each character (including white space) with a backslash (`\`) except for alphanumerics, underscores, hyphens, and dollar signs. If no command is specified, an interactive shell is executed. Most shells behave differently when a command is specified as compared to an interactive session; consult the shell's manual for details.

## **-t type, --type=type**

Run the command with an SELinux security context that includes the specified type. If no type is specified, the default type is derived from the role.

## **-U user, --other-user=user**

Used in conjunction with the `-l` option to list the privileges for user instead of for the invoking user. The security policy may restrict listing other users' privileges. When using the `sudoers` policy, the `-U` option is restricted to the root user and users with either the `list` privilege for the specified user or the ability to run any command as root or user on the current host.

## **-T timeout, --command-timeout=timeout**

Used to set a timeout for the command. If the timeout expires before the command has exited, the command will be terminated.

The security policy may restrict the user's ability to set timeouts. The sudoers policy requires that user-specified timeouts be explicitly enabled.

## **-u user, --user=user**

Run the command as a user other than the default target user (usually root). The user may be either a user name or a numeric user-ID (UID) prefixed with the `#` character (e.g., `#0` for UID 0). When running commands as a UID, many shells require that the `#` be escaped with a backslash (`\#`). Some security policies may restrict UIDs to those listed in the password database. The sudoers policy allows UIDs that are not in the password database as long as the `targetpw` option is not set. Other security policies may not support this.

## **-V, --version**

Print the sudo version string as well as the version string of any configured plugins. If the invoking user is already root, the `-V` option will display the options passed to `configure` when sudo was built; plugins may display additional information such as default options.

**-v, --validate**

Update the user's cached credentials, authenticating the user if necessary. For the sudoers plugin, this extends the sudo timeout for another 15 minutes by default, but does not run a command. Not all security policies support cached credentials.

**--** The **--** is used to delimit the end of the sudo options. Subsequent options are passed to the command.

Options that take a value may only be specified once unless otherwise indicated in the description. This is to help guard against problems caused by poorly written scripts that invoke sudo with user-controlled input.

Environment variables to be set for the command may also be passed as options to sudo in the form **VAR=value**, for example **LD\_LIBRARY\_PATH=/usr/local/pkg/lib**. Environment variables may be subject to restrictions imposed by the security policy plugin. The sudoers policy subjects environment variables passed as options to the same restrictions as existing environment variables with one important difference. If the **setenv** option is set in sudoers, the command to be run has the **SETENV** tag set or the command matched is **ALL**, the user may set variables that would otherwise be forbidden. See **sudoers(5)** for more information.

## COMMAND EXECUTION

When sudo executes a command, the security policy specifies the execution environment for the command. Typically, the real and effective user and group and IDs are set to match those of the target user, as specified in the password database, and the group vector is initialized based on the group database (unless the -P option was specified).

The following parameters may be specified by security policy:

- ? real and effective user-ID
- ? real and effective group-ID
- ? supplementary group-IDs
- ? the environment list
- ? current working directory
- ? file creation mode mask (umask)
- ? SELinux role and type
- ? scheduling priority (aka nice value)

## Process model

There are two distinct ways sudo can run a command.

If an I/O logging plugin is configured to log terminal I/O, or if the security policy explicitly requests it, a new pseudo-terminal (pty) is allocated and fork(2) is used to create a second sudo process, referred to as the monitor. The monitor creates a new terminal session with itself as the leader and the pty as its controlling terminal, calls fork(2) again, sets up the execution environment as described above, and then uses the execve(2) system call to run the command in the child process. The monitor exists to relay job control signals between the user's terminal and the pty the command is being run in. This makes it possible to suspend and resume the command normally. Without the monitor, the command would be in what POSIX terms an orphaned process group and it would not receive any job control signals from the kernel. When the command exits or is terminated by a signal, the monitor passes the command's exit status to the main sudo process and exits. After receiving the command's exit status, the main sudo process passes the command's exit status to the security policy's close function, as well as the close function of any configured audit plugin, and exits. This mode is the default for sudo versions 1.9.14 and above when using the sudoers policy.

If no pty is used, sudo calls fork(2), sets up the execution environ?

command in the child process. The main sudo process waits until the command has completed, then passes the command's exit status to the security policy's close function, as well as the close function of any configured audit plugins, and exits. As a special case, if the policy plugin does not define a close function, sudo will execute the command directly instead of calling fork(2) first. The sudoers policy plugin will only define a close function when I/O logging is enabled, a pty is required, an SELinux role is specified, the command has an associated timeout, or the pam\_session or pam\_setcred options are enabled. Both pam\_session and pam\_setcred are enabled by default on systems using PAM. This mode is the default for sudo versions prior to 1.9.14 when using the sudoers policy.

On systems that use PAM, the security policy's close function is responsible for closing the PAM session. It may also log the command's exit status.

## Signal handling

When the command is run as a child of the sudo process, sudo will relay signals it receives to the command. The SIGINT and SIGQUIT signals are only relayed when the command is being run in a new pty or when the signal was sent by a user process, not the kernel. This prevents the command from receiving SIGINT twice each time the user enters control-C. Some signals, such as SIGSTOP and SIGKILL, cannot be caught and

should be used instead of SIGSTOP when you wish to suspend a command being run by sudo.

As a special case, sudo will not relay signals that were sent by the command it is running. This prevents the command from accidentally killing itself. On some systems, the reboot(8) utility sends SIGTERM to all non-system processes other than itself before rebooting the system. This prevents sudo from relaying the SIGTERM signal it received back to reboot(8), which might then exit before the system was actually rebooted, leaving it in a half-dead state similar to single user mode.

Note, however, that this check only applies to the command run by sudo and not any other processes that the command may create. As a result, running a script that calls reboot(8) or shutdown(8) via sudo may cause the system to end up in this undefined state unless the reboot(8) or shutdown(8) are run using the exec() family of functions instead of system() (which interposes a shell between the command and the calling process).

## Plugins

Plugins may be specified via Plugin directives in the sudo.conf(5) file. They may be loaded as dynamic shared objects (on systems that support them), or compiled directly into the sudo binary. If no sudo.conf(5) file is present, or if it doesn't contain any Plugin lines, sudo will use sudoers(5) for the policy, auditing, and I/O log?

`/etc/sudo.conf` file and the `sudo_plugin(5)` manual for more information about the sudo plugin architecture.

## EXIT VALUE

Upon successful execution of a command, the exit status from sudo will be the exit status of the program that was executed. If the command terminated due to receipt of a signal, sudo will send itself the same signal that terminated the command.

If the `-l` option was specified without a command, sudo will exit with a value of 0 if the user is allowed to run sudo and they authenticated successfully (as required by the security policy). If a command is specified with the `-l` option, the exit value will only be 0 if the command is permitted by the security policy, otherwise it will be 1.

If there is an authentication failure, a configuration/permission problem, or if the given command cannot be executed, sudo exits with a value of 1. In the latter case, the error string is printed to the standard error. If sudo cannot `stat(2)` one or more entries in the user's `PATH`, an error is printed to the standard error. (If the directory does not exist or if it is not really a directory, the entry is ignored and no error is printed.) This should not happen under normal circumstances. The most common reason for `stat(2)` to return `?permission denied?` is if you are running an automounter and one of the

## SECURITY NOTES

sudo tries to be safe when executing external commands.

To prevent command spoofing, sudo checks "." and "" (both denoting current directory) last when searching for a command in the user's PATH (if one or both are in the PATH). Depending on the security policy, the user's PATH environment variable may be modified, replaced, or passed unchanged to the program that sudo executes.

Users should never be granted sudo privileges to execute files that are writable by the user or that reside in a directory that is writable by the user. If the user can modify or replace the command there is no way to limit what additional commands they can run.

By default, sudo will only log the command it explicitly runs. If a user runs a command such as `?sudo su?` or `?sudo sh?`, subsequent commands run from that shell are not subject to sudo's security policy. The same is true for commands that offer shell escapes (including most editors). If I/O logging is enabled, subsequent commands will have their input and/or output logged, but there will not be traditional logs for those commands. Because of this, care must be taken when giving users access to commands via sudo to verify that the command does not inadvertently give the user an effective root shell. For information on

`sudoers(5)`.

To prevent the disclosure of potentially sensitive information, `sudo` disables core dumps by default while it is executing (they are re-enabled for the command that is run). This historical practice dates from a time when most operating systems allowed set-user-ID processes to dump core by default. To aid in debugging `sudo` crashes, you may wish to re-enable core dumps by setting `?disable_coredump?` to `false` in the `sudo.conf(5)` file as follows:

```
Set disable_coredump false
```

See the `sudo.conf(5)` manual for more information.

## ENVIRONMENT

`sudo` utilizes the following environment variables. The security policy has control over the actual content of the command's environment.

**EDITOR**        Default editor to use in `-e` (`sudoedit`) mode if neither `SUDO_EDITOR` nor `VISUAL` is set.

**MAIL**         Set to the mail spool of the target user when the `-i` option is specified, or when `env_reset` is enabled in `sudoers` (unless `MAIL` is present in the `env_keep` list).

**HOME** Set to the home directory of the target user when the `-i` or `-H` options are specified, when the `-s` option is specified and `set_home` is set in sudoers, when `always_set_home` is enabled in sudoers, or when `env_reset` is enabled in sudoers and `HOME` is not present in the `env_keep` list.

**LOGNAME** Set to the login name of the target user when the `-i` option is specified, when the `set_logname` option is enabled in sudoers, or when the `env_reset` option is enabled in sudoers (unless `LOGNAME` is present in the `env_keep` list).

**PATH** May be overridden by the security policy.

**SHELL** Used to determine shell to run with `-s` option.

**SUDO\_ASKPASS** Specifies the path to a helper program used to read the password if no terminal is available or if the `-A` option is specified.

**SUDO\_COMMAND** Set to the command run by sudo, including any args. The args are truncated at 4096 characters to prevent a potential execution error.



# Linux UBUNTU Manual Pages

To get a file listing of an unreadable directory:

```
$ sudo ls /usr/local/protected
```

To list the home directory of user yaz on a machine where the file system holding ~yaz is not exported as root:

```
$ sudo -u yaz ls ~yaz
```

To edit the index.html file as user www:

```
$ sudoedit -u www ~www/htdocs/index.html
```

To view system logs only accessible to root and users in the adm group:

```
$ sudo -g adm more /var/log/syslog
```

To run an editor as jim with a different primary group:

```
$ sudoedit -u jim -g audio ~jim/sound.txt
```

To shut down a machine:

```
$ sudo shutdown -r +15 "quick reboot"
```

To make a usage listing of the directories in the /home partition. The commands are run in a sub-shell to allow the ?cd? command and file redirection to work.

```
$ sudo sh -c "cd /home ; du -s * | sort -rn > USAGE"
```

## DIAGNOSTICS

Error messages produced by sudo include:

**editing files in a writable directory is not permitted**

By default, sudoedit does not permit editing a file when any of the parent directories are writable by the invoking user. This avoids a race condition that could allow the user to overwrite an arbitrary file. See the sudoedit\_checkdir option in sudoers(5) for more information.

**editing symbolic links is not permitted**

By default, sudoedit does not follow symbolic links when opening files. See the sudoedit\_follow option in sudoers(5) for more information.

**effective uid is not 0, is sudo installed setuid root?**

sudo was not run with root privileges. The sudo binary must be owned by the root user and have the set-user-ID bit set. Also,

option or on an NFS file system that maps uid 0 to an unprivileged uid.

effective uid is not 0, is sudo on a file system with the 'nosuid' option set or an NFS file system without root privileges? sudo was not run with root privileges. The sudo binary has the proper owner and permissions but it still did not run with root privileges. The most common reason for this is that the file system the sudo binary is located on is mounted with the 'nosuid' option or it is an NFS file system that maps uid 0 to an unprivileged uid.

**fatal error, unable to load plugins**

An error occurred while loading or initializing the plugins specified in sudo.conf(5).

**invalid environment variable name**

One or more environment variable names specified via the -E option contained an equal sign (=). The arguments to the -E option should be environment variable names without an associated value.

**no password was provided**

When sudo tried to read the password, it did not receive any

-S option is specified) and the standard input has been redirected from /dev/null.

a terminal is required to read the password

sudo needs to read the password but there is no mechanism available for it to do so. A terminal is not present to read the password from, sudo has not been configured to read from the standard input, the -S option was not used, and no askpass helper has been specified either via the sudo.conf(5) file or the SUDO\_ASKPASS environment variable.

no writable temporary directory found

sudoedit was unable to find a usable temporary directory in which to store its intermediate files.

The ?no new privileges? flag is set, which prevents sudo from running as root.

sudo was run by a process that has the Linux ?no new privileges? flag is set. This causes the set-user-ID bit to be ignored when running an executable, which will prevent sudo from functioning.

The most likely cause for this is running sudo within a container that sets this flag. Check the documentation to see if it is possible to configure the container such that the flag is not set.

**sudo must be owned by uid 0 and have the setuid bit set**

**sudo** was not run with root privileges. The **sudo** binary does not have the correct owner or permissions. It must be owned by the root user and have the set-user-ID bit set.

**sudoedit is not supported on this platform**

It is only possible to run **sudoedit** on systems that support setting the effective user-ID.

**timed out reading password**

The user did not enter a password before the password timeout (5 minutes by default) expired.

**you do not exist in the passwd database**

Your user-ID does not appear in the system **passwd** database.

**you may not specify environment variables in edit mode**

It is only possible to specify environment variables when running a command. When editing a file, the editor is run with the user's environment unmodified.

## SEE ALSO

**su(1)**, **stat(2)**, **login\_cap(3)**, **passwd(5)**, **sudo.conf(5)**, **sudo\_plugin(5)**, **sudoers(5)**, **sudoers\_timestamp(5)**, **sudoreplay(8)**, **visudo(8)**

## HISTORY

See the HISTORY.md file in the sudo distribution (<https://www.sudo.ws/about/history/>) for a brief history of sudo.

## AUTHORS

Many people have worked on sudo over the years; this version consists of code written primarily by:

Todd C. Miller

See the CONTRIBUTORS.md file in the sudo distribution (<https://www.sudo.ws/about/contributors/>) for an exhaustive list of people who have contributed to sudo.

## CAVEATS

There is no easy way to prevent a user from gaining a root shell if that user is allowed to run arbitrary commands via sudo. Also, many programs (such as editors) allow the user to run commands via shell escapes, thus avoiding sudo's checks. However, on most systems it is possible to prevent shell escapes with the sudoers(5) plugin's noexec functionality.

It is not meaningful to run the `?cd?` command directly via sudo, e.g.,

since when the command exits the parent process (your shell) will still be the same. The `-D` option can be used to run a command in a specific directory.

Running shell scripts via `sudo` can expose the same kernel bugs that make `set-user-ID` shell scripts unsafe on some operating systems (if your OS has a `/dev/fd/` directory, `set-user-ID` shell scripts are generally safe).

## BUGS

If you believe you have found a bug in `sudo`, you can submit a bug report at <https://bugzilla.sudo.ws/>

## SUPPORT

Limited free support is available via the `sudo-users` mailing list, see <https://www.sudo.ws/mailman/listinfo/sudo-users> to subscribe or search the archives.

## DISCLAIMER

`sudo` is provided `AS IS` and any express or implied warranties, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose are disclaimed. See the `LICENSE.md` file distributed with `sudo` or <https://www.sudo.ws/about/license/> for

# Linux UBUNTU Manual Pages

Sudo 1.9.15p5

August 9, 2023

SUDO(8)