



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'systemd-delta.1'

\$ man systemd-delta.1

SYSTEMD-DELTA(1)

systemd-delta

SYSTEMD-DELTA(1)

NAME

systemd-delta - Find overridden configuration files

SYNOPSIS

systemd-delta [OPTIONS...] [PREFIX[/**SUFFIX**]]**SUFFIX...**

DESCRIPTION

systemd-delta may be used to identify and compare configuration files that override other configuration files. Files in /etc/ have highest priority, files in /run/ have the second highest priority, ..., files in /usr/lib/ have lowest priority. Files in a directory with higher priority override files with the same name in directories of lower priority. In addition, certain configuration files can have ".d" directories which contain "drop-in" files with configuration snippets which augment the main configuration file. "Drop-in" files can be overridden in the same way by placing files with the same name in a directory of higher priority (except that, in case of "drop-in" files, both the "drop-in" file name and the name of the containing directory, which corresponds to the name of the main configuration file, must match). For a fuller explanation, see **systemd.unit(5)**.

The command line argument will be split into a prefix and a suffix. Either is optional.

The prefix must be one of the directories containing configuration files (/etc/, /run/,

/lib/, ...). If it is given, only overriding files contained in this directory will be

shown. Otherwise, all overriding files will be shown. The suffix must be a name of a

subdirectory containing configuration files like **tmpfiles.d**, **sysctl.d** or **systemd/system**.

If it is given, only configuration files in this subdirectory (across all configuration

paths) will be analyzed. Otherwise, all configuration files will be analyzed. If the

command line argument is not given at all, all configuration files will be analyzed. See below for some examples.

OPTIONS

The following options are understood:

-t, --type=

When listing the differences, only list those that are asked for. The list itself is a comma-separated list of desired difference types.

Recognized types are:

masked

 Show masked files

equivalent

 Show overridden files that while overridden, do not differ in content.

redirected

 Show files that are redirected to another.

overridden

 Show overridden, and changed files.

extended

 Show *.conf files in drop-in directories for units.

unchanged

 Show unmodified files too.

--diff=

When showing modified files, when a file is overridden show a diff as well. This option takes a boolean argument. If omitted, it defaults to true.

-h, --help

Print a short help text and exit.

--version

Print a short version string and exit.

--no-pager

Do not pipe output into a pager.

EXAMPLES

To see all local configuration:

systemd-delta

To see all runtime configuration:

```
systemd-delta /run
```

To see all system unit configuration changes:

```
systemd-delta systemd/system
```

To see all runtime "drop-in" changes for system units:

```
systemd-delta --type=extended /run/systemd/system
```

EXIT STATUS

On success, 0 is returned, a non-zero failure code otherwise.

SEE ALSO

[systemd\(1\)](#), [systemd.unit\(5\)](#)

[systemd 249](#)

[SYSTEMD-DELTA\(1\)](#)