



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'systemd-hibernate-resume.8'

```
$ man systemd-hibernate-resume.8
```

```
SYSTEMD-HIBERNATE-RESUME@.SERVICsystemd-hibernate-resume@.serSYSTEMD-HIBERNATE-RESUME@.SERVI  
CE(8)
```

NAME

systemd-hibernate-resume@.service, systemd-hibernate-resume - Resume from hibernation

SYNOPSIS

```
systemd-hibernate-resume@.service
```

```
/lib/systemd/systemd-hibernate-resume
```

DESCRIPTION

systemd-hibernate-resume@.service initiates the resume from hibernation. It is instantiated with the device to resume from as the template argument.

systemd-hibernate-resume only supports the in-kernel hibernation implementation, known as swsusp[1]. Internally, it works by writing the major:minor of specified device node to /sys/power/resume.

Failing to initiate a resume is not an error condition. It may mean that there was no resume image (e. g. if the system has been simply powered off and not hibernated). In such case, the boot is ordinarily continued.

SEE ALSO

systemd(1), systemd-hibernate-resume-generator(8)

NOTES

1. swsusp

<https://www.kernel.org/doc/Documentation/power/swsusp.txt>

systemd 249

SYSTEMD-HIBERNATE-RESUME@.SERVICE(8)