



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'systemd.directives.7'

\$ man systemd.directives.7

SYSTEMD.DIRECTIVES(7) systemd.directives SYSTEMD.DIRECTIVES(7)

NAME

systemd.directives - Index of configuration directives

UNIT DIRECTIVES

Directives for configuring units, used in unit files.

Accept=

systemd.socket(5)

AccuracySec=

systemd.timer(5)

After=

systemd.unit(5)

Alias=

systemd.unit(5)

AllowIsolate=

systemd.unit(5)

AllowedCPUs=

systemd.resource-control(5)

AllowedMemoryNodes=

systemd.resource-control(5)

Also=

systemd.unit(5)

AmbientCapabilities=

systemd.exec(5)

AppArmorProfile=

systemd.exec(5)

AssertACPower=

systemd.unit(5)

AssertArchitecture=

systemd.unit(5)

AssertCPUs=

systemd.unit(5)

AssertCapability=

systemd.unit(5)

AssertControlGroupController=

systemd.unit(5)

AssertDirectoryNotEmpty=

systemd.unit(5)

AssertEnvironment=

systemd.unit(5)

AssertFileIsExecutable=

systemd.unit(5)

AssertFileNotEmpty=

systemd.unit(5)

AssertFirstBoot=

systemd.unit(5)

AssertGroup=

systemd.unit(5)

AssertHost=

systemd.unit(5)

AssertKernelCommandLine=

systemd.unit(5)

AssertKernelVersion=

systemd.unit(5)

AssertMemory=

systemd.unit(5)

AssertNeedsUpdate=

systemd.unit(5)

AssertOSRelease=
systemd.unit(5)

AssertPathExists=
systemd.unit(5)

AssertPathExistsGlob=
systemd.unit(5)

AssertPathIsDirectory=
systemd.unit(5)

AssertPathIsEncrypted=
systemd.unit(5)

AssertPathIsMountPoint=
systemd.unit(5)

AssertPathIsReadWrite=
systemd.unit(5)

AssertPathIsSymbolicLink=
systemd.unit(5)

AssertSecurity=
systemd.unit(5)

AssertUser=
systemd.unit(5)

AssertVirtualization=
systemd.unit(5)

BPFProgram=
systemd.resource-control(5)

Backlog=
systemd.socket(5)

Before=
systemd.unit(5)

BindIPv6Only=
systemd.socket(5)

BindPaths=
systemd.exec(5)

BindReadOnlyPaths=

systemd.exec(5)

BindToDevice=

systemd.socket(5)

BindsTo=

systemd.unit(5)

BlockIOAccounting=

systemd.resource-control(5)

BlockIODeviceWeight=

systemd.resource-control(5)

BlockIOReadBandwidth=

systemd.resource-control(5)

BlockIOWeight=

systemd.resource-control(5)

BlockIOWriteBandwidth=

systemd.resource-control(5)

Broadcast=

systemd.socket(5)

BusName=

systemd.service(5)

CPUAccounting=

systemd.resource-control(5)

CPUAffinity=

systemd.exec(5)

CPUQuota=

systemd.resource-control(5)

CPUQuotaPeriodSec=

systemd.resource-control(5)

CPU SchedulingPolicy=

systemd.exec(5)

CPU SchedulingPriority=

systemd.exec(5)

CPU SchedulingResetOnFork=

systemd.exec(5)

CPUShares=

systemd.resource-control(5)

CPUWeight=

systemd.resource-control(5)

CacheDirectory=

systemd.exec(5)

CacheDirectoryMode=

systemd.exec(5)

CapabilityBoundingSet=

systemd.exec(5)

CollectMode=

systemd.unit(5)

ConditionACPower=

systemd.unit(5)

ConditionArchitecture=

systemd.unit(5)

ConditionCPUFeature=

systemd.unit(5)

ConditionCPUs=

systemd.unit(5)

ConditionCapability=

systemd.unit(5)

ConditionControlGroupController=

systemd.unit(5)

ConditionDirectoryNotEmpty=

systemd.unit(5)

ConditionEnvironment=

systemd.unit(5)

ConditionFileIsExecutable=

systemd.unit(5)

ConditionFileNotEmpty=

systemd.unit(5)

ConditionFirmware=

systemd.unit(5)

ConditionFirstBoot=

systemd.unit(5)

ConditionGroup=

systemd.unit(5)

ConditionHost=

systemd.unit(5)

ConditionKernelCommandLine=

systemd.unit(5)

ConditionKernelVersion=

systemd.unit(5)

ConditionMemory=

systemd.unit(5)

ConditionNeedsUpdate=

systemd.unit(5)

ConditionOSRelease=

systemd.unit(5)

ConditionPathExists=

systemd.unit(5)

ConditionPathExistsGlob=

systemd.unit(5)

ConditionPathIsDirectory=

systemd.unit(5)

ConditionPathIsEncrypted=

systemd.unit(5)

ConditionPathIsMountPoint=

systemd.unit(5)

ConditionPathIsReadWrite=

systemd.unit(5)

ConditionPathIsSymbolicLink=

systemd.unit(5)

ConditionSecurity=

systemd.unit(5)

ConditionUser=

systemd.unit(5)

ConditionVirtualization=

systemd.unit(5)

ConfigurationDirectory=

systemd.exec(5)

ConfigurationDirectoryMode=

systemd.exec(5)

Conflicts=

systemd.unit(5)

CoredumpFilter=

systemd.exec(5)

DefaultDependencies=

systemd.unit(5)

DefaultInstance=

systemd.unit(5)

DeferAcceptSec=

systemd.socket(5)

Delegate=

systemd.resource-control(5)

Description=

systemd.unit(5)

DeviceAllow=

systemd.resource-control(5)

DevicePolicy=

systemd.resource-control(5)

DirectoryMode=

systemd.automount(5), systemd.mount(5), systemd.path(5), systemd.socket(5)

DirectoryNotEmpty=

systemd.path(5)

DisableControllers=

systemd.resource-control(5)

Documentation=

systemd.unit(5)

DynamicUser=

systemd.exec(5)

Environment=

systemd.exec(5)

EnvironmentFile=

systemd.exec(5)

ExecCondition=

systemd.service(5)

ExecPaths=

systemd.exec(5)

ExecReload=

systemd.service(5)

ExecStart=

systemd.service(5)

ExecStartPost=

systemd.service(5), systemd.socket(5)

ExecStartPre=

systemd.service(5), systemd.socket(5)

ExecStop=

systemd.service(5)

ExecStopPost=

systemd.service(5), systemd.socket(5)

ExecStopPre=

systemd.socket(5)

ExtensionImages=

systemd.exec(5)

FailureAction=

systemd.unit(5)

FailureActionExitStatus=

systemd.unit(5)

FileDescriptorName=

systemd.socket(5)
FileDescriptorStoreMax=
systemd.service(5)
FinalKillSignal=
systemd.kill(5)
FixedRandomDelay=
systemd.timer(5)
FlushPending=
systemd.socket(5)
ForceUnmount=
systemd.mount(5)
FreeBind=
systemd.socket(5)
Group=
systemd.exec(5)
GuessMainPID=
systemd.service(5)
IOAccounting=
systemd.resource-control(5)
IODeviceLatencyTargetSec=
systemd.resource-control(5)
IODeviceWeight=
systemd.resource-control(5)
IOReadBandwidthMax=
systemd.resource-control(5)
IOReadIOPSMax=
systemd.resource-control(5)
IOSchedulingClass=
systemd.exec(5)
IOSchedulingPriority=
systemd.exec(5)
IOWeight=
systemd.resource-control(5)

IOWriteBandwidthMax=
systemd.resource-control(5)

IOWriteIOPSMax=
systemd.resource-control(5)

IPAccounting=
systemd.resource-control(5)

IPAddressAllow=
systemd.resource-control(5)

IPAddressDeny=
systemd.resource-control(5)

IPCNamespacePath=
systemd.exec(5)

IPegressFilterPath=
systemd.resource-control(5)

IPIngressFilterPath=
systemd.resource-control(5)

IPTOS=
systemd.socket(5)

IPTTL=
systemd.socket(5)

IgnoreOnIsolate=
systemd.unit(5)

IgnoreSIGPIPE=
systemd.exec(5)

InaccessiblePaths=
systemd.exec(5)

JobRunningTimeoutSec=
systemd.unit(5)

JobTimeoutAction=
systemd.unit(5)

JobTimeoutRebootArgument=
systemd.unit(5)

JobTimeoutSec=

systemd.unit(5)
JoinsNamespaceOf=
systemd.unit(5)
KeepAlive=
systemd.socket(5)
KeepAliveIntervalSec=
systemd.socket(5)
KeepAliveProbes=
systemd.socket(5)
KeepAliveTimeSec=
systemd.socket(5)
KeyringMode=
systemd.exec(5)
KillMode=
systemd.kill(5)
KillSignal=
systemd.kill(5)
LazyUnmount=
systemd.mount(5)
LimitAS=
systemd.exec(5)
LimitCORE=
systemd.exec(5)
LimitCPU=
systemd.exec(5)
LimitDATA=
systemd.exec(5)
LimitFSIZE=
systemd.exec(5)
LimitLOCKS=
systemd.exec(5)
LimitMEMLOCK=
systemd.exec(5)

LimitMSGQUEUE=

systemd.exec(5)

LimitNICE=

systemd.exec(5)

LimitNOFILE=

systemd.exec(5)

LimitNPROC=

systemd.exec(5)

LimitRSS=

systemd.exec(5)

LimitRTPRIO=

systemd.exec(5)

LimitRTTIME=

systemd.exec(5)

LimitSIGPENDING=

systemd.exec(5)

LimitSTACK=

systemd.exec(5)

ListenDatagram=

systemd.socket(5)

ListenFIFO=

systemd.socket(5)

ListenMessageQueue=

systemd.socket(5)

ListenNetlink=

systemd.socket(5)

ListenSequentialPacket=

systemd.socket(5)

ListenSpecial=

systemd.socket(5)

ListenStream=

systemd.socket(5)

ListenUSBFunction=

systemd.socket(5)

LoadCredential=
systemd.exec(5)

LockPersonality=
systemd.exec(5)

LogExtraFields=
systemd.exec(5)

LogLevelMax=
systemd.exec(5)

LogNamespace=
systemd.exec(5)

LogRateLimitBurst=
systemd.exec(5)

LogRateLimitIntervalSec=
systemd.exec(5)

LogsDirectory=
systemd.exec(5)

LogsDirectoryMode=
systemd.exec(5)

MakeDirectory=
systemd.path(5)

ManagedOOMMemoryPressure=
systemd.resource-control(5)

ManagedOOMMemoryPressureLimit=
systemd.resource-control(5)

ManagedOOMPreference=
systemd.resource-control(5)

ManagedOOMSwap=
systemd.resource-control(5)

Mark=
systemd.socket(5)

MaxConnections=
systemd.socket(5)

MaxConnectionsPerSource=

systemd.socket(5)

MemoryAccounting=

systemd.resource-control(5)

MemoryDenyWriteExecute=

systemd.exec(5)

MemoryHigh=

systemd.resource-control(5)

MemoryLimit=

systemd.resource-control(5)

MemoryLow=

systemd.resource-control(5)

MemoryMax=

systemd.resource-control(5)

MemoryMin=

systemd.resource-control(5)

MemorySwapMax=

systemd.resource-control(5)

MessageQueueMaxMessages=

systemd.socket(5)

MessageQueueMessageSize=

systemd.socket(5)

MountAPIVFS=

systemd.exec(5)

MountFlags=

systemd.exec(5)

MountImages=

systemd.exec(5)

NUMAMask=

systemd.exec(5)

NUMAPolicy=

systemd.exec(5)

NetworkNamespacePath=

systemd.exec(5)

Nice=

systemd.exec(5)

NoDelay=

systemd.socket(5)

NoExecPaths=

systemd.exec(5)

NoNewPrivileges=

systemd.exec(5)

NonBlocking=

systemd.service(5)

NotifyAccess=

systemd.service(5)

OOMPolicy=

systemd.service(5)

OOMScoreAdjust=

systemd.exec(5)

OnActiveSec=

systemd.timer(5)

OnBootSec=

systemd.timer(5)

OnCalendar=

systemd.timer(5)

OnClockChange=

systemd.timer(5)

OnFailure=

systemd.unit(5)

OnFailureJobMode=

systemd.unit(5)

OnStartupSec=

systemd.timer(5)

OnSuccess=

systemd.unit(5)

OnTimezoneChange=

systemd.timer(5)

OnUnitActiveSec=

systemd.timer(5)

OnUnitInactiveSec=

systemd.timer(5)

Options=

systemd.mount(5), systemd.swap(5)

PAMName=

systemd.exec(5)

PIDFile=

systemd.service(5)

PartOf=

systemd.unit(5)

PassCredentials=

systemd.socket(5)

PassEnvironment=

systemd.exec(5)

PassPacketInfo=

systemd.socket(5)

PassSecurity=

systemd.socket(5)

PathChanged=

systemd.path(5)

PathExists=

systemd.path(5)

PathExistsGlob=

systemd.path(5)

PathModified=

systemd.path(5)

Persistent=

systemd.timer(5)

Personality=

systemd.exec(5)

PipeSize=

systemd.socket(5)

Priority=

systemd.socket(5), systemd.swap(5)

PrivateDevices=

systemd.exec(5)

PrivateIPC=

systemd.exec(5)

PrivateMounts=

systemd.exec(5)

PrivateNetwork=

systemd.exec(5)

PrivateTmp=

systemd.exec(5)

PrivateUsers=

systemd.exec(5)

ProcSubset=

systemd.exec(5)

PropagatesReloadTo=

systemd.unit(5)

PropagatesStopTo=

systemd.unit(5)

ProtectClock=

systemd.exec(5)

ProtectControlGroups=

systemd.exec(5)

ProtectHome=

systemd.exec(5)

ProtectHostname=

systemd.exec(5)

ProtectKernelLogs=

systemd.exec(5)

ProtectKernelModules=

systemd.exec(5)

ProtectKernelTunables=

systemd.exec(5)

ProtectProc=

systemd.exec(5)

ProtectSystem=

systemd.exec(5)

RandomizedDelaySec=

systemd.timer(5)

ReadOnlyPaths=

systemd.exec(5)

ReadWriteOnly=

systemd.mount(5)

ReadWritePaths=

systemd.exec(5)

RebootArgument=

systemd.unit(5)

ReceiveBuffer=

systemd.socket(5)

RefuseManualStart=

systemd.unit(5)

RefuseManualStop=

systemd.unit(5)

ReloadPropagatedFrom=

systemd.unit(5)

RemainAfterElapse=

systemd.timer(5)

RemainAfterExit=

systemd.service(5)

RemoveIPC=

systemd.exec(5)

RemoveOnStop=

systemd.socket(5)

RequiredBy=

systemd.unit(5)

Requires=

systemd.unit(5)

RequiresMountsFor=

systemd.unit(5)

Requisite=

systemd.unit(5)

Restart=

systemd.service(5)

RestartForceExitStatus=

systemd.service(5)

RestartKillSignal=

systemd.kill(5)

RestartPreventExitStatus=

systemd.service(5)

RestartSec=

systemd.service(5)

RestrictAddressFamilies=

systemd.exec(5)

RestrictNamespaces=

systemd.exec(5)

RestrictRealtime=

systemd.exec(5)

RestrictSUIDSGID=

systemd.exec(5)

ReusePort=

systemd.socket(5)

RootDirectory=

systemd.exec(5)

RootDirectoryStartOnly=

systemd.service(5)

RootHash=

systemd.exec(5)

RootHashSignature=

systemd.exec(5)

RootImage=

systemd.exec(5)

RootImageOptions=

systemd.exec(5)

RootVerity=

systemd.exec(5)

RuntimeDirectory=

systemd.exec(5)

RuntimeDirectoryMode=

systemd.exec(5)

RuntimeDirectoryPreserve=

systemd.exec(5)

RuntimeMaxSec=

systemd.scope(5), systemd.service(5)

SELinuxContext=

systemd.exec(5)

SELinuxContextFromNet=

systemd.socket(5)

SecureBits=

systemd.exec(5)

SendBuffer=

systemd.socket(5)

SendSIGHUP=

systemd.kill(5)

SendSIGKILL=

systemd.kill(5)

Service=

systemd.socket(5)

SetCredential=

systemd.exec(5)

Slice=

systemd.resource-control(5)

SloppyOptions=

systemd.mount(5)

SmackLabel=

systemd.socket(5)

SmackLabelIPIn=

systemd.socket(5)

SmackLabelIPOut=

systemd.socket(5)

SmackProcessLabel=

systemd.exec(5)

SocketBindAllow=

systemd.resource-control(5)

SocketBindDeny=

systemd.resource-control(5)

SocketGroup=

systemd.socket(5)

SocketMode=

systemd.socket(5)

SocketProtocol=

systemd.socket(5)

SocketUser=

systemd.socket(5)

Sockets=

systemd.service(5)

SourcePath=

systemd.unit(5)

StandardError=

systemd.exec(5)

StandardInput=

systemd.exec(5)

StandardInputData=

systemd.exec(5)

StandardInputText=

systemd.exec(5)

StandardOutput=

systemd.exec(5)

StartLimitAction=

systemd.unit(5)

StartLimitBurst=

systemd.unit(5)

StartLimitIntervalSec=

systemd.unit(5)

StartupBlockIOWeight=

systemd.resource-control(5)

StartupCPUShares=

systemd.resource-control(5)

StartupCPUWeight=

systemd.resource-control(5)

StartupIOWeight=

systemd.resource-control(5)

StateDirectory=

systemd.exec(5)

StateDirectoryMode=

systemd.exec(5)

StopPropagatedFrom=

systemd.unit(5)

StopWhenUnneeded=

systemd.unit(5)

SuccessAction=

systemd.unit(5)

SuccessActionExitStatus=

systemd.unit(5)

SuccessExitStatus=

systemd.service(5)
SupplementaryGroups=
systemd.exec(5)
Symlinks=
systemd.socket(5)
SyslogFacility=
systemd.exec(5)
SyslogIdentifier=
systemd.exec(5)
SyslogLevel=
systemd.exec(5)
SyslogLevelPrefix=
systemd.exec(5)
SystemCallArchitectures=
systemd.exec(5)
SystemCallErrorNumber=
systemd.exec(5)
SystemCallFilter=
systemd.exec(5)
SystemCallLog=
systemd.exec(5)
TCPCongestion=
systemd.socket(5)
TTYPath=
systemd.exec(5)
TTYReset=
systemd.exec(5)
TTYVHangup=
systemd.exec(5)
TTYVTDisallocate=
systemd.exec(5)
TasksAccounting=
systemd.resource-control(5)

TasksMax=
systemd.resource-control(5)

TemporaryFileSystem=
systemd.exec(5)

TimeoutAbortSec=
systemd.service(5)

TimeoutCleanSec=
systemd.exec(5)

TimeoutIdleSec=
systemd.automount(5)

TimeoutSec=
systemd.mount(5), systemd.service(5), systemd.socket(5), systemd.swap(5)

TimeoutStartFailureMode=
systemd.service(5)

TimeoutStartSec=
systemd.service(5)

TimeoutStopFailureMode=
systemd.service(5)

TimeoutStopSec=
systemd.service(5)

TimerSlackNSec=
systemd.exec(5)

Timestamping=
systemd.socket(5)

Transparent=
systemd.socket(5)

TriggerLimitBurst=
systemd.socket(5)

TriggerLimitIntervalSec=
systemd.socket(5)

Type=
systemd.mount(5), systemd.service(5)

UMask=

systemd.exec(5)

USBFunctionDescriptors=

systemd.service(5)

USBFunctionStrings=

systemd.service(5)

Unit=

systemd.path(5), systemd.timer(5)

UnsetEnvironment=

systemd.exec(5)

Upholds=

systemd.unit(5)

User=

systemd.exec(5)

UtmpIdentifier=

systemd.exec(5)

UtmpMode=

systemd.exec(5)

WakeSystem=

systemd.timer(5)

WantedBy=

systemd.unit(5)

Wants=

systemd.unit(5)

WatchdogSec=

systemd.service(5)

WatchdogSignal=

systemd.kill(5)

What=

systemd.mount(5), systemd.swap(5)

Where=

systemd.automount(5), systemd.mount(5)

WorkingDirectory=

systemd.exec(5)

Writable=

systemd.socket(5)

OPTIONS ON THE KERNEL COMMAND LINE

Kernel boot options for configuring the behaviour of the systemd process.

-b

kernel-command-line(7), systemd(1)

1

kernel-command-line(7), systemd(1)

2

kernel-command-line(7), systemd(1)

3

kernel-command-line(7), systemd(1)

4

kernel-command-line(7), systemd(1)

5

kernel-command-line(7), systemd(1)

S

kernel-command-line(7), systemd(1)

bond=

systemd-network-generator.service(8)

bootdev=

systemd-network-generator.service(8)

bridge=

systemd-network-generator.service(8)

debug

kernel-command-line(7), systemd(1)

emergency

kernel-command-line(7), systemd(1)

fsck.mode=

kernel-command-line(7), systemd-fsck@.service(8)

fsck.repair=

kernel-command-line(7), systemd-fsck@.service(8)

fstab=

kernel-command-line(7), systemd-fstab-generator(8)

ifname=

systemd-network-generator.service(8)

ip=

systemd-network-generator.service(8)

locale.LANG=

kernel-command-line(7), systemd(1)

locale.LANGUAGE=

kernel-command-line(7), systemd(1)

locale.LC_ADDRESS=

kernel-command-line(7), systemd(1)

locale.LC_COLLATE=

kernel-command-line(7), systemd(1)

locale.LC_CTYPE=

kernel-command-line(7), systemd(1)

locale.LC_IDENTIFICATION=

kernel-command-line(7), systemd(1)

locale.LC_MEASUREMENT=

kernel-command-line(7), systemd(1)

locale.LC_MESSAGES=

kernel-command-line(7), systemd(1)

locale.LC_MONETARY=

kernel-command-line(7), systemd(1)

locale.LC_NAME=

kernel-command-line(7), systemd(1)

locale.LC_NUMERIC=

kernel-command-line(7), systemd(1)

locale.LC_PAPER=

kernel-command-line(7), systemd(1)

locale.LC_TELEPHONE=

kernel-command-line(7), systemd(1)

locale.LC_TIME=

kernel-command-line(7), systemd(1)

luks.crypttab=
 kernel-command-line(7), systemd-cryptsetup-generator(8)

luks.data=
 systemd-cryptsetup-generator(8)

luks.key=
 kernel-command-line(7), systemd-cryptsetup-generator(8)

luks.name=
 kernel-command-line(7), systemd-cryptsetup-generator(8)

luks.options=
 kernel-command-line(7), systemd-cryptsetup-generator(8)

luks.uuid=
 kernel-command-line(7), systemd-cryptsetup-generator(8)

luks=
 kernel-command-line(7), systemd-cryptsetup-generator(8)

modules_load=
 kernel-command-line(7), systemd-modules-load.service(8)

mount.usr=
 kernel-command-line(7), systemd-fstab-generator(8)

mount.usrflags=
 kernel-command-line(7), systemd-fstab-generator(8)

mount.usrfstype=
 kernel-command-line(7), systemd-fstab-generator(8)

net.ifnames=
 kernel-command-line(7), systemd-udev.service(8)

net.naming-scheme=
 kernel-command-line(7), systemd-udev.service(8)

noresume
 systemd-hibernate-resume-generator(8)

plymouth.enable=
 kernel-command-line(7)

quiet
 kernel-command-line(7), systemd(1)

quotacheck.mode=

kernel-command-line(7), systemd-quotacheck.service(8)

rd.emergency

kernel-command-line(7), systemd(1)

rd.fstab=

kernel-command-line(7), systemd-fstab-generator(8)

rd.luks.crypttab=

kernel-command-line(7), systemd-cryptsetup-generator(8)

rd.luks.data=

systemd-cryptsetup-generator(8)

rd.luks.key=

kernel-command-line(7), systemd-cryptsetup-generator(8)

rd.luks.name=

kernel-command-line(7), systemd-cryptsetup-generator(8)

rd.luks.options=

kernel-command-line(7), systemd-cryptsetup-generator(8)

rd.luks.uuid=

kernel-command-line(7), systemd-cryptsetup-generator(8)

rd.luks=

kernel-command-line(7), systemd-cryptsetup-generator(8)

rd.modules_load=

kernel-command-line(7), systemd-modules-load.service(8)

rd.peerdns=

systemd-network-generator.service(8)

rd.rescue

kernel-command-line(7), systemd(1)

rd.route=

systemd-network-generator.service(8)

rd.systemd.gpt_auto

systemd-gpt-auto-generator(8)

rd.systemd.gpt_auto=

kernel-command-line(7)

rd.systemd.unit=

kernel-command-line(7), systemd(1)

rd.systemd.verity=
 kernel-command-line(7), systemd-veritysetup-generator(8)

rd.udev.blockdev_read_only
 kernel-command-line(7), systemd-udev.service(8)

rd.udev.children_max=
 kernel-command-line(7), systemd-udev.service(8)

rd.udev.event_timeout=
 kernel-command-line(7), systemd-udev.service(8)

rd.udev.exec_delay=
 kernel-command-line(7), systemd-udev.service(8)

rd.udev.log_level=
 kernel-command-line(7), systemd-udev.service(8)

rd.udev.timeout_signal=
 kernel-command-line(7), systemd-udev.service(8)

rd.veritytab=
 kernel-command-line(7)

rescue
 kernel-command-line(7), systemd(1)

resume=
 kernel-command-line(7), systemd-hibernate-resume-generator(8)

resumeflags=
 kernel-command-line(7), systemd-hibernate-resume-generator(8)

ro
 kernel-command-line(7), systemd-gpt-auto-generator(8)

root=
 kernel-command-line(7), systemd-fstab-generator(8), systemd-gpt-auto-generator(8)

rootflags=
 kernel-command-line(7), systemd-fstab-generator(8)

rootfstype=
 kernel-command-line(7), systemd-fstab-generator(8)

roothash=
 kernel-command-line(7), systemd-veritysetup-generator(8)

rw

kernel-command-line(7), systemd-gpt-auto-generator(8)

s

kernel-command-line(7), systemd(1)

single

kernel-command-line(7), systemd(1)

systemd.clock-usec=

kernel-command-line(7)

systemd.condition-first-boot=

kernel-command-line(7)

systemd.condition-needs-update=

kernel-command-line(7)

systemd.confirm_spawn

kernel-command-line(7), systemd(1)

systemd.cpu_affinity=

kernel-command-line(7)

systemd.crash_chvt

kernel-command-line(7), systemd(1)

systemd.crash_reboot

kernel-command-line(7), systemd(1)

systemd.crash_shell

kernel-command-line(7), systemd(1)

systemd.debug_shell

kernel-command-line(7)

systemd.default_standard_error=

kernel-command-line(7), systemd(1)

systemd.default_standard_output=

kernel-command-line(7), systemd(1)

systemd.default_timeout_start_sec=

kernel-command-line(7)

systemd.dump_core

kernel-command-line(7), systemd(1)

systemd.early_core_pattern=

kernel-command-line(7)

systemd.firstboot=
 kernel-command-line(7)

systemd.gpt_auto
 systemd-gpt-auto-generator(8)

systemd.gpt_auto=
 kernel-command-line(7)

systemd.hostname=
 kernel-command-line(7)

systemd.journald.forward_to_console=
 kernel-command-line(7), systemd-journald.service(8)

systemd.journald.forward_to_kmsg=
 kernel-command-line(7), systemd-journald.service(8)

systemd.journald.forward_to_syslog=
 kernel-command-line(7), systemd-journald.service(8)

systemd.journald.forward_to_wall=
 kernel-command-line(7), systemd-journald.service(8)

systemd.legacy_systemd_cgroup_controller
 kernel-command-line(7), systemd(1)

systemd.log_color
 kernel-command-line(7), systemd(1)

systemd.log_level=
 kernel-command-line(7), systemd(1)

systemd.log_location
 systemd(1)

systemd.log_location=
 kernel-command-line(7)

systemd.log_target=
 kernel-command-line(7), systemd(1)

systemd.log_tid
 systemd(1)

systemd.log_time
 systemd(1)

systemd.machine_id=

kernel-command-line(7), systemd(1)

systemd.mask=
kernel-command-line(7)

systemd.random-seed=
kernel-command-line(7)

systemd.restore_state=
kernel-command-line(7), systemd-backlight@.service(8), systemd-rfkill.service(8)

systemd.run=
kernel-command-line(7)

systemd.run_failure_action=
kernel-command-line(7)

systemd.run_success_action=
kernel-command-line(7)

systemd.service_watchdogs
kernel-command-line(7)

systemd.service_watchdogs=
systemd(1)

systemd.setenv=
kernel-command-line(7), systemd(1)

systemd.show_status
kernel-command-line(7), systemd(1)

systemd.status_unit_format=
kernel-command-line(7), systemd(1)

systemd.swap
systemd-fstab-generator(8)

systemd.unified_cgroup_hierarchy
kernel-command-line(7), systemd(1)

systemd.unit=
kernel-command-line(7), systemd(1)

systemd.verity.root_options=
kernel-command-line(7)

systemd.verity=
kernel-command-line(7), systemd-veritysetup-generator(8)

systemd.verity_root_data=
 kernel-command-line(7), systemd-veritysetup-generator(8)

systemd.verity_root_hash=
 kernel-command-line(7), systemd-veritysetup-generator(8)

systemd.verity_root_options=
 systemd-veritysetup-generator(8)

systemd.volatile=
 kernel-command-line(7), systemd-fstab-generator(8)

systemd.wants=
 kernel-command-line(7)

systemd.watchdog_device=
 kernel-command-line(7)

udev.blockdev_read_only
 kernel-command-line(7), systemd-udev.service(8)

udev.children_max=
 kernel-command-line(7), systemd-udev.service(8)

udev.event_timeout=
 kernel-command-line(7), systemd-udev.service(8)

udev.exec_delay=
 kernel-command-line(7), systemd-udev.service(8)

udev.log_level=
 kernel-command-line(7), systemd-udev.service(8)

udev.timeout_signal=
 kernel-command-line(7), systemd-udev.service(8)

vconsole.font=
 kernel-command-line(7)

vconsole.font_map=
 kernel-command-line(7)

vconsole.font_unimap=
 kernel-command-line(7)

vconsole.keymap=
 kernel-command-line(7)

vconsole.keymap_toggle=

kernel-command-line(7)

veritytab=

kernel-command-line(7)

vlan=

systemd-network-generator.service(8)

ENVIRONMENT VARIABLES

Environment variables understood by the systemd manager and other programs and environment variable-compatible settings.

\$CACHE_DIRECTORY

systemd.exec(5)

\$CONFIGURATION_DIRECTORY

systemd.exec(5)

\$CREDENTIALS_DIRECTORY

systemd.exec(5)

\$EMAIL

pam_systemd(8)

\$EXIT_CODE

systemd.exec(5)

\$EXIT_STATUS

systemd.exec(5)

\$HOME

systemd.exec(5)

\$INVOCATION_ID

systemd.exec(5)

\$JOURNAL_STREAM

systemd.exec(5)

\$LANG

pam_systemd(8), systemd.exec(5)

\$LISTEN_FDNAMES

sd_listen_fds(3), systemd(1), systemd-socket-activate(1), systemd.exec(5)

\$LISTEN_FDS

sd_listen_fds(3), systemd(1), systemd-socket-activate(1), systemd.exec(5)

\$LISTEN_PID

sd_listen_fds(3), systemd(1), systemd-socket-activate(1), systemd.exec(5)

\$LOGNAME

systemd.exec(5)

\$LOGS_DIRECTORY

systemd.exec(5)

\$LOG_NAMESPACE

systemd.exec(5)

\$MAINPID

systemd.exec(5)

\$MANAGERPID

systemd.exec(5)

\$NOTIFY_SOCKET

sd_notify(3), systemd(1), systemd.exec(5)

\$PATH

systemd.exec(5)

\$PIDFILE

systemd.exec(5)

\$PREVLEVEL

runlevel(8)

\$RUNLEVEL

runlevel(8)

\$RUNTIME_DIRECTORY

systemd.exec(5)

\$SERVICE_RESULT

systemd.exec(5)

\$SHELL

systemd.exec(5)

\$STATE_DIRECTORY

systemd.exec(5)

\$SYSTEMD_COLORS

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemd(1),
systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-tmpfiles(8),
timedatectl(1)

\$SYSTEMD_DEBUGGER

coredumpctl(1)

\$SYSTEMD_EDITOR

systemctl(1)

\$SYSTEMD_ENVIRONMENT_GENERATOR_PATH

systemd(1)

\$SYSTEMD_EXEC_PID

systemd.exec(5)

\$SYSTEMD_GENERATOR_PATH

systemd(1)

\$SYSTEMD_LESS

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemd(1),
systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-tmpfiles(8),
timedatectl(1)

\$SYSTEMD_LESSCHARSET

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemd(1),
systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-tmpfiles(8),
timedatectl(1)

\$SYSTEMD_LOG_COLOR

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemd(1),
systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-socket-activate(1),
systemd-tmpfiles(8), timedatectl(1)

\$SYSTEMD_LOG_LEVEL

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemd(1),
systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-socket-activate(1),
systemd-tmpfiles(8), timedatectl(1)

\$SYSTEMD_LOG_LOCATION

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemd(1),
systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-socket-activate(1),
systemd-tmpfiles(8), timedatectl(1)

\$SYSTEMD_LOG_TARGET

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemd(1),
systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-socket-activate(1),

systemd-tmpfiles(8), timedatectl(1)

\$SYSTEMD_LOG_TID

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemd(1),
systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), timedatectl(1)

\$SYSTEMD_LOG_TIME

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemd(1),
systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-socket-activate(1),
systemd-tmpfiles(8), timedatectl(1)

\$SYSTEMD_NSS_RESOLVE_VALIDATE

nss-resolve(8)

\$SYSTEMD_PAGER

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemd(1),
systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-tmpfiles(8),
timedatectl(1)

\$SYSTEMD_PAGERSECURE

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemd(1),
systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-tmpfiles(8),
timedatectl(1)

\$SYSTEMD_RANDOM_SEED_CREDIT

systemd-random-seed.service(8)

\$SYSTEMD_UNIT_PATH

systemd(1)

\$SYSTEMD_URLIFY

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemd(1),
systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-tmpfiles(8),
timedatectl(1)

\$TERM

systemd.exec(5)

\$TZ

pam_systemd(8)

\$USER

systemd.exec(5)

\$WATCHDOG_PID

sd_watchdog_enabled(3), systemd.exec(5)

\$WATCHDOG_USEC

sd_watchdog_enabled(3), systemd.exec(5)

\$XDG_CONFIG_DIRS

systemd(1)

\$XDG_CONFIG_HOME

systemd(1)

\$XDG_DATA_DIRS

systemd(1)

\$XDG_DATA_HOME

systemd(1)

\$XDG_RUNTIME_DIR

pam_systemd(8), systemd.exec(5)

\$XDG_SEAT

pam_systemd(8)

\$XDG_SESSION_CLASS

pam_systemd(8)

\$XDG_SESSION_DESKTOP

pam_systemd(8)

\$XDG_SESSION_ID

pam_systemd(8)

\$XDG_SESSION_TYPE

pam_systemd(8)

\$XDG_VTNR

pam_systemd(8)

ANSI_COLOR=

os-release(5)

BUG_REPORT_URL=

os-release(5)

BUILD_ID=

os-release(5)

CHASSIS=

machine-info(5)

CPE_NAME=
os-release(5)

DEFAULT_HOSTNAME=
os-release(5)

DEPLOYMENT=
machine-info(5)

DOCUMENTATION_URL=
os-release(5)

HOME_URL=
os-release(5)

ICON_NAME=
machine-info(5)

ID=
os-release(5)

ID_LIKE=
os-release(5)

IMAGE_ID=
os-release(5)

IMAGE_VERSION=
os-release(5)

LOCATION=
machine-info(5)

LOGO=
os-release(5)

NAME=
os-release(5)

PRETTY_HOSTNAME=
machine-info(5)

PRETTY_NAME=
os-release(5)

PRIVACY_POLICY_URL=
os-release(5)

SUPPORT_URL=

os-release(5)

SYSEXT_LEVEL=

os-release(5)

VARIANT=

os-release(5)

VARIANT_ID=

os-release(5)

VERSION=

os-release(5)

VERSION_CODENAME=

os-release(5)

VERSION_ID=

os-release(5)

EFI VARIABLES

EFI variables understood by systemd-boot(7) and other programs.

LoaderBootCountPath

systemd-boot(7)

LoaderConfigTimeout

systemd-boot(7)

LoaderConfigTimeoutOneShot

systemd-boot(7)

LoaderDevicePartUUID

systemd-boot(7)

LoaderEntries

systemd-boot(7)

LoaderEntryDefault

systemd-boot(7)

LoaderEntryOneShot

systemd-boot(7)

LoaderEntrySelected

systemd-boot(7)

LoaderFeatures

systemd-boot(7)

LoaderFirmwareInfo

systemd-boot(7)

LoaderFirmwareType

systemd-boot(7)

LoaderImageIdentifier

systemd-boot(7)

LoaderInfo

systemd-boot(7)

LoaderRandomSeed

systemd-boot(7)

LoaderSystemToken

systemd-boot(7)

LoaderTimeExecUsec

systemd-boot(7)

LoaderTimeInitUsec

systemd-boot(7)

LoaderTimeMenuUsec

systemd-boot(7)

HOME AREA/USER ACCOUNT DIRECTIVES

Directives for configuring home areas and user accounts via systemd-homed.service(8).

UDEV DIRECTIVES

Directives for configuring systemd units through the udev database.

\$\$

udev(7)

\$attr{file}

udev(7)

\$devnode

udev(7)

\$devpath

udev(7)

\$driver

udev(7)

\$env{key}

udev(7)
\$id
udev(7)
\$kernel
udev(7)
\$links
udev(7)
\$major
udev(7)
\$minor
udev(7)
\$name
udev(7)
\$number
udev(7)
\$parent
udev(7)
\$result
udev(7)
\$root
udev(7)
\$sys
udev(7)
"%%"
udev(7)
%E{key}
udev(7)
"%M"
udev(7)
"%N"
udev(7)
"%P"
udev(7)

"%S"

udev(7)

"%b"

udev(7)

%c

udev(7)

%k

udev(7)

"%m"

udev(7)

"%n"

udev(7)

"%p"

udev(7)

%r

udev(7)

%s{file}

udev(7)

ACTION

udev(7)

ATTRS{filename}

udev(7)

ATTR{filename}

udev(7)

CONST{key}

udev(7)

DEVPATH

udev(7)

DRIVER

udev(7)

DRIVERS

udev(7)

ENV{key}

udev(7)

GOTO

udev(7)

GROUP

udev(7)

ID_AUTOSEAT

sd-login(3)

ID_FOR_SEAT

sd-login(3)

ID_MODEL=

systemd.device(5)

ID_MODEL_FROM_DATABASE=

systemd.device(5)

ID_SEAT

sd-login(3)

IMPORT{type}

udev(7)

KERNEL

udev(7)

KERNELS

udev(7)

LABEL

udev(7)

MODE

udev(7)

NAME

udev(7)

OPTIONS

udev(7)

OWNER

udev(7)

PROGRAM

udev(7)

RESULT

udev(7)

RUN{type}

udev(7)

SECLABEL{module}

udev(7)

SUBSYSTEM

udev(7)

SUBSYSTEMS

udev(7)

SYMLINK

udev(7)

SYSCTL{kernel parameter}

udev(7)

SYSTEMD_ALIAS=

systemd.device(5)

SYSTEMD_MOUNT_OPTIONS=

systemd-mount(1)

SYSTEMD_MOUNT_WHERE=

systemd-mount(1)

SYSTEMD_READY=

systemd.device(5)

SYSTEMD_USER_WANTS=

systemd.device(5)

SYSTEMD_WANTS=

systemd.device(5)

TAG

udev(7)

TAGS

udev(7)

TEST{octal mode mask}

udev(7)

db_persist

```
udev(7)
link_priority=
udev(7)
log_level=
udev(7)
nowatch
udev(7)
static_node=
udev(7)
string_escape=
udev(7)
watch
udev(7)
```

NETWORK DIRECTIVES

Directives for configuring network links through the net-setup-link udev builtin and networks through systemd-networkd.

```
ARP=
systemd.network(5)
ARPAllTargets=
systemd.netdev(5)
ARPIPTargets=
systemd.netdev(5)
ARPIntervalSec=
systemd.netdev(5)
ARPValidate=
systemd.netdev(5)
Activate=
systemd.netdev(5)
ActivationPolicy=
systemd.network(5)
ActiveSlave=
systemd.network(5)
AdActorSystem=
```

systemd.netdev(5)
AdActorSystemPriority=
systemd.netdev(5)
AdSelect=
systemd.netdev(5)
AdUserPortKey=
systemd.netdev(5)
AddPrefixRoute=
systemd.network(5)
Address=
systemd.network(5)
AddressAutoconfiguration=
systemd.network(5)
Advertise=
systemd.link(5)
AgeingTimeSec=
systemd.netdev(5)
Aggregation=
systemd.netdev(5)
Alias=
systemd.link(5)
AllMulticast=
systemd.network(5)
AllSlavesActive=
systemd.netdev(5)
AllowList=
systemd.network(5)
AllowLocalRemote=
systemd.netdev(5)
AllowPortToBeRoot=
systemd.network(5)
AllowedIPs=
systemd.netdev(5)

AlternativeName=

systemd.link(5)

AlternativeNamesPolicy=

systemd.link(5)

Announce=

systemd.network(5)

Anonymize=

systemd.network(5)

Architecture=

systemd.link(5), systemd.netdev(5), systemd.network(5)

Assign=

systemd.network(5)

AssignToLoopback=

systemd.netdev(5)

AssociatedWith=

systemd.network(5)

AutoJoin=

systemd.network(5)

AutoNegotiation=

systemd.link(5)

AutoNegotiationFlowControl=

systemd.link(5)

BSSID=

systemd.network(5)

Bands=

systemd.network(5)

Bandwidth=

systemd.network(5)

BatmanAdvanced=

systemd.network(5)

BindCarrier=

systemd.network(5)

BindToInterface=

systemd.network(5)

BitRate=

systemd.network(5)

BitsPerSecond=

systemd.link(5)

Blackhole=

systemd.network(5)

Bond=

systemd.network(5)

Bridge=

systemd.network(5)

BridgeLoopAvoidance=

systemd.netdev(5)

Broadcast=

systemd.network(5)

BroadcastMulticastQueueLength=

systemd.netdev(5)

Buckets=

systemd.network(5)

BufferBytes=

systemd.network(5)

BurstBytes=

systemd.network(5)

BusErrorReporting=

systemd.network(5)

CEThresholdSec=

systemd.network(5)

Cache=

resolved.conf(5)

CacheFromLocalhost=

resolved.conf(5)

CeilBufferBytes=

systemd.network(5)

CeilRate=

systemd.network(5)

ClassId=

systemd.network(5)

ClientIdentifier=

systemd.network(5)

CombinedChannels=

systemd.link(5)

ConfigureWithoutCarrier=

systemd.network(5)

ConnectionRetrySec=

timesyncd.conf(5)

CopyDSCP=

systemd.netdev(5)

Cost=

systemd.network(5)

DHCP=

systemd.network(5)

DHCPv6Server=

systemd.network(5)

DHCPv6Client=

systemd.network(5)

DHCPv6PrefixDelegation=

systemd.network(5)

DNS=

resolved.conf(5), systemd.network(5)

DNSDefaultRoute=

systemd.network(5)

DNSLifetimeSec=

systemd.network(5)

DNSOverTLS=

resolved.conf(5), systemd.network(5)

DNSSEC=

resolved.conf(5), systemd.network(5)

DNSSECNegativeTrustAnchors=
systemd.network(5)

DNSStubListener=
resolved.conf(5)

DNSStubListenerExtra=
resolved.conf(5)

DUIDRawData=
networkd.conf(5), systemd.network(5)

DUIDType=
networkd.conf(5), systemd.network(5)

DataBitRate=
systemd.network(5)

DataSamplePoint=
systemd.network(5)

DefaultClass=
systemd.network(5)

DefaultLeaseTimeSec=
systemd.network(5)

DefaultPVID=
systemd.netdev(5)

DefaultRouteOnDevice=
systemd.network(5)

DefaultVirtualQueue=
systemd.network(5)

DelayJitterSec=
systemd.network(5)

DelaySec=
systemd.network(5)

DenyList=
systemd.network(5)

Description=
systemd.link(5), systemd.netdev(5), systemd.network(5)

Destination=

systemd.network(5)

DestinationPort=

systemd.netdev(5), systemd.network(5)

DiscoverPathMTU=

systemd.netdev(5)

DistributedArpTable=

systemd.netdev(5)

Domains=

resolved.conf(5), systemd.network(5)

DownDelaySec=

systemd.netdev(5)

Driver=

systemd.link(5), systemd.network(5)

Duplex=

systemd.link(5)

DuplicateAddressDetection=

systemd.network(5)

DuplicateRate=

systemd.network(5)

DynamicTransmitLoadBalancing=

systemd.netdev(5)

ECN=

systemd.network(5)

ERSPANIndex=

systemd.netdev(5)

EgressQOSMaps=

systemd.netdev(5)

EgressUntagged=

systemd.network(5)

EmitDNS=

systemd.network(5)

EmitDomains=

systemd.network(5)

EmitLLDP=

systemd.network(5)

EmitLPR=

systemd.network(5)

EmitNTP=

systemd.network(5)

EmitPOP3=

systemd.network(5)

EmitRouter=

systemd.network(5)

EmitSIP=

systemd.network(5)

EmitSMTP=

systemd.network(5)

EmitTimezone=

systemd.network(5)

Encapsulation=

systemd.netdev(5)

EncapsulationLimit=

systemd.netdev(5)

EncapsulationType=

systemd.netdev(5)

Encrypt=

systemd.netdev(5)

Endpoint=

systemd.netdev(5)

EtherType=

systemd.netdev(5)

FDBAgeingSec=

systemd.netdev(5)

FDMode=

systemd.network(5)

FDNonISO=

systemd.network(5)

FOUDestinationPort=

systemd.netdev(5)

FOUSourcePort=

systemd.netdev(5)

FailOverMACPolicy=

systemd.netdev(5)

FallbackDNS=

resolved.conf(5)

FallbackLeaseLifetimeSec=

systemd.network(5)

FallbackNTP=

timesyncd.conf(5)

Family=

systemd.network(5)

FastLeave=

systemd.network(5)

FastOpenNoCookie=

systemd.network(5)

FirewallMark=

systemd.netdev(5), systemd.network(5)

Firmware=

systemd.link(5), systemd.netdev(5), systemd.network(5)

Flags=

systemd.netdev(5)

FlowLabel=

systemd.netdev(5)

FlowLimit=

systemd.network(5)

Flows=

systemd.network(5)

FooOverUDP=

systemd.netdev(5)

ForceDHCPv6PDOtherInformation=

systemd.network(5)

ForwardDelaySec=

systemd.netdev(5)

Fragmentation=

systemd.netdev(5)

From=

systemd.network(5)

GVRP=

systemd.netdev(5)

Gateway=

systemd.network(5)

GatewayBandwidthDown=

systemd.netdev(5)

GatewayBandwidthUp=

systemd.netdev(5)

GatewayMode=

systemd.netdev(5)

GatewayOnLink=

systemd.network(5)

GenericProtocolExtension=

systemd.netdev(5)

GenericRIO=

systemd.network(5)

GenericReceiveOffload=

systemd.link(5)

GenericSegmentOffloadMaxBytes=

systemd.link(5)

GenericSegmentOffloadMaxSegments=

systemd.link(5)

GenericSegmentationOffload=

systemd.link(5)

GratuitousARP=

systemd.netdev(5)

Group=

systemd.netdev(5), systemd.network(5)

GroupForwardMask=

systemd.netdev(5)

GroupPolicyExtension=

systemd.netdev(5)

HairPin=

systemd.network(5)

Handle=

systemd.network(5)

HelloTimeSec=

systemd.netdev(5)

HomeAddress=

systemd.network(5)

HopPenalty=

systemd.netdev(5)

Host=

systemd.link(5), systemd.netdev(5), systemd.network(5)

Hostname=

systemd.network(5)

IAID=

systemd.network(5)

IPDoNotFragment=

systemd.netdev(5)

IPForward=

systemd.network(5)

IPMasquerade=

systemd.network(5)

IPProtocol=

systemd.network(5)

IPServiceType=

systemd.network(5)

IPVLAN=

systemd.network(5)

IPVTAP=

systemd.network(5)

IPv4AcceptLocal=

systemd.network(5)

IPv4LLRoute=

systemd.network(5)

IPv4ProxyARP=

systemd.network(5)

IPv4RouteLocalnet=

systemd.network(5)

IPv6AcceptRA=

systemd.network(5)

IPv6DuplicateAddressDetection=

systemd.network(5)

IPv6FlowLabel=

systemd.netdev(5)

IPv6HopLimit=

systemd.network(5)

IPv6LinkLocalAddressGenerationMode=

systemd.network(5)

IPv6MTUBytes=

systemd.network(5)

IPv6Preference=

systemd.network(5)

IPv6PrivacyExtensions=

systemd.network(5)

IPv6ProxyNDP=

systemd.network(5)

IPv6ProxyNDPAddress=

systemd.network(5)

IPv6RapidDeploymentPrefix=
systemd.netdev(5)

IPv6SendRA=
systemd.network(5)

IPv6StableSecretAddress=
systemd.network(5)

IPv6Token=
systemd.network(5)

ISATAP=
systemd.netdev(5)

Id=
systemd.netdev(5), systemd.network(5)

IgnoreCarrierLoss=
systemd.network(5)

IncomingInterface=
systemd.network(5)

Independent=
systemd.netdev(5)

IngressQOSMaps=
systemd.netdev(5)

InitialAdvertisedReceiveWindow=
systemd.network(5)

InitialCongestionWindow=
systemd.network(5)

InitialQuantumBytes=
systemd.network(5)

InputKey=
systemd.netdev(5)

InterfaceId=
systemd.netdev(5)

IntervalSec=
systemd.network(5)

InvertRule=

systemd.network(5)

KeepConfiguration=

systemd.network(5)

KernelCommandLine=

systemd.link(5), systemd.netdev(5), systemd.network(5)

KernelVersion=

systemd.link(5), systemd.netdev(5), systemd.network(5)

Key=

systemd.netdev(5)

KeyFile=

systemd.netdev(5)

KeyId=

systemd.netdev(5)

Kind=

systemd.netdev(5)

L2MissNotification=

systemd.netdev(5)

L2TP=

systemd.network(5)

L3MissNotification=

systemd.netdev(5)

LACPTransmitRate=

systemd.netdev(5)

LLDP=

systemd.network(5)

LLMNR=

resolved.conf(5), systemd.network(5)

LPR=

systemd.network(5)

Label=

systemd.network(5)

LargeReceiveOffload=

systemd.link(5)

LatencySec=

systemd.network(5)

Layer2SpecificHeader=

systemd.netdev(5)

LearnPacketIntervalSec=

systemd.netdev(5)

Learning=

systemd.network(5)

LifetimeSec=

systemd.network(5)

LimitBytes=

systemd.network(5)

LinkLayerAddress=

systemd.network(5)

LinkLocalAddressing=

systemd.network(5)

LinkState=

systemd.network(5)

ListenOnly=

systemd.network(5)

ListenPort=

systemd.netdev(5), systemd.network(5)

Local=

systemd.netdev(5)

LooseBinding=

systemd.netdev(5)

LossRate=

systemd.network(5)

MACAddress=

systemd.link(5), systemd.netdev(5), systemd.network(5)

MACAddressPolicy=

systemd.link(5)

MACSpoofCheck=

systemd.network(5)

MACVLAN=

systemd.network(5)

MACVTAP=

systemd.network(5)

MACsec=

systemd.network(5)

MIIMonitorSec=

systemd.netdev(5)

MPUBytes=

systemd.network(5)

MTUBytes=

systemd.link(5), systemd.netdev(5), systemd.network(5)

MUDURL=

systemd.network(5)

MVRP=

systemd.netdev(5)

MacLearning=

systemd.netdev(5)

ManageForeignRoutes=

networkd.conf(5)

ManageForeignRoutingPolicyRules=

networkd.conf(5)

ManageTemporaryAddress=

systemd.network(5)

Managed=

systemd.network(5)

MaxAgeSec=

systemd.netdev(5)

MaxAttempts=

systemd.network(5)

MaxLeaseTimeSec=

systemd.network(5)

MaxPacketBytes=

systemd.network(5)

MaximumFDBEntries=

systemd.netdev(5)

MaximumRate=

systemd.network(5)

MemoryLimitBytes=

systemd.network(5)

Metric=

systemd.network(5)

MinLinks=

systemd.netdev(5)

Mode=

systemd.netdev(5)

MultiPathRoute=

systemd.network(5)

MultiQueue=

systemd.netdev(5)

Multicast=

systemd.network(5)

MulticastDNS=

resolved.conf(5), systemd.network(5)

MulticastFlood=

systemd.network(5)

MulticastGroupAddress=

systemd.network(5)

MulticastIGMPVersion=

systemd.netdev(5)

MulticastQuerier=

systemd.netdev(5)

MulticastRouter=

systemd.network(5)

MulticastSnooping=

systemd.netdev(5)

MulticastToUnicast=

systemd.network(5)

NTP=

systemd.network(5), timesyncd.conf(5)

Name=

systemd.dnssd(5), systemd.link(5), systemd.netdev(5), systemd.network(5)

NamePolicy=

systemd.link(5)

NeighborSuppression=

systemd.network(5)

NextHop=

systemd.network(5)

OnLink=

systemd.network(5)

OriginalName=

systemd.link(5)

OriginatorIntervalSec=

systemd.netdev(5)

OrphanMask=

systemd.network(5)

OtherChannels=

systemd.link(5)

OtherInformation=

systemd.network(5)

OutgoingInterface=

systemd.network(5)

OutputKey=

systemd.netdev(5)

OverheadBytes=

systemd.network(5)

POP3=

systemd.network(5)

PVID=

systemd.network(5)

Pacing=

systemd.network(5)

PacketInfo=

systemd.netdev(5)

PacketLimit=

systemd.network(5)

PacketNumber=

systemd.netdev(5)

PacketsPerSlave=

systemd.netdev(5)

Parent=

systemd.network(5)

Path=

systemd.link(5), systemd.network(5)

PeakRate=

systemd.network(5)

Peer=

systemd.netdev(5), systemd.network(5)

PeerPort=

systemd.netdev(5)

PeerSessionId=

systemd.netdev(5)

PeerTunnelId=

systemd.netdev(5)

PermanentMACAddress=

systemd.link(5), systemd.network(5)

PersistentKeepalive=

systemd.netdev(5)

PerturbPeriodSec=

systemd.network(5)

PollIntervalMaxSec=

timesyncd.conf(5)
PollIntervalMinSec=
timesyncd.conf(5)
PoolOffset=
systemd.network(5)
PoolSize=
systemd.network(5)
Port=
systemd.dnssd(5), systemd.link(5), systemd.netdev(5)
PortRange=
systemd.netdev(5)
PreferredLifetime=
systemd.network(5)
PreferredLifetimeSec=
systemd.network(5)
PreferredSource=
systemd.network(5)
Prefix=
systemd.network(5)
PrefixAllowList=
systemd.network(5)
PrefixDelegationHint=
systemd.network(5)
PrefixDenyList=
systemd.network(5)
PresharedKey=
systemd.netdev(5)
PresharedKeyFile=
systemd.netdev(5)
PrimaryReselectPolicy=
systemd.netdev(5)
PrimarySlave=
systemd.network(5)

Priority=

systemd.dnssd(5), systemd.netdev(5), systemd.network(5)

PriorityMap=

systemd.network(5)

PrivateKey=

systemd.netdev(5)

PrivateKeyFile=

systemd.netdev(5)

Promiscuous=

systemd.network(5)

Property=

systemd.link(5), systemd.network(5)

Protocol=

systemd.netdev(5), systemd.network(5)

ProxyARP=

systemd.network(5)

ProxyARPWiFi=

systemd.network(5)

PublicKey=

systemd.netdev(5)

QualityOfService=

systemd.network(5)

QuantumBytes=

systemd.network(5)

QueryReceiveSideScaling=

systemd.network(5)

QuickAck=

systemd.network(5)

RapidCommit=

systemd.network(5)

Rate=

systemd.network(5)

RateToQuantum=

systemd.network(5)

ReadEtcHosts=
resolved.conf(5)

ReceiveChecksumOffload=
systemd.link(5)

ReceiveQueues=
systemd.link(5)

ReduceARPProxy=
systemd.netdev(5)

RelayAgentCircuitId=
systemd.network(5)

RelayAgentRemoteId=
systemd.network(5)

RelayTarget=
systemd.network(5)

Remote=
systemd.netdev(5)

RemoteChecksumRx=
systemd.netdev(5)

RemoteChecksumTx=
systemd.netdev(5)

ReorderHeader=
systemd.netdev(5)

RequestBroadcast=
systemd.network(5)

RequestOptions=
systemd.network(5)

RequiredFamilyForOnline=
systemd.network(5)

RequiredForOnline=
systemd.network(5)

ResendIGMP=
systemd.netdev(5)

ResolveUnicastSingleLabel=

resolved.conf(5)

RestartSec=

systemd.network(5)

RootDistanceMaxSec=

timesyncd.conf(5)

Route=

systemd.network(5)

RouteAllowList=

systemd.network(5)

RouteDenyList=

systemd.network(5)

RouteMTUBytes=

systemd.network(5)

RouteMetric=

systemd.network(5)

RouteShortCircuit=

systemd.netdev(5)

RouteTable=

networkd.conf(5), systemd.network(5)

RouterAllowList=

systemd.network(5)

RouterDenyList=

systemd.network(5)

RouterLifetimeSec=

systemd.network(5)

RouterPreference=

systemd.network(5)

RoutesToDNS=

systemd.network(5)

RoutesToNTP=

systemd.network(5)

RoutingAlgorithm=

systemd.netdev(5)

RxBufferSize=

systemd.link(5)

RxChannels=

systemd.link(5)

RxFlowControl=

systemd.link(5)

RxJumboBufferSize=

systemd.link(5)

RxMiniBufferSize=

systemd.link(5)

SIP=

systemd.network(5)

SMTP=

systemd.network(5)

SSID=

systemd.network(5)

STP=

systemd.netdev(5)

SamplePoint=

systemd.network(5)

Scope=

systemd.network(5)

SendDecline=

systemd.network(5)

SendHostname=

systemd.network(5)

SendOption=

systemd.network(5)

SendRelease=

systemd.network(5)

SendVendorOption=

systemd.network(5)

SerializeTunneledPackets=

systemd.netdev(5)

ServerAddress=

systemd.network(5)

SessionId=

systemd.netdev(5)

Source=

systemd.network(5)

SourceMACAddress=

systemd.netdev(5)

SourcePort=

systemd.network(5)

SpeedMeter=

networkd.conf(5)

SpeedMeterIntervalSec=

networkd.conf(5)

StrictBands=

systemd.network(5)

SubnetId=

systemd.network(5)

SuppressPrefixLength=

systemd.network(5)

TCP6SegmentationOffload=

systemd.link(5)

TCPAdvertisedMaximumSegmentSize=

systemd.network(5)

TCPSegmentationOffload=

systemd.link(5)

TOS=

systemd.netdev(5)

TTL=

systemd.netdev(5)

TTLPropagate=

systemd.network(5)

Table=

systemd.netdev(5), systemd.network(5)

TargetSec=

systemd.network(5)

Termination=

systemd.network(5)

Timezone=

systemd.network(5)

To=

systemd.network(5)

Token=

systemd.network(5)

TransmitChecksumOffload=

systemd.link(5)

TransmitHashPolicy=

systemd.netdev(5)

TransmitQueueLength=

systemd.link(5)

TransmitQueues=

systemd.link(5)

TripleSampling=

systemd.network(5)

Trust=

systemd.network(5)

Tunnel=

systemd.network(5)

TunnelId=

systemd.netdev(5)

TxBufferSize=

systemd.link(5)

TxChannels=

systemd.link(5)

TxFlowControl=
systemd.link(5)

TxtData=
systemd.dnssd(5)

TxtText=
systemd.dnssd(5)

Type=
systemd.dnssd(5), systemd.link(5), systemd.network(5)

TypeOfService=
systemd.network(5)

UDP6ZeroChecksumRx=
systemd.netdev(5)

UDP6ZeroChecksumTx=
systemd.netdev(5)

UDPChecksum=
systemd.netdev(5)

UDPDestinationPort=
systemd.netdev(5)

UDPSourcePort=
systemd.netdev(5)

UnicastFlood=
systemd.network(5)

Unmanaged=
systemd.network(5)

UpDelaySec=
systemd.netdev(5)

UplinkInterface=
systemd.network(5)

UseAddress=
systemd.network(5)

UseAutonomousPrefix=
systemd.network(5)

UseBPDU=

systemd.network(5)

UseDNS=

systemd.network(5)

UseDomains=

systemd.network(5)

UseForEncoding=

systemd.netdev(5)

UseGateway=

systemd.network(5)

UseHostname=

systemd.network(5)

UseMTU=

systemd.network(5)

UseNTP=

systemd.network(5)

UseOnLinkPrefix=

systemd.network(5)

UseRoutes=

systemd.network(5)

UseSIP=

systemd.network(5)

UseTimezone=

systemd.network(5)

User=

systemd.netdev(5), systemd.network(5)

UserClass=

systemd.network(5)

VLAN=

systemd.network(5)

VLANFiltering=

systemd.netdev(5)

VLANId=

systemd.network(5)

VLANProtocol=

systemd.netdev(5), systemd.network(5)

VNI=

systemd.netdev(5), systemd.network(5)

VNetHeader=

systemd.netdev(5)

VRF=

systemd.network(5)

VXLAN=

systemd.network(5)

ValidLifetimeSec=

systemd.network(5)

VendorClass=

systemd.network(5)

VendorClassIdentifier=

systemd.network(5)

VirtualFunction=

systemd.network(5)

VirtualQueues=

systemd.network(5)

Virtualization=

systemd.link(5), systemd.netdev(5), systemd.network(5)

WLANInterfaceType=

systemd.network(5)

WakeOnLan=

systemd.link(5)

Weight=

systemd.dnssd(5), systemd.network(5)

WithoutRA=

systemd.network(5)

Xfrm=

systemd.network(5)

Fields in the journal events with a well known meaning.

CODE_FILE=

systemd.journal-fields(7)

CODE_FUNC=

systemd.journal-fields(7)

CODE_LINE=

systemd.journal-fields(7)

COREDUMP=

systemd-coredump(8)

COREDUMP_CGROUP=

systemd-coredump(8)

COREDUMP_COMM=

systemd-coredump(8)

COREDUMP_CONTAINER_CMDLINE=

systemd-coredump(8)

COREDUMP_CWD=

systemd-coredump(8)

COREDUMP_ENVIRON=

systemd-coredump(8)

COREDUMP_EXE=

systemd-coredump(8)

COREDUMP_FILENAME=

systemd-coredump(8)

COREDUMP_GID=

systemd-coredump(8)

COREDUMP_HOSTNAME=

systemd-coredump(8)

COREDUMP_OPEN_FDS=

systemd-coredump(8)

COREDUMP_OWNER_UID=

systemd-coredump(8)

COREDUMP_PACKAGE_JSON=

systemd-coredump(8)

COREDUMP_PACKAGE_NAME=
systemd-coredump(8)

COREDUMP_PACKAGE_VERSION=
systemd-coredump(8)

COREDUMP_PID=
systemd-coredump(8)

COREDUMP_PROC_LIMITS=
systemd-coredump(8)

COREDUMP_PROC_MAPS=
systemd-coredump(8)

COREDUMP_PROC_MOUNTINFO=
systemd-coredump(8)

COREDUMP_PROC_STATUS=
systemd-coredump(8)

COREDUMP_RLIMIT=
systemd-coredump(8)

COREDUMP_ROOT=
systemd-coredump(8)

COREDUMP_SIGNAL=
systemd-coredump(8)

COREDUMP_SIGNAL_NAME=
systemd-coredump(8)

COREDUMP_SLICE=
systemd-coredump(8)

COREDUMP_TIMESTAMP=
systemd-coredump(8)

COREDUMP_TRUNCATED=
systemd-coredump(8)

COREDUMP_UID=
systemd-coredump(8)

COREDUMP_UNIT=
systemd-coredump(8), systemd.journal-fields(7)

COREDUMP_USER_UNIT=

systemd-coredump(8), systemd.journal-fields(7)

DOCUMENTATION=

systemd.journal-fields(7)

ERRNO=

systemd.journal-fields(7)

INVOCATION_ID=

systemd.journal-fields(7)

MESSAGE=

systemd-coredump(8), systemd.journal-fields(7)

MESSAGE_ID=

systemd.journal-fields(7)

OBJECT_AUDIT_LOGINUID=

systemd.journal-fields(7)

OBJECT_AUDIT_SESSION=

systemd.journal-fields(7)

OBJECT_CMDLINE=

systemd.journal-fields(7)

OBJECT_COMM=

systemd.journal-fields(7)

OBJECT_EXE=

systemd.journal-fields(7)

OBJECT_GID=

systemd.journal-fields(7)

OBJECT_PID=

systemd.journal-fields(7)

OBJECT_SYSTEMD_CGROUP=

systemd.journal-fields(7)

OBJECT_SYSTEMD_OWNER_UID=

systemd.journal-fields(7)

OBJECT_SYSTEMD_SESSION=

systemd.journal-fields(7)

OBJECT_SYSTEMD_UNIT=

systemd.journal-fields(7)

OBJECT_SYSTEMD_USER_UNIT=

systemd.journal-fields(7)

OBJECT_UID=

systemd.journal-fields(7)

PRIORITY=

systemd.journal-fields(7)

SYSLOG_FACILITY=

systemd.journal-fields(7)

SYSLOG_IDENTIFIER=

systemd.journal-fields(7)

SYSLOG_PID=

systemd.journal-fields(7)

SYSLOG_RAW=

systemd.journal-fields(7)

SYSLOG_TIMESTAMP=

systemd.journal-fields(7)

TID=

systemd.journal-fields(7)

UNIT=

systemd.journal-fields(7)

USER_INVOCATION_ID=

systemd.journal-fields(7)

USER_UNIT=

systemd.journal-fields(7)

_AUDIT_LOGINUID=

systemd.journal-fields(7)

_AUDIT_SESSION=

systemd.journal-fields(7)

_BOOT_ID=

systemd.journal-fields(7)

_CAP_EFFECTIVE=

systemd.journal-fields(7)

_CMDLINE=

systemd.journal-fields(7)

_COMM=
systemd.journal-fields(7)

_EXE=
systemd.journal-fields(7)

_GID=
systemd.journal-fields(7)

_HOSTNAME=
systemd.journal-fields(7)

_KERNEL_DEVICE=
systemd.journal-fields(7)

_KERNEL_SUBSYSTEM=
systemd.journal-fields(7)

_LINE_BREAK=
systemd.journal-fields(7)

_MACHINE_ID=
systemd.journal-fields(7)

_NAMESPACE=
systemd.journal-fields(7)

_PID=
systemd.journal-fields(7)

_SELINUX_CONTEXT=
systemd.journal-fields(7)

_SOURCE_REALTIME_TIMESTAMP=
systemd.journal-fields(7)

_STREAM_ID=
systemd.journal-fields(7)

_SYSTEMD_CGROUP=
systemd.journal-fields(7)

_SYSTEMD_INVOCATION_ID=
systemd.journal-fields(7)

_SYSTEMD_OWNER_UID=
systemd.journal-fields(7)

_SYSTEMD_SESSION=

systemd.journal-fields(7)

_SYSTEMD_SLICE=

systemd.journal-fields(7)

_SYSTEMD_UNIT=

systemd.journal-fields(7)

_SYSTEMD_USER_SLICE=

systemd.journal-fields(7)

_SYSTEMD_USER_UNIT=

systemd.journal-fields(7)

_TRANSPORT=

systemd.journal-fields(7)

_UDEV_DEVLINK=

systemd.journal-fields(7)

_UDEV_DEVNODE=

systemd.journal-fields(7)

_UDEV_SYSNAME=

systemd.journal-fields(7)

_UID=

systemd.journal-fields(7)

__CURSOR=

systemd.journal-fields(7)

__MONOTONIC_TIMESTAMP=

systemd.journal-fields(7)

__REALTIME_TIMESTAMP=

systemd.journal-fields(7)

PAM CONFIGURATION DIRECTIVES

Directives for configuring PAM behaviour.

class=

pam_systemd(8)

debug

pam_systemd(8)

desktop=

pam_systemd(8)
systemd.cpu_weight=
pam_systemd(8)
systemd.io_weight=
pam_systemd(8)
systemd.memory_max=
pam_systemd(8)
systemd.runtime_max_sec=
pam_systemd(8)
systemd.tasks_max=
pam_systemd(8)
type=
pam_systemd(8)

/ETC/CRYPTTAB, /ETC/VERITYTAB AND /ETC/FSTAB OPTIONS

Options which influence mounted filesystems and encrypted volumes.

_netdev
crypttab(5), systemd.mount(5), veritytab(5)
auto
systemd.mount(5), systemd.swap(5)
bitlk
crypttab(5)
check-at-most-once
veritytab(5)
cipher=
crypttab(5)
discard
crypttab(5)
fido2-cid=
crypttab(5)
fido2-device=
crypttab(5)
fido2-rp=
crypttab(5)

hash=

crypttab(5)

header=

crypttab(5)

headless=

crypttab(5)

ignore-corruption

veritytab(5)

ignore-zero-blocks

veritytab(5)

key-slot=

crypttab(5)

keyfile-erase

crypttab(5)

keyfile-offset=

crypttab(5)

keyfile-size=

crypttab(5)

keyfile-timeout=

crypttab(5)

luks

crypttab(5)

no-read-workqueue

crypttab(5)

no-write-workqueue

crypttab(5)

noauto

crypttab(5), systemd.mount(5), systemd.swap(5), veritytab(5)

nofail

crypttab(5), systemd.mount(5), systemd.swap(5), veritytab(5)

offset=

crypttab(5)

panic-on-corruption

veritytab(5)
password-echo=
crypttab(5)
pkcs11-uri=
crypttab(5)
plain
crypttab(5)
read-only
crypttab(5)
readonly
crypttab(5)
restart-on-corruption
veritytab(5)
root-hash-signature=
veritytab(5)
same-cpu-crypt
crypttab(5)
sector-size=
crypttab(5)
size=
crypttab(5)
skip=
crypttab(5)
submit-from-crypt-cpus
crypttab(5)
swap
crypttab(5)
tcrypt
crypttab(5)
tcrypt-hidden
crypttab(5)
tcrypt-keyfile=
crypttab(5)

tcrypt-system

crypttab(5)

tcrypt-veracrypt

crypttab(5)

timeout=

crypttab(5)

tmp=

crypttab(5)

tpm2-device=

crypttab(5)

tpm2-pcrs=

crypttab(5)

tries=

crypttab(5)

try-empty-password=

crypttab(5)

verify

crypttab(5)

x-initrd.attach

crypttab(5), veritytab(5)

x-initrd.mount

systemd.mount(5)

x-systemd.after=

systemd.mount(5)

x-systemd.automount

systemd.mount(5)

x-systemd.before=

systemd.mount(5)

x-systemd.device-bound

systemd.mount(5)

x-systemd.device-timeout=

crypttab(5), systemd.mount(5), systemd.swap(5)

x-systemd.growfs

systemd.mount(5)
x-systemd.idle-timeout=
systemd.mount(5)
x-systemd.makefs
systemd.mount(5), systemd.swap(5)
x-systemd.mount-timeout=
systemd.mount(5)
x-systemd.required-by=
systemd.mount(5)
x-systemd.requires-mounts-for=
systemd.mount(5)
x-systemd.requires=
systemd.mount(5)
x-systemd.rw-only
systemd.mount(5)
x-systemd.wanted-by=
systemd.mount(5)

SYSTEMD.NSPAWN(5) DIRECTIVES

Directives for configuring systemd-nspawn containers.

AmbientCapability=
systemd.nspawn(5)
Bind=
systemd.nspawn(5)
BindReadOnly=
systemd.nspawn(5)
BindUser=
systemd.nspawn(5)
Boot=
systemd.nspawn(5)
Bridge=
systemd.nspawn(5)
CPUAffinity=
systemd.nspawn(5)

Capability=

systemd.nspawn(5)

DropCapability=

systemd.nspawn(5)

Environment=

systemd.nspawn(5)

Ephemeral=

systemd.nspawn(5)

Hostname=

systemd.nspawn(5)

IPVLAN=

systemd.nspawn(5)

Inaccessible=

systemd.nspawn(5)

Interface=

systemd.nspawn(5)

KillSignal=

systemd.nspawn(5)

LimitAS=

systemd.nspawn(5)

LimitCORE=

systemd.nspawn(5)

LimitCPU=

systemd.nspawn(5)

LimitDATA=

systemd.nspawn(5)

LimitFSIZE=

systemd.nspawn(5)

LimitLOCKS=

systemd.nspawn(5)

LimitMEMLOCK=

systemd.nspawn(5)

LimitMSGQUEUE=

systemd.nspawn(5)

LimitNICE=

systemd.nspawn(5)

LimitNOFILE=

systemd.nspawn(5)

LimitNPROC=

systemd.nspawn(5)

LimitRSS=

systemd.nspawn(5)

LimitRTPRIO=

systemd.nspawn(5)

LimitRTTIME=

systemd.nspawn(5)

LimitSIGPENDING=

systemd.nspawn(5)

LimitSTACK=

systemd.nspawn(5)

LinkJournal=

systemd.nspawn(5)

MACVLAN=

systemd.nspawn(5)

MachineID=

systemd.nspawn(5)

NoNewPrivileges=

systemd.nspawn(5)

NotifyReady=

systemd.nspawn(5)

OOMScoreAdjust=

systemd.nspawn(5)

Overlay=

systemd.nspawn(5)

OverlayReadOnly=

systemd.nspawn(5)

Parameters=

systemd.nspawn(5)

Personality=

systemd.nspawn(5)

PivotRoot=

systemd.nspawn(5)

Port=

systemd.nspawn(5)

Private=

systemd.nspawn(5)

PrivateUsers=

systemd.nspawn(5)

PrivateUsersOwnership=

systemd.nspawn(5)

ProcessTwo=

systemd.nspawn(5)

ReadOnly=

systemd.nspawn(5)

ResolvConf=

systemd.nspawn(5)

SystemCallFilter=

systemd.nspawn(5)

TemporaryFileSystem=

systemd.nspawn(5)

Timezone=

systemd.nspawn(5)

User=

systemd.nspawn(5)

VirtualEthernet=

systemd.nspawn(5)

VirtualEthernetExtra=

systemd.nspawn(5)

Volatile=

systemd.nspawn(5)

WorkingDirectory=

systemd.nspawn(5)

Zone=

systemd.nspawn(5)

PROGRAM CONFIGURATION OPTIONS

Directives for configuring the behaviour of the systemd process and other tools through configuration files.

AllowHibernation=

systemd-sleep.conf(5)

AllowHybridSleep=

systemd-sleep.conf(5)

AllowSuspend=

systemd-sleep.conf(5)

AllowSuspendThenHibernate=

systemd-sleep.conf(5)

Audit=

journald.conf(5)

CPUAffinity=

systemd-system.conf(5)

CapabilityBoundingSet=

systemd-system.conf(5)

Compress=

coredump.conf(5), journald.conf(5)

CrashChangeVT=

systemd-system.conf(5)

CrashReboot=

systemd-system.conf(5)

CrashShell=

systemd-system.conf(5)

CtrlAltDelBurstAction=

systemd-system.conf(5)

DefaultBlockIOAccounting=

systemd-system.conf(5)

DefaultCPUAcounting=

systemd-system.conf(5)

DefaultEnvironment=

systemd-system.conf(5)

DefaultIOAccounting=

systemd-system.conf(5)

DefaultIPAccounting=

systemd-system.conf(5)

DefaultLimitAS=

systemd-system.conf(5)

DefaultLimitCORE=

systemd-system.conf(5)

DefaultLimitCPU=

systemd-system.conf(5)

DefaultLimitDATA=

systemd-system.conf(5)

DefaultLimitFSIZE=

systemd-system.conf(5)

DefaultLimitLOCKS=

systemd-system.conf(5)

DefaultLimitMEMLOCK=

systemd-system.conf(5)

DefaultLimitMSGQUEUE=

systemd-system.conf(5)

DefaultLimitNICE=

systemd-system.conf(5)

DefaultLimitNOFILE=

systemd-system.conf(5)

DefaultLimitNPROC=

systemd-system.conf(5)

DefaultLimitRSS=

systemd-system.conf(5)

DefaultLimitRTPRIO=

systemd-system.conf(5)

DefaultLimitRTTIME=

systemd-system.conf(5)

DefaultLimitSIGPENDING=

systemd-system.conf(5)

DefaultLimitSTACK=

systemd-system.conf(5)

DefaultMemoryAccounting=

systemd-system.conf(5)

DefaultMemoryPressureDurationSec=

oomd.conf(5)

DefaultMemoryPressureLimit=

oomd.conf(5)

DefaultOOMPolicy=

systemd-system.conf(5)

DefaultRestartSec=

systemd-system.conf(5)

DefaultStandardError=

systemd-system.conf(5)

DefaultStandardOutput=

systemd-system.conf(5)

DefaultStartLimitBurst=

systemd-system.conf(5)

DefaultStartLimitIntervalSec=

systemd-system.conf(5)

DefaultTasksAccounting=

systemd-system.conf(5)

DefaultTasksMax=

systemd-system.conf(5)

DefaultTimeoutAbortSec=

systemd-system.conf(5)

DefaultTimeoutStartSec=

systemd-system.conf(5)

DefaultTimeoutStopSec=
systemd-system.conf(5)

DefaultTimerAccuracySec=
systemd-system.conf(5)

DumpCore=
systemd-system.conf(5)

ExternalSizeMax=
coredump.conf(5)

ForwardToConsole=
journald.conf(5)

ForwardToKMsg=
journald.conf(5)

ForwardToSyslog=
journald.conf(5)

ForwardToWall=
journald.conf(5)

HandleHibernateKey=
logind.conf(5)

HandleLidSwitch=
logind.conf(5)

HandleLidSwitchDocked=
logind.conf(5)

HandleLidSwitchExternalPower=
logind.conf(5)

HandlePowerKey=
logind.conf(5)

HandleRebootKey=
logind.conf(5)

HandleSuspendKey=
logind.conf(5)

HibernateDelaySec=
systemd-sleep.conf(5)

HibernateKeyIgnoreInhibited=

logind.conf(5)

HibernateMode=

systemd-sleep.conf(5)

HibernateState=

systemd-sleep.conf(5)

HoldoffTimeoutSec=

logind.conf(5)

HybridSleepMode=

systemd-sleep.conf(5)

HybridSleepState=

systemd-sleep.conf(5)

IdleAction=

logind.conf(5)

IdleActionSec=

logind.conf(5)

InhibitDelayMaxSec=

logind.conf(5)

InhibitorsMax=

logind.conf(5)

JournalSizeMax=

coredump.conf(5)

KExecWatchdogSec=

systemd-system.conf(5)

KeepFree=

coredump.conf(5)

KillExcludeUsers=

logind.conf(5)

KillOnlyUsers=

logind.conf(5)

KillUserProcesses=

logind.conf(5)

LidSwitchIgnoreInhibited=

logind.conf(5)

LineMax=

 journald.conf(5)

LogColor=

 systemd-system.conf(5)

LogLevel=

 systemd-system.conf(5)

LogLocation=

 systemd-system.conf(5)

LogTarget=

 systemd-system.conf(5)

LogTime=

 systemd-system.conf(5)

ManagerEnvironment=

 systemd-system.conf(5)

MaxFileSec=

 journald.conf(5)

MaxLevelConsole=

 journald.conf(5)

MaxLevelKMsg=

 journald.conf(5)

MaxLevelStore=

 journald.conf(5)

MaxLevelSyslog=

 journald.conf(5)

MaxLevelWall=

 journald.conf(5)

MaxRetentionSec=

 journald.conf(5)

MaxUse=

 coredump.conf(5)

NAutoVTs=

 logind.conf(5)

NUMAMask=

systemd-system.conf(5)

NUMAPolicy=

systemd-system.conf(5)

NetworkTimeoutSec=

journal-upload.conf(5)

NoNewPrivileges=

systemd-system.conf(5)

PowerKeyIgnoreInhibited=

logind.conf(5)

ProcessSizeMax=

coredump.conf(5)

RateLimitBurst=

journal.conf(5)

RateLimitIntervalSec=

journal.conf(5)

ReadKMsg=

journal.conf(5)

RebootKeyIgnoreInhibited=

logind.conf(5)

RebootWatchdogSec=

systemd-system.conf(5)

RemoveIPC=

logind.conf(5)

ReserveVT=

logind.conf(5)

RuntimeDirectoryInodesMax=

logind.conf(5)

RuntimeDirectorySize=

logind.conf(5)

RuntimeKeepFree=

journal.conf(5)

RuntimeMaxFileSize=

journald.conf(5)
RuntimeMaxFiles=
journald.conf(5)
RuntimeMaxUse=
journald.conf(5)
RuntimeWatchdogSec=
systemd-system.conf(5)
Seal=
journal-remote.conf(5), journald.conf(5)
ServerCertificateFile=
journal-remote.conf(5), journal-upload.conf(5)
ServerKeyFile=
journal-remote.conf(5), journal-upload.conf(5)
SessionsMax=
logind.conf(5)
ShowStatus=
systemd-system.conf(5)
SplitMode=
journal-remote.conf(5), journald.conf(5)
StatusUnitFormat=
systemd-system.conf(5)
Storage=
coredump.conf(5), journald.conf(5), pstore.conf(5)
SuspendKeyIgnoreInhibited=
logind.conf(5)
SuspendMode=
systemd-sleep.conf(5)
SuspendState=
systemd-sleep.conf(5)
SwapUsedLimit=
oomd.conf(5)
SyncIntervalSec=
journald.conf(5)

SystemCallArchitectures=

systemd-system.conf(5)

SystemKeepFree=

journald.conf(5)

SystemMaxFileSize=

journald.conf(5)

SystemMaxFiles=

journald.conf(5)

SystemMaxUse=

journald.conf(5)

TTYPath=

journald.conf(5)

TimerSlackNSec=

systemd-system.conf(5)

TrustedCertificateFile=

journal-remote.conf(5), journal-upload.conf(5)

URL=

journal-upload.conf(5)

Unlink=

pstore.conf(5)

UserStopDelaySec=

logind.conf(5)

WatchdogDevice=

systemd-system.conf(5)

children_max=

udev.conf(5)

event_timeout=

udev.conf(5)

exec_delay=

udev.conf(5)

resolve_names=

udev.conf(5)

timeout_signal=

udev.conf(5)

udev_log=

udev.conf(5)

COMMAND LINE OPTIONS

Command-line options accepted by programs in the systemd suite.

--accept

systemd-socket-activate(1)

--accept-cached

systemd-ask-password(1)

--acquired

busctl(1)

--action

udevadm(8)

--activatable

busctl(1)

--address

busctl(1)

--adjust-system-clock

timedatectl(1)

--after

systemctl(1)

--after-cursor

journalctl(1), systemd-journal-upload.service(8)

--all

journalctl(1), loginctl(1), machinectl(1), networkctl(1), systemctl(1), systemd-cgls(1), timedatectl(1)

--allow-interactive-authorization

busctl(1)

--ambient-capability

systemd-nspawn(1)

--any

systemd-networkd-wait-online.service(8)

--app-specific

systemd-id128(1)

--are-updates-enabled

resolvectl(1)

--as-pid2

systemd-nspawn(1)

--attr-match

udevadm(8)

--attr-nomatch

udevadm(8)

--attribute-walk

udevadm(8)

--augment-creds

busctl(1)

--auto-start

busctl(1)

--automount

systemd-mount(1)

--automount-property

systemd-mount(1)

--base-time

systemd-analyze(1)

--batch

systemd-cgtop(1)

--before

systemctl(1)

--bind

systemd-nspawn(1)

--bind-device

systemd-mount(1)

--bind-ro

systemd-nspawn(1)

--bind-user

systemd-nspawn(1)

--boot[=[ID][?offset]]all
journalctl(1), systemd-nspawn(1), systemd-tmpfiles(8)

--boot-loader-entry
systemctl(1)

--boot-loader-menu
systemctl(1)

--boot-path
bootctl(1)

--booted
systemd-notify(1)

--cache
resolvectl(1)

--can-factory-reset
systemd-repart(8)

--capability
systemd-nspawn(1)

--case-sensitive[=BOOLEAN]
journalctl(1)

--cat
portablectl(1)

--cat-config
systemd-binfmt.service(8), systemd-sysctl.service(8), systemd-sysusers(8), systemd-tmpfiles(8)

--catalog
journalctl(1)

--cert
systemd-journal-gatewayd.service(8), systemd-journal-remote.service(8), systemd-journal-upload.service(8)

--chdir
systemd-nspawn(1)

--check-inhibitors
systemctl(1)

--children-max

systemd-udev.service(8), udevadm(8)

--chroot

systemd-detect-virt(1)

--class

resolvectl(1)

--clean

systemd-tmpfiles(8)

--cleanup-db

udevadm(8)

--cname

resolvectl(1)

--collect

systemd-mount(1), systemd-run(1)

--commit

systemd-machine-id-setup(1)

--compress

systemd-journal-remote.service(8)

--confirm-spawn

systemd(1)

--connections-max

systemd-socket-proxyd(8)

--console

systemd-nspawn(1), systemd-tty-ask-password-agent(1)

--container

systemd-detect-virt(1)

--copy

portablectl(1)

--copy-from

systemd-dissect(1)

--copy-to

systemd-dissect(1)

--cpu

systemd-cgtop(1)

--cpu-affinity
systemd-nspawn(1)

--crash-reboot
systemd(1)

--crash-shell
systemd(1)

--crash-vt
systemd(1)

--create
systemd-tmpfiles(8)

--credential
systemd-ask-password(1)

--cursor
journalctl(1), systemd-journal-upload.service(8)

--cursor-file
journalctl(1)

--daemon
systemd-udevd.service(8)

--datagram
systemd-socket-activate(1)

--debug
systemd-udevd.service(8), udevadm(8)

--debugger
coredumpctl(1)

--debugger-arguments
coredumpctl(1)

--default-standard-error
systemd(1)

--default-standard-output
systemd(1)

--definitions
systemd-repart(8)

--delay

systemd-cgtop(1)

--depth

systemd-cgtop(1)

--description

systemd-mount(1), systemd-run(1)

--destination

busctl(1)

--device-id-of-file

udevadm(8)

--diff

systemd-delta(1)

--directory

coredumpctl(1), journalctl(1), systemd-journal-gatewayd.service(8), systemd-journal-upload.service(8), systemd-nspawn(1)

--disable-updates

resolvectl(1)

--discard

systemd-dissect(1), systemd-repart(8)

--discover

systemd-mount(1)

--disk-usage

journalctl(1)

--dmesg

journalctl(1)

--drop-capability

systemd-nspawn(1)

--dry-run

systemctl(1), systemd-repart(8), udevadm(8)

--dump-bus-properties

systemd(1)

--dump-catalog

journalctl(1)

--dump-configuration-items

systemd(1)

--dump-core

systemd(1)

--echo

systemd-ask-password(1)

--emoji

systemd-ask-password(1)

--empty

systemd-repart(8)

--enable

portablectl(1)

--enable-updates

resolvectl(1)

--ephemeral

systemd-nspawn(1)

--esp-path

bootctl(1)

--event-timeout

systemd-udev.service(8)

--exclude-prefix

systemd-tmpfiles(8)

--exec-delay

systemd-udev.service(8)

--exit

udevadm(8)

--exit-idle-time

systemd-socket-proxyd(8)

--exit-if-exists

udevadm(8)

--expect-reply

busctl(1)

--export

udevadm(8)

--export-db
udevadm(8)

--export-prefix
udevadm(8)

--extension
portablectl(1)

--facility
journalctl(1)

--factory-reset
systemd-repart(8)

--fail
systemctl(1)

--failed
systemctl(1)

--fdname
systemd-socket-activate(1)

--fido2-device
systemd-cryptenroll(1)

--fido2-with-client-pin
systemd-cryptenroll(1)

--fido2-with-user-presence
systemd-cryptenroll(1)

--fido2-with-user-verification
systemd-cryptenroll(1)

--field
coredumpctl(1), journalctl(1)

--fields
journalctl(1)

--file
coredumpctl(1), journalctl(1), systemd-journal-gatewayd.service(8), systemd-journal-upload.service(8)

--firmware-setup
systemctl(1)

--flush
journalctl(1)

--follow
journalctl(1), systemd-journal-upload.service(8)

--force
halt(8), journalctl(1), machinectl(1), systemctl(1), systemd-sysex(8)

--format
machinectl(1)

--from-pattern
systemd-analyze(1)

--fsck
systemd-dissect(1), systemd-mount(1)

--full
busctl(1), journalctl(1), loginctl(1), machinectl(1), networkctl(1), systemctl(1),
systemd-cgls(1), systemd-mount(1)

--fuzz
systemd-analyze(1)

--generators
systemd-analyze(1)

--getter
systemd-journal-remote.service(8)

--gid
systemd-run(1)

--global
systemctl(1), systemd-analyze(1)

--gnutls-log
systemd-journal-remote.service(8)

--graceful
bootctl(1)

--grep
journalctl(1)

--growfs
systemd-dissect(1)

--halt

halt(8), shutdown(8)

--header

journalctl(1)

--help

bootctl(1), busctl(1), coredumpctl(1), halt(8), hostnamectl(1), journalctl(1), kernel-
install(8), localectl(1), loginctl(1), machinectl(1), networkctl(1), oomctl(1),
portablectl(1), resolvectl(1), runlevel(8), shutdown(8), systemctl(1), systemd(1),
systemd-analyze(1), systemd-ask-password(1), systemd-binfmt.service(8), systemd-bless-
boot.service(8), systemd-cat(1), systemd-cgls(1), systemd-cgtop(1), systemd-
cryptenroll(1), systemd-delta(1), systemd-detect-virt(1), systemd-dissect(1), systemd-
escape(1), systemd-fsckd.service(8), systemd-hwdb(8), systemd-id128(1), systemd-
inhibit(1), systemd-journal-gatewayd.service(8), systemd-journal-remote.service(8),
systemd-journal-upload.service(8), systemd-machine-id-setup(1), systemd-mount(1),
systemd-networkd-wait-online.service(8), systemd-notify(1), systemd-nspawn(1),
systemd-path(1), systemd-repart(8), systemd-run(1), systemd-socket-activate(1),
systemd-socket-proxyd(8), systemd-suspend.service(8), systemd-sysctl.service(8),
systemd-sysext(8), systemd-sysusers(8), systemd-tmpfiles(8), systemd-tty-ask-password-
agent(1), systemd-udev.service(8), telinit(8), timedatectl(1), udevadm(8)

--host

busctl(1), hostnamectl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1),
systemctl(1), systemd-analyze(1), systemd-mount(1), systemd-run(1), timedatectl(1)

--hostname

systemd-nspawn(1)

--icon

systemd-ask-password(1)

--id

systemd-ask-password(1)

--identifier

journalctl(1), systemd-cat(1)

--ignore

systemd-networkd-wait-online.service(8)

--image

journalctl(1), systemd-machine-id-setup(1), systemd-nspawn(1), systemd-repart(8),
systemd-sysusers(8), systemd-tmpfiles(8)

--inaccessible

systemd-nspawn(1)

--inetd

systemd-socket-activate(1)

--inline

systemd-sysusers(8)

--instance

systemd-escape(1)

--interface

resolvectl(1), systemd-networkd-wait-online.service(8)

--interval

journalctl(1)

--ipv4

systemd-networkd-wait-online.service(8)

--ipv6

systemd-networkd-wait-online.service(8)

--iterations

systemd-analyze(1), systemd-cgtop(1)

--job-mode

systemctl(1)

--json

busctl(1), coredumpctl(1), hostnamectl(1), networkctl(1), systemd-dissect(1), systemd-repart(8), systemd-sysext(8)

--keep-unit

systemd-nspawn(1)

--kernel

udevadm(8)

--key

systemd-journal-gatewayd.service(8), systemd-journal-remote.service(8), systemd-journal-upload.service(8)

--key-file

systemd-repart(8)

--keyname

systemd-ask-password(1)

--kill-signal

systemd-nspawn(1)

--kill-who

loginctl(1), machinectl(1), systemctl(1)

--legend

resolvectl(1), systemctl(1)

--level-prefix

systemd-cat(1)

--lines

journalctl(1), loginctl(1), machinectl(1), networkctl(1), systemctl(1)

--link-journal

systemd-nspawn(1)

--list

busctl(1), systemd-detect-virt(1), systemd-inhibit(1), systemd-mount(1), systemd-tty-ask-password-agent(1)

--list-boots

journalctl(1)

--list-catalog

journalctl(1)

--listen

systemd-socket-activate(1)

--listen-http

systemd-journal-remote.service(8)

--listen-https

systemd-journal-remote.service(8)

--listen-raw

systemd-journal-remote.service(8)

--load-credential

systemd-nspawn(1)

--log-color

systemd(1)

--log-level

systemd(1), udevadm(8)

--log-location

systemd(1)

--log-target

systemd(1)

--log-time

systemd(1)

--machine

busctl(1), hostnamectl(1), journalctl(1), localectl(1), loginctl(1), machinectl(1),
portablectl(1), systemctl(1), systemd-analyze(1), systemd-cgls(1), systemd-cgtop(1),
systemd-mount(1), systemd-nspawn(1), systemd-run(1), timedatectl(1)

--machine-id

systemd(1)

--make-machine-id-directory

bootctl(1)

--man

systemd-analyze(1)

--mangle

systemd-escape(1)

--marked

systemctl(1)

--match

busctl(1)

--max-addresses

machinectl(1)

--merge

journalctl(1), systemd-journal-gatewayd.service(8), systemd-journal-upload.service(8)

--message

systemctl(1)

--mkdir

machinectl(1), systemctl(1), systemd-dissect(1)

--mode
systemd-inhibit(1)

--monitor
timedatectl(1)

--mount
systemd-dissect(1)

--multiple
systemd-ask-password(1)

--name
udevadm(8)

--name-match
udevadm(8)

--namespace
journalctl(1)

--network
resolvectl(1)

--network-bridge
systemd-nspawn(1)

--network-interface
systemd-nspawn(1)

--network-ipvlan
systemd-nspawn(1)

--network-macvlan
systemd-nspawn(1)

--network-namespace-path
systemd-nspawn(1)

--network-veth
systemd-nspawn(1)

--network-veth-extra
systemd-nspawn(1)

--network-zone
systemd-nspawn(1)

--nice

systemd-run(1)

--no-ask-password

hostnamectl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1),
systemctl(1), systemd-mount(1), systemd-run(1), timedatectl(1)

--no-block

portablectl(1), systemctl(1), systemd-mount(1), systemd-notify(1), systemd-run(1)

--no-convert

localectl(1)

--no-full

journalctl(1)

--no-hostname

journalctl(1)

--no-legend

busctl(1), coredumpctl(1), loginctl(1), machinectl(1), networkctl(1), portablectl(1),
systemd-dissect(1), systemd-inhibit(1), systemd-mount(1), systemd-repart(8), systemd-
sysext(8)

--no-new-privileges

systemd-nspawn(1)

--no-output

systemd-ask-password(1)

--no-pager

bootctl(1), busctl(1), coredumpctl(1), journalctl(1), localectl(1), loginctl(1),
machinectl(1), networkctl(1), oomctl(1), portablectl(1), resolvectl(1), systemctl(1),
systemd-analyze(1), systemd-binfmt.service(8), systemd-cgls(1), systemd-delta(1),
systemd-dissect(1), systemd-inhibit(1), systemd-mount(1), systemd-nspawn(1), systemd-
repart(8), systemd-sysctl.service(8), systemd-sysext(8), systemd-sysusers(8), systemd-
tmpfiles(8), timedatectl(1)

--no-reload

portablectl(1), systemctl(1)

--no-sync

halt(8)

--no-tail

journalctl(1)

--no-tty

systemd-ask-password(1)

--no-variables

bootctl(1)

--no-wall

halt(8), shutdown(8), systemctl(1), telinit(8)

--no-wtmp

halt(8)

--notify-ready

systemd-nspawn(1)

--now

portablectl(1), systemctl(1)

--oci-bundle

systemd-nspawn(1)

--on-active

systemd-run(1)

--on-boot

systemd-run(1)

--on-calendar

systemd-run(1)

--on-clock-change

systemd-run(1)

--on-startup

systemd-run(1)

--on-timezone-change

systemd-run(1)

--on-unit-active

systemd-run(1)

--on-unit-inactive

systemd-run(1)

--oom-score-adjust

systemd-nspawn(1)

--operational-state

systemd-networkd-wait-online.service(8)

--options

systemd-mount(1)

--order

systemd-analyze(1), systemd-cgtop(1)

--output

coredumpctl(1), journalctl(1), loginctl(1), machinectl(1), systemctl(1), systemd-journal-remote.service(8)

--output-fields

journalctl(1)

--overlay

systemd-nspawn(1)

--overlay-ro

systemd-nspawn(1)

--owner

systemd-mount(1)

--pager-end

journalctl(1)

--parent-match

udevadm(8)

--password

systemd-cryptenroll(1)

--path

systemd-escape(1), udevadm(8)

--path-property

systemd-run(1)

--personality

systemd-nspawn(1)

--pid

systemd-notify(1)

--ping

udevadm(8)

--pipe

systemd-nspawn(1), systemd-run(1)

--pivot-root

systemd-nspawn(1)

--pkcs11-token-uri

systemd-cryptenroll(1)

--plain

systemctl(1)

--plymouth

systemd-tty-ask-password-agent(1)

--port

systemd-nspawn(1)

--poweroff

halt(8), shutdown(8)

--prefix

systemd-sysctl.service(8), systemd-tmpfiles(8)

--preset-mode

systemctl(1)

--pretty

hostnamectl(1), systemd-id128(1), systemd-repart(8)

--print

systemd-machine-id-setup(1)

--print-boot-path

bootctl(1)

--print-esp-path

bootctl(1)

--priority

journalctl(1), systemd-cat(1)

--private-network

systemd-nspawn(1)

--private-users

systemd-detect-virt(1), systemd-nspawn(1)

--private-users-ownership

systemd-nspawn(1)

--profile
portablectl(1)

--property
loginctl(1), machinectl(1), systemctl(1), systemd-mount(1), systemd-nspawn(1),
systemd-run(1), timedatectl(1), udevadm(8)

--property-match
udevadm(8)

--protocol
resolvectl(1)

--pty
systemd-run(1)

--query
systemd-tty-ask-password-agent(1), udevadm(8)

--quiet
busctl(1), coredumpctl(1), journalctl(1), machinectl(1), portablectl(1), systemctl(1),
systemd-detect-virt(1), systemd-mount(1), systemd-networkd-wait-online.service(8),
systemd-nspawn(1), systemd-run(1), udevadm(8)

--raw
resolvectl(1), systemd-cgtop(1)

--read-only
machinectl(1), systemctl(1), systemd-dissect(1), systemd-nspawn(1)

--ready
systemd-notify(1)

--reboot
halt(8), shutdown(8)

--reboot-argument
systemctl(1)

--recovery-key
systemd-cryptenroll(1)

--recursive
systemctl(1), systemd-cgtop(1)

--register
systemd-nspawn(1)

--relinquish-var
journalctl(1)

--reload
udevadm(8)

--remain-after-exit
systemd-run(1)

--remove
systemd-tmpfiles(8)

--replace
systemd-sysusers(8), systemd-tmpfiles(8)

--require
systemd-analyze(1)

--resolv-conf
systemd-nspawn(1)

--resolve-names
systemd-udevd.service(8), udevadm(8)

--reverse
coredumpctl(1), journalctl(1), systemctl(1)

--rlimit
systemd-nspawn(1)

--root
journalctl(1), systemctl(1), systemd-analyze(1), systemd-hwdb(8), systemd-machine-id-setup(1), systemd-repart(8), systemd-sysext(8), systemd-sysusers(8), systemd-tmpfiles(8), udevadm(8)

--root-hash
systemd-dissect(1), systemd-nspawn(1)

--root-hash-sig
systemd-dissect(1), systemd-nspawn(1)

--rotate
journalctl(1)

--runtime
portablectl(1), systemctl(1)

--same-dir

systemd-run(1)

--save-state

systemd-journal-upload.service(8)

--scope

systemd-run(1)

--seal

systemd-journal-remote.service(8)

--search

resolvectl(1)

--seed

systemd-repart(8)

--selinux-apifs-context

systemd-nspawn(1)

--selinux-context

systemd-nspawn(1)

--send-sighup

systemd-run(1)

--seqpacket

systemd-socket-activate(1)

--service-address

resolvectl(1)

--service-txt

resolvectl(1)

--service-type

systemd-run(1)

--service-watchdogs

systemd(1)

--set-credential

systemd-nspawn(1)

--setenv

machinectl(1), systemd-nspawn(1), systemd-run(1), systemd-socket-activate(1)

--settings

systemd-nspawn(1)

--settle
udevadm(8)

--setup-keys
journalctl(1)

--shell
systemd-run(1)

--show-cursor
journalctl(1)

--show-machine
busctl(1)

--show-status
systemd(1)

--show-transaction
systemctl(1)

--show-types
systemctl(1)

--signal
loginctl(1), machinectl(1), systemctl(1)

--since
coredumpctl(1), journalctl(1)

--size
busctl(1), systemd-repart(8)

--slice
systemd-nspawn(1), systemd-run(1)

--slice-inherit
systemd-run(1)

--smart-relinquish-var
journalctl(1)

--socket-property
systemd-run(1)

--split-mode
systemd-journal-remote.service(8)

--start-exec-queue

udevadm(8)

--state

systemctl(1)

--static

hostnamectl(1)

--stats

networkctl(1)

--status

systemd-notify(1)

--stderr-priority

systemd-cat(1)

--stop-exec-queue

udevadm(8)

--strict

systemd-hwdb(8)

--subsystem-match

udevadm(8)

--subsystem-nomatch

udevadm(8)

--suffix

systemd-escape(1), systemd-path(1)

--sync

journalctl(1)

--synthesize

resolvectl(1)

--sysname-match

udevadm(8)

--system

busctl(1), journalctl(1), systemctl(1), systemd(1), systemd-analyze(1), systemd-journal-gatewayd.service(8), systemd-journal-upload.service(8), systemd-mount(1), systemd-run(1)

--system-call-filter

systemd-nspawn(1)

--tag-match
udevadm(8)

--template
systemd-escape(1), systemd-nspawn(1)

--test
systemd(1)

--timeout
busctl(1), systemd-ask-password(1), systemd-networkd-wait-online.service(8),
udevadm(8)

--timeout-idle-sec
systemd-mount(1)

--timeout-signal
systemd-udevd.service(8)

--timer-property
systemd-run(1)

--timestamp
systemctl(1)

--timezone
systemd-nspawn(1)

--tmpfs
systemd-nspawn(1)

--to-pattern
systemd-analyze(1)

--tpm2-device
systemd-cryptenroll(1), systemd-repart(8)

--tpm2-pcrs
systemd-cryptenroll(1), systemd-repart(8)

--transient
hostnamectl(1)

--trust
systemd-journal-gatewayd.service(8), systemd-journal-remote.service(8), systemd-
journal-upload.service(8)

--trust-anchor

resolvectl(1)

--type

resolvectl(1), systemctl(1), systemd-delta(1), systemd-mount(1), udevadm(8)

--udev

udevadm(8)

--uid

machinectl(1), systemd-notify(1), systemd-run(1)

--umount

systemd-mount(1)

--unescape

systemd-escape(1)

--unique

busctl(1)

--unit

journalctl(1), systemd(1), systemd-cgls(1), systemd-run(1)

--unregister

systemd-binfmt.service(8)

--until

coredumpctl(1), journalctl(1)

--update-catalog

journalctl(1)

--url

systemd-journal-remote.service(8), systemd-journal-upload.service(8)

--user

busctl(1), journalctl(1), systemctl(1), systemd(1), systemd-analyze(1), systemd-journal-gatewayd.service(8), systemd-journal-upload.service(8), systemd-mount(1), systemd-nspawn(1), systemd-run(1), systemd-tmpfiles(8)

--user-unit

journalctl(1), systemd-cgls(1)

--usr

systemd-hwdb(8)

--utc

journalctl(1)

--uuid

systemd-id128(1), systemd-nspawn(1), udevadm(8)

--vacuum-files

journalctl(1)

--vacuum-size

journalctl(1)

--vacuum-time

journalctl(1)

--validate

resolvectl(1)

--value

loginctl(1), machinectl(1), systemctl(1), timedatectl(1)

--verbose

busctl(1), kernel-install(8), udevadm(8)

--verify

journalctl(1), machinectl(1)

--verify-key

journalctl(1)

--verity-data

systemd-dissect(1), systemd-nspawn(1)

--version

bootctl(1), busctl(1), coredumpctl(1), hostnamectl(1), journalctl(1), localectl(1),
loginctl(1), machinectl(1), networkctl(1), oomctl(1), portablectl(1), resolvectl(1),
systemctl(1), systemd(1), systemd-analyze(1), systemd-binfmt.service(8), systemd-
bless-boot.service(8), systemd-cat(1), systemd-cgls(1), systemd-cgtop(1), systemd-
cryptenroll(1), systemd-delta(1), systemd-detect-virt(1), systemd-dissect(1), systemd-
escape(1), systemd-fsckd.service(8), systemd-id128(1), systemd-inhibit(1), systemd-
journal-gatewayd.service(8), systemd-journal-remote.service(8), systemd-journal-
upload.service(8), systemd-machine-id-setup(1), systemd-mount(1), systemd-networkd-
wait-online.service(8), systemd-notify(1), systemd-nspawn(1), systemd-path(1),
systemd-repart(8), systemd-run(1), systemd-socket-activate(1), systemd-socket-
proxyd(8), systemd-suspend.service(8), systemd-sysctl.service(8), systemd-sysext(8),
systemd-sysusers(8), systemd-tmpfiles(8), systemd-tty-ask-password-agent(1), systemd-

udev.service(8), timedatectl(1)

--vm

systemd-detect-virt(1)

--volatile

systemd-nspawn(1)

--wait

systemctl(1), systemd-run(1)

--wait-daemon[

udevadm(8)

--wait-for-initialization[=SECONDS]

udevadm(8)

--wall

systemd-tty-ask-password-agent(1)

--watch

systemd-tty-ask-password-agent(1)

--watch-bind

busctl(1)

--what

systemctl(1), systemd-inhibit(1)

--who

systemd-inhibit(1)

--why

systemd-inhibit(1)

--wipe-slot

systemd-cryptenroll(1)

--with-dependencies

systemctl(1)

--working-directory

systemd-run(1)

--wtmp-only

halt(8)

--xml-interface

busctl(1)

--zone

resolvectl(1)

-1

coredumpctl(1), systemd-cgtop(1)

-4

resolvectl(1), systemd-networkd-wait-online.service(8)

-6

resolvectl(1), systemd-networkd-wait-online.service(8)

-A

coredumpctl(1), systemd-mount(1), udevadm(8)

-D

coredumpctl(1), journalctl(1), systemd-journal-gatewayd.service(8), systemd-journal-upload.service(8), systemd-nspawn(1), systemd-udevd.service(8)

-E

machinectl(1), systemd-nspawn(1), systemd-run(1), systemd-socket-activate(1), systemd-tmpfiles(8), udevadm(8)

-F

coredumpctl(1), journalctl(1)

-G

systemd-mount(1), systemd-run(1)

-H

busctl(1), hostnamectl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), shutdown(8), systemctl(1), systemd-analyze(1), systemd-mount(1), systemd-run(1), timedatectl(1)

-I

resolvectl(1)

-L

systemd-nspawn(1)

-M

busctl(1), hostnamectl(1), journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemctl(1), systemd-analyze(1), systemd-cgls(1), systemd-cgtop(1), systemd-dissect(1), systemd-mount(1), systemd-nspawn(1), systemd-run(1), timedatectl(1)

-N

journalctl(1), systemd-udev.service(8), udevadm(8)

-P

shutdown(8), systemctl(1), systemd-cgtop(1), systemd-nspawn(1), systemd-run(1),
udevadm(8)

-R

resolvectl(1), udevadm(8)

-S

coredumpctl(1), journalctl(1), systemd-nspawn(1), systemd-run(1), udevadm(8)

-T

systemctl(1)

-U

coredumpctl(1), journalctl(1), systemd-nspawn(1)

-V

resolvectl(1)

-Z

systemd-nspawn(1)

-a

journalctl(1), loginctl(1), machinectl(1), networkctl(1), resolvectl(1), systemctl(1),
systemd-dissect(1), systemd-id128(1), systemd-nspawn(1), systemd-socket-activate(1),
timedatectl(1), udevadm(8)

-b

journalctl(1), systemd-cgtop(1), systemd-nspawn(1), udevadm(8)

-c

journalctl(1), resolvectl(1), shutdown(8), systemd-cgtop(1), systemd-detect-virt(1),
systemd-socket-proxyd(8), systemd-udev.service(8), udevadm(8)

-d

halt(8), resolvectl(1), systemd-cgtop(1), systemd-run(1), systemd-socket-activate(1),
systemd-udev.service(8), udevadm(8)

-e

journalctl(1), systemd-ask-password(1), systemd-udev.service(8), udevadm(8)

-f

halt(8), journalctl(1), resolvectl(1), systemctl(1)

-g

journalctl(1), udevadm(8)

-h

bootctl(1), busctl(1), coredumpctl(1), hostnamectl(1), journalctl(1), kernel-install(8), localectl(1), loginctl(1), machinectl(1), networkctl(1), oomctl(1), portablectl(1), resolvectl(1), shutdown(8), systemctl(1), systemd(1), systemd-analyze(1), systemd-ask-password(1), systemd-binfmt.service(8), systemd-bless-boot.service(8), systemd-cat(1), systemd-cgls(1), systemd-cgtop(1), systemd-cryptenroll(1), systemd-delta(1), systemd-detect-virt(1), systemd-dissect(1), systemd-escape(1), systemd-fsckd.service(8), systemd-hwdb(8), systemd-id128(1), systemd-inhibit(1), systemd-journal-gatewayd.service(8), systemd-journal-remote.service(8), systemd-journal-upload.service(8), systemd-machine-id-setup(1), systemd-mount(1), systemd-networkd-wait-online.service(8), systemd-notify(1), systemd-nspawn(1), systemd-path(1), systemd-repart(8), systemd-run(1), systemd-socket-activate(1), systemd-socket-proxyd(8), systemd-suspend.service(8), systemd-sysctl.service(8), systemd-sysex(8), systemd-sysusers(8), systemd-tmpfiles(8), systemd-tty-ask-password-agent(1), systemd-udev.service(8), timedatectl(1), udevadm(8)

-i

resolvectl(1), systemctl(1), systemd-cgtop(1), systemd-networkd-wait-online.service(8), systemd-nspawn(1)

-j

busctl(1), systemd-nspawn(1)

-k

journalctl(1), shutdown(8), systemd-cgls(1), systemd-cgtop(1), udevadm(8)

-l

busctl(1), journalctl(1), loginctl(1), machinectl(1), networkctl(1), resolvectl(1), systemctl(1), systemd-cgls(1), systemd-mount(1), systemd-socket-activate(1), udevadm(8)

-m

journalctl(1), resolvectl(1), systemd-cgtop(1), systemd-dissect(1), systemd-escape(1), systemd-journal-gatewayd.service(8), systemd-journal-upload.service(8), udevadm(8)

-n

coredumpctl(1), halt(8), journalctl(1), loginctl(1), machinectl(1), networkctl(1),

systemctl(1), systemd-ask-password(1), systemd-cgtop(1), systemd-nspawn(1), udevadm(8)

-O

coredumpctl(1), journalctl(1), loginctl(1), machinectl(1), systemctl(1), systemd-mount(1), systemd-networkd-wait-online.service(8)

-p

bootctl(1), halt(8), journalctl(1), loginctl(1), machinectl(1), portablectl(1), resolvectl(1), systemctl(1), systemd-cat(1), systemd-cgtop(1), systemd-escape(1), systemd-id128(1), systemd-mount(1), systemd-nspawn(1), systemd-run(1), timedatectl(1), udevadm(8)

-q

busctl(1), coredumpctl(1), journalctl(1), machinectl(1), portablectl(1), systemctl(1), systemd-detect-virt(1), systemd-mount(1), systemd-networkd-wait-online.service(8), systemd-nspawn(1), systemd-run(1), udevadm(8)

-r

coredumpctl(1), journalctl(1), resolvectl(1), shutdown(8), systemctl(1), systemd-cgtop(1), systemd-detect-virt(1), systemd-dissect(1), systemd-hwdb(8), systemd-run(1), udevadm(8)

-s

loginctl(1), machinectl(1), networkctl(1), systemctl(1), systemd-hwdb(8), systemd-udev.service(8), udevadm(8)

-t

journalctl(1), resolvectl(1), systemctl(1), systemd-cat(1), systemd-cgtop(1), systemd-delta(1), systemd-mount(1), systemd-run(1), systemd-udev.service(8), udevadm(8)

-u

journalctl(1), resolvectl(1), systemd-cgls(1), systemd-escape(1), systemd-id128(1), systemd-journal-upload.service(8), systemd-mount(1), systemd-nspawn(1), systemd-run(1), udevadm(8)

-v

kernel-install(8), resolvectl(1), systemd-detect-virt(1), udevadm(8)

-W

halt(8), udevadm(8)

-x

bootctl(1), journalctl(1), resolvectl(1), systemd-dissect(1), systemd-nspawn(1),

udevadm(8)

-y

udevadm(8)

K

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemctl(1),
systemd(1), systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-
tmpfiles(8), timedatectl(1)

X

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemctl(1),
systemd(1), systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-
tmpfiles(8), timedatectl(1)

arp

systemd.link(5)

attach

systemd-veritysetup@.service(8)

audit

systemd.journal-fields(7)

au

systemd.link(5)

auto

systemd.resource-control(5)

bad

systemd-bless-boot.service(8)

bnc

systemd.link(5)

broadcast

systemd.link(5)

cat

journalctl(1)

closed

systemd.resource-control(5)

database

systemd.link(5)

detach

systemd-veritysetup@.service(8)

driver

systemd.journal-fields(7)

export

journalctl(1)

fibre

systemd.link(5)

good

systemd-bless-boot.service(8)

help

systemd-veritysetup@.service(8)

hibernate

systemd-suspend.service(8)

hybrid-sleep

systemd-suspend.service(8)

indeterminate

systemd-bless-boot.service(8)

install

bootctl(1)

is-installed

bootctl(1)

journal

systemd.journal-fields(7)

json

journalctl(1)

json-pretty

journalctl(1)

json-seq

journalctl(1)

json-sse

journalctl(1)

keep

systemd.link(5)

kernel

systemd.journal-fields(7), systemd.link(5)

link-layer

networkd.conf(5)

link-layer-time[:TIME]

networkd.conf(5)

list

bootctl(1), systemd-sysext(8)

mac

systemd.link(5)

magic

systemd.link(5)

merge

systemd-sysext(8)

mii

systemd.link(5)

multicast

systemd.link(5)

none

systemd.link(5)

onboard

systemd.link(5)

path

systemd.link(5)

persistent

systemd.link(5)

phy

systemd.link(5)

pretty

systemctl(1)

random

systemd.link(5)

random-seed

bootctl(1)

refresh

systemd-sysex(8)

remove

bootctl(1)

secureon

systemd.link(5)

set-default

bootctl(1)

set-oneshot

bootctl(1)

short

journalctl(1)

short-full

journalctl(1)

short-iso

journalctl(1)

short-iso-precise

journalctl(1)

short-monotonic

journalctl(1)

short-precise

journalctl(1)

short-unix

journalctl(1)

slot

systemd.link(5)

status

bootctl(1), systemd-bless-boot.service(8), systemd-sysex(8)

stdout

systemd.journal-fields(7)

strict

systemd.resource-control(5)

suspend

systemd-suspend.service(8)

suspend-then-hibernate

systemd-suspend.service(8)

syslog

systemd.journal-fields(7)

tp

systemd.link(5)

unicast

systemd.link(5)

unmerge

systemd-sysex(8)

update

bootctl(1)

us

systemctl(1)

us+utc

systemctl(1)

utc

systemctl(1)

uuid

networkd.conf(5)

vendor

networkd.conf(5)

verbose

journalctl(1)

with-unit

journalctl(1)

?s

systemctl(1)

?s+utc

systemctl(1)

CONSTANTS

Various constants used and/or defined by systemd.

-1

sd_journal_get_fd(3), sd_login_monitor_new(3)

'h'

sd_bus_message_read_basic(3)

's'

sd_bus_message_read_basic(3)

'y'

sd_bus_message_read_basic(3)

-

systemd.resource-control(5)

-0

journalctl(1)

-1

journalctl(1), sd_event_run(3), sd_event_wait(3), sd_journal_get_fd(3)

-E2BIG

sd_journal_get_data(3), sd_journal_query_unique(3)

-EADDRINUSE

sd_bus_request_name(3)

-EADDRNOTAVAIL

sd_journal_get_data(3), sd_journal_query_unique(3)

-EAGAIN

sd_hwdb_get(3)

-EALREADY

sd_bus_request_name(3)

-EBADF

sd_bus_set_fd(3), sd_pid_get_owner_uid(3)

-EBADMSG

sd_bus_message_read(3), sd_bus_message_read_array(3), sd_bus_message_read_basic(3),
sd_bus_message_read_strv(3), sd_bus_message_seal(3), sd_bus_message_skip(3),
sd_journal_get_data(3), sd_journal_query_unique(3)

-EBUSY

sd_bus_message_open_container(3), sd_bus_process(3), sd_bus_track_new(3),
sd_event_add_child(3), sd_event_add_signal(3), sd_event_run(3), sd_event_wait(3)

-ECHILD

sd_bus_add_node_enumerator(3), sd_bus_add_object(3), sd_bus_add_object_manager(3),
sd_bus_attach_event(3), sd_bus_call(3), sd_bus_can_send(3), sd_bus_close(3),
sd_bus_emit_signal(3), sd_bus_enqueue_for_read(3), sd_bus_get_fd(3),
sd_bus_get_n_queued_read(3), sd_bus_get_name_creds(3), sd_bus_get_name_machine_id(3),
sd_bus_is_open(3), sd_bus_list_names(3), sd_bus_negotiate_fds(3), sd_bus_process(3),
sd_bus_query_sender_creds(3), sd_bus_request_name(3), sd_bus_send(3),
sd_bus_set_address(3), sd_bus_set_close_on_exit(3), sd_bus_set_connected_signal(3),
sd_bus_set_description(3), sd_bus_set_exit_on_disconnect(3), sd_bus_set_fd(3),
sd_bus_set_sender(3), sd_bus_set_server(3), sd_bus_set_watch_bind(3),
sd_bus_slot_set_floating(3), sd_bus_start(3), sd_bus_wait(3), sd_event_add_child(3),
sd_event_add_defer(3), sd_event_add_inotify(3), sd_event_add_io(3),
sd_event_add_signal(3), sd_event_add_time(3), sd_event_exit(3), sd_event_get_fd(3),
sd_event_now(3), sd_event_run(3), sd_event_set_watchdog(3),
sd_event_source_get_pending(3), sd_event_source_set_description(3),
sd_event_source_set_enabled(3), sd_event_source_set_floating(3),
sd_event_source_set_prepare(3), sd_event_source_set_priority(3),
sd_event_source_set_ratelimit(3), sd_event_wait(3), sd_journal_get_data(3),
sd_journal_open(3), sd_journal_query_unique(3)

-ECONNRESET

sd_bus_call(3), sd_bus_process(3), sd_bus_send(3)

-EDOM

sd_event_add_child(3), sd_event_add_inotify(3), sd_event_add_io(3),
sd_event_add_signal(3), sd_event_add_time(3), sd_event_source_get_pending(3),
sd_event_source_set_exit_on_failure(3), sd_event_source_set_prepare(3),
sd_event_source_set_ratelimit(3)

-EEXIST

sd_bus_add_object(3), sd_bus_message_set_destination(3), sd_bus_request_name(3)

-EINVAL

sd_bus_add_node_enumerator(3), sd_bus_add_object(3), sd_bus_add_object_manager(3),
sd_bus_call(3), sd_bus_creds_get_pid(3), sd_bus_creds_new_from_pid(3),

sd_bus_default(3), sd_bus_emit_signal(3), sd_bus_error(3), sd_bus_error_add_map(3),
sd_bus_get_fd(3), sd_bus_get_name_creds(3), sd_bus_get_name_machine_id(3),
sd_bus_interface_name_is_valid(3), sd_bus_list_names(3), sd_bus_message_append(3),
sd_bus_message_append_array(3), sd_bus_message_append_basic(3),
sd_bus_message_append_string_memfd(3), sd_bus_message_append_strv(3),
sd_bus_message_at_end(3), sd_bus_message_copy(3), sd_bus_message_get_cookie(3),
sd_bus_message_get_monotonic_usec(3), sd_bus_message_get_signature(3),
sd_bus_message_get_type(3), sd_bus_message_new(3), sd_bus_message_new_method_call(3),
sd_bus_message_new_method_error(3), sd_bus_message_new_signal(3),
sd_bus_message_open_container(3), sd_bus_message_read(3),
sd_bus_message_read_array(3), sd_bus_message_read_basic(3),
sd_bus_message_read_strv(3), sd_bus_message_rewind(3), sd_bus_message_seal(3),
sd_bus_message_sensitive(3), sd_bus_message_set_destination(3),
sd_bus_message_set_expect_reply(3), sd_bus_message_skip(3),
sd_bus_message_verify_type(3), sd_bus_negotiate_fds(3), sd_bus_process(3),
sd_bus_query_sender_creds(3), sd_bus_reply_method_error(3),
sd_bus_reply_method_return(3), sd_bus_request_name(3), sd_bus_send(3),
sd_bus_set_address(3), sd_bus_set_description(3), sd_bus_set_exit_on_disconnect(3),
sd_bus_set_fd(3), sd_bus_set_method_call_timeout(3), sd_bus_set_server(3),
sd_bus_slot_set_description(3), sd_bus_slot_set_destroy_callback(3),
sd_bus_slot_set_floating(3), sd_bus_start(3), sd_bus_track_add_name(3),
sd_bus_track_new(3), sd_bus_wait(3), sd_event_add_child(3), sd_event_add_defer(3),
sd_event_add_inotify(3), sd_event_add_io(3), sd_event_add_signal(3),
sd_event_add_time(3), sd_event_exit(3), sd_event_get_fd(3), sd_event_now(3),
sd_event_run(3), sd_event_set_watchdog(3), sd_event_source_get_pending(3),
sd_event_source_set_description(3), sd_event_source_set_destroy_callback(3),
sd_event_source_set_enabled(3), sd_event_source_set_exit_on_failure(3),
sd_event_source_set_floating(3), sd_event_source_set_prepare(3),
sd_event_source_set_priority(3), sd_event_source_set_ratelimit(3), sd_event_wait(3),
sd_hwdb_get(3), sd_hwdb_new(3), sd_journal_get_data(3), sd_journal_query_unique(3),
sd_login_monitor_new(3), sd_machine_get_class(3), sd_path_lookup(3),
sd_pid_get_owner_uid(3), sd_seat_get_active(3), sd_session_is_active(3),
sd_uid_get_state(3)

-EIO

sd_bus_error(3), sd_id128_get_machine(3), sd_journal_get_data(3),
sd_journal_query_unique(3)

-ELOOP

sd_bus_call(3)

-EMFILE

sd_event_new(3)

-ENOBUFS

sd_bus_send(3), sd_journal_get_data(3), sd_journal_query_unique(3)

-ENODATA

sd_bus_creds_get_pid(3), sd_bus_message_get_cookie(3),
sd_bus_message_get_monotonic_usec(3), sd_bus_negotiate_fds(3), sd_bus_set_address(3),
sd_bus_set_description(3), sd_event_exit(3), sd_pid_get_owner_uid(3),
sd_seat_get_active(3), sd_session_is_active(3), sd_uid_get_state(3)

-ENOENT

sd_hwdb_get(3), sd_hwdb_new(3), sd_id128_get_machine(3), sd_journal_get_data(3),
sd_journal_query_unique(3)

-ENOEXEC

sd_event_source_set_ratelimit(3)

-ENOMEDIUM

sd_bus_default(3), sd_id128_get_machine(3)

-ENOMEM

sd_bus_add_node_enumerator(3), sd_bus_add_object(3), sd_bus_add_object_manager(3),
sd_bus_call(3), sd_bus_creds_get_pid(3), sd_bus_creds_new_from_pid(3),
sd_bus_default(3), sd_bus_emit_signal(3), sd_bus_error(3), sd_bus_error_add_map(3),
sd_bus_get_name_creds(3), sd_bus_get_name_machine_id(3), sd_bus_list_names(3),
sd_bus_message_append(3), sd_bus_message_append_array(3),
sd_bus_message_append_basic(3), sd_bus_message_append_string_memfd(3),
sd_bus_message_append_strv(3), sd_bus_message_copy(3), sd_bus_message_new(3),
sd_bus_message_new_method_call(3), sd_bus_message_new_method_error(3),
sd_bus_message_new_signal(3), sd_bus_message_open_container(3),
sd_bus_message_skip(3), sd_bus_new(3), sd_bus_reply_method_error(3),
sd_bus_reply_method_return(3), sd_bus_send(3), sd_bus_set_description(3),

sd_bus_slot_set_description(3), sd_bus_track_add_name(3), sd_bus_track_new(3),
sd_event_add_child(3), sd_event_add_defer(3), sd_event_add_inotify(3),
sd_event_add_io(3), sd_event_add_signal(3), sd_event_add_time(3), sd_event_new(3),
sd_event_source_get_pending(3), sd_event_source_set_description(3),
sd_event_source_set_enabled(3), sd_event_source_set_prepare(3),
sd_event_source_set_priority(3), sd_get_seats(3), sd_hwdb_new(3),
sd_journal_get_data(3), sd_login_monitor_new(3), sd_machine_get_class(3),
sd_path_lookup(3), sd_pid_get_owner_uid(3), sd_seat_get_active(3),
sd_session_is_active(3), sd_uid_get_state(3)

-ENOMEM

sd_bus_message_seal(3)

-ENOPKG

sd_bus_add_node_enumerator(3), sd_bus_add_object(3), sd_bus_add_object_manager(3),
sd_bus_can_send(3), sd_bus_emit_signal(3), sd_bus_get_fd(3), sd_bus_get_name_creds(3),
sd_bus_get_name_machine_id(3), sd_bus_list_names(3), sd_bus_negotiate_fds(3),
sd_bus_set_address(3), sd_bus_set_description(3), sd_bus_set_exit_on_disconnect(3),
sd_bus_set_fd(3), sd_bus_set_method_call_timeout(3), sd_bus_set_server(3),
sd_bus_start(3)

-ENOTCONN

sd_bus_call(3), sd_bus_can_send(3), sd_bus_get_fd(3), sd_bus_list_names(3),
sd_bus_message_new(3), sd_bus_message_new_method_call(3),
sd_bus_message_new_method_error(3), sd_bus_message_new_signal(3), sd_bus_process(3),
sd_bus_query_sender_creds(3), sd_bus_reply_method_error(3),
sd_bus_reply_method_return(3), sd_bus_request_name(3), sd_bus_send(3),
sd_bus_set_server(3), sd_bus_wait(3)

-ENXIO

sd_bus_creds_get_pid(3), sd_bus_message_append(3), sd_bus_message_append_array(3),
sd_bus_message_append_basic(3), sd_bus_message_append_string_memfd(3),
sd_bus_message_append_strv(3), sd_bus_message_copy(3), sd_bus_message_read(3),
sd_bus_message_read_basic(3), sd_bus_message_read_strv(3), sd_bus_message_skip(3),
sd_bus_set_description(3), sd_bus_slot_set_description(3), sd_event_new(3),
sd_event_source_set_description(3), sd_id128_get_machine(3), sd_machine_get_class(3),
sd_path_lookup(3), sd_seat_get_active(3), sd_session_is_active(3), sd_uid_get_state(3)

-EOPNOTSUPP

sd_bus_creds_new_from_pid(3), sd_bus_message_new_method_call(3),
sd_bus_message_read_array(3), sd_bus_send(3), sd_event_add_child(3),
sd_event_add_time(3), sd_event_now(3), sd_path_lookup(3)

-EOVERFLOW

sd_event_add_time(3)

-EPERM

sd_bus_get_fd(3), sd_bus_get_name_creds(3), sd_bus_message_append(3),
sd_bus_message_append_array(3), sd_bus_message_append_basic(3),
sd_bus_message_append_string_memfd(3), sd_bus_message_append_strv(3),
sd_bus_message_at_end(3), sd_bus_message_copy(3), sd_bus_message_new_method_call(3),
sd_bus_message_new_method_error(3), sd_bus_message_open_container(3),
sd_bus_message_read_array(3), sd_bus_message_read_strv(3), sd_bus_message_rewind(3),
sd_bus_message_set_destination(3), sd_bus_message_set_expect_reply(3),
sd_bus_message_skip(3), sd_bus_message_verify_type(3), sd_bus_negotiate_fds(3),
sd_bus_query_sender_creds(3), sd_bus_reply_method_error(3),
sd_bus_reply_method_return(3), sd_bus_set_address(3), sd_bus_set_description(3),
sd_bus_set_fd(3), sd_bus_set_sender(3), sd_bus_set_server(3), sd_bus_start(3),
sd_id128_get_machine(3)

-EPROTONOSUPPORT

sd_journal_get_data(3), sd_journal_query_unique(3)

-EPROTOTYPE

sd_bus_add_object(3)

-ESOCKTNOSUPPORT

sd_bus_default(3)

-ESRCH

sd_bus_creds_new_from_pid(3), sd_bus_emit_signal(3), sd_bus_request_name(3),
sd_pid_get_owner_uid(3)

-ESTALE

sd_bus_message_append(3), sd_bus_message_append_array(3),
sd_bus_message_append_basic(3), sd_bus_message_append_string_memfd(3),
sd_bus_message_append_strv(3), sd_bus_message_copy(3),
sd_bus_message_open_container(3), sd_bus_slot_set_floating(3), sd_event_add_child(3),

sd_event_add_defer(3), sd_event_add_inotify(3), sd_event_add_io(3),
sd_event_add_signal(3), sd_event_add_time(3), sd_event_exit(3), sd_event_run(3),
sd_event_source_get_pending(3), sd_event_source_set_prepare(3),
sd_event_source_set_priority(3), sd_event_wait(3), sd_journal_get_realtime_usec(3)

-ETIMEDOUT

sd_bus_call(3)

-EUNATCH

sd_bus_track_add_name(3)

/org/freedesktop/systemd1

org.freedesktop.systemd1(5)

0

kernel-install(8), org.freedesktop.resolve1(5), sd_bus_add_object(3), sd_bus_error(3),
sd_event_add_time(3), sd_journal_add_match(3), systemctl(1), systemd.netdev(5),
systemd.resource-control(5), tmpfiles.d(5), udev_device_get_syspath(3),
udev_device_has_tag(3), udev_enumerate_add_match_subsystem(3),
udev_enumerate_scan_devices(3), udev_monitor_filter_update(3),
udev_monitor_receive_device(3)

0755

systemd.exec(5)

0xFF

sd-id128(3)

0xFFFF

sd_uid_get_state(3)

0xFFFFFFFF

sd_uid_get_state(3)

1

journalctl(1), sd_bus_add_object(3), systemctl(1), systemd-oomd.service(8), systemd-
tmpfiles(8), systemd.network(5), udev_device_get_syspath(3)

10

systemd-journald.service(8)

128

systemd.resource-control(5)

19532

systemd-journal-upload.service(8)

2

journalctl(1), systemctl(1), systemd.network(5)

3

systemctl(1)

4

systemctl(1)

443

resolvectl(1)

4a67b082-0a4c-41cf-b6c7-440b29bb8c4

systemd-bless-boot.service(8)

4a67b082-0a4c-41cf-b6c7-440b29bb8c4f

systemd-gpt-auto-generator(8)

4f68bce3-e8cd-4db1-96e7-fbcaf984b709

repart.d(5)

65

systemd-tmpfiles(8)

73

systemd-tmpfiles(8)

77

kernel-install(8)

8cf2644b-4b0b-428f-9387-6d876050dc67

systemd-repart(8)

:

systemd.resource-control(5)

A

tmpfiles.d(5)

ACTION

udev_device_new_from_syspath(3)

AF_INET

journal.d.conf(5), org.freedesktop.machine1(5), org.freedesktop.resolve1(5),

sd_is_fifo(3), systemd.exec(5), systemd.resource-control(5), systemd.socket(5)

AF_INET6

org.freedesktop.machine1(5), org.freedesktop.resolve1(5), sd_is_fifo(3),
systemd.exec(5), systemd.resource-control(5), systemd.socket(5)

AF_NETLINK

systemd.exec(5), systemd.socket(5)

AF_PACKET

systemd.exec(5), systemd.socket(5)

AF_UNIX

busctl(1), crypttab(5), daemon(7), journald.conf(5), machinectl(1), nss-resolve(8),
pam_systemd(8), sd_is_fifo(3), sd_notify(3), systemctl(1), systemd(1), systemd-
journal-gatewayd.service(8), systemd-journal-remote.service(8), systemd-repart(8),
systemd.exec(5), systemd.netdev(5), systemd.socket(5)

AF_UNSPEC

org.freedesktop.resolve1(5), sd_is_fifo(3)

AF_VSOCK

systemd.socket(5)

ALLOW_INTERACTIVE_AUTHORIZATION

sd_bus_message_set_expect_reply(3), sd_bus_set_description(3)

AND

systemd.exec(5)

ANY

resolvectl(1)

B

tmpfiles.d(5)

BLKDISCARD

systemd-repart(8)

BUS_MESSAGE_NO_REPLY_EXPECTED

sd_bus_call(3)

C

tmpfiles.d(5)

CAP_AUDIT_CONTROL

systemd-nspawn(1)

CAP_AUDIT_WRITE

systemd-nspawn(1)

CAP_CHOWN

systemd-nspawn(1)

CAP_DAC_OVERRIDE

systemd-nspawn(1), systemd.exec(5)

CAP_DAC_READ_SEARCH

systemd-nspawn(1)

CAP_FOWNER

systemd-nspawn(1), systemd-tmpfiles(8)

CAP_FSETID

systemd-nspawn(1)

CAP_IPC_OWNER

systemd-nspawn(1)

CAP_KILL

systemd-nspawn(1)

CAP_LEASE

systemd-nspawn(1)

CAP_LINUX_IMMUTABLE

systemd-nspawn(1)

CAP_MKNOD

systemd-nspawn(1), systemd.exec(5)

CAP_NET_ADMIN

systemd-nspawn(1)

CAP_NET_BIND_SERVICE

systemd-nspawn(1)

CAP_NET_BROADCAST

systemd-nspawn(1)

CAP_NET_RAW

systemd-nspawn(1)

CAP_SETFCAP

systemd-nspawn(1)

CAP_SETGID

systemd-nspawn(1)

CAP_SETPCAP

systemd-nspawn(1)

CAP_SETUID

systemd-nspawn(1)

CAP_SYSLOG

systemd.exec(5)

CAP_SYS_ADMIN

org.freedesktop.systemd1(5), sd_bus_add_object(3), systemd-nspawn(1), systemd.exec(5)

CAP_SYS_BOOT

systemd-nspawn(1)

CAP_SYS_CHROOT

systemd-nspawn(1)

CAP_SYS_MODULE

systemd.exec(5)

CAP_SYS_NICE

systemd-nspawn(1)

CAP_SYS_PTRACE

systemd-nspawn(1), systemd.exec(5)

CAP_SYS_RAWIO

systemd.exec(5)

CAP_SYS_RESOURCE

systemd-nspawn(1)

CAP_SYS_TIME

systemd.exec(5)

CAP_SYS_TTY_CONFIG

systemd-nspawn(1)

CAP_WAKE_ALARM

systemd.exec(5)

CLOCK_BOOTTIME

sd-event(3)

CLOCK_BOOTTIME

sd_event_add_time(3), sd_event_now(3), systemd.timer(5)

CLOCK_BOOTTIME_ALARM

sd-event(3), sd_event_add_time(3), sd_event_now(3)

CLOCK_MONOTONIC

org.freedesktop.login1(5), org.freedesktop.systemd1(5), sd-event(3), sd_bus_get_fd(3),
sd_bus_message_get_monotonic_usec(3), sd_event_add_time(3), sd_event_now(3),
sd_journal_get_cutoff_realtime_usec(3), sd_journal_get_fd(3),
sd_journal_get_realtime_usec(3), sd_journal_seek_head(3), sd_login_monitor_new(3),
systemd.journal-fields(7), systemd.timer(5)

CLOCK_REALTIME

org.freedesktop.login1(5), org.freedesktop.systemd1(5), org.freedesktop.timedate1(5),
sd-event(3), sd_bus_message_get_monotonic_usec(3), sd_event_add_time(3),
sd_event_now(3), sd_journal_get_cutoff_realtime_usec(3),
sd_journal_get_realtime_usec(3), sd_journal_seek_head(3), systemd.journal-fields(7),
systemd.special(7), systemd.timer(5)

CLOCK_REALTIME_ALARM

sd-event(3), sd_event_add_time(3), sd_event_now(3)

CLONE_NEWNS

systemd.exec(5)

DEVPATH

udev_device_new_from_syspath(3)

DHCPDECLINE

systemd.network(5)

EACCES

systemd.exec(5)

EOPNOTSUPP

sd_event_add_child(3)

EPERM

systemd.exec(5)

EPIPE

systemd-journald.service(8)

EPOLLERR

sd_event_add_io(3), sd_notify(3)

EPOLLET

sd-event(3), sd_event_add_io(3)

EPOLLHUP

sd_event_add_io(3), sd_notify(3)

EPOLLIN

sd_event_add_io(3), sd_event_get_fd(3)

EPOLLOUT

sd_event_add_io(3)

EPOLLPRI

sd_event_add_io(3)

EPOLLRDHUP

sd_event_add_io(3)

ESC

systemctl(1)

EUCLEAN

sd-bus-errors(3), systemd.exec(5)

EXIT_ADDRESS_FAMILIES

systemd.exec(5)

EXIT_APPARMOR_PROFILE

systemd.exec(5)

EXIT_CACHE_DIRECTORY

systemd.exec(5)

EXIT_CAPABILITIES

systemd.exec(5)

EXIT_CGROUP

systemd.exec(5)

EXIT_CHDIR

systemd.exec(5)

EXIT_CHOWN

systemd.exec(5)

EXIT_CHROOT

systemd.exec(5)

EXIT_CONFIGURATION_DIRECTORY

systemd.exec(5)

EXIT_CONFIRM

systemd.exec(5)

EXIT_CPUAFFINITY

systemd.exec(5)

EXIT_CREDENTIALS

systemd.exec(5)

EXIT_EXEC

systemd.exec(5)

EXIT_FAILURE

sd_bus_set_exit_on_disconnect(3), systemd-tmpfiles(8), systemd.exec(5)

EXIT_FDS

systemd.exec(5)

EXIT_GROUP

systemd.exec(5)

EXIT_INVALIDARGUMENT

systemd.exec(5)

EXIT_IOPRIO

systemd.exec(5)

EXIT_KEYRING

systemd.exec(5)

EXIT_LIMITS

systemd.exec(5)

EXIT_LOGS_DIRECTORY

systemd.exec(5)

EXIT_MEMORY

systemd.exec(5)

EXIT_NAMESPACE

systemd.exec(5)

EXIT_NETWORK

systemd.exec(5)

EXIT_NICE

systemd.exec(5)

EXIT_NOPERMISSION

systemd.exec(5)

EXIT_NOTCONFIGURED

systemd.exec(5)

EXIT_NOTIMPLEMENTED

systemd.exec(5)

EXIT_NOTINSTALLED

systemd.exec(5)

EXIT_NOTRUNNING

systemd.exec(5)

EXIT_NO_NEW_PRIVILEGES

systemd.exec(5)

EXIT_NUMA_POLICY

systemd.exec(5)

EXIT_OOM_ADJUST

systemd.exec(5)

EXIT_PAM

systemd.exec(5)

EXIT_PERSONALITY

systemd.exec(5)

EXIT_RUNTIME_DIRECTORY

systemd.exec(5)

EXIT_SECCOMP

systemd.exec(5)

EXIT_SECUREBITS

systemd.exec(5)

EXIT_SELINUX_CONTEXT

systemd.exec(5)

EXIT_SETSCHEDULER

systemd.exec(5)

EXIT_SETSID

systemd.exec(5)

EXIT_SIGNAL_MASK

systemd.exec(5)

EXIT_SMACK_PROCESS_LABEL

systemd.exec(5)

EXIT_STATE_DIRECTORY

systemd.exec(5)

EXIT_STDERR

systemd.exec(5)

EXIT_STDIN

systemd.exec(5)

EXIT_STDOUT

systemd.exec(5)

EXIT_SUCCESS

systemd.exec(5)

EXIT_TIMERSLACK

systemd.exec(5)

EXIT_USER

systemd.exec(5)

EX_CANTCREAT

systemd-tmpfiles(8), systemd.exec(5)

EX_CONFIG

systemd.exec(5)

EX_DATAERR

systemd-tmpfiles(8), systemd.exec(5)

EX_IOERR

systemd.exec(5)

EX_NOHOST

systemd.exec(5)

EX_NOINPUT

systemd.exec(5)

EX_NOPERM

systemd.exec(5)

EX_NOUSER

systemd.exec(5)

EX_OSERR

systemd.exec(5)

EX_OSFILE

systemd.exec(5)

EX_PROTOCOL

systemd.exec(5)

EX_SOFTWARE

systemd.exec(5)

EX_TEMPFAIL

systemd.exec(5)

EX_UNAVAILABLE

systemd.exec(5)

EX_USAGE

systemd.exec(5)

GPT_FLAG_NO_AUTO

systemd-gpt-auto-generator(8)

GPT_FLAG_NO_BLOCK_IO_PROTOCOL

systemd-gpt-auto-generator(8)

GPT_FLAG_READ_ONLY

systemd-gpt-auto-generator(8)

IFF_UP

org.freedesktop.resolve1(5)

IN

resolvectl(1)

INIT_PROCESS

systemd.exec(5)

IN_ACCESS

sd_event_add_inotify(3)

IN_ATTRIB

sd_event_add_inotify(3)

IN_CLOSE_WRITE

sd_event_add_inotify(3)

IN_MASK_ADD

sd_event_add_inotify(3)

IN_ONESHOT

sd_event_add_inotify(3)

IPPROTO_SCTP

systemd.socket(5)

IPPROTO_UDPLITE

systemd.socket(5)

IPV6_FREEBIND

daemon(7), systemd.socket(5)

IPV6_RECVPKTINFO

systemd.socket(5)

IPV6_TRANSPARENT

systemd.socket(5)

IPV6_UNICAST_HOPS

systemd.socket(5)

IP_FREEBIND

daemon(7), systemd.socket(5)

IP_PKTINFO

systemd.socket(5)

IP_TOS

systemd.socket(5)

IP_TRANSPARENT

systemd.socket(5)

IP_TTL

systemd.socket(5)

LINE_MAX - 8

sd_journal_print(3)

LOGIN_PROCESS

systemd.exec(5)

LOG_ALERT

sd_journal_print(3), sd_journal_stream_fd(3)

LOG_CRIT

sd_journal_print(3), sd_journal_stream_fd(3)

LOG_DEBUG

sd_journal_print(3), sd_journal_stream_fd(3)

LOG_EMERG

sd_journal_print(3), sd_journal_stream_fd(3)

LOG_ERR

sd_journal_print(3), sd_journal_stream_fd(3)

LOG_INFO

sd_journal_print(3), sd_journal_stream_fd(3)

LOG_NOTICE

sd_journal_print(3), sd_journal_stream_fd(3)

LOG_WARNING

sd_journal_print(3), sd_journal_stream_fd(3)

M

tmpfiles.d(5)

MAP_ANON

systemd.exec(5)

MESSAGE_ID=fc2e22bc6ee647b6b90729ab34a250b1

systemd-coredump(8)

MSDOS_SUPER_MAGIC

file-hierarchy(7)

MS_NOSUID

systemd.exec(5)

MS_SLAVE

systemd.exec(5)

NETLINK_PKTINFO

systemd.socket(5)

NL

systemctl(1)

NO_ADDRESS

org.freedesktop.resolve1(5)

NO_AUTO_START

sd_bus_message_set_expect_reply(3)

NO_REPLY_EXPECTED

sd_bus_message_set_expect_reply(3)

NUL

crypttab(5), journald.conf(5), pam_systemd(8), sd-id128(3), sd_bus_creds_get_pid(3),

sd_bus_message_append(3), sd_bus_message_append_basic(3),
sd_bus_message_append_string_memfd(3), sd_bus_message_append_strv(3),
sd_bus_message_read(3), sd_bus_message_read_array(3), sd_bus_path_encode(3),
sd_event_source_set_description(3), sd_hwdb_get(3), sd_id128_to_string(3),
sd_journal_add_match(3), sd_path_lookup(3), systemd-ask-password(1), systemd-
journal.service(8), systemd-nspawn(1), systemd.exec(5), systemd.journal-fields(7),
systemd.network(5), systemd.socket(5), systemd.unit(5), udev(7),
udev_device_has_tag(3)

NULL

sd-login(3), sd_bus_add_match(3), sd_bus_add_node_enumerator(3), sd_bus_add_object(3),
sd_bus_add_object_manager(3), sd_bus_attach_event(3), sd_bus_call(3),
sd_bus_can_send(3), sd_bus_close(3), sd_bus_creds_get_pid(3),
sd_bus_creds_new_from_pid(3), sd_bus_default(3), sd_bus_emit_signal(3),
sd_bus_error(3), sd_bus_get_current_handler(3), sd_bus_interface_name_is_valid(3),
sd_bus_is_open(3), sd_bus_list_names(3), sd_bus_message_append(3),
sd_bus_message_append_array(3), sd_bus_message_append_basic(3),
sd_bus_message_append_strv(3), sd_bus_message_at_end(3), sd_bus_message_copy(3),
sd_bus_message_get_signature(3), sd_bus_message_get_type(3), sd_bus_message_new(3),
sd_bus_message_new_method_call(3), sd_bus_message_new_method_error(3),
sd_bus_message_new_signal(3), sd_bus_message_open_container(3),
sd_bus_message_read(3), sd_bus_message_read_array(3), sd_bus_message_read_basic(3),
sd_bus_message_read_strv(3), sd_bus_message_rewind(3), sd_bus_message_seal(3),
sd_bus_message_sensitive(3), sd_bus_message_set_destination(3),
sd_bus_message_set_expect_reply(3), sd_bus_message_skip(3),
sd_bus_message_verify_type(3), sd_bus_new(3), sd_bus_path_encode(3),
sd_bus_process(3), sd_bus_query_sender_creds(3), sd_bus_reply_method_error(3),
sd_bus_reply_method_return(3), sd_bus_request_name(3), sd_bus_send(3),
sd_bus_set_address(3), sd_bus_set_description(3), sd_bus_set_exit_on_disconnect(3),
sd_bus_set_method_call_timeout(3), sd_bus_set_property(3), sd_bus_set_sender(3),
sd_bus_set_server(3), sd_bus_slot_get_bus(3), sd_bus_slot_ref(3),
sd_bus_slot_set_description(3), sd_bus_slot_set_destroy_callback(3),
sd_bus_slot_set_floating(3), sd_bus_slot_set_userdata(3), sd_bus_start(3),
sd_bus_track_add_name(3), sd_bus_track_new(3), sd_event_add_child(3),

sd_event_add_defer(3), sd_event_add_inotify(3), sd_event_add_io(3),
sd_event_add_signal(3), sd_event_add_time(3), sd_event_exit(3), sd_event_new(3),
sd_event_run(3), sd_event_source_get_event(3), sd_event_source_set_description(3),
sd_event_source_set_destroy_callback(3), sd_event_source_set_enabled(3),
sd_event_source_set_floating(3), sd_event_source_set_prepare(3),
sd_event_source_set_userdata(3), sd_event_source_unref(3), sd_event_wait(3),
sd_get_seats(3), sd_hwdb_get(3), sd_hwdb_new(3), sd_id128_to_string(3), sd_is_fifo(3),
sd_journal_get_cutoff_realtime_usec(3), sd_journal_get_data(3),
sd_journal_get_realtime_usec(3), sd_journal_has_runtime_files(3), sd_journal_open(3),
sd_journal_print(3), sd_journal_query_unique(3), sd_listen_fds(3),
sd_login_monitor_new(3), sd_machine_get_class(3), sd_path_lookup(3),
sd_pid_get_owner_uid(3), sd_seat_get_active(3), sd_session_is_active(3),
sd_uid_get_state(3), sd_watchdog_enabled(3), udev_device_get_syspath(3),
udev_device_has_tag(3), udev_device_new_from_syspath(3), udev_enumerate_new(3),
udev_enumerate_scan_devices(3), udev_list_entry(3), udev_monitor_new_from_netlink(3),
udev_monitor_receive_device(3), udev_new(3)

OR

systemd.exec(5)

O_NONBLOCK

sd_event_add_io(3), sd_journal_stream_fd(3), systemd.service(5)

P

systemd.net-naming-scheme(7)

PACKET_AUXDATA

systemd.socket(5)

PAM_SUCCESS

pam_systemd(8)

POLLERR

systemd.service(5)

POLLHUP

systemd.service(5)

POLLIN

sd_bus_get_fd(3), sd_event_get_fd(3), sd_journal_get_fd(3), sd_login_monitor_new(3)

POLLOUT

sd_bus_get_fd(3), sd_journal_get_fd(3), sd_login_monitor_new(3)

PROT_EXEC

file-hierarchy(7), systemd.exec(5)

PROT_WRITE

systemd.exec(5)

PR_SET_NO_NEW_PRIVS

systemd-nspawn(1), systemd.nspawn(5)

RLIMIT_NICE

systemd-nspawn(1)

RLIMIT_NOFILE

daemon(7), systemd-nspawn(1)

RLIMIT_NPROC

systemd-nspawn(1)

SCHED_DEADLINE

systemd.exec(5)

SCHED_FIFO

systemd.exec(5)

SCHED_RR

systemd.exec(5)

SD_BUS_ARGS(...)

sd_bus_add_object(3)

SD_BUS_ARGS()

sd_bus_add_object(3)

SD_BUS_CREDS_AUDIT_LOGIN_UID

sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_AUDIT_SESSION_ID

sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_AUGMENT

sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_BOUNDING_CAPS

sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_CGROUP

sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_CMDLINE
sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_COMM
sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_DESCRIPTION
sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_EFFECTIVE_CAPS
sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_EGID
sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_EUID
sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_EXE
sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_FSGID
sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_FSUID
sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_GID
sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_INHERITABLE_CAPS
sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_OWNER_UID
sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_PERMITTED_CAPS
sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_PID
sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_PPID
sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_SELINUX_CONTEXT
sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_SESSION

sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_SGID

sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_SLICE

sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_SUID

sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_SUPPLEMENTARY_GIDS

sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_TID

sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_TID_COMM

sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_TTY

sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_UID

sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_UNIQUE_NAME

sd_bus_creds_new_from_pid(3), sd_bus_negotiate_fds(3)

SD_BUS_CREDS_UNIT

sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_USER_SLICE

sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_USER_UNIT

sd_bus_creds_new_from_pid(3)

SD_BUS_CREDS_WELL_KNOWN_NAMES

sd_bus_creds_new_from_pid(3), sd_bus_negotiate_fds(3)

SD_BUS_ERROR_ACCESS_DENIED

sd-bus-errors(3)

SD_BUS_ERROR_ADDRESS_IN_USE

sd-bus-errors(3)

SD_BUS_ERROR_AUTH_FAILED

sd-bus-errors(3)

SD_BUS_ERROR_BAD_ADDRESS

sd-bus-errors(3)

SD_BUS_ERROR_DISCONNECTED

sd-bus-errors(3)

SD_BUS_ERROR_FAILED

sd-bus-errors(3)

SD_BUS_ERROR_FILE_EXISTS

sd-bus-errors(3)

SD_BUS_ERROR_FILE_NOT_FOUND

sd-bus-errors(3)

SD_BUS_ERROR_INCONSISTENT_MESSAGE

sd-bus-errors(3)

SD_BUS_ERROR_INTERACTIVE_AUTHORIZATION_REQUIRED

sd-bus-errors(3)

SD_BUS_ERROR_INVALID_ARGS

sd-bus-errors(3)

SD_BUS_ERROR_INVALID_SIGNATURE

sd-bus-errors(3)

SD_BUS_ERROR_IO_ERROR

sd-bus-errors(3)

SD_BUS_ERROR_LIMITS_EXCEEDED

sd-bus-errors(3)

SD_BUS_ERROR_MAKE_CONST(name, message)

sd_bus_error(3)

SD_BUS_ERROR_MAKE_CONST()

sd_bus_error(3)

SD_BUS_ERROR_MAP(name, code)

sd_bus_error_add_map(3)

SD_BUS_ERROR_MAP()

sd_bus_error_add_map(3)

SD_BUS_ERROR_MAP_END

sd_bus_error_add_map(3)

SD_BUS_ERROR_MATCH_RULE_INVALID

sd-bus-errors(3)

SD_BUS_ERROR_MATCH_RULE_NOT_FOUND

sd-bus-errors(3)

SD_BUS_ERROR_NAME_HAS_NO_OWNER

sd-bus-errors(3)

SD_BUS_ERROR_NOT_SUPPORTED

sd-bus-errors(3), sd_bus_message_new_method_error(3)

SD_BUS_ERROR_NO_MEMORY

sd-bus-errors(3), sd_bus_error(3)

SD_BUS_ERROR_NO_NETWORK

sd-bus-errors(3)

SD_BUS_ERROR_NO_REPLY

sd-bus-errors(3)

SD_BUS_ERROR_NO_SERVER

sd-bus-errors(3)

SD_BUS_ERROR_NULL

sd_bus_call(3), sd_bus_error(3)

SD_BUS_ERROR_PROPERTY_READ_ONLY

sd-bus-errors(3)

SD_BUS_ERROR_SERVICE_UNKNOWN

sd-bus-errors(3)

SD_BUS_ERROR_TIMEOUT

sd-bus-errors(3)

SD_BUS_ERROR_UNIX_PROCESS_ID_UNKNOWN

sd-bus-errors(3)

SD_BUS_ERROR_UNKNOWN_INTERFACE

sd-bus-errors(3)

SD_BUS_ERROR_UNKNOWN_METHOD

sd-bus-errors(3)

SD_BUS_ERROR_UNKNOWN_OBJECT

sd-bus-errors(3)

SD_BUS_ERROR_UNKNOWN_PROPERTY

sd-bus-errors(3)

SD_BUS_MESSAGE_DUMP_SUBTREE_ONLY

sd_bus_message_dump(3)

SD_BUS_MESSAGE_DUMP_WITH_HEADER

sd_bus_message_dump(3)

SD_BUS_MESSAGE_METHOD_CALL

sd_bus_message_get_type(3), sd_bus_message_new(3)

SD_BUS_MESSAGE_METHOD_ERROR

sd_bus_message_get_type(3), sd_bus_message_new(3)

SD_BUS_MESSAGE_METHOD_RETURN

sd_bus_message_get_type(3), sd_bus_message_new(3)

SD_BUS_MESSAGE_SIGNAL

sd_bus_message_get_type(3), sd_bus_message_new(3)

SD_BUS_METHOD(member, signature, result, handler, flags)

sd_bus_add_object(3)

SD_BUS_METHOD()

sd_bus_add_object(3)

SD_BUS_METHOD_WITH_ARGS(member, args, result, handler, flags)

sd_bus_add_object(3)

SD_BUS_METHOD_WITH_ARGS()

sd_bus_add_object(3)

SD_BUS_METHOD_WITH_ARGS_OFFSET(member, args, result, handler, offset, flags)

sd_bus_add_object(3)

SD_BUS_METHOD_WITH_ARGS_OFFSET()

sd_bus_add_object(3)

SD_BUS_METHOD_WITH_NAMES(member, signature, in_names, result, out_names, handler, flags)

sd_bus_add_object(3)

SD_BUS_METHOD_WITH_NAMES()

sd_bus_add_object(3)

SD_BUS_METHOD_WITH_NAMES_OFFSET(member, signature, in_names, result, out_names, handler,
offset, flags)

sd_bus_add_object(3)

SD_BUS_METHOD_WITH_NAMES_OFFSET()

sd_bus_add_object(3)

SD_BUS_METHOD_WITH_OFFSET(member, signature, result, handler, offset, flags)

sd_bus_add_object(3)

SD_BUS_METHOD_WITH_OFFSET()

sd_bus_add_object(3)

SD_BUS_NAME_ALLOW_REPLACEMENT

sd_bus_request_name(3)

SD_BUS_NAME_QUEUE

sd_bus_request_name(3)

SD_BUS_NAME_REPLACE_EXISTING

sd_bus_request_name(3)

SD_BUS_NO_ARGS

sd_bus_add_object(3)

SD_BUS_NO_RESULT

sd_bus_add_object(3)

SD_BUS_PARAM(name)

sd_bus_add_object(3)

SD_BUS_PARAM()

sd_bus_add_object(3)

SD_BUS_PROPERTY(member, signature, get, offset, flags)

sd_bus_add_object(3)

SD_BUS_PROPERTY()

sd_bus_add_object(3)

SD_BUS_RESULT(...)

sd_bus_add_object(3)

SD_BUS_RESULT()

sd_bus_add_object(3)

SD_BUS_SIGNAL(member, signature, flags)

sd_bus_add_object(3)

SD_BUS_SIGNAL()

sd_bus_add_object(3)

SD_BUS_SIGNAL_WITH_ARGS(member, args, flags)

sd_bus_add_object(3)

SD_BUS_SIGNAL_WITH_ARGS()

```

    sd_bus_add_object(3)
SD_BUS_SIGNAL_WITH_NAMES(member, signature, names, flags)
    sd_bus_add_object(3)
SD_BUS_SIGNAL_WITH_NAMES()
    sd_bus_add_object(3)
SD_BUS_TYPE
    sd_bus_can_send(3)
SD_BUS_TYPE_ARRAY
    sd_bus_message_append(3), sd_bus_message_open_container(3), sd_bus_message_read(3)
SD_BUS_TYPE_BOOLEAN
    sd_bus_message_append(3), sd_bus_message_append_basic(3), sd_bus_message_read(3),
    sd_bus_message_read_basic(3)
SD_BUS_TYPE_BYTE
    sd_bus_message_append(3), sd_bus_message_append_basic(3), sd_bus_message_read(3),
    sd_bus_message_read_basic(3)
SD_BUS_TYPE_DICT_ENTRY
    sd_bus_message_open_container(3)
SD_BUS_TYPE_DICT_ENTRY_BEGIN
    sd_bus_message_append(3), sd_bus_message_read(3)
SD_BUS_TYPE_DICT_ENTRY_END
    sd_bus_message_append(3), sd_bus_message_read(3)
SD_BUS_TYPE_DOUBLE
    sd_bus_message_append(3), sd_bus_message_append_basic(3), sd_bus_message_read(3),
    sd_bus_message_read_basic(3)
SD_BUS_TYPE_INT16
    sd_bus_message_append(3), sd_bus_message_append_basic(3), sd_bus_message_read(3),
    sd_bus_message_read_basic(3)
SD_BUS_TYPE_INT32
    sd_bus_message_append(3), sd_bus_message_append_basic(3), sd_bus_message_read(3),
    sd_bus_message_read_basic(3)
SD_BUS_TYPE_INT64
    sd_bus_message_append(3), sd_bus_message_append_basic(3), sd_bus_message_read(3),
    sd_bus_message_read_basic(3)

```

SD_BUS_TYPE_OBJECT_PATH

sd_bus_message_append(3), sd_bus_message_append_basic(3), sd_bus_message_read(3),
sd_bus_message_read_basic(3)

SD_BUS_TYPE_SIGNATURE

sd_bus_message_append(3), sd_bus_message_append_basic(3), sd_bus_message_read(3),
sd_bus_message_read_basic(3)

SD_BUS_TYPE_STRING

sd_bus_message_append(3), sd_bus_message_append_basic(3), sd_bus_message_read(3),
sd_bus_message_read_basic(3)

SD_BUS_TYPE_STRUCT

sd_bus_message_open_container(3)

SD_BUS_TYPE_STRUCT_BEGIN

sd_bus_message_append(3), sd_bus_message_read(3)

SD_BUS_TYPE_STRUCT_END

sd_bus_message_append(3), sd_bus_message_read(3)

SD_BUS_TYPE_UINT16

sd_bus_message_append(3), sd_bus_message_append_basic(3), sd_bus_message_read(3),
sd_bus_message_read_basic(3)

SD_BUS_TYPE_UINT32

sd_bus_message_append(3), sd_bus_message_append_basic(3), sd_bus_message_read(3),
sd_bus_message_read_basic(3)

SD_BUS_TYPE_UINT64

sd_bus_message_append(3), sd_bus_message_append_basic(3), sd_bus_message_read(3),
sd_bus_message_read_basic(3)

SD_BUS_TYPE_UNIX_FD

sd_bus_message_append(3), sd_bus_message_append_basic(3), sd_bus_message_read(3),
sd_bus_message_read_basic(3), sd_bus_negotiate_fds(3)

SD_BUS_TYPE_VARIANT

sd_bus_message_append(3), sd_bus_message_open_container(3), sd_bus_message_read(3)

SD_BUS_VTABLE_ABSOLUTE_OFFSET

sd_bus_add_object(3)

SD_BUS_VTABLE_CAPABILITY(capability)

sd_bus_add_object(3)

SD_BUS_VTABLE_DEPRECATED

sd_bus_add_object(3)

SD_BUS_VTABLE_END

sd_bus_add_object(3)

SD_BUS_VTABLE_HIDDEN

sd_bus_add_object(3)

SD_BUS_VTABLE_METHOD_NO_REPLY

sd_bus_add_object(3)

SD_BUS_VTABLE_PROPERTY_CONST

sd_bus_add_object(3)

SD_BUS_VTABLE_PROPERTY_EMITS_CHANGE

sd_bus_add_object(3)

SD_BUS_VTABLE_PROPERTY_EMITS_INVALIDATION

sd_bus_add_object(3)

SD_BUS_VTABLE_PROPERTY_EXPLICIT

sd_bus_add_object(3)

SD_BUS_VTABLE_SENSITIVE

sd_bus_add_object(3)

SD_BUS_VTABLE_START(flags)

sd_bus_add_object(3)

SD_BUS_VTABLE_START()

sd_bus_add_object(3)

SD_BUS_VTABLE_UNPRIVILEGED

sd_bus_add_object(3)

SD_BUS_WRITABLE_PROPERTY(member, signature, get, set, offset, flags)

sd_bus_add_object(3)

SD_BUS_WRITABLE_PROPERTY()

sd_bus_add_object(3)

SD_EVENT_ARMED

sd_event_wait(3)

SD_EVENT_EXITING

sd_event_wait(3)

SD_EVENT_FINISHED

```

sd_event_wait(3)
SD_EVENT_INITIAL
sd_event_wait(3)
SD_EVENT_OFF
sd_event_add_child(3), sd_event_add_defer(3), sd_event_add_io(3),
sd_event_add_signal(3), sd_event_add_time(3), sd_event_source_set_enabled(3),
sd_event_source_set_ratelimit(3), sd_event_source_unref(3)
SD_EVENT_ON
sd_event_add_child(3), sd_event_add_defer(3), sd_event_add_inotify(3),
sd_event_add_io(3), sd_event_add_signal(3), sd_event_add_time(3),
sd_event_source_set_enabled(3)
SD_EVENT_ONESHOT
sd_event_add_child(3), sd_event_add_defer(3), sd_event_add_inotify(3),
sd_event_add_time(3), sd_event_source_set_enabled(3)
SD_EVENT_PENDING
sd_event_wait(3)
SD_EVENT_PREPARING
sd_event_wait(3)
SD_EVENT_PRIORITY_IDLE
sd_event_source_set_priority(3)
SD_EVENT_PRIORITY_IMPORTANT
sd_event_source_set_priority(3)
SD_EVENT_PRIORITY_NORMAL
sd_event_source_set_priority(3)
SD_EVENT_RUNNING
sd_event_wait(3)
SD_ID128_ALLF
sd_id128_get_machine(3), sd_id128_randomize(3)
SD_ID128_FORMAT_STR
sd-id128(3), sd_id128_to_string(3)
SD_ID128_NULL
sd-id128(3), sd_bus_set_server(3), sd_id128_get_machine(3), sd_id128_randomize(3)
SD_ID128_UUID_FORMAT_STR

```

sd-id128(3)

SD_JOURNAL_ALL_NAMESPACES

sd_journal_open(3)

SD_JOURNAL_APPEND

sd_journal_get_fd(3)

SD_JOURNAL_CURRENT_USER

sd_journal_open(3)

SD_JOURNAL_INCLUDE_DEFAULT_NAMESPACE

sd_journal_open(3)

SD_JOURNAL_INVALIDATE

sd_journal_get_fd(3)

SD_JOURNAL_LOCAL_ONLY

sd_journal_get_usage(3), sd_journal_open(3)

SD_JOURNAL_NOP

sd_journal_get_fd(3)

SD_JOURNAL_OS_ROOT

sd_journal_open(3)

SD_JOURNAL_RUNTIME_ONLY

sd_journal_open(3)

SD_JOURNAL_SUPPRESS_LOCATION

sd_journal_print(3)

SD_JOURNAL_SYSTEM

sd_journal_open(3)

SD_LISTEN_FDS_START

sd_listen_fds(3)

SD_LOGIND_KEXEC_REBOOT

org.freedesktop.login1(5)

SD_LOGIND_ROOT_CHECK_INHIBITORS

org.freedesktop.login1(5)

SD_PATH_BINFMT

sd_path_lookup(3)

SD_PATH_CATALOG

sd_path_lookup(3)

SD_PATH_MODULES_LOAD

sd_path_lookup(3)

SD_PATH_SEARCH_BINARIES

sd_path_lookup(3)

SD_PATH_SEARCH_BINARIES_DEFAULT

sd_path_lookup(3)

SD_PATH_SEARCH_CONFIGURATION

sd_path_lookup(3)

SD_PATH_SEARCH_CONFIGURATION_FACTORY

sd_path_lookup(3)

SD_PATH_SEARCH_LIBRARY_ARCH

sd_path_lookup(3)

SD_PATH_SEARCH_LIBRARY_PRIVATE

sd_path_lookup(3)

SD_PATH_SEARCH_SHARED

sd_path_lookup(3)

SD_PATH_SEARCH_STATE_FACTORY

sd_path_lookup(3)

SD_PATH_SYSCTL

sd_path_lookup(3)

SD_PATH_SYSTEMD_SEARCH_NETWORK

sd_path_lookup(3)

SD_PATH_SYSTEMD_SEARCH_SYSTEM_GENERATOR

sd_path_lookup(3)

SD_PATH_SYSTEMD_SEARCH_SYSTEM_UNIT

sd_path_lookup(3)

SD_PATH_SYSTEMD_SEARCH_USER_GENERATOR

sd_path_lookup(3)

SD_PATH_SYSTEMD_SEARCH_USER_UNIT

sd_path_lookup(3)

SD_PATH_SYSTEMD_SHUTDOWN

sd_path_lookup(3)

SD_PATH_SYSTEMD_SLEEP

sd_path_lookup(3)
SD_PATH_SYSTEMD_SYSTEM_CONF
sd_path_lookup(3)
SD_PATH_SYSTEMD_SYSTEM_GENERATOR
sd_path_lookup(3)
SD_PATH_SYSTEMD_SYSTEM_PRESET
sd_path_lookup(3)
SD_PATH_SYSTEMD_SYSTEM_UNIT
sd_path_lookup(3)
SD_PATH_SYSTEMD_USER_CONF
sd_path_lookup(3)
SD_PATH_SYSTEMD_USER_GENERATOR
sd_path_lookup(3)
SD_PATH_SYSTEMD_USER_PRESET
sd_path_lookup(3)
SD_PATH_SYSTEMD_USER_UNIT
sd_path_lookup(3)
SD_PATH_SYSTEMD_UTIL
sd_path_lookup(3)
SD_PATH_SYSTEM_BINARIES
sd_path_lookup(3)
SD_PATH_SYSTEM_CONFIGURATION
sd_path_lookup(3)
SD_PATH_SYSTEM_CONFIGURATION_FACTORY
sd_path_lookup(3)
SD_PATH_SYSTEM_INCLUDE
sd_path_lookup(3)
SD_PATH_SYSTEM_LIBRARY_ARCH
sd_path_lookup(3)
SD_PATH_SYSTEM_LIBRARY_PRIVATE
sd_path_lookup(3)
SD_PATH_SYSTEM_RUNTIME
sd_path_lookup(3)

SD_PATH_SYSTEM_RUNTIME_LOGS

sd_path_lookup(3)

SD_PATH_SYSTEM_SHARED

sd_path_lookup(3)

SD_PATH_SYSTEM_STATE_CACHE

sd_path_lookup(3)

SD_PATH_SYSTEM_STATE_FACTORY

sd_path_lookup(3)

SD_PATH_SYSTEM_STATE_LOGS

sd_path_lookup(3)

SD_PATH_SYSTEM_STATE_PRIVATE

sd_path_lookup(3)

SD_PATH_SYSTEM_STATE_SPOOL

sd_path_lookup(3)

SD_PATH_SYSUSERS

sd_path_lookup(3)

SD_PATH_TEMPORARY

sd_path_lookup(3)

SD_PATH_TEMPORARY_LARGE

sd_path_lookup(3)

SD_PATH_TMPFILES

sd_path_lookup(3)

SD_PATH_USER

sd_path_lookup(3)

SD_PATH_USER_BINARIES

sd_path_lookup(3)

SD_PATH_USER_CONFIGURATION

sd_path_lookup(3)

SD_PATH_USER_DESKTOP

sd_path_lookup(3)

SD_PATH_USER_DOCUMENTS

sd_path_lookup(3)

SD_PATH_USER_DOWNLOAD

sd_path_lookup(3)

SD_PATH_USER_LIBRARY_ARCH

sd_path_lookup(3)

SD_PATH_USER_LIBRARY_PRIVATE

sd_path_lookup(3)

SD_PATH_USER_MUSIC

sd_path_lookup(3)

SD_PATH_USER_PICTURES

sd_path_lookup(3)

SD_PATH_USER_PUBLIC

sd_path_lookup(3)

SD_PATH_USER_RUNTIME

sd_path_lookup(3)

SD_PATH_USER_SHARED

sd_path_lookup(3)

SD_PATH_USER_STATE_CACHE

sd_path_lookup(3)

SD_PATH_USER_TEMPLATES

sd_path_lookup(3)

SD_PATH_USER_VIDEOS

sd_path_lookup(3)

SD_WARNING

sd_journal_stream_fd(3)

SEQNUM

udev_device_new_from_syspath(3)

SHM_EXEC

systemd.exec(5)

SIGABRT

systemd-udev.service(8), systemd.kill(5), systemd.service(5)

SIGCHLD

sd_event_add_child(3)

SIGCONT

systemd.kill(5)

SIGHUP

daemon(7), org.freedesktop.hostname1(5), systemd(1), systemd.kill(5),
systemd.service(5)

SIGINT

logind(1), machinectl(1), systemctl(1), systemd(1), systemd.service(5),
systemd.special(7)

SIGKILL

sd_event_add_child(3), systemd-nspawn(1), systemd-udevd.service(8), systemd.kill(5),
systemd.mount(5), systemd.resource-control(5), systemd.service(5), systemd.socket(5),
systemd.swap(5)

SIGPIPE

systemd-journald.service(8), systemd.exec(5), systemd.service(5)

SIGPWR

systemd(1)

SIGQUIT

systemd.kill(5)

SIGRTMIN+0

systemd(1)

SIGRTMIN+1

resolvectl(1), systemd(1), systemd-resolved.service(8)

SIGRTMIN+13

systemd(1)

SIGRTMIN+14

systemd(1)

SIGRTMIN+15

systemd(1)

SIGRTMIN+16

systemd(1)

SIGRTMIN+2

systemd(1)

SIGRTMIN+20

systemd(1)

SIGRTMIN+21

systemd(1)

SIGRTMIN+22

systemd(1)

SIGRTMIN+23

systemd(1)

SIGRTMIN+24

systemd(1)

SIGRTMIN+26

systemd(1)

SIGRTMIN+27

systemd(1)

SIGRTMIN+28

systemd(1)

SIGRTMIN+3

systemd(1), systemd-nspawn(1)

SIGRTMIN+4

systemd(1)

SIGRTMIN+5

systemd(1)

SIGRTMIN+6

systemd(1)

SIGSTOP

loginctl(1), machinectl(1), systemctl(1)

SIGSYS

systemd.exec(5)

SIGTERM

daemon(7), loginctl(1), machinectl(1), org.freedesktop.systemd1(5), sd_event_exit(3),
systemctl(1), systemd(1), systemd-nspawn(1), systemd.kill(5), systemd.mount(5),
systemd.service(5), systemd.socket(5), systemd.special(7), systemd.swap(5)

SIGUSR1

journald.conf(5), systemd(1), systemd-journald.service(8), systemd-resolved.service(8)

SIGUSR2

resolvectl(1), systemd(1), systemd-resolved.service(8)

SIGWINCH

systemd(1)

SIG_DFL

daemon(7)

SOCK_DGRAM

sd_is_fifo(3), systemd-socket-activate(1), systemd.socket(5)

SOCK_RAW

systemd.socket(5)

SOCK_SEQPACKET

systemd-socket-activate(1), systemd.exec(5), systemd.socket(5)

SOCK_STREAM

sd_is_fifo(3), systemd-socket-activate(1), systemd.socket(5)

SO_BINDTODEVICE

systemd.socket(5)

SO_BROADCAST

systemd.socket(5)

SO_KEEPALIVE

systemd.socket(5)

SO_MARK

systemd.socket(5)

SO_PASSCRED

systemd.socket(5)

SO_PASSSEC

systemd.socket(5)

SO_PRIORITY

systemd.netdev(5), systemd.socket(5)

SO_RCVBUF

systemd.socket(5)

SO_REUSEPORT

systemd.socket(5)

SO_SNDBUF

systemd.socket(5)

SO_TIMESTAMP

systemd.socket(5)

SO_TIMESTAMPNS

systemd.socket(5)

SUBSYSTEM

udev_device_new_from_syspath(3)

TAB

systemctl(1)

TCP_DEFER_ACCEPT

systemd.socket(5)

TCP_KEEPINTVL

systemd.socket(5)

TEMPFAIL

systemd.service(5)

TFD_TIMER_CANCEL_ON_SET

org.freedesktop.timedate1(5)

TIOCSTI

systemd-nspawn(1)

UINT64_MAX

sd_bus_get_fd(3), sd_bus_wait(3), sd_event_add_time(3)

USER_PROCESS

systemd.exec(5)

WCONTINUED

sd_event_add_child(3)

WEXITED

sd_event_add_child(3)

WSTOPPED

sd_event_add_child(3)

_NSIG

daemon(7)

_SC_ARG_MAX

systemctl(1)

_SD_BUS_CREDS_ALL

sd_bus_creds_new_from_pid(3)

a

systemd.net-naming-scheme(7), tmpfiles.d(5)

abcmABM

tmpfiles.d(5)

activating

systemctl(1)

active

systemctl(1)

alert

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemctl(1),
systemd(1), systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-
tmpfiles(8), timedatectl(1)

all

journalctl(1), systemctl(1), systemd.exec(5), udevadm(8)

any

systemd.resource-control(5)

application/json

systemd-journal-gatewayd.service(8)

application/vnd.fdo.journal

systemd-journal-gatewayd.service(8)

arm64

repart.d(5), systemd-system.conf(5), systemd.dnssd(5), systemd.unit(5), sysusers.d(5),
tmpfiles.d(5)

auto

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemctl(1),
systemd(1), systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-
tmpfiles(8), timedatectl(1)

b

systemd.net-naming-scheme(7), tmpfiles.d(5), udev_device_new_from_syspath(3)

bad-setting

systemctl(1)

bind4

systemd.resource-control(5)

bind6

systemd.resource-control(5)

c

systemd.net-naming-scheme(7), tmpfiles.d(5), udev_device_new_from_syspath(3)

cache

systemctl(1)

cgroup

systemd.exec(5)

cgroup/bind4

systemd.resource-control(5)

cgroup/bind6

systemd.resource-control(5)

configuration

systemctl(1)

connect4

systemd.resource-control(5)

connect6

systemd.resource-control(5)

console

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemctl(1),
systemd(1), systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-
tmpfiles(8), timedatectl(1)

console-prefixed

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemctl(1),
systemd(1), systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-
tmpfiles(8), timedatectl(1)

const

sd_bus_add_object(3)

continue

systemd.service(5)

control-group

systemd.kill(5)

crit

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemctl(1),
systemd(1), systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-
tmpfiles(8), timedatectl(1)

d

systemd.net-naming-scheme(7), tmpfiles.d(5)

deactivating

systemctl(1)

debug

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemctl(1),
systemd(1), systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-
tmpfiles(8), timedatectl(1)

default

systemd.exec(5)

device

systemd.resource-control(5)

early

udevadm(8)

egress

systemd.resource-control(5)

elf-headers

systemd.exec(5)

emerg

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemctl(1),
systemd(1), systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-
tmpfiles(8), timedatectl(1)

en

systemd.net-naming-scheme(7)

err

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemctl(1),
systemd(1), systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-
tmpfiles(8), timedatectl(1)

error

sd_bus_message_new_method_error(3), systemctl(1), systemd(1)

esp

repart.d(5), systemd.exec(5)

f

systemd.net-naming-scheme(7)

failed

systemctl(1), systemd.unit(5)

false

sd_bus_error(3)

getsockopt

systemd.resource-control(5)

h

tmpfiles.d(5)

home

repart.d(5), systemd.exec(5)

host

systemd-journal-remote.service(8)

https

systemd-journal-upload.service(8)

i

systemd.net-naming-scheme(7)

ib

systemd.net-naming-scheme(7)

inactive

systemctl(1), systemd.unit(5)

infinity

systemd-socket-proxyd(8), systemd.exec(5)

info

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemctl(1),

systemd(1), systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-

tmpfiles(8), timedatectl(1)

ingress

systemd.resource-control(5)

invalidates

sd_bus_add_object(3)

ipc

systemd.exec(5)

ipv4

systemd.resource-control(5)

ipv6

systemd.resource-control(5)

journal

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemctl(1),
systemd(1), systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-
tmpfiles(8), timedatectl(1)

journal-or-kmsg

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemctl(1),
systemd(1), systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-
tmpfiles(8), timedatectl(1)

keep

systemd.net-naming-scheme(7)

keep-caps

systemd.exec(5)

kernel.modules_disabled

systemd.exec(5)

kill

systemd.service(5)

kmsg

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemctl(1),
systemd(1), systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-
tmpfiles(8), timedatectl(1)

late

udevadm(8)

latest

systemd.net-naming-scheme(7)

libsystemd

sd-bus(3), sd-bus-errors(3), sd-daemon(3), sd-event(3), sd-hwdb(3), sd-id128(3), sd-

journal(3), sd-login(3), sd_booted(3), sd_bus_add_match(3),
sd_bus_add_node_enumerator(3), sd_bus_add_object(3), sd_bus_add_object_manager(3),
sd_bus_attach_event(3), sd_bus_call(3), sd_bus_call_method(3), sd_bus_can_send(3),
sd_bus_close(3), sd_bus_creds_get_pid(3), sd_bus_creds_new_from_pid(3),
sd_bus_default(3), sd_bus_emit_signal(3), sd_bus_enqueue_for_read(3), sd_bus_error(3),
sd_bus_error_add_map(3), sd_bus_get_current_handler(3), sd_bus_get_fd(3),
sd_bus_get_name_creds(3), sd_bus_get_name_machine_id(3),
sd_bus_interface_name_is_valid(3), sd_bus_is_open(3), sd_bus_list_names(3),
sd_bus_message_append(3), sd_bus_message_append_array(3),
sd_bus_message_append_basic(3), sd_bus_message_append_string_memfd(3),
sd_bus_message_append_strv(3), sd_bus_message_at_end(3), sd_bus_message_copy(3),
sd_bus_message_dump(3), sd_bus_message_get_cookie(3),
sd_bus_message_get_monotonic_usec(3), sd_bus_message_get_signature(3),
sd_bus_message_get_type(3), sd_bus_message_new(3), sd_bus_message_new_method_call(3),
sd_bus_message_new_method_error(3), sd_bus_message_new_signal(3),
sd_bus_message_open_container(3), sd_bus_message_read(3), sd_bus_message_rewind(3),
sd_bus_message_seal(3), sd_bus_message_sensitive(3),
sd_bus_message_set_destination(3), sd_bus_message_set_expect_reply(3),
sd_bus_message_skip(3), sd_bus_message_verify_type(3), sd_bus_negotiate_fds(3),
sd_bus_new(3), sd_bus_path_encode(3), sd_bus_process(3), sd_bus_query_sender_creds(3),
sd_bus_reply_method_error(3), sd_bus_reply_method_return(3), sd_bus_request_name(3),
sd_bus_send(3), sd_bus_set_address(3), sd_bus_set_close_on_exit(3),
sd_bus_set_connected_signal(3), sd_bus_set_description(3),
sd_bus_set_exit_on_disconnect(3), sd_bus_set_fd(3), sd_bus_set_method_call_timeout(3),
sd_bus_set_property(3), sd_bus_set_sender(3), sd_bus_set_server(3),
sd_bus_set_watch_bind(3), sd_bus_slot_get_bus(3), sd_bus_slot_ref(3),
sd_bus_slot_set_description(3), sd_bus_slot_set_destroy_callback(3),
sd_bus_slot_set_floating(3), sd_bus_slot_set_userdata(3), sd_bus_start(3),
sd_bus_track_add_name(3), sd_bus_track_new(3), sd_bus_wait(3), sd_event_add_child(3),
sd_event_add_defer(3), sd_event_add_inotify(3), sd_event_add_io(3),
sd_event_add_signal(3), sd_event_add_time(3), sd_event_exit(3), sd_event_get_fd(3),
sd_event_new(3), sd_event_now(3), sd_event_run(3), sd_event_set_watchdog(3),
sd_event_source_get_event(3), sd_event_source_get_pending(3),

sd_event_source_set_description(3), sd_event_source_set_destroy_callback(3),
sd_event_source_set_enabled(3), sd_event_source_set_exit_on_failure(3),
sd_event_source_set_floating(3), sd_event_source_set_prepare(3),
sd_event_source_set_priority(3), sd_event_source_set_ratelimit(3),
sd_event_source_set_userdata(3), sd_event_source_unref(3), sd_event_wait(3),
sd_get_seats(3), sd_hwdb_get(3), sd_hwdb_new(3), sd_id128_get_machine(3),
sd_id128_randomize(3), sd_id128_to_string(3), sd_is_fifo(3), sd_journal_add_match(3),
sd_journal_enumerate_fields(3), sd_journal_get_catalog(3), sd_journal_get_cursor(3),
sd_journal_get_cutoff_realtime_usec(3), sd_journal_get_data(3), sd_journal_get_fd(3),
sd_journal_get_realtime_usec(3), sd_journal_get_usage(3),
sd_journal_has_runtime_files(3), sd_journal_next(3), sd_journal_open(3),
sd_journal_print(3), sd_journal_query_unique(3), sd_journal_seek_head(3),
sd_journal_stream_fd(3), sd_listen_fds(3), sd_login_monitor_new(3),
sd_machine_get_class(3), sd_notify(3), sd_path_lookup(3), sd_pid_get_owner_uid(3),
sd_seat_get_active(3), sd_session_is_active(3), sd_uid_get_state(3),
sd_watchdog_enabled(3)

link-local

systemd.resource-control(5)

linux-generic

repart.d(5)

loaded

systemctl(1)

localhost

systemd.resource-control(5)

logs

systemctl(1)

m

systemd.resource-control(5), tmpfiles.d(5)

masked

systemctl(1)

max_equalizers=N+1

systemd.network(5)

min

tmpfiles.d(5)

mips64-le-n32

systemd.exec(5)

mips64-n32

systemd.exec(5)

mixed

systemd.kill(5)

mnt

systemd.exec(5)

ms

tmpfiles.d(5)

multi

systemd.resource-control(5)

multicast

systemd.resource-control(5)

n

systemd.net-naming-scheme(7)

name

udevadm(8)

native

systemd.exec(5)

net

systemd.exec(5)

never

udevadm(8)

nobody

systemd-nspawn(1)

noexec

systemd.exec(5)

none

systemd-journal-remote.service(8), systemd.kill(5)

not-found

systemctl(1)

notice

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemctl(1),
systemd(1), systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-
tmpfiles(8), timedatectl(1)

null

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemctl(1),
systemd(1), systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-
tmpfiles(8), timedatectl(1)

o

systemd.net-naming-scheme(7)

org.freedesktop.DBus.Deprecated

sd_bus_add_object(3)

org.freedesktop.DBus.Introspectable.Introspect

busctl(1), sd_bus_add_node_enumerator(3), sd_bus_add_object(3)

org.freedesktop.DBus.Method.NoReply

sd_bus_add_object(3)

org.freedesktop.DBus.ObjectManager

sd_bus_add_object_manager(3), sd_bus_emit_signal(3)

org.freedesktop.DBus.ObjectManager.GetManagedObjects

sd_bus_add_node_enumerator(3)

org.freedesktop.DBus.Peer

sd_bus_get_name_machine_id(3)

org.freedesktop.DBus.Properties

sd_bus_emit_signal(3), sd_bus_set_property(3)

org.freedesktop.DBus.Properties.PropertiesChanged

sd_bus_add_object(3)

org.freedesktop.DBus.Property.EmitsChangedSignal

sd_bus_add_object(3)

org.freedesktop.locale1.set-keyboard

org.freedesktop.locale1(5)

org.freedesktop.locale1.set-locale

org.freedesktop.locale1(5)

org.freedesktop.resolve1.Aborted

org.freedesktop.resolve1(5)
org.freedesktop.resolve1.CNameLoop
org.freedesktop.resolve1(5)
org.freedesktop.resolve1.DnsError.NXDOMAIN
org.freedesktop.resolve1(5)
org.freedesktop.resolve1.DnsError.REFUSED
org.freedesktop.resolve1(5)
org.freedesktop.resolve1.DnssecFailed
org.freedesktop.resolve1(5)
org.freedesktop.resolve1.InvalidReply
org.freedesktop.resolve1(5)
org.freedesktop.resolve1.LinkBusy
org.freedesktop.resolve1(5)
org.freedesktop.resolve1.NetworkDown
org.freedesktop.resolve1(5)
org.freedesktop.resolve1.NoNameServers
org.freedesktop.resolve1(5)
org.freedesktop.resolve1.NoSuchLink
org.freedesktop.resolve1(5)
org.freedesktop.resolve1.NoSuchRR
org.freedesktop.resolve1(5)
org.freedesktop.resolve1.NoSuchService
org.freedesktop.resolve1(5)
org.freedesktop.resolve1.NoTrustAnchor
org.freedesktop.resolve1(5)
org.freedesktop.resolve1.ResourceRecordTypeUnsupported
org.freedesktop.resolve1(5)
org.freedesktop.systemd1.Explicit
sd_bus_add_object(3)
org.freedesktop.systemd1.Privileged
sd_bus_add_object(3)
p
systemd.net-naming-scheme(7)

path

udevadm(8)

pid

systemd.exec(5)

post_bind4

systemd.resource-control(5)

post_bind6

systemd.resource-control(5)

ppc

systemd.exec(5)

ppc-le

systemd.exec(5)

ppc64

systemd.exec(5)

ppc64-le

systemd.exec(5)

private-anonymous

systemd.exec(5)

private-dax

systemd.exec(5)

private-file-backed

systemd.exec(5)

private-huge

systemd.exec(5)

process

systemd.kill(5)

property

udevadm(8)

r

systemd.resource-control(5)

random

systemd-repart(8)

recvmsg4

systemd.resource-control(5)

recvmsg6

systemd.resource-control(5)

reloading

systemctl(1)

root

repart.d(5), systemd.exec(5)

root-arm

repart.d(5)

root-arm-verity

repart.d(5)

root-arm64

repart.d(5)

root-arm64-verity

repart.d(5)

root-ia64

repart.d(5)

root-ia64-verity

repart.d(5)

root-riscv32

repart.d(5)

root-riscv32-verity

repart.d(5)

root-riscv64

repart.d(5)

root-riscv64-verity

repart.d(5)

root-secondary

repart.d(5)

root-secondary-verity

repart.d(5)

root-verity

repart.d(5)

root-x86

repart.d(5)

root-x86-64

repart.d(5)

root-x86-64-verity

repart.d(5)

root-x86-verity

repart.d(5)

runtime

systemctl(1)

rw

systemd.exec(5)

rwm

systemd.exec(5)

s

systemd.net-naming-scheme(7), tmpfiles.d(5)

s390

systemd.exec(5)

s390x

systemd.exec(5)

sch_teql

systemd.network(5)

sendmsg4

systemd.resource-control(5)

sendmsg6

systemd.resource-control(5)

setsockopt

systemd.resource-control(5)

shared-anonymous

systemd.exec(5)

shared-dax

systemd.exec(5)

shared-file-backed

systemd.exec(5)

shared-huge

systemd.exec(5)

simple

systemd-run(1)

sl

systemd.net-naming-scheme(7)

sock_create

systemd.resource-control(5)

sock_ops

systemd.resource-control(5)

srv

repart.d(5), systemd.exec(5)

state

systemctl(1)

stop

systemd.service(5)

swap

repart.d(5)

symlink

udevadm(8)

sysctl

systemd.resource-control(5)

syslog

systemctl(1)

tcp

resolvectl(1), systemd.resource-control(5)

text/event-stream

systemd-journal-gatewayd.service(8)

text/plain

systemd-journal-gatewayd.service(8)

tmp

repart.d(5), systemd.exec(5)

true

sd_bus_add_object(3), systemd-oomd.service(8)

u

systemd.net-naming-scheme(7)

udev_hwdb

libudev(3)

udev_queue

libudev(3)

udp

systemd.resource-control(5)

us

tmpfiles.d(5)

user

systemd.exec(5)

usr

repart.d(5), systemd.exec(5)

usr-arm

repart.d(5)

usr-arm-verity

repart.d(5)

usr-arm64

repart.d(5)

usr-arm64-verity

repart.d(5)

usr-ia64

repart.d(5)

usr-ia64-verity

repart.d(5)

usr-riscv32

repart.d(5)

usr-riscv32-verity

repart.d(5)

usr-riscv64

repart.d(5)

usr-riscv64-verity

repart.d(5)

usr-secondary

repart.d(5)

usr-secondary-verity

repart.d(5)

usr-verity

repart.d(5)

usr-x86

repart.d(5)

usr-x86-64

repart.d(5)

usr-x86-64-verity

repart.d(5)

usr-x86-verity

repart.d(5)

uts

systemd.exec(5)

v

systemd.net-naming-scheme(7)

v238

systemd.net-naming-scheme(7)

v239

systemd.net-naming-scheme(7)

v240

systemd.net-naming-scheme(7)

v241

systemd.net-naming-scheme(7)

v243

systemd.net-naming-scheme(7)

v245

systemd.net-naming-scheme(7)

v247

systemd.net-naming-scheme(7)

v249

systemd.net-naming-scheme(7)

var

repart.d(5), systemd.exec(5)

w

systemd.resource-control(5), tmpfiles.d(5)

warning

journalctl(1), localectl(1), loginctl(1), machinectl(1), portablectl(1), systemctl(1),
systemd(1), systemd-analyze(1), systemd-inhibit(1), systemd-nspawn(1), systemd-
tmpfiles(8), timedatectl(1)

wl

systemd.net-naming-scheme(7)

ww

systemd.net-naming-scheme(7)

x

systemd.net-naming-scheme(7)

x32

systemd.exec(5)

x86

repart.d(5), systemd-system.conf(5), systemd.dnssd(5), systemd.exec(5),
systemd.unit(5), sysusers.d(5), tmpfiles.d(5)

x86-64

repart.d(5), systemd-system.conf(5), systemd.dnssd(5), systemd.exec(5),
systemd.unit(5), sysusers.d(5), tmpfiles.d(5)

xbootldr

repart.d(5), systemd.exec(5)

yes

systemd.resource-control(5)

DNS RESOURCE RECORD TYPES

A

resolvectl(1)

AAAA

resolvectl(1)

CNAME

resolvectl(1)

DNAME

resolvectl(1)

DNSKEY

dnssec-trust-anchors.d(5)

DS

dnssec-trust-anchors.d(5)

MX

resolvectl(1)

OPENPGP

resolvectl(1)

OPENPGPKEY

resolvectl(1)

PTR

resolvectl(1)

SRV

org.freedesktop.resolve1(5), resolvectl(1), systemd.dnssd(5)

TLSA

resolvectl(1)

TXT

org.freedesktop.resolve1(5), resolvectl(1)

MISCELLANEOUS OPTIONS AND DIRECTIVES

Other configuration elements which don't fit in any of the above groups.

\$LISTEN_FDS

systemd-journal-remote.service(8)

A

tmpfiles.d(5)

A+

tmpfiles.d(5)

C

tmpfiles.d(5)

CopyBlocks=

repart.d(5)

CopyFiles=

repart.d(5)

D

tmpfiles.d(5)

Encrypt=

repart.d(5)

FactoryReset=

repart.d(5)

Flags=

repart.d(5)

Format=

repart.d(5)

GrowFileSystem=

repart.d(5)

H

tmpfiles.d(5)

ID_NET_LABEL_ONBOARD=

systemd.net-naming-scheme(7)

ID_NET_NAME_MAC=

systemd.net-naming-scheme(7)

ID_NET_NAME_ONBOARD=

systemd.net-naming-scheme(7)

ID_NET_NAME_PATH=

systemd.net-naming-scheme(7)

ID_NET_NAME_SLOT=

systemd.net-naming-scheme(7)

L

tmpfiles.d(5)

L+

tmpfiles.d(5)

Label=

repart.d(5)

MakeDirectories=

repart.d(5)

NoAuto=

repart.d(5)

PaddingMaxBytes=

repart.d(5)

PaddingMinBytes=

repart.d(5)

PaddingWeight=

repart.d(5)

Priority=

repart.d(5)

Q

tmpfiles.d(5)

R

tmpfiles.d(5)

ReadOnly=

repart.d(5)

SizeMaxBytes=

repart.d(5)

SizeMinBytes=

repart.d(5)

T

tmpfiles.d(5)

Type=

repart.d(5)

UUID=

repart.d(5)

Weight=

repart.d(5)

X

tmpfiles.d(5)

Z

tmpfiles.d(5)

a

tmpfiles.d(5)

a+

tmpfiles.d(5)

b

tmpfiles.d(5)

b+

tmpfiles.d(5)

c

tmpfiles.d(5)

c+

tmpfiles.d(5)

d

tmpfiles.d(5)

e

tmpfiles.d(5)

equivalent

systemd-delta(1)

extended

systemd-delta(1)

f

tmpfiles.d(5)

f+

tmpfiles.d(5)

g

sysusers.d(5)

h

tmpfiles.d(5)

m

sysusers.d(5)

masked

systemd-delta(1)

overridden

systemd-delta(1)

p

tmpfiles.d(5)

p+

tmpfiles.d(5)

q

tmpfiles.d(5)

r

sysusers.d(5), tmpfiles.d(5)

redirected

systemd-delta(1)

t

tmpfiles.d(5)

u

sysusers.d(5)

unchanged

systemd-delta(1)

user.coredump.comm

systemd-coredump(8)

user.coredump.exe

systemd-coredump(8)

user.coredump.gid

systemd-coredump(8)

user.coredump.hostname

systemd-coredump(8)

user.coredump.pid

systemd-coredump(8)

user.coredump.rlimit

systemd-coredump(8)

user.coredump.signal

systemd-coredump(8)

user.coredump.timestamp

systemd-coredump(8)

user.coredump.uid

systemd-coredump(8)

v

tmpfiles.d(5)

w

tmpfiles.d(5)

w+

tmpfiles.d(5)

x

tmpfiles.d(5)

z

tmpfiles.d(5)

SPECIFIERS

Short strings which are substituted in configuration directives.

"%%"

repart.d(5), systemd-system.conf(5), systemd.dnssd(5), systemd.mount(5),
systemd.swap(5), systemd.unit(5), sysusers.d(5), tmpfiles.d(5)

"%A"

repart.d(5), systemd-system.conf(5), systemd.dnssd(5), systemd.unit(5), sysusers.d(5),
tmpfiles.d(5)

"%B"

repart.d(5), systemd-system.conf(5), systemd.dnssd(5), systemd.unit(5), sysusers.d(5),
tmpfiles.d(5)

"%C"

systemd.unit(5), tmpfiles.d(5)

"%E"

systemd.unit(5)

"%G"

systemd.unit(5), tmpfiles.d(5)

"%H"

```

repart.d(5), systemd-system.conf(5), systemd.dnssd(5), systemd.unit(5), sysusers.d(5),
tmpfiles.d(5)
"%I"
systemd.unit(5)
"%J"
systemd.unit(5)
"%L "
systemd.unit(5), tmpfiles.d(5)
"%M"
repart.d(5), systemd-system.conf(5), systemd.dnssd(5), systemd.unit(5), sysusers.d(5),
tmpfiles.d(5)
"%N"
systemd.unit(5)
"%P"
systemd.unit(5)
"%S"
systemd.unit(5), tmpfiles.d(5)
"%T"
repart.d(5), systemd-system.conf(5), systemd.unit(5), sysusers.d(5), tmpfiles.d(5)
"%U"
systemd.unit(5), tmpfiles.d(5)
"%V"
repart.d(5), systemd-system.conf(5), systemd.unit(5), sysusers.d(5), tmpfiles.d(5)
"%W"
repart.d(5), systemd-system.conf(5), systemd.dnssd(5), systemd.unit(5), sysusers.d(5),
tmpfiles.d(5)
"%a"
repart.d(5), systemd-system.conf(5), systemd.dnssd(5), systemd.unit(5), sysusers.d(5),
tmpfiles.d(5)
"%b"
repart.d(5), systemd-system.conf(5), systemd.dnssd(5), systemd.unit(5), sysusers.d(5),
tmpfiles.d(5)
"%f"

```

```

systemd.unit(5)

"%g"

systemd.unit(5), tmpfiles.d(5)

"%h"

systemd.unit(5), tmpfiles.d(5)

"%i"

systemd.unit(5)

"%j"

systemd.unit(5)

"%l"

repart.d(5), systemd-system.conf(5), systemd.unit(5), sysusers.d(5), tmpfiles.d(5)

"%m"

repart.d(5), systemd-system.conf(5), systemd.dnssd(5), systemd.unit(5), sysusers.d(5),
tmpfiles.d(5)

"%n"

systemd.unit(5)

"%o"

repart.d(5), systemd-system.conf(5), systemd.dnssd(5), systemd.unit(5), sysusers.d(5),
tmpfiles.d(5)

"%p"

systemd.unit(5)

"%s"

systemd.unit(5)

"%t"

systemd.unit(5), tmpfiles.d(5)

"%u"

systemd.unit(5), tmpfiles.d(5)

"%v"

repart.d(5), systemd-system.conf(5), systemd.dnssd(5), systemd.unit(5), sysusers.d(5),
tmpfiles.d(5)

"%w"

repart.d(5), systemd-system.conf(5), systemd.dnssd(5), systemd.unit(5), sysusers.d(5),
tmpfiles.d(5)

```


FILES AND DIRECTORIES

Paths and file names referred to in the documentation.

/

file-hierarchy(7), repart.d(5), systemd-gpt-auto-generator(8), systemd-nspawn(1),
systemd-remount-fs.service(8), systemd-repart(8), systemd.nspawn(5),
systemd.special(7), systemd.unit(5), tmpfiles.d(5)

\$XDG_CONFIG_DIRS/systemd/user/

systemd.unit(5)

\$XDG_DATA_DIRS/systemd/user/

systemd.unit(5)

\$XDG_DATA_HOME/systemd/user/

systemd.unit(5)

\$XDG_RUNTIME_DIR/systemd/generator/

systemd.unit(5)

\$XDG_RUNTIME_DIR/systemd/generator.early/

systemd.unit(5)

\$XDG_RUNTIME_DIR/systemd/generator.late/

systemd.unit(5)

\$XDG_RUNTIME_DIR/systemd/transient/

systemd.unit(5)

\$XDG_RUNTIME_DIR/systemd/user/

systemd.unit(5)

\$XDG_RUNTIME_DIR/systemd/user.control/

systemd.unit(5)

\$XDG_RUNTIME_DIR/user-tmpfiles.d/*.conf

tmpfiles.d(5)

-.mount

systemd.special(7)

-.slice

systemd.special(7)

/EFI/Linux/

systemd-boot(7)

/bin/

file-hierarchy(7), systemd-nspawn(1), systemd.exec(5), systemd.service(5)

/bin/bash

systemd-run(1)

/bin/echo

systemd.service(5)

/bin/ls

systemd-cat(1)

/bin/mount

systemctl(1)

/bin/sh

machinectl(1), sysusers.d(5)

/bin/umount

systemctl(1)

/boot/

bootctl(1), file-hierarchy(7), kernel-install(8), systemd-boot(7), systemd-gpt-auto-generator(8), systemd-nspawn(1), systemd.exec(5)

/boot/efi/

bootctl(1), kernel-install(8), systemd-boot(7)

/dev/

file-hierarchy(7), systemd-debug-generator(8), systemd-nspawn(1), systemd-remount-fs.service(8), systemd.device(5), systemd.exec(5), systemd.generator(7), systemd.journal-fields(7), systemd.resource-control(5), udev(7), udevadm(8)

/dev/block/

systemd.resource-control(5)

/dev/char/

systemd.resource-control(5)

/dev/console

journald.conf(5), systemd-getty-generator(8), systemd-nspawn(1), systemd-tty-ask-password-agent(1), systemd.exec(5)

/dev/disk/by-label/...

systemd-fstab-generator(8)

/dev/disk/by-uuid/...

systemd-fstab-generator(8)

/dev/full

systemd.resource-control(5)

/dev/hidraw1

crypttab(5), systemd-cryptenroll(1)

/dev/initctl

systemd(1), systemd-initctl.service(8)

/dev/kmsg

journald.conf(5), systemd-journal.service(8), systemd.exec(5), systemd.generator(7)

/dev/log

systemctl(1), systemd-journal.service(8)

/dev/loop-control

systemd.exec(5)

/dev/mapper/

crypttab(5), veritytab(5)

/dev/mapper/home

systemd-gpt-auto-generator(8)

/dev/mapper/root

systemd-gpt-auto-generator(8)

/dev/mapper/srv

systemd-gpt-auto-generator(8)

/dev/mapper/tmp

systemd-gpt-auto-generator(8)

/dev/mapper/var

systemd-gpt-auto-generator(8)

/dev/mem

systemd.exec(5)

/dev/net/tun

systemd.netdev(5)

/dev/null

binfmt.d(5), coredump.conf(5), daemon(7), dnsssec-trust-anchors.d(5), environment.d(5),
hwdb(7), journal-remote.conf(5), journal-upload.conf(5), journald.conf(5), kernel-
install(8), logind.conf(5), modules-load.d(5), networkd.conf(5), oomd.conf(5),
org.freedesktop.systemd1(5), pstore.conf(5), resolved.conf(5), sysctl.d(5),

systemctl(1), systemd-sleep.conf(5), systemd-system.conf(5), systemd.environment-generator(7), systemd.exec(5), systemd.generator(7), systemd.link(5),
systemd.netdev(5), systemd.network(5), systemd.preset(5), systemd.resource-control(5),
systemd.unit(5), sysusers.d(5), timesyncd.conf(5), tmpfiles.d(5), udev(7)

/dev/port

systemd.exec(5)

/dev/random

systemd.exec(5), systemd.resource-control(5)

/dev/rtc0

systemd.exec(5)

/dev/rtc1

systemd.exec(5)

/dev/sda

systemd.exec(5)

/dev/sda5

systemd.resource-control(5)

/dev/shm/

file-hierarchy(7), systemd.exec(5)

/dev/tpmrm0

crypttab(5), systemd-cryptenroll(1)

/dev/tty9

systemd-debug-generator(8)

/dev/urandom

crypttab(5), sd_id128_randomize(3), systemd-random-seed.service(8), systemd.resource-control(5)

/dev/watchdog

systemd-system.conf(5)

/dev/zero

systemd.exec(5), systemd.resource-control(5)

/efi/

bootctl(1), file-hierarchy(7), kernel-install(8), systemd-boot(7), systemd-gpt-auto-generator(8), systemd-nspawn(1), systemd.exec(5)

/etc/

binfmt.d(5), coredump.conf(5), environment.d(5), file-hierarchy(7), hwdb(7), journal-remote.conf(5), journal-upload.conf(5), journal.d.conf(5), kernel-command-line(7), logind.conf(5), machine-id(5), machinectl(1), modules-load.d(5), networkd.conf(5), nss-myhostname(8), oomd.conf(5), org.freedesktop.systemd1(5), os-release(5), portablectl(1), pstore.conf(5), resolved.conf(5), sysctl.d(5), systemctl(1), systemd-delta(1), systemd-fstab-generator(8), systemd-machine-id-commit.service(8), systemd-machine-id-setup(1), systemd-modules-load.service(8), systemd-nspawn(1), systemd-sleep.conf(5), systemd-sysex(8), systemd-system.conf(5), systemd-sysusers(8), systemd-timedated.service(8), systemd-update-done.service(8), systemd-volatile-root.service(8), systemd.dnssd(5), systemd.environment-generator(7), systemd.exec(5), systemd.generator(7), systemd.link(5), systemd.mount(5), systemd.netdev(5), systemd.network(5), systemd.preset(5), systemd.unit(5), timesyncd.conf(5), tmpfiles.d(5), udev(7)

/etc/.updated

systemd-update-done.service(8)

/etc/adjtime

timedatectl(1)

/etc/binfmt.d/*.conf

binfmt.d(5)

/etc/cryptsetup-keys.d/

crypttab(5), systemd-cryptsetup@.service(8)

/etc/crypttab

crypttab(5), systemd-cryptenroll(1), systemd-cryptsetup-generator(8), systemd-cryptsetup@.service(8), systemd-gpt-auto-generator(8)

/etc/dnssec-trust-anchors.d/

dnssec-trust-anchors.d(5)

/etc/dnssec-trust-anchors.d/*.negative

dnssec-trust-anchors.d(5)

/etc/dnssec-trust-anchors.d/*.positive

dnssec-trust-anchors.d(5)

/etc/environment

environment.d(5)

/etc/environment.d/*.conf

environment.d(5)

/etc/extensions/

systemd-sysex(8)

/etc/fstab

crypttab(5), kernel-command-line(7), org.freedesktop.systemd1(5), systemd(1), systemd-fsck@.service(8), systemd-fstab-generator(8), systemd-gpt-auto-generator(8), systemd-mount(1), systemd-remount-fs.service(8), systemd.automount(5), systemd.generator(7), systemd.mount(5), systemd.special(7), systemd.swap(5)

/etc/group

nss-systemd(8), systemd-nspawn(1), systemd-tmpfiles(8), systemd.exec(5), sysusers.d(5)

/etc/gshadow

nss-systemd(8)

/etc/hostname

hostname(5), kernel-command-line(7), machine-info(5), org.freedesktop.hostname1(5), systemd-hostnamed.service(8)

/etc/hosts

nss-myhostname(8), nss-resolve(8), org.freedesktop.hostname1(5), org.freedesktop.resolve1(5), resolvectl(1), resolved.conf(5), systemd-resolved.service(8)

/etc/init.d/

systemd-sysv-generator(8)

/etc/initrd-release

bootup(7), os-release(5)

/etc/kernel/cmdline

kernel-install(8)

/etc/kernel/install.d/

kernel-install(8)

/etc/kernel/install.d/*.install

kernel-install(8)

/etc/kernel/tries

kernel-install(8), systemd-boot(7)

/etc/locale.conf

locale.conf(5), localectl(1), systemd(1)

/etc/localtime

localtime(5), systemd-nspawn(1), systemd.network(5), systemd.nspawn(5), timedatectl(1)

/etc/machine-id

bootctl(1), kernel-install(8), machine-id(5), org.freedesktop.machine1(5),
sd_bus_get_name_machine_id(3), sd_id128_get_machine(3), systemd-machine-id-
commit.service(8), systemd-machine-id-setup(1), systemd-nspawn(1), systemd.unit(5)

/etc/machine-info

machine-info(5), org.freedesktop.hostname1(5), systemd-hostnamed.service(8)

/etc/modules-load.d/program.conf

modules-load.d(5)

/etc/modules-load.d/*.conf

modules-load.d(5)

/etc/modules-load.d/bridge.conf

sysctl.d(5)

/etc/mtab

org.freedesktop.systemd1(5)

/etc/nsswitch.conf

nss-myhostname(8), nss-mymachines(8), nss-resolve(8), nss-systemd(8)

/etc/os-release

kernel-install(8), os-release(5), repart.d(5), systemd-nspawn(1), systemd-
system.conf(5), systemd.dnssd(5), systemd.unit(5), sysusers.d(5), tmpfiles.d(5)

/etc/passwd

nss-systemd(8), systemd-nspawn(1), systemd-tmpfiles(8), systemd.exec(5), sysusers.d(5)

/etc/portables/

portablectl(1)

/etc/rc.local

systemd-rc-local-generator(8)

/etc/repart.d/*.conf

repart.d(5), systemd-repart(8)

/etc/resolv.conf

org.freedesktop.resolve1(5), resolvectl(1), resolved.conf(5), systemd-nspawn(1),
systemd-resolved.service(8), systemd.network(5), systemd.nspawn(5)

/etc/shadow

```

nss-systemd(8)
/etc/ssl/ca/trusted.pem
systemd-journal-remote.service(8), systemd-journal-upload.service(8)
/etc/ssl/certs/journal-remote.pem
systemd-journal-remote.service(8)
/etc/ssl/certs/journal-upload.pem
systemd-journal-upload.service(8)
/etc/ssl/private/journal-remote.pem
systemd-journal-remote.service(8)
/etc/ssl/private/journal-upload.pem
systemd-journal-upload.service(8)
/etc/sysctl.d/*.conf
sysctl.d(5)
/etc/sysctl.d/20-rp_filter.conf
sysctl.d(5)
/etc/sysctl.d/50-coredump.conf
systemd-sysctl.service(8)
/etc/sysctl.d/bridge.conf
sysctl.d(5)
/etc/sysctl.d/domain-name.conf
sysctl.d(5)
/etc/systemd/
coredump.conf(5), journal-remote.conf(5), journal-upload.conf(5), journald.conf(5),
logind.conf(5), networkd.conf(5), oomd.conf(5), pstore.conf(5), resolved.conf(5),
systemd-sleep.conf(5), systemd-system.conf(5), timesyncd.conf(5)
/etc/systemd/*.conf.d/
coredump.conf(5), journal-remote.conf(5), journal-upload.conf(5), journald.conf(5),
logind.conf(5), networkd.conf(5), oomd.conf(5), pstore.conf(5), resolved.conf(5),
systemd-sleep.conf(5), systemd-system.conf(5), timesyncd.conf(5)
/etc/systemd/coredump.conf
coredump.conf(5), systemd-coredump(8)
/etc/systemd/coredump.conf.d/*.conf
coredump.conf(5), systemd-coredump(8)

```


/etc/systemd/dnssd
systemd.dnssd(5)

/etc/systemd/import-pubring.gpg
machinectl(1)

/etc/systemd/journal-remote.conf
journal-remote.conf(5), systemd-journal-upload.service(8)

/etc/systemd/journal-remote.conf.d/*.conf
journal-remote.conf(5)

/etc/systemd/journal-upload.conf
journal-upload.conf(5), systemd-journal-upload.service(8)

/etc/systemd/journal-upload.conf.d/*.conf
journal-upload.conf(5)

/etc/systemd/journaled.conf
journaled.conf(5), systemd-journaled.service(8)

/etc/systemd/journaled.conf.d/*.conf
journaled.conf(5)

/etc/systemd/journaled@NAMESPACE.conf
journaled.conf(5), systemd-journaled.service(8)

/etc/systemd/logind.conf
logind.conf(5), systemd-analyze(1)

/etc/systemd/logind.conf.d/*.conf
logind.conf(5)

/etc/systemd/network
systemd-networkd.service(8), systemd.link(5), systemd.netdev(5), systemd.network(5)

/etc/systemd/network/*.network
systemd-resolved.service(8)

/etc/systemd/networkd.conf
networkd.conf(5)

/etc/systemd/networkd.conf.d/*.conf
networkd.conf(5)

/etc/systemd/nspawn/
systemd-nspawn(1), systemd.nspawn(5)

/etc/systemd/oomd.conf

oomd.conf(5)

/etc/systemd/oomd.conf.d/*.conf

oomd.conf(5)

/etc/systemd/portable/profile/

portablectl(1)

/etc/systemd/pstore.conf

pstore.conf(5), systemd-pstore.service(8)

/etc/systemd/pstore.conf.d/

pstore.conf(5)

/etc/systemd/pstore.conf.d/*.conf

systemd-pstore.service(8)

/etc/systemd/resolved.conf

org.freedesktop.resolve1(5), resolvectl(1), resolved.conf(5), systemd-resolved.service(8)

/etc/systemd/resolved.conf.d/*.conf

resolved.conf(5)

/etc/systemd/sleep.conf

systemd-sleep.conf(5), systemd-suspend.service(8)

/etc/systemd/sleep.conf.d/*.conf

systemd-sleep.conf(5)

/etc/systemd/system/

systemctl(1), systemd.unit(5)

/etc/systemd/system-environment-generators/

systemd.environment-generator(7)

/etc/systemd/system-generators/

systemd.generator(7)

/etc/systemd/system-preset/

systemd.preset(5)

/etc/systemd/system-preset/*.preset

systemd.preset(5)

/etc/systemd/system.attached

org.freedesktop.systemd1(5), portablectl(1), systemd.unit(5)

/etc/systemd/system.conf

org.freedesktop.systemd1(5), systemd-system.conf(5)

/etc/systemd/system.conf.d/*.conf

systemd-system.conf(5)

/etc/systemd/system.control/

systemd.unit(5)

/etc/systemd/system/ctrl-alt-del.service

systemd.unit(5)

/etc/systemd/system/httpd.service

systemd.unit(5)

/etc/systemd/system/httpd.service.d/local.conf

systemd.unit(5)

/etc/systemd/system/systemd-nspawn@foobar.service.d/50-network.conf

systemd-nspawn(1)

/etc/systemd/timesyncd.conf

timesyncd.conf(5)

/etc/systemd/timesyncd.conf.d/*.conf

timesyncd.conf(5)

/etc/systemd/user/

systemd.unit(5)

/etc/systemd/user-environment-generators/

systemd.environment-generator(7)

/etc/systemd/user-generators/

systemd.generator(7)

/etc/systemd/user-preset/*.preset

systemd.preset(5)

/etc/systemd/user.conf

systemd-system.conf(5)

/etc/systemd/user.conf.d/*.conf

systemd-system.conf(5)

/etc/sysusers.d

sysusers.d(5)

/etc/sysusers.d/*.conf

sysusers.d(5)

/etc/sysusers.d/00-overrides.conf

systemd-sysusers(8)

/etc/sysusers.d/radvd.conf

systemd-sysusers(8)

/etc/tmpfiles.d

tmpfiles.d(5)

/etc/tmpfiles.d/*.conf

tmpfiles.d(5)

/etc/udev/hwdb.bin

hwdb(7)

/etc/udev/hwdb.d

hwdb(7)

/etc/udev/rules.d

udev(7)

/etc/udev/rules.d/99-bridge.rules

sysctl.d(5)

/etc/udev/udev.conf

udev.conf(5)

/etc/userdb/

nss-systemd(8)

/etc/vconsole.conf

localectl(1)

/etc/veritytab

veritytab(5)

/etc/xdg

systemd.unit(5)

/etc/xdg/systemd/user

systemd.unit(5)

/etc/xdg/user-dirs.conf

sd_path_lookup(3)

/home/

file-hierarchy(7), repart.d(5), systemctl(1), systemd-gpt-auto-generator(8), systemd-repart(8), systemd.exec(5), systemd.generator(7), tmpfiles.d(5)

/home/lennart

systemd.automount(5)

/lib/

file-hierarchy(7), systemd-nspawn(1)

/lib/systemd/system-generators/

systemd.generator(7)

/lib64/

file-hierarchy(7)

/loader/entries/

systemd-boot(7)

/loader/loader.conf

systemd-boot(7)

/loader/random-seed

loader.conf(5), systemd-boot(7)

/log/

systemd.exec(5)

/opt/

systemd-sysext(8), systemd.exec(5)

/org/freedesktop/LogControl1

org.freedesktop.LogControl1(5)

/proc/

busctl(1), file-hierarchy(7), sd-login(3), sd_bus_creds_get_pid(3),
sd_bus_creds_new_from_pid(3), sd_is_fifo(3), sd_pid_get_owner_uid(3), systemd(1),
systemd-coredump(8), systemd-remount-fs.service(8), systemd.exec(5),
systemd.generator(7), systemd.socket(5), tmpfiles.d(5)

/proc/\$PID/ns/ipc

systemd.exec(5)

/proc/\$PID/ns/net

systemd-nspawn(1), systemd.exec(5)

/proc/1/cmdline

systemd.unit(5)

/proc/acpi

systemd.exec(5)

/proc/cmdline

kernel-command-line(7), kernel-install(8), systemd(1), systemd.unit(5)

/proc/devices

systemd.resource-control(5)

/proc/fs

systemd.exec(5)

/proc/irq

systemd.exec(5)

/proc/kmsg

systemd.exec(5)

/proc/latency_stats

systemd.exec(5)

/proc/self/cgroup

systemd-coredump(8)

/proc/self/fd

daemon(7)

/proc/self/mountinfo

systemd.mount(5)

/proc/self/mounts

org.freedesktop.systemd1(5)

/proc/self/oom_score_adj

systemd-nspawn(1)

/proc/self/sessionid

pam_systemd(8)

/proc/sys/

file-hierarchy(7), systemd-nspawn(1), systemd-sysctl.service(8), systemd.exec(5)

/proc/sys/kernel/core_pattern

systemd-sysctl.service(8)

/proc/sys/kernel/domainname

sysctl.d(5)

/proc/sys/kernel/hostname

org.freedesktop.hostname1(5)

/proc/sys/kernel/modules_disabled

```

systemd.exec(5)
/proc/sys/kernel/random/boot_id
sd_id128_get_machine(3)
/proc/sys/net/ipv4/conf/enp3s0.200/forwarding
sysctl.d(5)
/proc/sys/net/ipv4/ip_default_ttl
systemd.netdev(5)
/proc/sys/net/ipv4/tcp_keepalive_time
systemd.socket(5)
/proc/sys/net/ipv6/bindv6only
systemd.socket(5)
/proc/sysrq-trigger
systemd.exec(5)
/proc/timer_stats
systemd.exec(5)
/root/
file-hierarchy(7), systemd.exec(5)
/run/
binfmt.d(5), crypttab(5), environment.d(5), file-hierarchy(7), modules-load.d(5),
org.freedesktop.systemd1(5), sd-login(3), sd_notify(3), sysctl.d(5), systemctl(1),
systemd-delta(1), systemd-journald.service(8), systemd-modules-load.service(8),
systemd-nspawn(1), systemd-timedated.service(8), systemd.dnssd(5),
systemd.environment-generator(7), systemd.exec(5), systemd.generator(7),
systemd.link(5), systemd.netdev(5), systemd.network(5), systemd.preset(5),
systemd.service(5), systemd.unit(5), tmpfiles.d(5), udev(7)
/run/binfmt.d/*.conf
binfmt.d(5)
/run/cryptsetup-keys.d/
crypttab(5), systemd-cryptsetup@.service(8)
/run/dnssec-trust-anchors.d/
dnssec-trust-anchors.d(5)
/run/dnssec-trust-anchors.d/*.negative
dnssec-trust-anchors.d(5)

```

/run/dnsssec-trust-anchors.d/*.positive

dnsssec-trust-anchors.d(5)

/run/environment.d/*.conf

environment.d(5)

/run/extensions/

systemd-sysex(8)

/run/host/incoming/

systemd.exec(5)

/run/host/os-release

os-release(5)

/run/host/userdb/

nss-systemd(8)

/run/hosts/home/

systemd-nspawn(1)

/run/log/

file-hierarchy(7)

/run/log/journal/

journalctl(1), journald.conf(5), sd_journal_open(3), systemd-journald.service(8)

/run/media/system/

systemd-mount(1)

/run/modules-load.d/*.conf

modules-load.d(5)

/run/netns

systemd-nspawn(1)

/run/nologin

shutdown(8), systemd-user-sessions.service(8)

/run/portables/

portablectl(1)

/run/repart.d/*.conf

repart.d(5), systemd-repart(8)

/run/screens

tmpfiles.d(5)

/run/sysctl.d/*.conf

sysctl.d(5)
/run/sysctl.d/50-coredump.conf
systemd-sysctl.service(8)
/run/systemd/nspawn/
systemd.nspawn(5)
/run/systemd/coredump.conf.d/*.conf
coredump.conf(5)
/run/systemd/dnssd
systemd.dnssd(5)
/run/systemd/generator
systemd.generator(7), systemd.unit(5)
/run/systemd/generator.early
systemd.generator(7), systemd.unit(5)
/run/systemd/generator.late
systemd.generator(7), systemd.unit(5)
/run/systemd/journal-remote.conf.d/*.conf
journal-remote.conf(5)
/run/systemd/journal-upload.conf.d/*.conf
journal-upload.conf(5)
/run/systemd/journal/dev-log
systemd-journald.service(8)
/run/systemd/journal/socket
systemd-journald.service(8)
/run/systemd/journal/stdout
systemd-journald.service(8)
/run/systemd/journal/syslog
journald.conf(5)
/run/systemd/journald.conf.d/*.conf
journald.conf(5)
/run/systemd/journald@NAMESPACE.conf.d/*.conf
journald.conf(5)
/run/systemd/logind.conf.d/*.conf
logind.conf(5)

/run/systemd/network/

systemd-network-generator.service(8), systemd-networkd.service(8), systemd.link(5),
systemd.netdev(5), systemd.network(5)

/run/systemd/notify

systemd(1)

/run/systemd/nspawn/

systemd-nspawn(1), systemd.nspawn(5)

/run/systemd/portables/

portablectl(1)

/run/systemd/private

systemd(1)

/run/systemd/propagate

systemd.exec(5)

/run/systemd/resolve/io.systemd.Resolve

nss-resolve(8)

/run/systemd/resolve/resolv.conf

org.freedesktop.resolve1(5), resolvectl(1), systemd-nspawn(1), systemd-
resolved.service(8)

/run/systemd/resolve/stub-resolv.conf

systemd-nspawn(1), systemd-resolved.service(8)

/run/systemd/resolved.conf.d/*.conf

resolved.conf(5)

/run/systemd/sleep.conf.d/*.conf

systemd-sleep.conf(5)

/run/systemd/system/

sd_booted(3), systemctl(1), systemd.unit(5)

/run/systemd/system-environment-generators/

systemd.environment-generator(7)

/run/systemd/system-generators/

systemd.generator(7)

/run/systemd/system-preset/*.preset

systemd.preset(5)

/run/systemd/system.attached

org.freedesktop.systemd1(5), portablectl(1), systemd.unit(5)

/run/systemd/system.conf.d/*.conf

systemd-system.conf(5)

/run/systemd/system.control/

systemd.unit(5)

/run/systemd/systemd/

systemctl(1)

/run/systemd/timesync/synchronized

systemd-time-wait-sync.service(8), systemd-timesyncd.service(8)

/run/systemd/timesyncd.conf.d/*.conf

timesyncd.conf(5)

/run/systemd/transient/

systemd.unit(5)

/run/systemd/user/

systemd.unit(5)

/run/systemd/user-environment-generators/

systemd.environment-generator(7)

/run/systemd/user-generators/

systemd.generator(7)

/run/systemd/user-preset/*.preset

systemd.preset(5)

/run/systemd/user.conf.d/*.conf

systemd-system.conf(5)

/run/sysusers.d

sysusers.d(5)

/run/sysusers.d/*.conf

sysusers.d(5)

/run/tmpfiles.d

tmpfiles.d(5)

/run/tmpfiles.d/*.conf

tmpfiles.d(5)

/run/udev/rules.d

udev(7)

```

/run/udev/static_node-tags/tag
    udev(7)
/run/user/
    file-hierarchy(7), systemd.exec(5), user@.service(5)
/run/user/$UID
    pam_systemd(8)
/run/userdb/
    nss-systemd(8), systemd-nspawn(1)
/run/utmp
    runlevel(8)
/sbin/
    file-hierarchy(7), systemd.exec(5)
/sbin/fsck.type
    systemd-fsck@.service(8)
/sbin/init
    systemd(1)
/sbin/mkfs.type
    systemd-makefs@.service(8)
/sbin/mkswap
    systemd-makefs@.service(8)
/srv/
    file-hierarchy(7), repart.d(5), systemd-gpt-auto-generator(8), systemd-repart(8)
/srv/webserver
    systemd.unit(5)
/srv/www
    systemd.unit(5)
/sys/
    file-hierarchy(7), loginctl(1), org.freedesktop.login1(5), sd_is_fifo(3), systemd(1),
    systemd-nspawn(1), systemd-remount-fs.service(8), systemd-tmpfiles(8),
    systemd.device(5), systemd.exec(5), systemd.generator(7), systemd.journal-fields(7),
    systemd.socket(5), tmpfiles.d(5), udev_device_new_from_syspath(3), udevadm(8)
/sys/class/subsystem/name/max_brightness
    org.freedesktop.login1(5)

```

/sys/class/dmi/id/product_uuid
org.freedesktop.hostname1(5)

/sys/devices
udev_device_new_from_syspath(3)

/sys/fs/bpf/
systemd.resource-control(5)

/sys/fs/cgroup/
file-hierarchy(7), sd-login(3), sd_pid_get_owner_uid(3), systemd-cgls(1),
systemd.exec(5)

/sys/fs/cgroup/systemd
org.freedesktop.systemd1(5), systemd(1)

/sys/fs/cgroup/unified/
file-hierarchy(7)

/sys/fs/pstore/
systemd-pstore.service(8)

/sys/fs/selinux/
systemd-nspawn(1)

/sys/module/kernel/parameters/crash_kexec_post_notifiers
systemd-pstore.service(8)

/sys/module/printk/parameters/always_kmsg_dump
systemd-pstore.service(8)

/sys/power/disk
systemd-sleep.conf(5)

/sys/power/resume
systemd-hibernate-resume@.service(8)

/sys/power/state
systemd-sleep.conf(5), systemd-suspend.service(8)

/sysroot
bootup(7), systemd-gpt-auto-generator(8), systemd-repart(8), systemd.special(7)

/sysroot/etc/fstab
bootup(7)

/system-update
systemd-system-update-generator(8), systemd.offline-updates(7), systemd.special(7)

/sysusr/

systemd.special(7)

/tmp/

crypttab(5), file-hierarchy(7), repart.d(5), systemd-system.conf(5), systemd-tmpfiles(8), systemd.exec(5), systemd.special(7), systemd.unit(5), sysusers.d(5), tmpfiles.d(5)

/upload

systemd-journal-remote.service(8)

/usr/

binfmt.d(5), bootup(7), coredump.conf(5), environment.d(5), file-hierarchy(7), journal-remote.conf(5), journal-upload.conf(5), journal.d.conf(5), kernel-command-line(7), logind.conf(5), machinectl(1), modules-load.d(5), networkd.conf(5), oomd.conf(5), org.freedesktop.systemd1(5), portablectl(1), pstore.conf(5), repart.d(5), resolved.conf(5), sysctl.d(5), systemctl(1), systemd-dissect(1), systemd-fstab-generator(8), systemd-modules-load.service(8), systemd-nspawn(1), systemd-remount-fs.service(8), systemd-sleep.conf(5), systemd-sysexits(8), systemd-system.conf(5), systemd-timedated.service(8), systemd-update-done.service(8), systemd-volatile-root.service(8), systemd.exec(5), systemd.generator(7), systemd.mount(5), systemd.network(5), systemd.special(7), systemd.unit(5), timesyncd.conf(5), udev(7)

/usr/bin/

file-hierarchy(7), systemd.exec(5), systemd.service(5)

/usr/bin/mount

org.freedesktop.systemd1(5)

/usr/bin/umount

org.freedesktop.systemd1(5)

/usr/include/

file-hierarchy(7)

/usr/include/stdlib.h

systemd-tmpfiles(8)

/usr/include/sysexits.h

systemd-tmpfiles(8)

/usr/lib/

binfmt.d(5), environment.d(5), file-hierarchy(7), hwdb(7), modules-load.d(5),

sysctl.d(5), systemd-delta(1), systemd-timedated.service(8), systemd.dnssd(5),
systemd.link(5), systemd.netdev(5), systemd.network(5), systemd.preset(5),
systemd.unit(5), udev(7)

/usr/lib/binfmt.d/*.conf

binfmt.d(5)

/usr/lib/dnssec-trust-anchors.d/

dnssec-trust-anchors.d(5)

/usr/lib/dnssec-trust-anchors.d/*.negative

dnssec-trust-anchors.d(5)

/usr/lib/dnssec-trust-anchors.d/*.positive

dnssec-trust-anchors.d(5)

/usr/lib/environment.d/*.conf

environment.d(5)

/usr/lib/extension-release.d/extension-release.\$name

systemd-sysex(8)

/usr/lib/extensions/

systemd-sysex(8)

/usr/lib/kernel/install.d/

kernel-install(8)

/usr/lib/kernel/install.d/*.install

kernel-install(8)

/usr/lib/machines/

machinectl(1)

/usr/lib/modules

systemd.exec(5)

/usr/lib/modules-load.d/*.conf

modules-load.d(5)

/usr/lib/os-release

kernel-install(8), os-release(5), systemd-nspawn(1), systemd-sysex(8)

/usr/lib/portables/

portablectl(1)

/usr/lib/repart.d/*.conf

repart.d(5), systemd-repart(8)

/usr/lib/sysctl.d/*.conf

sysctl.d(5)

/usr/lib/sysctl.d/50-coredump.conf

systemd-coredump(8), systemd-sysctl.service(8)

/usr/lib/systemd/*.conf.d/

coredump.conf(5), journal-remote.conf(5), journal-upload.conf(5), journal.d.conf(5),

logind.conf(5), networkd.conf(5), oomd.conf(5), pstore.conf(5), resolved.conf(5),

systemd-sleep.conf(5), systemd-system.conf(5), timesyncd.conf(5)

/usr/lib/systemd/coredump.conf.d/*.conf

coredump.conf(5)

/usr/lib/systemd/dnssd

systemd.dnssd(5)

/usr/lib/systemd/import-pubring.gpg

machinectl(1)

/usr/lib/systemd/journal-remote.conf.d/*.conf

journal-remote.conf(5)

/usr/lib/systemd/journal-upload.conf.d/*.conf

journal-upload.conf(5)

/usr/lib/systemd/journal.d.conf.d/*.conf

journal.d.conf(5)

/usr/lib/systemd/journal.d@NAMESPACE.conf.d/*.conf

journal.d.conf(5)

/usr/lib/systemd/logind.conf

systemd-analyze(1)

/usr/lib/systemd/logind.conf.d/*.conf

logind.conf(5)

/lib/systemd/network

systemd-networkd.service(8), systemd.link(5), systemd.netdev(5), systemd.network(5)

/lib/systemd/network/80-container-host0.network

systemd-nspawn(1)

/lib/systemd/network/80-container-ve.network

systemd-nspawn(1)

/lib/systemd/network/80-container-vz.network

systemd-nspawn(1)

/lib/systemd/networkd.conf.d/*.conf

networkd.conf(5)

/usr/lib/systemd/ntp-units.d/

systemd-timedated.service(8)

/usr/lib/systemd/oomd.conf.d/*.conf

oomd.conf(5)

/usr/lib/systemd/portable/profile/

portablectl(1)

/usr/lib/systemd/portable/profile/default/service.conf

portablectl(1)

/usr/lib/systemd/random-seed

systemd-random-seed.service(8)

/usr/lib/systemd/resolv.conf

systemd-nspawn(1), systemd-resolved.service(8)

/usr/lib/systemd/resolved.conf.d/*.conf

resolved.conf(5)

/usr/lib/systemd/sleep.conf.d/*.conf

systemd-sleep.conf(5)

/lib/systemd/system

systemd(1), systemd.unit(5)

/lib/systemd/system-bless-boot

systemd-bless-boot.service(8)

/lib/systemd/system-boot-check-no-failures

systemd-boot-check-no-failures.service(8)

/lib/systemd/system-environment-generators/

systemd.environment-generator(7)

/lib/systemd/system-environment-generators/some-generator

systemd.environment-generator(7)

/lib/systemd/system-generators/systemd-bless-boot-generator

systemd-bless-boot-generator(8)

/lib/systemd/system-generators/systemd-cryptsetup-generator

systemd-cryptsetup-generator(8)

/lib/systemd/system-generators/systemd-debug-generator
systemd-debug-generator(8)

/lib/systemd/system-generators/systemd-fstab-generator
systemd-fstab-generator(8)

/lib/systemd/system-generators/systemd-getty-generator
systemd-getty-generator(8)

/lib/systemd/system-generators/systemd-gpt-auto-generator
systemd-gpt-auto-generator(8)

/lib/systemd/system-generators/systemd-hibernate-resume-generator
systemd-hibernate-resume-generator(8)

/lib/systemd/system-generators/systemd-rc-local-generator
systemd-rc-local-generator(8)

/lib/systemd/system-generators/systemd-run-generator
systemd-run-generator(8)

/lib/systemd/system-generators/systemd-system-update-generator
systemd-system-update-generator(8)

/lib/systemd/system-generators/systemd-sysv-generator
systemd-sysv-generator(8)

/lib/systemd/system-generators/systemd-veritysetup-generator
systemd-veritysetup-generator(8)

/lib/systemd/system-preset/*.preset
systemd.preset(5)

/lib/systemd/system-shutdown/
systemd-halt.service(8)

/lib/systemd/system-sleep
systemd-suspend.service(8)

/lib/systemd/system.conf.d/*.conf
systemd-system.conf(5)

/lib/systemd/system/httpd.service
systemd.unit(5)

/lib/systemd/systemd
systemd(1)

/lib/systemd/systemd-backlight

systemd-backlight@.service(8)
/lib/systemd/systemd-binfmt
systemd-binfmt.service(8)
/lib/systemd/systemd-coredump
systemd-coredump(8)
/lib/systemd/systemd-cryptsetup
systemd-cryptsetup@.service(8)
/lib/systemd/systemd-fsck
systemd-fsck@.service(8)
/lib/systemd/systemd-fsckd
systemd-fsckd.service(8)
/lib/systemd/systemd-growfs
systemd-makefs@.service(8)
/lib/systemd/systemd-hibernate-resume
systemd-hibernate-resume@.service(8)
/lib/systemd/systemd-hostnamed
systemd-hostnamed.service(8)
/lib/systemd/systemd-importd
systemd-importd.service(8)
/lib/systemd/systemd-initctl
systemd-initctl.service(8)
/lib/systemd/systemd-journal-gatewayd
systemd-journal-gatewayd.service(8)
/lib/systemd/systemd-journal-remote
systemd-journal-remote.service(8)
/lib/systemd/systemd-journal-upload
systemd-journal-upload.service(8)
/lib/systemd/systemd-journald
systemd-journald.service(8)
/lib/systemd/systemd-localed
systemd-localed.service(8)
/lib/systemd/systemd-logind
systemd-logind.service(8)

/lib/systemd/systemd-machined
systemd-machined.service(8)

/lib/systemd/systemd-makefs
systemd-makefs@.service(8)

/lib/systemd/systemd-modules-load
systemd-modules-load.service(8)

/lib/systemd/systemd-network-generator
systemd-network-generator.service(8)

/lib/systemd/systemd-networkd
systemd-networkd.service(8)

/lib/systemd/systemd-networkd-wait-online
systemd-networkd-wait-online.service(8)

/lib/systemd/systemd-oomd
systemd-oomd.service(8)

/lib/systemd/systemd-portabled
systemd-portabled.service(8)

/lib/systemd/systemd-pstore
systemd-pstore.service(8)

/lib/systemd/systemd-quotacheck
systemd-quotacheck.service(8)

/lib/systemd/systemd-remount-fs
systemd-remount-fs.service(8)

/lib/systemd/systemd-resolved
systemd-resolved.service(8)

/lib/systemd/systemd-rfkill
systemd-rfkill.service(8)

/lib/systemd/systemd-shutdown
systemd-halt.service(8)

/lib/systemd/systemd-sysctl
systemd-sysctl.service(8)

/lib/systemd/systemd-time-wait-sync
systemd-time-wait-sync.service(8)

/lib/systemd/systemd-timedated

systemd-timedated.service(8)
/lib/systemd/systemd-timesyncd
systemd-timesyncd.service(8)
/lib/systemd/systemd-udev
systemd-udev.service(8)
/lib/systemd/systemd-update-done
systemd-update-done.service(8)
/lib/systemd/systemd-update-utmp
systemd-update-utmp.service(8)
/lib/systemd/systemd-user-runtime-dir
user@.service(5)
/lib/systemd/systemd-user-sessions
systemd-user-sessions.service(8)
/lib/systemd/systemd-veritysetup
systemd-veritysetup@.service(8)
/lib/systemd/systemd-volatile-root
systemd-volatile-root.service(8)
/usr/lib/systemd/timesyncd.conf.d/*.conf
timesyncd.conf(5)
/usr/lib/systemd/user/
systemd.unit(5)
/usr/lib/systemd/user-environment-generators/
systemd.environment-generator(7)
/usr/lib/systemd/user-environment-generators/30-systemd-environment-d-generator
systemd-environment-d-generator(8)
/usr/lib/systemd/user-environment-generators/some-generator
systemd.environment-generator(7)
/usr/lib/systemd/user-generators/
systemd.generator(7)
/usr/lib/systemd/user-generators/systemd-xdg-autostart-generator
systemd-xdg-autostart-generator(8)
/usr/lib/systemd/user-preset/*.preset
systemd.preset(5)

/usr/lib/systemd/user.conf.d/*.conf
systemd-system.conf(5)

/usr/lib/sysusers.d
sysusers.d(5)

/usr/lib/sysusers.d/*.conf
sysusers.d(5)

/usr/lib/sysusers.d/radvd.conf
systemd-sysusers(8)

/usr/lib/tmpfiles.d
tmpfiles.d(5)

/usr/lib/tmpfiles.d/*.conf
tmpfiles.d(5)

/usr/lib/tmpfiles.d/systemd.conf
systemd-coredump(8)

/usr/lib/tmpfiles/systemd-pstore.conf
systemd-pstore.service(8)

/lib/udev
udev(7)

/lib/udev/hwdb.bin
hwdb(7)

/lib/udev/hwdb.d
hwdb(7)

/lib/udev/rules.d
udev(7)

/usr/lib/userdb/
nss-systemd(8)

/lib64/
file-hierarchy(7)

/lib64/firefox/firefox
coredumpctl(1)

/usr/local/bin
systemd.exec(5), systemd.service(5)

/usr/local/lib/

- binfmt.d(5), environment.d(5), modules-load.d(5), sysctl.d(5), systemd-
timedated.service(8), systemd.dnssd(5)
- /usr/local/lib/extensions/
 - systemd-sysex(8)
- /usr/local/lib/machines/
 - machinectl(1)
- /usr/local/lib/portables/
 - portablectl(1)
- /usr/local/lib/systemd/*.conf.d/
 - coredump.conf(5), journal-remote.conf(5), journal-upload.conf(5), journald.conf(5),
logind.conf(5), networkd.conf(5), oomd.conf(5), pstore.conf(5), resolved.conf(5),
systemd-sleep.conf(5), systemd-system.conf(5), timesyncd.conf(5)
- /usr/local/lib/systemd/dnssd
 - systemd.dnssd(5)
- /usr/local/lib/systemd/network
 - systemd.network(5)
- /usr/local/lib/systemd/system
 - systemd(1), systemd.unit(5)
- /usr/local/lib/systemd/system-environment-generators/
 - systemd.environment-generator(7)
- /usr/local/lib/systemd/system-generators/
 - systemd.generator(7)
- /usr/local/lib/systemd/user
 - systemd.unit(5)
- /usr/local/lib/systemd/user-environment-generators/
 - systemd.environment-generator(7)
- /usr/local/lib/systemd/user-generators/
 - systemd.generator(7)
- /usr/local/lib/udev/rules.d
 - udev(7)
- /usr/local/sbin
 - systemd.exec(5)
- /usr/local/share

```

systemd.unit(5)
/usr/local/share/systemd/user
    systemd.unit(5)
/usr/sbin/
    file-hierarchy(7), systemd.exec(5)
/usr/sbin/nologin
    sysusers.d(5)
/usr/share/
    file-hierarchy(7), systemd.unit(5)
/usr/share/dbus-1/system-services/org.example.simple-dbus-service.service
    systemd.service(5)
/usr/share/doc/
    file-hierarchy(7)
/usr/share/factory/
    file-hierarchy(7), tmpfiles.d(5)
/usr/share/factory/etc/
    file-hierarchy(7)
/usr/share/factory/var/
    file-hierarchy(7)
/usr/share/systemd/user
    systemd.unit(5)
/usr/share/user-tmpfiles.d/
    systemd-tmpfiles(8)
/usr/share/user-tmpfiles.d/*.conf
    tmpfiles.d(5)
/usr/share/zoneinfo/
    localtime(5)
/usr/share/zoneinfo/zone.tab
    org.freedesktop.timedate1(5)
/var/
    file-hierarchy(7), journald.conf(5), kernel-command-line(7), repart.d(5),
    systemctl(1), systemd-fstab-generator(8), systemd-gpt-auto-generator(8), systemd-
    journald.service(8), systemd-nspawn(1), systemd-random-seed.service(8), systemd-

```


sysext(8), systemd-update-done.service(8), systemd-volatile-root.service(8),
systemd.exec(5), systemd.generator(7), systemd.offline-updates(7), systemd.special(7),
systemd.unit(5), tmpfiles.d(5)

/var/.updated

systemd-update-done.service(8)

/var/cache/

file-hierarchy(7), systemd.exec(5), systemd.unit(5), tmpfiles.d(5)

/var/cache/dnf/

tmpfiles.d(5)

/var/cache/krb5rcache/

tmpfiles.d(5)

/var/cache/private

systemd.exec(5)

/var/lib/

file-hierarchy(7), systemd.exec(5), systemd.unit(5), tmpfiles.d(5)

/var/lib/container/

machinectl(1)

/var/lib/dbus/machine-id

machine-id(5)

/var/lib/extensions/

systemd-sysext(8)

/var/lib/journal/

journalctl(1)

/var/lib/machines/

machinectl(1), org.freedesktop.import1(5), systemd-nspawn(1), systemd.nspawn(5),
tmpfiles.d(5)

/var/lib/portables/

portablectl(1)

/var/lib/private

systemd.exec(5)

/var/lib/systemd

systemd.exec(5)

/var/lib/systemd/backlight/

systemd-backlight@.service(8)

/var/lib/systemd/coredump/

coredump.conf(5), coredumpctl(1), systemd-coredump(8)

/var/lib/systemd/journal-upload/state

systemd-journal-upload.service(8)

/var/lib/systemd/pstore/

pstore.conf(5), systemd-pstore.service(8)

/var/lib/systemd/random-seed

systemd-random-seed.service(8)

/var/lib/systemd/rfkill/

systemd-rfkill.service(8)

/var/lib/systemd/timesync/clock

systemd-timesyncd.service(8)

/var/lock

systemctl(1)

/var/log/

file-hierarchy(7), systemd.exec(5), systemd.unit(5), tmpfiles.d(5)

/var/log/journal/

journalctl(1), journald.conf(5), sd_journal_open(3), systemd-journald.service(8),
systemd-nspawn(1)

/var/log/journal/remote/

systemd-journal-remote.service(8)

/var/log/journal/remote/remote-some.host.journal

systemd-journal-remote.service(8)

/var/log/private

systemd.exec(5)

/var/run/

file-hierarchy(7), systemctl(1), tmpfiles.d(5)

/var/spool/

file-hierarchy(7)

/var/tmp/

file-hierarchy(7), repart.d(5), systemd-gpt-auto-generator(8), systemd-nspawn(1),
systemd-system.conf(5), systemd.exec(5), systemd.special(7), systemd.unit(5),

sysusers.d(5), tmpfiles.d(5)

ESP/loader/entries/*.conf

loader.conf(5)

ESP/loader/loader.conf

loader.conf(5)

automount.automount

systemd.automount(5), systemd.unit(5)

basic.target

systemd.special(7)

blockdev@.target

systemd.special(7)

bluetooth.target

systemd.special(7)

boot-complete.target

systemd.special(7)

bootctl

bootctl(1)

busctl

busctl(1)

coredumpctl

coredumpctl(1)

cryptsetup-pre.target

systemd.special(7)

cryptsetup.target

systemd.special(7)

ctrl-alt-del.target

systemd.special(7)

dbus.service

systemd.special(7)

dbus.socket

systemd.special(7)

default.target

systemd.special(7)

device.device

systemd.device(5), systemd.unit(5)

display-manager.service

systemd.special(7)

emergency.target

systemd.special(7)

exit.target

systemd.special(7)

final.target

systemd.special(7)

first-boot-complete.target

systemd.special(7)

getty-pre.target

systemd.special(7)

getty.target

systemd.special(7)

graphical.target

systemd.special(7)

halt

halt(8)

halt.target

systemd.special(7)

hibernate.target

systemd.special(7)

hostnamectl

hostnamectl(1)

hybrid-sleep.target

systemd.special(7)

init

systemd(1)

init.scope

systemd.special(7)

initrd-fs.target

systemd.special(7)
initrd-root-device.target
systemd.special(7)
initrd-root-fs.target
systemd.special(7)
initrd-usr-fs.target
systemd.special(7)
initrd.target
systemd.special(7)
journalctl
journalctl(1)
kbrequest.target
systemd.special(7)
kernel-install
kernel-install(8)
kexec.target
systemd.special(7)
libnss_myhostname.so.2
nss-myhostname(8)
libnss_mymachines.so.2
nss-mymachines(8)
libnss_resolve.so.2
nss-resolve(8)
libnss_systemd.so.2
nss-systemd(8)
link.link
systemd.link(5)
local-fs-pre.target
systemd.special(7)
local-fs.target
systemd.special(7)
localectl
localectl(1)

loginctl

loginctl(1)

machine.slice

systemd.special(7)

machinectl

machinectl(1)

machines.target

systemd.special(7)

mount.mount

systemd.exec(5), systemd.kill(5), systemd.mount(5), systemd.resource-control(5),

systemd.unit(5)

multi-user.target

systemd.special(7)

netdev.netdev

systemd.netdev(5)

network.network

systemd.network(5)

network-online.target

systemd.special(7)

network-pre.target

systemd.special(7)

network.target

systemd.special(7)

network_service.dnssd

systemd.dnssd(5)

networkctl

networkctl(1)

nss-lookup.target

systemd.special(7)

nss-user-lookup.target

systemd.special(7)

oomctl

oomctl(1)

pam_systemd.so

pam_systemd(8)

path.path

systemd.path(5), systemd.unit(5)

paths.target

systemd.special(7)

pkg-config

libudev(3), sd-bus(3), sd-daemon(3), sd-event(3), sd-hwdb(3), sd-id128(3), sd-journal(3), sd-login(3)

portablectl

portablectl(1)

poweroff

halt(8)

poweroff.target

systemd.special(7)

printer.target

systemd.special(7)

rc-local.service

systemd-rc-local-generator(8)

reboot

halt(8)

reboot.target

systemd.special(7)

remote-cryptsetup.target

systemd.special(7)

remote-fs-pre.target

systemd.special(7)

remote-fs.target

systemd.special(7)

remote-veritysetup.target

systemd.special(7)

rescue.target

systemd.special(7)

resolvel

resolvel(1)

rpcbind.target

systemd.special(7)

runlevel

runlevel(8)

runlevel2.target

systemd.special(7)

runlevel3.target

systemd.special(7)

runlevel4.target

systemd.special(7)

runlevel5.target

systemd.special(7)

scope.scope

systemd.kill(5), systemd.resource-control(5), systemd.scope(5), systemd.unit(5)

service.service

systemd.exec(5), systemd.kill(5), systemd.resource-control(5), systemd.service(5),

systemd.unit(5)

shutdown

shutdown(8)

shutdown.target

systemd.special(7)

sigpwr.target

systemd.special(7)

sleep.target

systemd.special(7)

slice.slice

systemd.resource-control(5), systemd.slice(5), systemd.unit(5)

slices.target

systemd.special(7)

smartcard.target

systemd.special(7)

socket.socket

systemd.exec(5), systemd.kill(5), systemd.resource-control(5), systemd.socket(5),
systemd.unit(5)

sockets.target

systemd.special(7)

sound.target

systemd.special(7)

suspend-then-hibernate.target

systemd.special(7)

suspend.target

systemd.special(7)

swap.swap

systemd.exec(5), systemd.kill(5), systemd.resource-control(5), systemd.swap(5),
systemd.unit(5)

swap.target

systemd.special(7)

sysinit.target

systemd.special(7)

syslog.socket

systemd.special(7)

system-systemd\x2dcryptsetup.slice

systemd-cryptsetup@.service(8)

system-update-cleanup.service

systemd.special(7)

system-update-pre.target

systemd.special(7)

system-update.target

systemd.special(7)

system.slice

systemd.special(7)

systemctl

systemctl(1)

systemd-analyze

systemd-analyze(1)

systemd-ask-password

systemd-ask-password(1)

systemd-ask-password-console.path

systemd-ask-password-console.service(8)

systemd-ask-password-console.service

systemd-ask-password-console.service(8)

systemd-ask-password-wall.path

systemd-ask-password-console.service(8)

systemd-ask-password-wall.service

systemd-ask-password-console.service(8)

systemd-backlight@.service

systemd-backlight@.service(8)

systemd-binfmt.service

systemd-binfmt.service(8)

systemd-bless-boot.service

systemd-bless-boot.service(8)

systemd-boot-check-no-failures.service

systemd-boot-check-no-failures.service(8)

systemd-boot-system-token.service

systemd-boot-system-token.service(8)

systemd-cat

systemd-cat(1)

systemd-cgls

systemd-cgls(1)

systemd-cgtop

systemd-cgtop(1)

systemd-coredump.socket

systemd-coredump(8)

systemd-coredump@.service

systemd-coredump(8)

systemd-cryptenroll

systemd-cryptenroll(1)

systemd-cryptsetup@.service
 systemd-cryptsetup@.service(8)

systemd-delta
 systemd-delta(1)

systemd-detect-virt
 systemd-detect-virt(1)

systemd-dissect
 systemd-dissect(1)

systemd-escape
 systemd-escape(1)

systemd-fsck-root.service
 systemd-fsck@.service(8)

systemd-fsck@.service
 systemd-fsck@.service(8)

systemd-fsckd.service
 systemd-fsckd.service(8)

systemd-fsckd.socket
 systemd-fsckd.service(8)

systemd-growfs@mountpoint.service
 systemd-makefs@.service(8)

systemd-halt.service
 systemd-halt.service(8)

systemd-hibernate-resume@.service
 systemd-hibernate-resume@.service(8)

systemd-hibernate.service
 systemd-suspend.service(8)

systemd-hostnamed.service
 systemd-hostnamed.service(8)

systemd-hwdb
 systemd-hwdb(8)

systemd-hybrid-sleep.service
 systemd-suspend.service(8)

systemd-id128

systemd-id128(1)

systemd-importd.service

 systemd-importd.service(8)

systemd-inhibit

 systemd-inhibit(1)

systemd-initctl.service

 systemd-initctl.service(8)

systemd-initctl.socket

 systemd-initctl.service(8)

systemd-journal-gatewayd.service

 systemd-journal-gatewayd.service(8)

systemd-journal-gatewayd.socket

 systemd-journal-gatewayd.service(8)

systemd-journal-remote.service

 systemd-journal-remote.service(8)

systemd-journal-remote.socket

 systemd-journal-remote.service(8)

systemd-journal-upload.service

 systemd-journal-upload.service(8)

systemd-journald-audit.socket

 systemd-journald.service(8)

systemd-journald-dev-log.socket

 systemd-journald.service(8)

systemd-journald-varlink@.socket

 systemd-journald.service(8)

systemd-journald.service

 systemd-journald.service(8)

systemd-journald.socket

 systemd-journald.service(8)

systemd-journald@.service

 systemd-journald.service(8)

systemd-journald@.socket

 systemd-journald.service(8)

systemd-kexec.service
 systemd-halt.service(8)
systemd-locale.service
 systemd-locale.service(8)
systemd-logind.service
 systemd-logind.service(8)
systemd-machine-id-commit.service
 systemd-machine-id-commit.service(8)
systemd-machine-id-setup
 systemd-machine-id-setup(1)
systemd-machined.service
 systemd-machined.service(8)
systemd-makefs@device.service
 systemd-makefs@.service(8)
systemd-mkswap@device.service
 systemd-makefs@.service(8)
systemd-modules-load.service
 systemd-modules-load.service(8)
systemd-mount
 systemd-mount(1)
systemd-network-generator.service
 systemd-network-generator.service(8)
systemd-networkd-wait-online.service
 systemd-networkd-wait-online.service(8)
systemd-networkd.service
 systemd-networkd.service(8)
systemd-notify
 systemd-notify(1)
systemd-nspawn
 systemd-nspawn(1)
systemd-oomd.service
 systemd-oomd.service(8)
systemd-path

systemd-path(1)

systemd-portabled.service

 systemd-portabled.service(8)

systemd-poweroff.service

 systemd-halt.service(8)

systemd-pstore.service

 systemd-pstore.service(8)

systemd-quotacheck.service

 systemd-quotacheck.service(8)

systemd-random-seed.service

 systemd-random-seed.service(8)

systemd-reboot.service

 systemd-halt.service(8)

systemd-remount-fs.service

 systemd-remount-fs.service(8)

systemd-repart

 systemd-repart(8)

systemd-repart.service

 systemd-repart(8)

systemd-resolved.service

 systemd-resolved.service(8)

systemd-rfkill.service

 systemd-rfkill.service(8)

systemd-rfkill.socket

 systemd-rfkill.service(8)

systemd-run

 systemd-run(1)

systemd-socket-activate

 systemd-socket-activate(1)

systemd-socket-proxyd

 systemd-socket-proxyd(8)

systemd-suspend-then-hibernate.service

 systemd-suspend.service(8)

systemd-suspend.service
 systemd-suspend.service(8)

systemd-sysctl.service
 systemd-sysctl.service(8)

systemd-sysex

 systemd-sysex(8)

systemd-sysex.service
 systemd-sysex(8)

systemd-sysusers
 systemd-sysusers(8)

systemd-sysusers.service
 systemd-sysusers(8)

systemd-time-wait-sync.service
 systemd-time-wait-sync.service(8)

systemd-timedated.service
 systemd-timedated.service(8)

systemd-timesyncd.service
 systemd-timesyncd.service(8)

systemd-tmpfiles
 systemd-tmpfiles(8)

systemd-tmpfiles-clean.service
 systemd-tmpfiles(8)

systemd-tmpfiles-clean.timer
 systemd-tmpfiles(8)

systemd-tmpfiles-setup-dev.service
 systemd-tmpfiles(8)

systemd-tmpfiles-setup.service
 systemd-tmpfiles(8)

systemd-tty-ask-password-agent
 systemd-tty-ask-password-agent(1)

systemd-udev-settle.service
 systemd-udev-settle.service(8)

systemd-udev-control.socket

systemd-udev.service(8)
systemd-udev-kernel.socket
systemd-udev.service(8)
systemd-udev.service
systemd-udev.service(8)
systemd-update-done.service
systemd-update-done.service(8)
systemd-update-utmp-runlevel.service
systemd-update-utmp.service(8)
systemd-update-utmp.service
systemd-update-utmp.service(8)
systemd-user-sessions.service
systemd-user-sessions.service(8)
systemd-veritysetup@.service
systemd-veritysetup@.service(8)
systemd-volatile-root.service
systemd-volatile-root.service(8)
target.target
systemd.target(5), systemd.unit(5)
telinit
telinit(8)
time-set.target
systemd.special(7)
time-sync.target
systemd.special(7)
timedatectl
timedatectl(1)
timer.timer
systemd.timer(5), systemd.unit(5)
timers.target
systemd.special(7)
udevadm
udevadm(8)

umount.target

systemd.special(7)

usb-gadget.target

systemd.special(7)

user-UID.slice

user@.service(5)

user-runtime-dir@UID.service

user@.service(5)

user.slice

systemd.special(7)

user@UID.service

user@.service(5)

veritysetup-pre.target

systemd.special(7)

veritysetup.target

systemd.special(7)

~/.config/environment.d/*.conf

environment.d(5)

~/.config/systemd/user/

systemd.unit(5)

~/.config/systemd/user.conf

systemd-system.conf(5)

~/.config/systemd/user.control/

systemd.unit(5)

~/.config/user-tmpfiles.d/*.conf

tmpfiles.d(5)

~/.local/share/user-tmpfiles.d/*.conf

tmpfiles.d(5)

D-BUS INTERFACES

Interfaces exposed over D-Bus.

org.freedesktop.LogControl1

org.freedesktop.LogControl1(5)

org.freedesktop.hostname1

org.freedesktop.hostname1(5)
org.freedesktop.import1.Manager
org.freedesktop.import1(5)
org.freedesktop.import1.Transfer
org.freedesktop.import1(5)
org.freedesktop.locale1
org.freedesktop.locale1(5)
org.freedesktop.login1.Manager
org.freedesktop.login1(5)
org.freedesktop.login1.Seat
org.freedesktop.login1(5)
org.freedesktop.login1.Session
org.freedesktop.login1(5)
org.freedesktop.login1.User
org.freedesktop.login1(5)
org.freedesktop.machine1.Machine
org.freedesktop.machine1(5)
org.freedesktop.machine1.Manager
org.freedesktop.machine1(5)
org.freedesktop.oom1.Manager
org.freedesktop.oom1(5)
org.freedesktop.portable1.Image
org.freedesktop.portable1(5)
org.freedesktop.portable1.Manager
org.freedesktop.portable1(5)
org.freedesktop.resolve1.Link
org.freedesktop.resolve1(5)
org.freedesktop.resolve1.Manager
org.freedesktop.resolve1(5)
org.freedesktop.systemd1.Automount
org.freedesktop.systemd1(5)
org.freedesktop.systemd1.Device
org.freedesktop.systemd1(5)

org.freedesktop.systemd1.Job
 org.freedesktop.systemd1(5)
org.freedesktop.systemd1.Manager
 org.freedesktop.systemd1(5)
org.freedesktop.systemd1.Mount
 org.freedesktop.systemd1(5)
org.freedesktop.systemd1.Path
 org.freedesktop.systemd1(5)
org.freedesktop.systemd1.Scope
 org.freedesktop.systemd1(5)
org.freedesktop.systemd1.Service
 org.freedesktop.systemd1(5)
org.freedesktop.systemd1.Slice
 org.freedesktop.systemd1(5)
org.freedesktop.systemd1.Socket
 org.freedesktop.systemd1(5)
org.freedesktop.systemd1.Swap
 org.freedesktop.systemd1(5)
org.freedesktop.systemd1.Timer
 org.freedesktop.systemd1(5)
org.freedesktop.systemd1.Unit
 org.freedesktop.systemd1(5)
org.freedesktop.timedate1
 org.freedesktop.timedate1(5)

D-BUS METHODS

Methods exposed in the D-Bus interface.

Abandon()

 org.freedesktop.systemd1(5)

AbandonScope()

 org.freedesktop.systemd1(5)

Activate()

 org.freedesktop.login1(5)

ActivateSession()

org.freedesktop.login1(5)

ActivateSessionOnSeat()

org.freedesktop.login1(5)

AddDependencyUnitFiles()

org.freedesktop.systemd1(5)

Attach()

org.freedesktop.portable1(5)

AttachDevice()

org.freedesktop.login1(5)

AttachImage()

org.freedesktop.portable1(5)

AttachImageWithExtensions()

org.freedesktop.portable1(5)

AttachProcesses()

org.freedesktop.systemd1(5)

AttachProcessesToUnit()

org.freedesktop.systemd1(5)

AttachWithExtensions()

org.freedesktop.portable1(5)

BindMount()

org.freedesktop.machine1(5), org.freedesktop.systemd1(5)

BindMountMachine()

org.freedesktop.machine1(5)

BindMountUnit()

org.freedesktop.systemd1(5)

CanHalt()

org.freedesktop.login1(5)

CanHibernate()

org.freedesktop.login1(5)

CanHybridSleep()

org.freedesktop.login1(5)

CanPowerOff()

org.freedesktop.login1(5)

CanReboot()
 org.freedesktop.login1(5)

CanRebootParameter()
 org.freedesktop.login1(5)

CanRebootToBootLoaderEntry()
 org.freedesktop.login1(5)

CanRebootToBootLoaderMenu()
 org.freedesktop.login1(5)

CanRebootToFirmwareSetup()
 org.freedesktop.login1(5)

CanSuspend()
 org.freedesktop.login1(5)

CanSuspendThenHibernate()
 org.freedesktop.login1(5)

Cancel()
 org.freedesktop.import1(5), org.freedesktop.systemd1(5)

CancelJob()
 org.freedesktop.systemd1(5)

CancelScheduledShutdown()
 org.freedesktop.login1(5)

CancelTransfer()
 org.freedesktop.import1(5)

Clean()
 org.freedesktop.systemd1(5)

CleanPool()
 org.freedesktop.machine1(5)

CleanUnit()
 org.freedesktop.systemd1(5)

ClearJobs()
 org.freedesktop.systemd1(5)

CloneImage()
 org.freedesktop.machine1(5)

CopyFrom()

org.freedesktop.machine1(5)
CopyFromMachine()
org.freedesktop.machine1(5)
CopyTo()
org.freedesktop.machine1(5)
CopyToMachine()
org.freedesktop.machine1(5)
CreateMachine()
org.freedesktop.machine1(5)
CreateMachineWithNetwork()
org.freedesktop.machine1(5)
CreateSession()
org.freedesktop.login1(5)
Describe()
org.freedesktop.hostname1(5)
Detach()
org.freedesktop.portable1(5)
DetachImage()
org.freedesktop.portable1(5)
DetachImageWithExtensions()
org.freedesktop.portable1(5)
DetachWithExtensions()
org.freedesktop.portable1(5)
DisableUnitFiles()
org.freedesktop.systemd1(5)
DisableUnitFilesWithFlags()
org.freedesktop.systemd1(5)
Dump()
org.freedesktop.systemd1(5)
DumpByFileDescriptor()
org.freedesktop.oom1(5), org.freedesktop.systemd1(5)
EnableUnitFiles()
org.freedesktop.systemd1(5)

EnableUnitFilesWithFlags()
 org.freedesktop.systemd1(5)

EnqueueJob()
 org.freedesktop.systemd1(5)

EnqueueMarkedJobs()
 org.freedesktop.systemd1(5)

EnqueueUnitJob()
 org.freedesktop.systemd1(5)

Exit()
 org.freedesktop.systemd1(5)

ExportRaw()
 org.freedesktop.import1(5)

ExportTar()
 org.freedesktop.import1(5)

FlushCaches()
 org.freedesktop.resolve1(5)

FlushDevices()
 org.freedesktop.login1(5)

Freeze()
 org.freedesktop.systemd1(5)

FreezeUnit()
 org.freedesktop.systemd1(5)

GetAddresses()
 org.freedesktop.machine1(5)

GetAfter()
 org.freedesktop.systemd1(5)

GetBefore()
 org.freedesktop.systemd1(5)

GetDefaultTarget()
 org.freedesktop.systemd1(5)

GetDynamicUsers()
 org.freedesktop.systemd1(5)

GetImage()

org.freedesktop.machine1(5), org.freedesktop.portable1(5)

GetImageHostname()

org.freedesktop.machine1(5)

GetImageMachineID()

org.freedesktop.machine1(5)

GetImageMachineInfo()

org.freedesktop.machine1(5)

GetImageMetadata()

org.freedesktop.portable1(5)

GetImageMetadataWithExtensions()

org.freedesktop.portable1(5)

GetImageOSRelease()

org.freedesktop.machine1(5), org.freedesktop.portable1(5)

GetImageState()

org.freedesktop.portable1(5)

GetJob()

org.freedesktop.systemd1(5)

GetJobAfter()

org.freedesktop.systemd1(5)

GetJobBefore()

org.freedesktop.systemd1(5)

GetLink()

org.freedesktop.resolve1(5)

GetMachine()

org.freedesktop.machine1(5)

GetMachineAddresses()

org.freedesktop.machine1(5)

GetMachineByPID()

org.freedesktop.machine1(5)

GetMachineOSRelease()

org.freedesktop.machine1(5)

GetMachineUIDShift()

org.freedesktop.machine1(5)

GetMetadata()
 org.freedesktop.portable1(5)

GetMetadataWithExtensions()
 org.freedesktop.portable1(5)

GetOSRelease()
 org.freedesktop.machine1(5), org.freedesktop.portable1(5)

GetProcesses()
 org.freedesktop.systemd1(5)

GetProductUUID()
 org.freedesktop.hostname1(5)

GetSeat()
 org.freedesktop.login1(5)

GetSession()
 org.freedesktop.login1(5)

GetSessionByPID()
 org.freedesktop.login1(5)

GetState()
 org.freedesktop.portable1(5)

GetUIDShift()
 org.freedesktop.machine1(5)

GetUnit()
 org.freedesktop.systemd1(5)

GetUnitByControlGroup()
 org.freedesktop.systemd1(5)

GetUnitByInvocationID()
 org.freedesktop.systemd1(5)

GetUnitByPID()
 org.freedesktop.systemd1(5)

GetUnitFileLinks()
 org.freedesktop.systemd1(5)

GetUnitFileState()
 org.freedesktop.systemd1(5)

GetUnitProcesses()

org.freedesktop.systemd1(5)

GetUser()

org.freedesktop.login1(5)

GetUserByPID()

org.freedesktop.login1(5)

Halt()

org.freedesktop.login1(5), org.freedesktop.systemd1(5)

HaltWithFlags()

org.freedesktop.login1(5)

Hibernate()

org.freedesktop.login1(5)

HibernateWithFlags()

org.freedesktop.login1(5)

HybridSleep()

org.freedesktop.login1(5)

HybridSleepWithFlags()

org.freedesktop.login1(5)

ImportFileSystem()

org.freedesktop.import1(5)

ImportRaw()

org.freedesktop.import1(5)

ImportTar()

org.freedesktop.import1(5)

Inhibit()

org.freedesktop.login1(5)

KExec()

org.freedesktop.systemd1(5)

Kill()

org.freedesktop.login1(5), org.freedesktop.machine1(5), org.freedesktop.systemd1(5)

KillMachine()

org.freedesktop.machine1(5)

KillSession()

org.freedesktop.login1(5)

KillUnit()

org.freedesktop.systemd1(5)

KillUser()

org.freedesktop.login1(5)

LinkUnitFiles()

org.freedesktop.systemd1(5)

ListImages()

org.freedesktop.machine1(5), org.freedesktop.portable1(5)

ListInhibitors()

org.freedesktop.login1(5)

ListJobs()

org.freedesktop.systemd1(5)

ListMachines()

org.freedesktop.machine1(5)

ListSeats()

org.freedesktop.login1(5)

ListSessions()

org.freedesktop.login1(5)

ListTimezones()

org.freedesktop.timedate1(5)

ListTransfers()

org.freedesktop.import1(5)

ListUnitFiles()

org.freedesktop.systemd1(5)

ListUnitFilesByPatterns()

org.freedesktop.systemd1(5)

ListUnits()

org.freedesktop.systemd1(5)

ListUnitsByNames()

org.freedesktop.systemd1(5)

ListUnitsByPatterns()

org.freedesktop.systemd1(5)

ListUnitsFiltered()

org.freedesktop.systemd1(5)

ListUsers()

org.freedesktop.login1(5)

LoadUnit()

org.freedesktop.systemd1(5)

Lock()

org.freedesktop.login1(5)

LockSession()

org.freedesktop.login1(5)

LockSessions()

org.freedesktop.login1(5)

LookupDynamicUserByName()

org.freedesktop.systemd1(5)

LookupDynamicUserByUID()

org.freedesktop.systemd1(5)

MapFromMachineGroup()

org.freedesktop.machine1(5)

MapFromMachineUser()

org.freedesktop.machine1(5)

MapToMachineGroup()

org.freedesktop.machine1(5)

MapToMachineUser()

org.freedesktop.machine1(5)

MarkImageReadOnly()

org.freedesktop.machine1(5), org.freedesktop.portable1(5)

MarkReadOnly()

org.freedesktop.portable1(5)

MaskUnitFiles()

org.freedesktop.systemd1(5)

MountImage()

org.freedesktop.systemd1(5)

MountImageUnit()

org.freedesktop.systemd1(5)

OpenLogin()
 org.freedesktop.machine1(5)

OpenMachineLogin()
 org.freedesktop.machine1(5)

OpenMachinePTY()
 org.freedesktop.machine1(5)

OpenMachineRootDirectory()
 org.freedesktop.machine1(5)

OpenMachineShell()
 org.freedesktop.machine1(5)

OpenPTY()
 org.freedesktop.machine1(5)

OpenRootDirectory()
 org.freedesktop.machine1(5)

OpenShell()
 org.freedesktop.machine1(5)

PauseDeviceComplete()
 org.freedesktop.login1(5)

PowerOff()
 org.freedesktop.login1(5), org.freedesktop.systemd1(5)

PowerOffWithFlags()
 org.freedesktop.login1(5)

PresetAllUnitFiles()
 org.freedesktop.systemd1(5)

PresetUnitFiles()
 org.freedesktop.systemd1(5)

PresetUnitFilesWithMode()
 org.freedesktop.systemd1(5)

PullRaw()
 org.freedesktop.import1(5)

PullTar()
 org.freedesktop.import1(5)

Reattach()

org.freedesktop.portable1(5)

ReattachImage()

org.freedesktop.portable1(5)

ReattachImageWithExtensions()

org.freedesktop.portable1(5)

ReattacheWithExtensions()

org.freedesktop.portable1(5)

Reboot()

org.freedesktop.login1(5), org.freedesktop.systemd1(5)

RebootWithFlags()

org.freedesktop.login1(5)

ReenableUnitFiles()

org.freedesktop.systemd1(5)

Reexecute()

org.freedesktop.systemd1(5)

Ref()

org.freedesktop.systemd1(5)

RefUnit()

org.freedesktop.systemd1(5)

RegisterMachine()

org.freedesktop.machine1(5)

RegisterMachineWithNetwork()

org.freedesktop.machine1(5)

RegisterService()

org.freedesktop.resolve1(5)

ReleaseControl()

org.freedesktop.login1(5)

ReleaseDevice()

org.freedesktop.login1(5)

ReleaseSession()

org.freedesktop.login1(5)

Reload()

org.freedesktop.systemd1(5)

ReloadOrRestart()

org.freedesktop.systemd1(5)

ReloadOrRestartUnit()

org.freedesktop.systemd1(5)

ReloadOrTryRestart()

org.freedesktop.systemd1(5)

ReloadOrTryRestartUnit()

org.freedesktop.systemd1(5)

ReloadUnit()

org.freedesktop.systemd1(5)

Remove()

org.freedesktop.portable1(5)

RemoveImage()

org.freedesktop.machine1(5), org.freedesktop.portable1(5)

RenameImage()

org.freedesktop.machine1(5)

ResetFailed()

org.freedesktop.systemd1(5)

ResetFailedUnit()

org.freedesktop.systemd1(5)

ResetServerFeatures()

org.freedesktop.resolve1(5)

ResetStatistics()

org.freedesktop.resolve1(5)

ResolveAddress()

org.freedesktop.resolve1(5)

ResolveHostname()

org.freedesktop.resolve1(5)

ResolveRecord()

org.freedesktop.resolve1(5)

ResolveService()

org.freedesktop.resolve1(5)

Restart()

org.freedesktop.systemd1(5)
RestartUnit()
org.freedesktop.systemd1(5)
Revert()
org.freedesktop.resolve1(5)
RevertLink()
org.freedesktop.resolve1(5)
RevertUnitFiles()
org.freedesktop.systemd1(5)
ScheduleShutdown()
org.freedesktop.login1(5)
SetBrightness()
org.freedesktop.login1(5)
SetChassis()
org.freedesktop.hostname1(5)
SetDNS()
org.freedesktop.resolve1(5)
SetDNSEx()
org.freedesktop.resolve1(5)
SetDNSOverTLS()
org.freedesktop.resolve1(5)
SetDNSSEC()
org.freedesktop.resolve1(5)
SetDNSSECNegativeTrustAnchors()
org.freedesktop.resolve1(5)
SetDefaultRoute()
org.freedesktop.resolve1(5)
SetDefaultTarget()
org.freedesktop.systemd1(5)
SetDeployment()
org.freedesktop.hostname1(5)
SetDomains()
org.freedesktop.resolve1(5)

SetEnvironment()
 org.freedesktop.systemd1(5)

SetExitCode()
 org.freedesktop.systemd1(5)

SetHostname()
 org.freedesktop.hostname1(5)

SetIconName()
 org.freedesktop.hostname1(5)

SetIdleHint()
 org.freedesktop.login1(5)

SetImageLimit()
 org.freedesktop.machine1(5), org.freedesktop.portable1(5)

SetLLMNR()
 org.freedesktop.resolve1(5)

SetLimit()
 org.freedesktop.portable1(5)

SetLinkDNS()
 org.freedesktop.resolve1(5)

SetLinkDNSEx()
 org.freedesktop.resolve1(5)

SetLinkDNSOverTLS()
 org.freedesktop.resolve1(5)

SetLinkDNSSEC()
 org.freedesktop.resolve1(5)

SetLinkDNSSECNegativeTrustAnchors()
 org.freedesktop.resolve1(5)

SetLinkDefaultRoute()
 org.freedesktop.resolve1(5)

SetLinkDomains()
 org.freedesktop.resolve1(5)

SetLinkLLMNR()
 org.freedesktop.resolve1(5)

SetLinkMulticastDNS()

org.freedesktop.resolve1(5)

SetLocalRTC()

org.freedesktop.timedate1(5)

SetLocale()

org.freedesktop.locale1(5)

SetLocation()

org.freedesktop.hostname1(5)

SetLockedHint()

org.freedesktop.login1(5)

SetMulticastDNS()

org.freedesktop.resolve1(5)

SetNTP()

org.freedesktop.timedate1(5)

SetPoolLimit()

org.freedesktop.machine1(5), org.freedesktop.portable1(5)

SetPrettyHostname()

org.freedesktop.hostname1(5)

SetProperties()

org.freedesktop.systemd1(5)

SetRebootParameter()

org.freedesktop.login1(5)

SetRebootToBootLoaderEntry()

org.freedesktop.login1(5)

SetRebootToBootLoaderMenu()

org.freedesktop.login1(5)

SetRebootToFirmwareSetup()

org.freedesktop.login1(5)

SetShowStatus()

org.freedesktop.systemd1(5)

SetStaticHostname()

org.freedesktop.hostname1(5)

SetTime()

org.freedesktop.timedate1(5)

SetTimezone()
 org.freedesktop.timedate1(5)

SetType()
 org.freedesktop.login1(5)

SetUnitProperties()
 org.freedesktop.systemd1(5)

SetUserLinger()
 org.freedesktop.login1(5)

SetVConsoleKeyboard()
 org.freedesktop.locale1(5)

SetWallMessage()
 org.freedesktop.login1(5)

SetX11Keyboard()
 org.freedesktop.locale1(5)

Start()
 org.freedesktop.systemd1(5)

StartTransientUnit()
 org.freedesktop.systemd1(5)

StartUnit()
 org.freedesktop.systemd1(5)

StartUnitReplace()
 org.freedesktop.systemd1(5)

Stop()
 org.freedesktop.systemd1(5)

StopUnit()
 org.freedesktop.systemd1(5)

Subscribe()
 org.freedesktop.systemd1(5)

Suspend()
 org.freedesktop.login1(5)

SuspendThenHibernate()
 org.freedesktop.login1(5)

SuspendThenHibernateWithFlags()

org.freedesktop.login1(5)
SuspendWithFlags()
org.freedesktop.login1(5)
SwitchRoot()
org.freedesktop.systemd1(5)
SwitchTo()
org.freedesktop.login1(5)
SwitchToNext()
org.freedesktop.login1(5)
SwitchToPrevious()
org.freedesktop.login1(5)
TakeControl()
org.freedesktop.login1(5)
TakeDevice()
org.freedesktop.login1(5)
Terminate()
org.freedesktop.login1(5), org.freedesktop.machine1(5)
TerminateMachine()
org.freedesktop.machine1(5)
TerminateSeat()
org.freedesktop.login1(5)
TerminateSession()
org.freedesktop.login1(5)
TerminateUser()
org.freedesktop.login1(5)
Thaw()
org.freedesktop.systemd1(5)
ThawUnit()
org.freedesktop.systemd1(5)
TryRestart()
org.freedesktop.systemd1(5)
TryRestartUnit()
org.freedesktop.systemd1(5)

Unlock()

org.freedesktop.login1(5)

UnlockSession()

org.freedesktop.login1(5)

UnlockSessions()

org.freedesktop.login1(5)

UnmaskUnitFiles()

org.freedesktop.systemd1(5)

Unref()

org.freedesktop.systemd1(5)

UnrefUnit()

org.freedesktop.systemd1(5)

UnregisterMachine()

org.freedesktop.machine1(5)

UnregisterService()

org.freedesktop.resolve1(5)

UnsetAndSetEnvironment()

org.freedesktop.systemd1(5)

UnsetEnvironment()

org.freedesktop.systemd1(5)

Unsubscribe()

org.freedesktop.systemd1(5)

D-BUS PROPERTIES

Properties exposed in the D-Bus interface.

Accept

org.freedesktop.systemd1(5)

AccuracyUsec

org.freedesktop.systemd1(5)

Active

org.freedesktop.login1(5)

ActiveEnterTimestamp

org.freedesktop.systemd1(5)

ActiveEnterTimestampMonotonic

org.freedesktop.systemd1(5)

ActiveExitTimestamp

org.freedesktop.systemd1(5)

ActiveExitTimestampMonotonic

org.freedesktop.systemd1(5)

ActiveSession

org.freedesktop.login1(5)

ActiveState

org.freedesktop.systemd1(5)

After

org.freedesktop.systemd1(5)

AllowIsolate

org.freedesktop.systemd1(5)

AllowedCPUs

org.freedesktop.systemd1(5)

AllowedMemoryNodes

org.freedesktop.systemd1(5)

AmbientCapabilities

org.freedesktop.systemd1(5)

AppArmorProfile

org.freedesktop.systemd1(5)

Architecture

org.freedesktop.systemd1(5)

AssertResult

org.freedesktop.systemd1(5)

AssertTimestamp

org.freedesktop.systemd1(5)

AssertTimestampMonotonic

org.freedesktop.systemd1(5)

Asserts

org.freedesktop.systemd1(5)

Audit

org.freedesktop.login1(5)

BPFProgram

org.freedesktop.systemd1(5)

Backlog

org.freedesktop.systemd1(5)

Before

org.freedesktop.systemd1(5)

BindIPv6Only

org.freedesktop.systemd1(5)

BindPaths

org.freedesktop.systemd1(5)

BindReadOnlyPaths

org.freedesktop.systemd1(5)

BindToDevice

org.freedesktop.systemd1(5)

BindsTo

org.freedesktop.systemd1(5)

BlockIOAccounting

org.freedesktop.systemd1(5)

BlockIODeviceWeight

org.freedesktop.systemd1(5)

BlockIOReadBandwidth

org.freedesktop.systemd1(5)

BlockIOWeight

org.freedesktop.systemd1(5)

BlockIOWriteBandwidth

org.freedesktop.systemd1(5)

BlockInhibited

org.freedesktop.login1(5)

BootLoaderEntries

org.freedesktop.login1(5)

BoundBy

org.freedesktop.systemd1(5)

Broadcast

org.freedesktop.systemd1(5)

BusName

org.freedesktop.systemd1(5)

CPUAccounting

org.freedesktop.systemd1(5)

CPUAffinity

org.freedesktop.systemd1(5)

CPUAffinityFromNUMA

org.freedesktop.systemd1(5)

CPUQuotaPerSecUSec

org.freedesktop.systemd1(5)

CPUQuotaPeriodUSec

org.freedesktop.systemd1(5)

CPU schedulingPolicy

org.freedesktop.systemd1(5)

CPU schedulingPriority

org.freedesktop.systemd1(5)

CPU schedulingResetOnFork

org.freedesktop.systemd1(5)

CPUShares

org.freedesktop.systemd1(5)

CPUUsageNSec

org.freedesktop.systemd1(5)

CPUWeight

org.freedesktop.systemd1(5)

CacheDirectory

org.freedesktop.systemd1(5)

CacheDirectoryMode

org.freedesktop.systemd1(5)

CacheStatistics

org.freedesktop.resolve1(5)

CanClean

org.freedesktop.systemd1(5)

CanFreeze

org.freedesktop.systemd1(5)

CanGraphical

org.freedesktop.login1(5)

CanIsolate

org.freedesktop.systemd1(5)

CanNTP

org.freedesktop.timedate1(5)

CanReload

org.freedesktop.systemd1(5)

CanStart

org.freedesktop.systemd1(5)

CanStop

org.freedesktop.systemd1(5)

CanTTY

org.freedesktop.login1(5)

CapabilityBoundingSet

org.freedesktop.systemd1(5)

Chassis

org.freedesktop.hostname1(5)

Class

org.freedesktop.login1(5), org.freedesktop.machine1(5)

CleanResult

org.freedesktop.systemd1(5)

CollectMode

org.freedesktop.systemd1(5)

ConditionResult

org.freedesktop.systemd1(5)

ConditionTimestamp

org.freedesktop.systemd1(5)

ConditionTimestampMonotonic

org.freedesktop.systemd1(5)

Conditions

org.freedesktop.systemd1(5)
ConfigurationDirectory
org.freedesktop.systemd1(5)
ConfigurationDirectoryMode
org.freedesktop.systemd1(5)
ConfirmSpawn
org.freedesktop.systemd1(5)
ConflictedBy
org.freedesktop.systemd1(5)
Conflicts
org.freedesktop.systemd1(5)
ConsistsOf
org.freedesktop.systemd1(5)
ControlGroup
org.freedesktop.systemd1(5)
ControlPID
org.freedesktop.systemd1(5)
Controller
org.freedesktop.systemd1(5)
CoredumpFilter
org.freedesktop.systemd1(5)
CreationTimestamp
org.freedesktop.portable1(5)
CtrlAltDelBurstAction
org.freedesktop.systemd1(5)
CurrentDNSServer
org.freedesktop.resolve1(5)
CurrentDNSServerEx
org.freedesktop.resolve1(5)
DNS
org.freedesktop.resolve1(5)
DNSEx
org.freedesktop.resolve1(5)

DNSOverTLS

org.freedesktop.resolve1(5)

DNSSEC

org.freedesktop.resolve1(5)

DNSSECNegativeTrustAnchors

org.freedesktop.resolve1(5)

DNSSECStatistics

org.freedesktop.resolve1(5)

DNSSECSupported

org.freedesktop.resolve1(5)

DNSStubListener

org.freedesktop.resolve1(5)

DefaultBlockIOAccounting

org.freedesktop.systemd1(5)

DefaultCPUAccounting

org.freedesktop.systemd1(5)

DefaultDependencies

org.freedesktop.systemd1(5)

DefaultHostname

org.freedesktop.hostname1(5)

DefaultLimitAS

org.freedesktop.systemd1(5)

DefaultLimitASSoft

org.freedesktop.systemd1(5)

DefaultLimitCORE

org.freedesktop.systemd1(5)

DefaultLimitCORESoft

org.freedesktop.systemd1(5)

DefaultLimitCPU

org.freedesktop.systemd1(5)

DefaultLimitCPUSoft

org.freedesktop.systemd1(5)

DefaultLimitDATA

org.freedesktop.systemd1(5)
DefaultLimitDATASoft
org.freedesktop.systemd1(5)
DefaultLimitFSIZE
org.freedesktop.systemd1(5)
DefaultLimitFSIZESoft
org.freedesktop.systemd1(5)
DefaultLimitLOCKS
org.freedesktop.systemd1(5)
DefaultLimitLOCKSSoft
org.freedesktop.systemd1(5)
DefaultLimitMEMLOCK
org.freedesktop.systemd1(5)
DefaultLimitMEMLOCKSoft
org.freedesktop.systemd1(5)
DefaultLimitMSGQUEUE
org.freedesktop.systemd1(5)
DefaultLimitMSGQUEUESoft
org.freedesktop.systemd1(5)
DefaultLimitNICE
org.freedesktop.systemd1(5)
DefaultLimitNICESoft
org.freedesktop.systemd1(5)
DefaultLimitNOFILE
org.freedesktop.systemd1(5)
DefaultLimitNOFILESoft
org.freedesktop.systemd1(5)
DefaultLimitNPROC
org.freedesktop.systemd1(5)
DefaultLimitNPROCSoft
org.freedesktop.systemd1(5)
DefaultLimitRSS
org.freedesktop.systemd1(5)

DefaultLimitRSSSoft
org.freedesktop.systemd1(5)

DefaultLimitRTPRIO
org.freedesktop.systemd1(5)

DefaultLimitRTPRIOSoft
org.freedesktop.systemd1(5)

DefaultLimitRTTIME
org.freedesktop.systemd1(5)

DefaultLimitRTTIMESoft
org.freedesktop.systemd1(5)

DefaultLimitSIGPENDING
org.freedesktop.systemd1(5)

DefaultLimitSIGPENDINGSoft
org.freedesktop.systemd1(5)

DefaultLimitSTACK
org.freedesktop.systemd1(5)

DefaultLimitSTACKSoft
org.freedesktop.systemd1(5)

DefaultMemoryAccounting
org.freedesktop.systemd1(5)

DefaultMemoryLow
org.freedesktop.systemd1(5)

DefaultMemoryMin
org.freedesktop.systemd1(5)

DefaultOOMPolicy
org.freedesktop.systemd1(5)

DefaultRestartUsec
org.freedesktop.systemd1(5)

DefaultRoute
org.freedesktop.resolve1(5)

DefaultStandardError
org.freedesktop.systemd1(5)

DefaultStandardOutput

org.freedesktop.systemd1(5)

DefaultStartLimitBurst

org.freedesktop.systemd1(5)

DefaultStartLimitIntervalUsec

org.freedesktop.systemd1(5)

DefaultTasksAccounting

org.freedesktop.systemd1(5)

DefaultTasksMax

org.freedesktop.systemd1(5)

DefaultTimeoutAbortUsec

org.freedesktop.systemd1(5)

DefaultTimeoutStartUsec

org.freedesktop.systemd1(5)

DefaultTimeoutStopUsec

org.freedesktop.systemd1(5)

DefaultTimerAccuracyUsec

org.freedesktop.systemd1(5)

DeferAcceptUsec

org.freedesktop.systemd1(5)

DelayInhibited

org.freedesktop.login1(5)

Delegate

org.freedesktop.systemd1(5)

DelegateControllers

org.freedesktop.systemd1(5)

Deployment

org.freedesktop.hostname1(5)

Description

org.freedesktop.systemd1(5)

Desktop

org.freedesktop.login1(5)

DeviceAllow

org.freedesktop.systemd1(5)

DevicePolicy

org.freedesktop.systemd1(5)

DirectoryMode

org.freedesktop.systemd1(5)

DisableControllers

org.freedesktop.systemd1(5)

Display

org.freedesktop.login1(5)

Docked

org.freedesktop.login1(5)

Documentation

org.freedesktop.systemd1(5)

Domains

org.freedesktop.resolve1(5)

DropInPaths

org.freedesktop.systemd1(5)

DynamicUser

org.freedesktop.systemd1(5)

EffectiveCPUs

org.freedesktop.systemd1(5)

EffectiveMemoryNodes

org.freedesktop.systemd1(5)

EnableWallMessages

org.freedesktop.login1(5)

Environment

org.freedesktop.systemd1(5)

EnvironmentFiles

org.freedesktop.systemd1(5)

ExecActivate

org.freedesktop.systemd1(5)

ExecCondition

org.freedesktop.systemd1(5)

ExecConditionEx

org.freedesktop.systemd1(5)

ExecDeactivate

org.freedesktop.systemd1(5)

ExecMainCode

org.freedesktop.systemd1(5)

ExecMainExitTimestamp

org.freedesktop.systemd1(5)

ExecMainExitTimestampMonotonic

org.freedesktop.systemd1(5)

ExecMainPID

org.freedesktop.systemd1(5)

ExecMainStartTimestamp

org.freedesktop.systemd1(5)

ExecMainStartTimestampMonotonic

org.freedesktop.systemd1(5)

ExecMainStatus

org.freedesktop.systemd1(5)

ExecMount

org.freedesktop.systemd1(5)

ExecPaths

org.freedesktop.systemd1(5)

ExecReload

org.freedesktop.systemd1(5)

ExecReloadEx

org.freedesktop.systemd1(5)

ExecRemount

org.freedesktop.systemd1(5)

ExecStart

org.freedesktop.systemd1(5)

ExecStartEx

org.freedesktop.systemd1(5)

ExecStartPost

org.freedesktop.systemd1(5)

ExecStartPostEx

org.freedesktop.systemd1(5)

ExecStartPre

org.freedesktop.systemd1(5)

ExecStartPreEx

org.freedesktop.systemd1(5)

ExecStop

org.freedesktop.systemd1(5)

ExecStopEx

org.freedesktop.systemd1(5)

ExecStopPost

org.freedesktop.systemd1(5)

ExecStopPostEx

org.freedesktop.systemd1(5)

ExecStopPre

org.freedesktop.systemd1(5)

ExecUnmount

org.freedesktop.systemd1(5)

ExitCode

org.freedesktop.systemd1(5)

ExtensionImages

org.freedesktop.systemd1(5)

FailureAction

org.freedesktop.systemd1(5)

FailureActionExitStatus

org.freedesktop.systemd1(5)

FallbackDNS

org.freedesktop.resolve1(5)

FallbackDNSEx

org.freedesktop.resolve1(5)

Features

org.freedesktop.systemd1(5)

FileDescriptorName

org.freedesktop.systemd1(5)

FileDescriptorStoreMax

org.freedesktop.systemd1(5)

FinalKillSignal

org.freedesktop.systemd1(5)

FinishTimestamp

org.freedesktop.systemd1(5)

FinishTimestampMonotonic

org.freedesktop.systemd1(5)

FirmwareTimestamp

org.freedesktop.systemd1(5)

FirmwareTimestampMonotonic

org.freedesktop.systemd1(5)

FixedRandomDelay

org.freedesktop.systemd1(5)

FlushPending

org.freedesktop.systemd1(5)

Following

org.freedesktop.systemd1(5)

ForceUnmount

org.freedesktop.systemd1(5)

FragmentPath

org.freedesktop.systemd1(5)

FreeBind

org.freedesktop.systemd1(5)

FreezerState

org.freedesktop.systemd1(5)

GID

org.freedesktop.login1(5), org.freedesktop.systemd1(5)

GeneratorsFinishTimestamp

org.freedesktop.systemd1(5)

GeneratorsFinishTimestampMonotonic

org.freedesktop.systemd1(5)

GeneratorsStartTimestamp

org.freedesktop.systemd1(5)

GeneratorsStartTimestampMonotonic

org.freedesktop.systemd1(5)

Group

org.freedesktop.systemd1(5)

GuessMainPID

org.freedesktop.systemd1(5)

HandleHibernateKey

org.freedesktop.login1(5)

HandleLidSwitch

org.freedesktop.login1(5)

HandleLidSwitchDocked

org.freedesktop.login1(5)

HandleLidSwitchExternalPower

org.freedesktop.login1(5)

HandlePowerKey

org.freedesktop.login1(5)

HandleSuspendKey

org.freedesktop.login1(5)

HardwareModel

org.freedesktop.hostname1(5)

HardwareVendor

org.freedesktop.hostname1(5)

HoldoffTimeoutUSec

org.freedesktop.login1(5)

HomeURL

org.freedesktop.hostname1(5)

Hostname

org.freedesktop.hostname1(5)

HostnameSource

org.freedesktop.hostname1(5)

IOAccounting

org.freedesktop.systemd1(5)
IODeviceLatencyTargetUsec
org.freedesktop.systemd1(5)
IODeviceWeight
org.freedesktop.systemd1(5)
IOReadBandwidthMax
org.freedesktop.systemd1(5)
IOReadBytes
org.freedesktop.systemd1(5)
IOReadIOPSMax
org.freedesktop.systemd1(5)
IOReadOperations
org.freedesktop.systemd1(5)
IOSchedulingClass
org.freedesktop.systemd1(5)
IOSchedulingPriority
org.freedesktop.systemd1(5)
IOWeight
org.freedesktop.systemd1(5)
IOWriteBandwidthMax
org.freedesktop.systemd1(5)
IOWriteBytes
org.freedesktop.systemd1(5)
IOWriteIOPSMax
org.freedesktop.systemd1(5)
IOWriteOperations
org.freedesktop.systemd1(5)
IPAccounting
org.freedesktop.systemd1(5)
IPAddressAllow
org.freedesktop.systemd1(5)
IPAddressDeny
org.freedesktop.systemd1(5)

IPCNamespacePath

org.freedesktop.systemd1(5)

IPegressBytes

org.freedesktop.systemd1(5)

IPegressFilterPath

org.freedesktop.systemd1(5)

IPegressPackets

org.freedesktop.systemd1(5)

IPIngressBytes

org.freedesktop.systemd1(5)

IPIngressFilterPath

org.freedesktop.systemd1(5)

IPIngressPackets

org.freedesktop.systemd1(5)

IPTOS

org.freedesktop.systemd1(5)

IPTTL

org.freedesktop.systemd1(5)

IconName

org.freedesktop.hostname1(5)

Id

org.freedesktop.import1(5), org.freedesktop.login1(5), org.freedesktop.machine1(5),

org.freedesktop.systemd1(5)

IdleAction

org.freedesktop.login1(5)

IdleActionUsec

org.freedesktop.login1(5)

IdleHint

org.freedesktop.login1(5)

IdleSinceHint

org.freedesktop.login1(5)

IdleSinceHintMonotonic

org.freedesktop.login1(5)

IgnoreOnIsolate

org.freedesktop.systemd1(5)

IgnoreSIGPIPE

org.freedesktop.systemd1(5)

InaccessiblePaths

org.freedesktop.systemd1(5)

InactiveEnterTimestamp

org.freedesktop.systemd1(5)

InactiveEnterTimestampMonotonic

org.freedesktop.systemd1(5)

InactiveExitTimestamp

org.freedesktop.systemd1(5)

InactiveExitTimestampMonotonic

org.freedesktop.systemd1(5)

InhibitDelayMaxUSec

org.freedesktop.login1(5)

InhibitorsMax

org.freedesktop.login1(5)

InitRDGeneratorsFinishTimestamp

org.freedesktop.systemd1(5)

InitRDGeneratorsFinishTimestampMonotonic

org.freedesktop.systemd1(5)

InitRDGeneratorsStartTimestamp

org.freedesktop.systemd1(5)

InitRDGeneratorsStartTimestampMonotonic

org.freedesktop.systemd1(5)

InitRDSecurityFinishTimestamp

org.freedesktop.systemd1(5)

InitRDSecurityFinishTimestampMonotonic

org.freedesktop.systemd1(5)

InitRDSecurityStartTimestamp

org.freedesktop.systemd1(5)

InitRDSecurityStartTimestampMonotonic

org.freedesktop.systemd1(5)

InitRDTimestamp

org.freedesktop.systemd1(5)

InitRDTimestampMonotonic

org.freedesktop.systemd1(5)

InitRDUnitsLoadFinishTimestamp

org.freedesktop.systemd1(5)

InitRDUnitsLoadFinishTimestampMonotonic

org.freedesktop.systemd1(5)

InitRDUnitsLoadStartTimestamp

org.freedesktop.systemd1(5)

InitRDUnitsLoadStartTimestampMonotonic

org.freedesktop.systemd1(5)

InvocationID

org.freedesktop.systemd1(5)

Job

org.freedesktop.systemd1(5)

JobRunningTimeoutUsec

org.freedesktop.systemd1(5)

JobTimeoutAction

org.freedesktop.systemd1(5)

JobTimeoutRebootArgument

org.freedesktop.systemd1(5)

JobTimeoutUsec

org.freedesktop.systemd1(5)

JobType

org.freedesktop.systemd1(5)

JoinsNamespaceOf

org.freedesktop.systemd1(5)

KExecWatchdogUsec

org.freedesktop.systemd1(5)

KeepAlive

org.freedesktop.systemd1(5)

KeepAliveIntervalUsec

org.freedesktop.systemd1(5)

KeepAliveProbes

org.freedesktop.systemd1(5)

KeepAliveTimeUsec

org.freedesktop.systemd1(5)

KernelName

org.freedesktop.hostname1(5)

KernelRelease

org.freedesktop.hostname1(5)

KernelTimestamp

org.freedesktop.systemd1(5)

KernelTimestampMonotonic

org.freedesktop.systemd1(5)

KernelVersion

org.freedesktop.hostname1(5)

KeyringMode

org.freedesktop.systemd1(5)

KillExcludeUsers

org.freedesktop.login1(5)

KillMode

org.freedesktop.systemd1(5)

KillOnlyUsers

org.freedesktop.login1(5)

KillSignal

org.freedesktop.systemd1(5)

KillUserProcesses

org.freedesktop.login1(5)

LLMNR

org.freedesktop.resolve1(5)

LLMNRHostname

org.freedesktop.resolve1(5)

LastTriggerUsec

org.freedesktop.systemd1(5)

LastTriggerUsecMonotonic

org.freedesktop.systemd1(5)

LazyUnmount

org.freedesktop.systemd1(5)

Leader

org.freedesktop.login1(5), org.freedesktop.machine1(5)

LidClosed

org.freedesktop.login1(5)

Limit

org.freedesktop.portable1(5)

LimitAS

org.freedesktop.systemd1(5)

LimitASSoft

org.freedesktop.systemd1(5)

LimitCORE

org.freedesktop.systemd1(5)

LimitCORESoft

org.freedesktop.systemd1(5)

LimitCPU

org.freedesktop.systemd1(5)

LimitCPUSoft

org.freedesktop.systemd1(5)

LimitDATA

org.freedesktop.systemd1(5)

LimitDATASoft

org.freedesktop.systemd1(5)

LimitExclusive

org.freedesktop.portable1(5)

LimitFSIZE

org.freedesktop.systemd1(5)

LimitFSIZESoft

org.freedesktop.systemd1(5)

LimitLOCKS

org.freedesktop.systemd1(5)

LimitLOCKSSoft

org.freedesktop.systemd1(5)

LimitMEMLOCK

org.freedesktop.systemd1(5)

LimitMEMLOCKSoft

org.freedesktop.systemd1(5)

LimitMSGQUEUE

org.freedesktop.systemd1(5)

LimitMSGQUEUESoft

org.freedesktop.systemd1(5)

LimitNICE

org.freedesktop.systemd1(5)

LimitNICESoft

org.freedesktop.systemd1(5)

LimitNOFILE

org.freedesktop.systemd1(5)

LimitNOFILESoft

org.freedesktop.systemd1(5)

LimitNPROC

org.freedesktop.systemd1(5)

LimitNPROCSOFT

org.freedesktop.systemd1(5)

LimitRSS

org.freedesktop.systemd1(5)

LimitRSSSoft

org.freedesktop.systemd1(5)

LimitRTPRIO

org.freedesktop.systemd1(5)

LimitRTPRIOSoft

org.freedesktop.systemd1(5)

LimitRTTIME

org.freedesktop.systemd1(5)

LimitRTTIMESoft

org.freedesktop.systemd1(5)

LimitSIGPENDING

org.freedesktop.systemd1(5)

LimitSIGPENDINGSoft

org.freedesktop.systemd1(5)

LimitSTACK

org.freedesktop.systemd1(5)

LimitSTACKSoft

org.freedesktop.systemd1(5)

Linger

org.freedesktop.login1(5)

Listen

org.freedesktop.systemd1(5)

LoadCredential

org.freedesktop.systemd1(5)

LoadError

org.freedesktop.systemd1(5)

LoadState

org.freedesktop.systemd1(5)

LoaderTimestamp

org.freedesktop.systemd1(5)

LoaderTimestampMonotonic

org.freedesktop.systemd1(5)

Local

org.freedesktop.import1(5)

LocalRTC

org.freedesktop.timedate1(5)

Locale

org.freedesktop.locale1(5)

Location

org.freedesktop.hostname1(5)

LockPersonality

org.freedesktop.systemd1(5)

LockedHint

org.freedesktop.login1(5)

LogExtraFields

org.freedesktop.systemd1(5)

LogLevel

org.freedesktop.LogControl1(5), org.freedesktop.systemd1(5)

LogLevelMax

org.freedesktop.systemd1(5)

LogNamespace

org.freedesktop.systemd1(5)

LogRateLimitBurst

org.freedesktop.systemd1(5)

LogRateLimitIntervalUsec

org.freedesktop.systemd1(5)

LogTarget

org.freedesktop.LogControl1(5), org.freedesktop.systemd1(5)

LogsDirectory

org.freedesktop.systemd1(5)

LogsDirectoryMode

org.freedesktop.systemd1(5)

MainPID

org.freedesktop.systemd1(5)

MakeDirectory

org.freedesktop.systemd1(5)

ManagedOOMMemoryPressure

org.freedesktop.systemd1(5)

ManagedOOMMemoryPressureLimit

org.freedesktop.systemd1(5)

ManagedOOMPreference

org.freedesktop.systemd1(5)

ManagedOOMSwap

org.freedesktop.systemd1(5)

Mark

org.freedesktop.systemd1(5)

Markers

org.freedesktop.systemd1(5)

MaxConnections

org.freedesktop.systemd1(5)

MaxConnectionsPerSource

org.freedesktop.systemd1(5)

MemoryAccounting

org.freedesktop.systemd1(5)

MemoryAvailable

org.freedesktop.systemd1(5)

MemoryCurrent

org.freedesktop.systemd1(5)

MemoryDenyWriteExecute

org.freedesktop.systemd1(5)

MemoryHigh

org.freedesktop.systemd1(5)

MemoryLimit

org.freedesktop.systemd1(5)

MemoryLow

org.freedesktop.systemd1(5)

MemoryMax

org.freedesktop.systemd1(5)

MemoryMin

org.freedesktop.systemd1(5)

MemorySwapMax

org.freedesktop.systemd1(5)

MessageQueueMaxMessages

org.freedesktop.systemd1(5)

MessageQueueMessageSize

org.freedesktop.systemd1(5)

ModificationTimestamp

org.freedesktop.portable1(5)

MountAPIVFS

org.freedesktop.systemd1(5)

MountFlags

org.freedesktop.systemd1(5)

MountImages

org.freedesktop.systemd1(5)

MulticastDNS

org.freedesktop.resolve1(5)

NAccepted

org.freedesktop.systemd1(5)

NAutoVTs

org.freedesktop.login1(5)

NConnections

org.freedesktop.systemd1(5)

NCurrentInhibitors

org.freedesktop.login1(5)

NCurrentSessions

org.freedesktop.login1(5)

NFailedJobs

org.freedesktop.systemd1(5)

NFailedUnits

org.freedesktop.systemd1(5)

NFileDescriptorStore

org.freedesktop.systemd1(5)

NInstalledJobs

org.freedesktop.systemd1(5)

NJobs

org.freedesktop.systemd1(5)

NNames

org.freedesktop.systemd1(5)

NRefused

org.freedesktop.systemd1(5)

NRestarts

org.freedesktop.systemd1(5)

NTP

org.freedesktop.timedate1(5)

NTPSynchronized

org.freedesktop.timedate1(5)

NUMAMask

org.freedesktop.systemd1(5)

NUMAPolicy

org.freedesktop.systemd1(5)

Name

org.freedesktop.login1(5), org.freedesktop.machine1(5), org.freedesktop.portable1(5)

Names

org.freedesktop.systemd1(5)

NeedDaemonReload

org.freedesktop.systemd1(5)

NetworkInterfaces

org.freedesktop.machine1(5)

NetworkNamespacePath

org.freedesktop.systemd1(5)

NextElapseUsecMonotonic

org.freedesktop.systemd1(5)

NextElapseUsecRealtime

org.freedesktop.systemd1(5)

Nice

org.freedesktop.systemd1(5)

NoDelay

org.freedesktop.systemd1(5)

NoExecPaths

org.freedesktop.systemd1(5)

NoNewPrivileges

org.freedesktop.systemd1(5)

NonBlocking

org.freedesktop.systemd1(5)

NotifyAccess

org.freedesktop.systemd1(5)

OOMPPolicy

org.freedesktop.systemd1(5)

OOMScoreAdjust

org.freedesktop.systemd1(5)

OnClockChange

org.freedesktop.systemd1(5)

OnExternalPower

org.freedesktop.login1(5)

OnFailure

org.freedesktop.systemd1(5)

OnFailureJobMode

org.freedesktop.systemd1(5)

OnFailureOf

org.freedesktop.systemd1(5)

OnSuccess

org.freedesktop.systemd1(5)

OnSuccessJobMode

org.freedesktop.systemd1(5)

OnSuccessOf

org.freedesktop.systemd1(5)

OnTimezoneChange

org.freedesktop.systemd1(5)

OperatingSystemCPENAME

org.freedesktop.hostname1(5)

OperatingSystemPrettyName

org.freedesktop.hostname1(5)

Options

org.freedesktop.systemd1(5)

PAMName

org.freedesktop.systemd1(5)

PIDFile

org.freedesktop.systemd1(5)

PartOf

org.freedesktop.systemd1(5)

PassCredentials

org.freedesktop.systemd1(5)

PassEnvironment

org.freedesktop.systemd1(5)

PassPacketInfo

org.freedesktop.systemd1(5)

PassSecurity

org.freedesktop.systemd1(5)

Path

org.freedesktop.portable1(5)

Paths

org.freedesktop.systemd1(5)

Perpetual

org.freedesktop.systemd1(5)

Persistent

org.freedesktop.systemd1(5)

Personality

org.freedesktop.systemd1(5)

PipeSize

org.freedesktop.systemd1(5)

PoolLimit

org.freedesktop.machine1(5), org.freedesktop.portable1(5)

PoolPath

org.freedesktop.machine1(5), org.freedesktop.portable1(5)

PoolUsage

org.freedesktop.machine1(5), org.freedesktop.portable1(5)

PreparingForShutdown

org.freedesktop.login1(5)

PreparingForSleep

org.freedesktop.login1(5)

PrettyHostname

org.freedesktop.hostname1(5)

Priority

org.freedesktop.systemd1(5)

PrivateDevices

org.freedesktop.systemd1(5)

PrivateIPC

org.freedesktop.systemd1(5)

PrivateMounts

org.freedesktop.systemd1(5)

PrivateNetwork

org.freedesktop.systemd1(5)

PrivateTmp

org.freedesktop.systemd1(5)

PrivateUsers

org.freedesktop.systemd1(5)

ProcSubset

org.freedesktop.systemd1(5)

Profiles

org.freedesktop.portable1(5)

Progress

org.freedesktop.import1(5), org.freedesktop.systemd1(5)

PropagatesReloadTo

org.freedesktop.systemd1(5)

PropagatesStopTo

org.freedesktop.systemd1(5)

ProtectClock

org.freedesktop.systemd1(5)

ProtectControlGroups

org.freedesktop.systemd1(5)

ProtectHome

org.freedesktop.systemd1(5)

ProtectHostname

org.freedesktop.systemd1(5)

ProtectKernelLogs

org.freedesktop.systemd1(5)

ProtectKernelModules

org.freedesktop.systemd1(5)

ProtectKernelTunables

org.freedesktop.systemd1(5)

ProtectProc

org.freedesktop.systemd1(5)

ProtectSystem

org.freedesktop.systemd1(5)

RTCTimeUsec

org.freedesktop.timedate1(5)

RandomizedDelayUsec

org.freedesktop.systemd1(5)

ReadOnly

org.freedesktop.portable1(5)

ReadOnlyPaths

org.freedesktop.systemd1(5)

ReadWriteOnly

org.freedesktop.systemd1(5)

ReadWritePaths

org.freedesktop.systemd1(5)

RebootArgument

org.freedesktop.systemd1(5)

RebootParameter

org.freedesktop.login1(5)

RebootToBootLoaderEntry

org.freedesktop.login1(5)

RebootToBootLoaderMenu

org.freedesktop.login1(5)

RebootToFirmwareSetup

org.freedesktop.login1(5)

RebootWatchdogUsec

org.freedesktop.systemd1(5)

ReceiveBuffer

org.freedesktop.systemd1(5)

Refs

org.freedesktop.systemd1(5)

RefuseManualStart

org.freedesktop.systemd1(5)

RefuseManualStop

org.freedesktop.systemd1(5)

ReloadPropagatedFrom

org.freedesktop.systemd1(5)

ReloadResult

org.freedesktop.systemd1(5)

RemainAfterElapse

org.freedesktop.systemd1(5)

RemainAfterExit

org.freedesktop.systemd1(5)

Remote

org.freedesktop.import1(5), org.freedesktop.login1(5)

RemoteHost

org.freedesktop.login1(5)

RemoteUser

org.freedesktop.login1(5)

RemoveIPC

org.freedesktop.login1(5), org.freedesktop.systemd1(5)

RemoveOnStop

org.freedesktop.systemd1(5)

RequiredBy

org.freedesktop.systemd1(5)

Requires

org.freedesktop.systemd1(5)

RequiresMountsFor

org.freedesktop.systemd1(5)

Requisite

org.freedesktop.systemd1(5)

RequisiteOf

org.freedesktop.systemd1(5)

ResolveConfMode

org.freedesktop.resolve1(5)

Restart

org.freedesktop.systemd1(5)

RestartForceExitStatus

org.freedesktop.systemd1(5)

RestartKillSignal

org.freedesktop.systemd1(5)

RestartPreventExitStatus

org.freedesktop.systemd1(5)

RestartUsec

org.freedesktop.systemd1(5)

RestrictAddressFamilies

org.freedesktop.systemd1(5)

RestrictNamespaces

org.freedesktop.systemd1(5)

RestrictRealtime

org.freedesktop.systemd1(5)

RestrictSUIDSGID

org.freedesktop.systemd1(5)

Result

org.freedesktop.systemd1(5)

ReusePort

org.freedesktop.systemd1(5)

RootDirectory

org.freedesktop.machine1(5), org.freedesktop.systemd1(5)

RootDirectoryStartOnly

org.freedesktop.systemd1(5)

RootHash

org.freedesktop.systemd1(5)

RootHashPath

org.freedesktop.systemd1(5)

RootHashSignature

org.freedesktop.systemd1(5)

RootHashSignaturePath

org.freedesktop.systemd1(5)

RootImage

org.freedesktop.systemd1(5)

RootImageOptions

org.freedesktop.systemd1(5)

RootVerity

org.freedesktop.systemd1(5)

RuntimeDirectory

org.freedesktop.systemd1(5)

RuntimeDirectoryInodesMax

org.freedesktop.login1(5)

RuntimeDirectoryMode

org.freedesktop.systemd1(5)

RuntimeDirectoryPreserve

org.freedesktop.systemd1(5)

RuntimeDirectorySize

org.freedesktop.login1(5)

RuntimeMaxUsec

org.freedesktop.systemd1(5)

RuntimePath

org.freedesktop.login1(5)

RuntimeWatchdogUsec

org.freedesktop.systemd1(5)

SELinuxContext

org.freedesktop.systemd1(5)

SameProcessGroup

org.freedesktop.systemd1(5)

ScheduledShutdown

org.freedesktop.login1(5)

Scope

org.freedesktop.login1(5)

ScopesMask

org.freedesktop.resolve1(5)

Seat

org.freedesktop.login1(5)

SecureBits

org.freedesktop.systemd1(5)

SecurityFinishTimestamp

org.freedesktop.systemd1(5)

SecurityFinishTimestampMonotonic

org.freedesktop.systemd1(5)

SecurityStartTimestamp

org.freedesktop.systemd1(5)

SecurityStartTimestampMonotonic

org.freedesktop.systemd1(5)

SendBuffer

org.freedesktop.systemd1(5)

SendSIGHUP

org.freedesktop.systemd1(5)

SendSIGKILL

org.freedesktop.systemd1(5)

Service

org.freedesktop.login1(5), org.freedesktop.machine1(5)

ServiceWatchdogs

org.freedesktop.systemd1(5)

Sessions

org.freedesktop.login1(5)

SessionsMax

org.freedesktop.login1(5)

SetCredential

org.freedesktop.systemd1(5)

ShowStatus

org.freedesktop.systemd1(5)

Slice

org.freedesktop.login1(5), org.freedesktop.systemd1(5)

SliceOf

org.freedesktop.systemd1(5)

SloppyOptions

org.freedesktop.systemd1(5)

SmackLabel

org.freedesktop.systemd1(5)

SmackLabelIPIn

org.freedesktop.systemd1(5)

SmackLabelIPOut

org.freedesktop.systemd1(5)

SmackProcessLabel

org.freedesktop.systemd1(5)

SocketBindAllow

org.freedesktop.systemd1(5)

SocketBindDeny

org.freedesktop.systemd1(5)

SocketGroup

org.freedesktop.systemd1(5)

SocketMode

org.freedesktop.systemd1(5)

SocketProtocol

org.freedesktop.systemd1(5)

SocketUser

org.freedesktop.systemd1(5)

SourcePath

org.freedesktop.systemd1(5)

StandardError

org.freedesktop.systemd1(5)

StandardErrorFileDescriptorName

org.freedesktop.systemd1(5)

StandardInput

org.freedesktop.systemd1(5)

StandardInputData

org.freedesktop.systemd1(5)

StandardInputFileDescriptorName

org.freedesktop.systemd1(5)

StandardOutput

org.freedesktop.systemd1(5)

StandardOutputFileDescriptorName

org.freedesktop.systemd1(5)

StartLimitAction

org.freedesktop.systemd1(5)

StartLimitBurst

org.freedesktop.systemd1(5)

StartLimitIntervalUsec

org.freedesktop.systemd1(5)

StartupBlockIOWeight

org.freedesktop.systemd1(5)

StartupCPUShares

org.freedesktop.systemd1(5)

StartupCPUWeight

org.freedesktop.systemd1(5)

StartupIOWeight

org.freedesktop.systemd1(5)

State

org.freedesktop.login1(5), org.freedesktop.machine1(5), org.freedesktop.systemd1(5)

StateChangeTimestamp

org.freedesktop.systemd1(5)

StateChangeTimestampMonotonic

org.freedesktop.systemd1(5)

StateDirectory

org.freedesktop.systemd1(5)

StateDirectoryMode

org.freedesktop.systemd1(5)

StaticHostname

org.freedesktop.hostname1(5)

StatusErrno

org.freedesktop.systemd1(5)

StatusText

org.freedesktop.systemd1(5)

StopPropagatedFrom

org.freedesktop.systemd1(5)

StopWhenUnneeded

org.freedesktop.systemd1(5)

SubState

org.freedesktop.systemd1(5)

SuccessAction

org.freedesktop.systemd1(5)

SuccessActionExitStatus

org.freedesktop.systemd1(5)

SuccessExitStatus

org.freedesktop.systemd1(5)

SupplementaryGroups

org.freedesktop.systemd1(5)

Symlinks

org.freedesktop.systemd1(5)

SysFSPath

org.freedesktop.systemd1(5)

SyslogFacility

org.freedesktop.systemd1(5)

SyslogIdentifier

org.freedesktop.LogControl1(5), org.freedesktop.systemd1(5)

SyslogLevel

org.freedesktop.systemd1(5)

SyslogLevelPrefix

org.freedesktop.systemd1(5)

SyslogPriority

org.freedesktop.systemd1(5)

SystemCallArchitectures

org.freedesktop.systemd1(5)

SystemCallErrorNumber

org.freedesktop.systemd1(5)

SystemCallFilter

org.freedesktop.systemd1(5)

SystemCallLog

org.freedesktop.systemd1(5)

SystemState

org.freedesktop.systemd1(5)

TCPCongestion

org.freedesktop.systemd1(5)

TTY

org.freedesktop.login1(5)

TTYPath

org.freedesktop.systemd1(5)

TTYReset

org.freedesktop.systemd1(5)

TTYVHangup

org.freedesktop.systemd1(5)

TTYVTDisallocate

org.freedesktop.systemd1(5)

Tainted

org.freedesktop.systemd1(5)

TasksAccounting

org.freedesktop.systemd1(5)

TasksCurrent

org.freedesktop.systemd1(5)

TasksMax

org.freedesktop.systemd1(5)

TemporaryFileSystem

org.freedesktop.systemd1(5)

TimeUsec

org.freedesktop.timedate1(5)

TimeoutAbortUsec

org.freedesktop.systemd1(5)

TimeoutCleanUsec

org.freedesktop.systemd1(5)

TimeoutIdleUsec

org.freedesktop.systemd1(5)

TimeoutStartFailureMode

org.freedesktop.systemd1(5)

TimeoutStartUsec

org.freedesktop.systemd1(5)

TimeoutStopFailureMode

org.freedesktop.systemd1(5)

TimeoutStopUsec

org.freedesktop.systemd1(5)

TimeoutUsec

org.freedesktop.systemd1(5)

TimerSlackNsec

org.freedesktop.systemd1(5)

TimersCalendar

org.freedesktop.systemd1(5)

TimersMonotonic

org.freedesktop.systemd1(5)

Timestamp

org.freedesktop.login1(5), org.freedesktop.machine1(5)

TimestampMonotonic

org.freedesktop.login1(5), org.freedesktop.machine1(5)

Timestamping

org.freedesktop.systemd1(5)

Timezone

org.freedesktop.timedate1(5)

TransactionStatistics

org.freedesktop.resolve1(5)

Transient

org.freedesktop.systemd1(5)

Transparent

org.freedesktop.systemd1(5)

TriggerLimitBurst

org.freedesktop.systemd1(5)

TriggerLimitIntervalUsec

org.freedesktop.systemd1(5)

TriggeredBy

org.freedesktop.systemd1(5)

Triggers

org.freedesktop.systemd1(5)

Type

org.freedesktop.import1(5), org.freedesktop.login1(5), org.freedesktop.portable1(5),

org.freedesktop.systemd1(5)

UID

org.freedesktop.login1(5), org.freedesktop.systemd1(5)

UMask

org.freedesktop.systemd1(5)

USBFunctionDescriptors

org.freedesktop.systemd1(5)

USBFunctionStrings

org.freedesktop.systemd1(5)

Unit

org.freedesktop.machine1(5), org.freedesktop.systemd1(5)

UnitFilePreset

org.freedesktop.systemd1(5)

UnitFileState

org.freedesktop.systemd1(5)

UnitPath

org.freedesktop.systemd1(5)

UnitsLoadFinishTimestamp

org.freedesktop.systemd1(5)

UnitsLoadFinishTimestampMonotonic

org.freedesktop.systemd1(5)

UnitsLoadStartTimestamp

org.freedesktop.systemd1(5)

UnitsLoadStartTimestampMonotonic

org.freedesktop.systemd1(5)

UnsetEnvironment

org.freedesktop.systemd1(5)

Usage

org.freedesktop.portable1(5)

UsageExclusive

org.freedesktop.portable1(5)

User

org.freedesktop.login1(5), org.freedesktop.systemd1(5)

UserStopDelayUsec

org.freedesktop.login1(5)

UserspaceTimestamp

org.freedesktop.systemd1(5)

UserspaceTimestampMonotonic

org.freedesktop.systemd1(5)

UtmpIdentifier

org.freedesktop.systemd1(5)

UtmpMode

org.freedesktop.systemd1(5)

VConsoleKeymap

org.freedesktop.locale1(5)

VConsoleKeymapToggle

org.freedesktop.locale1(5)

VTNr

org.freedesktop.login1(5)

Verify

org.freedesktop.import1(5)

Version

org.freedesktop.systemd1(5)

Virtualization

org.freedesktop.systemd1(5)

WakeSystem

org.freedesktop.systemd1(5)

WallMessage

org.freedesktop.login1(5)

WantedBy

org.freedesktop.systemd1(5)

Wants

org.freedesktop.systemd1(5)

WatchdogSignal

org.freedesktop.systemd1(5)

WatchdogTimestamp

org.freedesktop.systemd1(5)

WatchdogTimestampMonotonic

org.freedesktop.systemd1(5)

WatchdogUsec

org.freedesktop.systemd1(5)

What

org.freedesktop.systemd1(5)

Where

org.freedesktop.systemd1(5)

WorkingDirectory

org.freedesktop.systemd1(5)

Writable

org.freedesktop.systemd1(5)

X11Layout

org.freedesktop.locale1(5)

X11Model

org.freedesktop.locale1(5)

X11Options

org.freedesktop.locale1(5)

X11Variant

org.freedesktop.locale1(5)

D-BUS SIGNALS

Signals emitted in the D-Bus interface.

JobNew

org.freedesktop.systemd1(5)

JobRemoved

org.freedesktop.systemd1(5)

Lock

org.freedesktop.login1(5)

LogMessage

org.freedesktop.import1(5)

MachineNew

org.freedesktop.machine1(5)

MachineRemoved

org.freedesktop.machine1(5)

PauseDevice

org.freedesktop.login1(5)

PrepareForShutdown

org.freedesktop.login1(5)

PrepareForSleep

org.freedesktop.login1(5)

Reloading

org.freedesktop.systemd1(5)

RequestStop

org.freedesktop.systemd1(5)

ResumeDevice

org.freedesktop.login1(5)

SeatNew

org.freedesktop.login1(5)

SeatRemoved

org.freedesktop.login1(5)

SessionNew

org.freedesktop.login1(5)

SessionRemoved

org.freedesktop.login1(5)

StartupFinished

org.freedesktop.systemd1(5)

TransferNew

org.freedesktop.import1(5)

TransferRemoved

org.freedesktop.import1(5)

UnitFilesChanged

org.freedesktop.systemd1(5)

UnitNew

org.freedesktop.systemd1(5)

UnitRemoved

org.freedesktop.systemd1(5)

Unlock

org.freedesktop.login1(5)

UserNew

org.freedesktop.login1(5)

UserRemoved

org.freedesktop.login1(5)

COLOPHON

This index contains 4870 entries in 22 sections, referring to 351 individual manual pages.

systemd 249

SYSTEMD.DIRECTIVES(7)