



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'tanhf.3'

```
$ man tanhf.3
```

TANH(3)

Linux Programmer's Manual

TANH(3)

NAME

tanh, tanhf, tanhl - hyperbolic tangent function

SYNOPSIS

```
#include <math.h>

double tanh(double x);

float tanhf(float x);

long double tanhl(long double x);
```

Link with -Im.

Feature Test Macro Requirements for glibc (see [feature_test_macros\(7\)](#)):

tanhf(), tanhl():

```
_ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L
|| /* Since glibc 2.19: */ _DEFAULT_SOURCE
|| /* Glibc versions <= 2.19: */ _BSD_SOURCE || _SVID_SOURCE
```

DESCRIPTION

These functions return the hyperbolic tangent of x , which is defined mathematically as:

$$\tanh(x) = \sinh(x) / \cosh(x)$$

RETURN VALUE

On success, these functions return the hyperbolic tangent of x .

If x is a NaN, a NaN is returned

If x is $+0$ (-0) $+0$ (-0) is returned

If x is positive infinity (negative infinity), $+1$ (-1) is returned

ERRORS

No errors occur.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?tanh(), tanhf(), tanhl() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

C99, POSIX.1-2001, POSIX.1-2008.

The variant returning double also conforms to SVr4, 4.3BSD, C89.

SEE ALSO

acosh(3), asinh(3), atanh(3), cosh(3), ctanh(3), sinh(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

2017-09-15

TANH(3)