



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'tracker3-extract.1'

\$ man tracker3-extract.1

TRACKER3-EXTRACT(1)

Tracker manual

TRACKER3-EXTRACT(1)

NAME

tracker3-extract - Extract metadata from a file.

SYNOPSIS

tracker3 extract FILE

DESCRIPTION

tracker3 extract reads the file provided and extracts any metadata it can from this file, then displays the metadata on standard output.

The metadata is displayed as a SPARQL update command, that can be run against a SPARQL endpoint to update its copy of the metadata.

The actual extraction is done by a separate process. This is done to isolate the calling process from any memory leaks or crashes in the libraries Tracker uses to extract metadata.

For more information see the libtracker-extract reference documentation.

OPTIONS

-o, --output-format=<FORMAT>

Choose which format to use to output results. Supported formats are sparql, turtle and json-ld.

EXAMPLES

Using command line to extract metadata from a file

\$ tracker3 extract /path/to/some/file.mp3

ENVIRONMENT

G_MESSAGES_DEBUG

Controls verbose log output from GLib-based code. Use `G_MESSAGES_DEBUG=Tracker` to see only Tracker-related logs, or `G_MESSAGES_DEBUG=all` to see everything.

TRACKER_DEBUG

Enables more specialized debug output. Pass a comma-separated list of one or more

keywords:

config

extractor configuration

statistics

show statistics about how many files were processed

status

log the status messages that are published over D-Bus

SEE ALSO

`tracker3-sparql(1)`, `tracker3-status(1)`, `tracker3-info(1)`.

? /usr/lib/tracker-1.0/extract-modules/

? /usr/share/tracker/extract-rules/

3.3.3

12/01/2023

TRACKER3-EXTRACT(1)