



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'transmission-gtk.1'

\$ man transmission-gtk.1

TRANSMISSION-GTK(1) BSD General Commands Manual TRANSMISSION-GTK(1)

NAME

transmission-gtk ? a bittorrent client

SYNOPSIS

transmission-gtk -?

transmission-gtk [-pqm] [torrent-file ...]

DESCRIPTION

transmission-gtk is a fast and easy BitTorrent client.

BitTorrent is a peer-to-peer file transfer protocol which uses a metainfo file (usually with the .torrent file extension) and a central tracker to distribute file data amongst a group of peers. For more information on the BitTorrent protocol see <http://www.bittorrent.org/>

OPTIONS

-? --help

Show help options

-p --paused

Start with all torrents paused

-m --minimized

Start minimized in notification area

-g, --config-dir directory

Where to look for configuration files. This can be used to swap between using the cli, daemon, gtk, and qt clients. See <https://github.com/transmission/transmission/wiki/Configuration-Files> for more information.

Multiple .torrent files may be added at startup by appending them on the command line. If

transmission-gtk is already running, the torrents will be added to the running instance.

ENVIRONMENT

TRANSMISSION_HOME

Sets the default config-dir.

http_proxy libcurl uses this environment variable when performing tracker announces. If set, this overrides the GNOME proxy preferences.

FILES

~/.config/transmission

The config-dir used when neither [TRANSMISSION_HOME] nor [-g] is specified.

AUTHORS

transmission-gtk was written by Charles Kerr, Josh Elsasser, Eric Petit, Mitchell Livingston, and Mike Gelfand.

SEE ALSO

transmission-create(1), transmission-daemon(1), transmission-edit(1), transmission-gtk(1), transmission-qt(1), transmission-remote(1), transmission-show(1)
<https://transmissionbt.com/>

BSD

May 20, 2008

BSD