



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'update-cracklib.8'

\$ man update-cracklib.8

update-cracklib(8) System Manager's Manual update-cracklib(8)

NAME

update-cracklib - Regenerate cracklib dictionary

SYNOPSIS

update-cracklib

DESCRIPTION

update-cracklib builds a compressed and accumulated version of wordlists stored in the di?

rectories given in cracklib's configuration file /etc/cracklib/cracklib.conf. Programs us?

ing cracklib2 need this database to be of any use.

By default this script is called by cron every day.

RESULT

update-cracklib prints out two numbers: the number of words read from the ASCII dictionar?

ies and the number of words eventually written into the cracklib database; if no error oc?

curred, these should be equal.

0 is returned on success, otherwise an error message is printed to standard error and -1 is returned.

FILES

/etc/cracklib/cracklib.conf

shell script that sets cracklib_dictpath_src which must be a space separated list of source dictionary files.

SEE ALSO

cracklib(3), crack_mkdict(8)

AUTHOR

This program and manual page was written by Martin Pitt <martin@piware.de> for the Debian
GNU/Linux System (but may be used by others).

Martin Pitt

June 09, 2003

update-cracklib(8)