



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'wcschr.3'

\$ man wcschr.3

WCSCHR(3)

Linux Programmer's Manual

WCSCHR(3)

NAME

wcschr - search a wide character in a wide-character string

SYNOPSIS

```
#include <wchar.h>
wchar_t *wcschr(const wchar_t *wcs, wchar_t wc);
```

DESCRIPTION

The wcschr() function is the wide-character equivalent of the strchr(3) function. It searches the first occurrence of wc in the wide-character string pointed to by wcs.

RETURN VALUE

The wcschr() function returns a pointer to the first occurrence of wc in the wide-character string pointed to by wcs, or NULL if wc does not occur in the string.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?wcschr() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C99.

SEE ALSO

strchr(3), wcspbrk(3), wcsrchr(3), wcsstr(3), wmemchr(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

GNU

2015-08-08

WCSCHR(3)