



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'wcscpy.3'

\$ man wcscpy.3

WCSCPY(3)

Linux Programmer's Manual

WCSCPY(3)

NAME

wcscpy - copy a wide-character string

SYNOPSIS

```
#include <wchar.h>
wchar_t *wcscpy(wchar_t *dest, const wchar_t *src);
```

DESCRIPTION

The wcscpy() function is the wide-character equivalent of the strcpy(3) function. It copies the wide-character string pointed to by src, including the terminating null wide character (L'\0'), to the array pointed to by dest.

The strings may not overlap.

The programmer must ensure that there is room for at least wcslen(src)+1 wide characters at dest.

RETURN VALUE

wcscpy() returns dest.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?wcscpy() ? Thread safety ? MT-Safe ?

??

POSIX.1-2001, POSIX.1-2008, C99.

SEE ALSO

strcpy(3), wcpcpy(3), wcscat(3), wcsdup(3), wmemcpy(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

GNU

2019-03-06

WCSCPY(3)