



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'wmemcpy.3'

\$ man wmemcpy.3

WMEMCPY(3)

Linux Programmer's Manual

WMEMCPY(3)

NAME

wmemcpy - copy an array of wide-characters

SYNOPSIS

```
#include <wchar.h>

wchar_t *wmemcpy(wchar_t *dest, const wchar_t *src, size_t n);
```

DESCRIPTION

The `wmemcpy()` function is the wide-character equivalent of the `memcpy(3)` function. It copies `n` wide characters from the array starting at `src` to the array starting at `dest`.

The arrays may not overlap; use `wmemmove(3)` to copy between overlapping arrays.

The programmer must ensure that there is room for at least `n` wide characters at `dest`.

RETURN VALUE

`wmemcpy()` returns `dest`.

ATTRIBUTES

For an explanation of the terms used in this section, see `attributes(7)`.

??

?Interface ? Attribute ? Value ?

??

?`wmemcpy()` ? Thread safety ? MT-Safe ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C99.

SEE ALSO

memcpy(3), wcscpy(3), wmemmove(3), wmempcpy(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

GNU

2015-08-08

WMEMCPY(3)