



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'AptPkg::PkgRecords.3pm'***

**C:\>man AptPkg::PkgRecords.3pm**

AptPkg::PkgRecords(3pm) User Contributed Perl Documentation AptPkg::PkgRecords(3pm)

### NAME

AptPkg::PkgRecords - APT package description class

### SYNOPSIS

use AptPkg::PkgRecords;

### DESCRIPTION

The AptPkg::PkgRecords module provides an interface to the parsed contents of package files.

#### AptPkg::PkgRecords

The AptPkg::PkgRecords package implements the APT pkgRecords class.

An instance of the AptPkg::PkgRecords class may be fetched using the "packages" method from an AptPkg::Cache object.

#### Methods

##### lookup(PACK)

Return a hash (or hash reference, depending on context) for the given package.

PACK may either be an AptPkg::Cache::VerFile object, an AptPkg::Cache::DescFile object or a package name.

The hash contains the following keys:

"FileName", "Checksum-FileSize", "MD5Hash", "SHA256", "SourcePkg",  
"Maintainer", "ShortDesc", "LongDesc" and "Name".

with values taken from the packages or translation file.

Note that "LongDesc" is generally not useful for AptPkg::Cache::VerFile objects, which refer to the Packages file, as these no longer contain the full description (now in the Translation files).

If PACK is a package name, these additional values are set:

"Section" and "VerStr".

and the following values are overridden with the translated versions:

"ShortDesc" and "LongDesc".

## SEE ALSO

AptPkg::Cache(3pm), AptPkg(3pm).

## AUTHOR

Brendan O'Dea <bod@debian.org>