



Rocky Enterprise Linux 9.2 Manual Pages on command 'B::Hooks::EndOfScope::XS.3pm'

C:\>man B::Hooks::EndOfScope::XS.3pm

B::Hooks::EndOfScope::XS(3pmUser Contributed Perl DocumentatiB::Hooks::EndOfScope::XS(3pm)

NAME

B::Hooks::EndOfScope::XS - Execute code after a scope finished compilation - XS implementation

VERSION

version 0.24

DESCRIPTION

This is the implementation of B::Hooks::EndOfScope based on Variable::Magic, which is an XS module dependent on a compiler. It will always be automatically preferred if Variable::Magic is available.

FUNCTIONS

on_scope_end

```
on_scope_end { ... };
```

```
on_scope_end $code;
```

Registers \$code to be executed after the surrounding scope has been compiled.

This is exported by default. See Sub::Exporter on how to customize it.

SUPPORT

Bugs may be submitted through the RT bug tracker

<<https://rt.cpan.org/Public/Dist/Display.html?Name=B-Hooks-EndOfScope>> (or

bug-B-Hooks-EndOfScope@rt.cpan.org <<mailto:bug-B-Hooks-EndOfScope@rt.cpan.org>>).

AUTHORS

? Florian Ragwitz <rafl@debian.org>

? Peter Rabbitson <ribasushi@leporine.io>

COPYRIGHT AND LICENCE

This software is copyright (c) 2008 by Florian Ragwitz.

This is free software; you can redistribute it and/or modify it under the same terms as the Perl 5 programming language system itself.

perl v5.26.2

2018-05-14

B::Hooks::EndOfScope::XS(3pm)