



Rocky Enterprise Linux 9.2 Manual Pages on command 'Dpkg::Control::Info.3perl'

C:\>man Dpkg::Control::Info.3perl

Dpkg::Control::Info(3perl) libdpkg-perl Dpkg::Control::Info(3perl)

NAME

Dpkg::Control::Info - parse files like debian/control

DESCRIPTION

It provides an object to access data of files that follow the same syntax as debian/control.

METHODS

`$c = Dpkg::Control::Info->new(%opts)`

Create a new Dpkg::Control::Info object. Loads the file from the filename option, if no option is specified filename defaults to debian/control. If a scalar is passed instead, it will be used as the filename. If filename is "-", it parses the standard input. If filename is undef no loading will be performed.

`$c->reset()`

Resets what got read.

`$c->parse($fh, $description)`

Parse a control file from the given filehandle. Exits in case of errors.

\$description is used to describe the filehandle, ideally it's a filename or a description of where the data comes from. It is used in error messages. The data in the object is reset before parsing new control files.

`$c->load($file)`

Load the content of \$file. Exits in case of errors. If file is "-", it loads from the standard input.

`$c->[0]`

`$c->get_source()`

Returns a `Dpkg::Control` object containing the fields concerning the source package.

`$c->get_pkg_by_idx($idx)`

Returns a `Dpkg::Control` object containing the fields concerning the binary package numbered \$idx (starting at 1).

`$c->get_pkg_by_name($name)`

Returns a `Dpkg::Control` object containing the fields concerning the binary package named \$name.

`$c->get_packages()`

Returns a list containing the `Dpkg::Control` objects for all binary packages.

`$str = $c->output([$fh])`

Return the content info into a string. If \$fh is specified print it into the filehandle.

`"$c"`

Return a string representation of the content.

`@{$c}`

Return a list of `Dpkg::Control` objects, the first one is corresponding to

source information and the following ones are the binary packages information.

CHANGES

Version 1.01 (dpkg 1.18.0)

New argument: The `$c->new()` constructor accepts an `%opts` argument.

Version 1.00 (dpkg 1.15.6)

Mark the module as public.

1.19.7 2022-05-25 Dpkg::Control::Info(3perl)