



Rocky Enterprise Linux 9.2 Manual Pages on command 'Dpkg::Gettext.3perl'

C:\>man Dpkg::Gettext.3perl

Dpkg::Gettext(3perl) libdpkg-perl Dpkg::Gettext(3perl)

NAME

Dpkg::Gettext - convenience wrapper around Locale::gettext

DESCRIPTION

The Dpkg::Gettext module is a convenience wrapper over the Locale::gettext module, to guarantee we always have working gettext functions, and to add some commonly used aliases.

ENVIRONMENT

DPKG_NLS

When set to 0, this environment variable will disable the National Language Support in all Dpkg modules.

VARIABLES

\$Dpkg::Gettext::DEFAULT_TEXT_DOMAIN

Specifies the default text domain name to be used with the short function aliases. This is intended to be used by the Dpkg modules, so that they can produce localized messages even when the calling program has set the current domain with `textdomain()`. If you would like to use the aliases for your own modules, you might want to set this variable to `undef`, or to another domain,

but then the Dpkg modules will not produce localized messages.

FUNCTIONS

`$domain = textdomain($new_domain)`

Compatibility `textdomain()` fallback when `Locale::gettext` is not available.

If `$new_domain` is not `undef`, it will set the current domain to `$new_domain`.

Returns the current domain, after possibly changing it.

`$trans = ngettext($msgid, $msgid_plural, $n)`

Compatibility `ngettext()` fallback when `Locale::gettext` is not available.

Returns `$msgid` if `$n` is 1 or `$msgid_plural` otherwise.

`$trans = g_($msgid)`

Calls `dgettext()` on the `$msgid` and returns its translation for the current locale. If `dgettext()` is not available, simply returns `$msgid`.

`$trans = C_($msgctxt, $msgid)`

Calls `dgettext()` on the `$msgid` and returns its translation for the specific `$msgctxt` supplied. If `dgettext()` is not available, simply returns `$msgid`.

`$trans = P_($msgid, $msgid_plural, $n)`

Calls `dngettext()`, returning the correct translation for the plural form dependent on `$n`. If `dngettext()` is not available, returns `$msgid` if `$n` is 1 or `$msgid_plural` otherwise.

`$msgid = N_($msgid)`

A pseudo function that serves as a marked for automated extraction of messages, but does not call `gettext()`. The run-time translation is done at a different place in the code.

Version 1.03 (dpkg 1.19.0)

New envvar: Add support for new DPKG-NLS environment variable.

Version 1.02 (dpkg 1.18.3)

New function: N_().

Version 1.01 (dpkg 1.18.0)

Now the short aliases (g_ and P_) will call domain aware functions with \$DEFAULT_TEXT_DOMAIN.

New functions: g_(), C_().

Deprecated function: _g().

Version 1.00 (dpkg 1.15.6)

Mark the module as public.

1.19.7

2022-05-25

Dpkg::Gettext(3perl)