



Rocky Enterprise Linux 9.2 Manual Pages on command 'Font::TTF::AATutils.3pm'

C:\>man Font::TTF::AATutils.3pm

Font::TTF::AATutils(3pm) User Contributed Perl Documentation Font::TTF::AATutils(3pm)

NAME

Font::TTF::AATutils - Utility functions for AAT tables

$(\$classes, \$states) = \text{AAT_read_subtable}(\$fh, \$baseOffset, \$subtableStart, \$limits)$

$\$length = \text{AAT_write_state_table}(\$fh, \$classes, \$states, \$numExtraTables, \$packEntry)$

$\$packEntry$ is a subroutine for packing an entry into binary form, called as

$\$dat = \$packEntry(\$entry, \$entryTable, \$numEntries)$

where the entry is a comma-separated list of nextStateOffset, flags, actions

$(\$classes, \$states, \$entries) = \text{AAT_read_state_table}(\$fh, \$numActionWords)$

$(\$format, \$lookup) = \text{AAT_read_lookup}(\$fh, \$valueSize, \$length, \$default)$

$\text{AAT_write_lookup}(\$fh, \$format, \$lookup, \$valueSize, \$default)$

AUTHOR

Jonathan Kew <<http://scripts.sil.org/FontUtils>>.

LICENSING

Copyright (c) 1998-2016, SIL International (<http://www.sil.org>)

This module is released under the terms of the Artistic License 2.0. For details, see the full text of the license in the file LICENSE.

perl v5.24.1

2016-08-28

Font::TTF::AATutils(3pm)