



Rocky Enterprise Linux 9.2 Manual Pages on command 'Font::TTF::Dumper.3pm'

C:\>man Font::TTF::Dumper.3pm

Font::TTF::Dumper(3pm) User Contributed Perl Documentation Font::TTF::Dumper(3pm)

NAME

Font::TTF::Dumper - Debug dump of a font datastructure, avoiding recursion on '

PARENT'

SYNOPSIS

```
use Font::TTF::Dumper;

# Print a table from the font structure:
print ttfdump($font->{$tag});

# Print font table with name
print ttfdump($font->{'head'}, 'head');

# Print font table with name and other options
print ttfdump($font->{'head'}, 'head', %opts);

# Print one glyph's data:
print ttfdump($font->{'loca'}->read->{'glyphs'}[$gid], "glyph_{$gid}");
```

DESCRIPTION

Font::TTF data structures are trees created from hashes and arrays. When trying to figure out how the structures work, sometimes it is helpful to use Data::Dumper on them. However, many of the object structures have ' PARENT' links that refer back to the object's parent, which means that Data::Dumper ends up dumping the whole font no matter what.

The main purpose of this module is to invoke Data::Dumper with a filter that skips over the ' PARENT' element of any hash.

To reduce output further, this module also skips over 'CACHE' elements and any hash element whose value is a `Font::TTF::Glyph` or `Font::TTF::Font` object. (Really should make this configurable.)

If `$opts{'d'}`, then set Deepcopy mode to minimize use of crossreferencing.

AUTHOR

Bob Hallissy <<http://scripts.sil.org/FontUtils>>.

LICENSING

Copyright (c) 1998-2016, SIL International (<http://www.sil.org>)

This module is released under the terms of the Artistic License 2.0. For details, see the full text of the license in the file LICENSE.

perl v5.24.1

2016-08-28

Font::TTF::Dumper(3pm)