



Rocky Enterprise Linux 9.2 Manual Pages on command 'Font::TTF::Features::Size.3pm'

C:\>man Font::TTF::Features::Size.3pm

Font::TTF::Features::Size(3pUser Contributed Perl DocumentatFont::TTF::Features::Size(3pm)

NAME

Font::TTF::Features::Size - Class for Size Feature Parameters

DESCRIPTION

Handles the Feature Parameters valus for Size features

INSTANCE VARIABLES

INFILE

The read file handle

OFFSET

Location of the file in the input file

DesignSize

Design Size in decipoints

SubFID

Identifier for the fonts in a subfamily

SubFNameID

The 'name' table name ID for the subfamily name

MinSize

Bottom end of recommended usage size range

MaxSize

Top end of recommended usage size range

METHODS

`$t->read`

Reads the Feature Params

`$t->out($fh)`

Writes the FeatureParams table to the output

`Font::TTF::Features::Sset->new()`

Creates a new FeatureParams object. Table instance variables are passed in at this point as an associative array.

AUTHOR

David Raymond <<http://scripts.sil.org/FontUtils>>.

LICENSING

Copyright (c) 1998-2016, SIL International (<http://www.sil.org>)

This module is released under the terms of the Artistic License 2.0. For details, see the full text of the license in the file LICENSE.

perl v5.24.1

2016-08-28

Font::TTF::Features::Size(3pm)