



Rocky Enterprise Linux 9.2 Manual Pages on command 'Font::TTF::Features::Sset.3pm'

C:\>man Font::TTF::Features::Sset.3pm

Font::TTF::Features::Sset(3pUser Contributed Perl DocumentatFont::TTF::Features::Sset(3pm)

NAME

Font::TTF::Features::Sset - Class for Stylistic Set Feature Parameters

DESCRIPTION

Handles the Feature Parameters value for Stylistic Sets

INSTANCE VARIABLES

INFILE

The read file handle

OFFSET

Location of the file in the input file

Version

The minor version number, currently always 0

UINameID

The 'name' table name ID that specifies a string (or strings, for multiple languages) for a user-interface label for this feature

METHODS

`$t->read`

Reads the Feature Params

`$t->out($fh)`

Writes the FeatureParams table to the output

`Font::TTF::Features::Sset->new()`

Creates a new FeatureParams object. Values for INFILE and OFFSET can be passed as parameters

AUTHOR

David Raymond <<http://scripts.sil.org/FontUtils>>.

LICENSING

Copyright (c) 1998-2016, SIL International (<http://www.sil.org>)

This module is released under the terms of the Artistic License 2.0. For details, see the full text of the license in the file LICENSE.

perl v5.24.1

2016-08-28

Font::TTF::Features::Sset(3pm)