



Rocky Enterprise Linux 9.2 Manual Pages on command 'Font::TTF::OTTags.3pm'

C:\>man Font::TTF::OTTags.3pm

Font::TTF::OTTags(3pm) User Contributed Perl Documentation Font::TTF::OTTags(3pm)

NAME

Font::TTF::OTTags - Utilities for TrueType/OpenType tags

SYNOPSIS

```
use Font::TTF::OTTags qw( %tttags %ttnames %iso639 readtagsfile );
```

```
# Look at built-in stuff:
```

```
$script_tag = $tttags{'SCRIPT'}{'Cypriot Syllabary'}; # returns 'cprt'
```

```
$lang_name = $ttnames{'LANGUAGE'}{'ALT'}; # returns 'Altai'
```

```
# Map iso639-2 tag to/from OT lang tag
```

```
@isotags = $iso639{'ALT'}; # returns [ 'atv', 'alt' ]
```

```
$lang_tag = $iso639{'atv'}; # returns 'ALT'
```

```
# Read latest tags file to add to built-in definitions
```

```
readtagsfile ("C:\\Program Files\\Microsoft VOLT\\TAGS.txt");
```

First-level keys to %tttags and %ttnames are:

SCRIPT

retrieve script tag or name

LANGUAGE

retrieve language tag or name

FEATURE

retrieve feature tag or name

Built-in data has been derived from the 2014-07-11 draft of the 3rd edition of ISO/IEC 14496-22 (Information technology - Coding of audio-visual objects - Part 22: Open Font Format) which, when finalized and approved, will replace the second edition (ISO/IEC 14496-22:2009).

METHODS

readtagsfile (filename)

Read a file in the syntax of Tags.txt (included with Microsoft VOLT) to obtain additional/replacement tag definitions.

Returns 0 if cannot open the file; else 1.

AUTHOR

Bob Hallissy. <<http://scripts.sil.org/FontUtils>>.

LICENSING

Copyright (c) 1998-2016, SIL International (<http://www.sil.org>)

This module is released under the terms of the Artistic License 2.0. For details, see the full text of the license in the file LICENSE.