



Rocky Enterprise Linux 9.2 Manual Pages on command 'Font::TTF::PSNames.3pm'

C:\>man Font::TTF::PSNames.3pm

Font::TTF::PSNames(3pm) User Contributed Perl Documentation Font::TTF::PSNames(3pm)

NAME

Font::TTF::PSNames - Utilities for Postscript glyph name processing

SYNOPSIS

```
use Font::TTF::PSNames qw(parse lookup);

$name = lookup($uni);

$uni = parse($name);
```

METHODS

lookup (\$usv [, \$noAlt [, \$noUni]])

return the Adobe-recommended glyph name for a specific Unicode codepoint (integer).

By default returns "uniXXXX" names rather than "afiiNNNNN" or "SFnnnnnn" names

If \$noAlt is true, "afii" and "SF" names are returned rather than "uniXXXX".

if \$noUni is true, returns undef if it would have to resort to "uniXXXX" or

"uXXXXXX" style names. Essentially this represents a straight lookup in the Adobe-recommended list.

parse (\$glyphname)

Parse an Adobe-conformant glyph name, generating a Unicode codepoint sequence equivalent to the glyph (or glyph components, should the name represent a

ligature). In scalar context, returns a reference to an array of Unicodes

(decimal). Array is empty if the glyph name is non-conformant. In list context,

the first item returned is the same array reference as above. The second item is a

reference to an array containing the extensions (if any) present on the glyph name.

The '.' that precedes each extension is not included.

AUTHOR

Martin Hosken <<http://scripts.sil.org/FontUtils>>.

LICENSING

Copyright (c) 1998-2016, SIL International (<http://www.sil.org>)

This module is released under the terms of the Artistic License 2.0. For details,
see the full text of the license in the file LICENSE.

perl v5.24.1

2016-08-28

Font::TTF::PSNames(3pm)