



Rocky Enterprise Linux 9.2 Manual Pages on command 'Getopt::Long::Descriptive::Usage.3pm'

C:\>man Getopt::Long::Descriptive::Usage.3pm

Getopt::Long::Descriptive::User(Contributed Perl DocGetopt::Long::Descriptive::Usage(3pm)

NAME

Getopt::Long::Descriptive::Usage - the usage description for GLD

VERSION

version 0.104

SYNOPSIS

```
use Getopt::Long::Descriptive;

my ($opt, $usage) = describe_options( ... );

$usage->text; # complete usage message

$usage->die; # die with usage message
```

DESCRIPTION

This document only describes the methods of the Usage object. For information on how to use Getopt::Long::Descriptive, consult its documentation.

METHODS

new

```
my $usage = Getopt::Long::Descriptive::Usage->new(\%arg);
```

You really don't need to call this. GLD will do it for you.

Valid arguments are:

options - an arrayref of options

leader_text - the text that leads the usage; this may go away!

text

This returns the full text of the usage message.

leader_text

This returns the text that comes at the beginning of the usage message.

option_text

This returns the text describing the available options.

warn

This warns with the usage message.

die

This throws the usage message as an exception.

```
$usage_obj->die(\%arg);
```

Some arguments can be provided

pre_text - text to be prepended to the usage message

post_text - text to be appended to the usage message

The "pre_text" and "post_text" arguments are concatenated with the usage message with no line breaks, so supply this if you need them.

AUTHORS

? Hans Dieter Pearcey <hdp@cpan.org>

? Ricardo Signes <rjbs@cpan.org>

COPYRIGHT AND LICENSE

This software is copyright (c) 2005 by Hans Dieter Pearcey.

This is free software; you can redistribute it and/or modify it under the same terms as the Perl 5 programming language system itself.

perl v5.28.1

2019-07-06 Getopt::Long::Descriptive::Usage(3pm)