



Rocky Enterprise Linux 9.2 Manual Pages on command 'HTTP::Cookies.3pm'

C:\>man HTTP::Cookies.3pm

HTTP::Cookies(3pm) User Contributed Perl Documentation HTTP::Cookies(3pm)

NAME

HTTP::Cookies - HTTP cookie jars

VERSION

version 6.08

SYNOPSIS

```
use HTTP::Cookies;

$cookie_jar = HTTP::Cookies->new(
    file => "$ENV{'HOME'}/lwp_cookies.dat",
    autosave => 1,
);
```

```
use LWP;

my $browser = LWP::UserAgent->new;
$browser->cookie_jar($cookie_jar);
```

Or for an empty and temporary cookie jar:

```
use LWP;
```

```
my $browser = LWP::UserAgent->new;  
$browser->cookie_jar( {} );
```

DESCRIPTION

This class is for objects that represent a "cookie jar" -- that is, a database of all the HTTP cookies that a given LWP::UserAgent object knows about.

Cookies are a general mechanism which server side connections can use to both store and retrieve information on the client side of the connection. For more information about cookies refer to Cookie Spec http://curl.haxx.se/rfc/cookie_spec.html and Cookie Central <http://www.cookiecentral.com>. This module also implements the new style cookies described in RFC 2965 <https://tools.ietf.org/html/rfc2965>. The two variants of cookies are supposed to be able to coexist happily.

Instances of the class HTTP::Cookies are able to store a collection of Set-Cookie2: and Set-Cookie: headers and are able to use this information to initialize Cookie-headers in HTTP::Request objects. The state of a HTTP::Cookies object can be saved in and restored from files.

LIMITATIONS

This module does not support Public Suffix <https://publicsuffix.org/> encouraged by a more recent standard, RFC 6265 <https://tools.ietf.org/html/rfc6265>.

This module's shortcomings mean that a malicious Web site can set cookies to track your user agent across all sites under a top level domain. See `t/publicsuffix.t` in this module's distribution for details.

HTTP::CookieJar::LWP supports Public Suffix, but only provides a limited subset of this module's functionality and does not support standards older than RFC 6265.

METHODS

The following methods are provided:

`$cookie_jar = HTTP::Cookies->new`

The constructor takes hash style parameters. The following parameters are recognized:

`file:` name of the file to restore cookies from and save cookies to
`autosave:` save during destruction (bool)
`ignore_discard:` save even cookies that are requested to be discarded (bool)
`hide_cookie2:` do not add Cookie2 header to requests

Future parameters might include (not yet implemented):

`max_cookies` 300
`max_cookies_per_domain` 20
`max_cookie_size` 4096

`no_cookies` list of domain names that we never return cookies to

`$cookie_jar->get_cookies($url_or_domain)`

`$cookie_jar->get_cookies($url_or_domain, $cookie_key,...)`

Returns a hash of the cookies that applies to the given URL. If a domainname is given as argument, then a prefix of "https://" is assumed.

If one or more `$cookie_key` parameters are provided return the given values, or "undef" if the cookie isn't available.

`$cookie_jar->add_cookie_header($request)`

The `add_cookie_header()` method will set the appropriate `Cookie:-header` for the `HTTP::Request` object given as argument. The `$request` must have a valid url attribute before this method is called.

`$cookie_jar->extract_cookies($response)`

The `extract_cookies()` method will look for `Set-Cookie:` and `Set-Cookie2:` headers

in the HTTP::Response object passed as argument. Any of these headers that are found are used to update the state of the \$cookie_jar.

```
$cookie_jar->set_cookie( $version, $key, $val, $path, $domain, $port, $path_spec,  
$secure, $maxage, $discard, \%rest )
```

The set_cookie() method updates the state of the \$cookie_jar. The \$key, \$val, \$domain, \$port and \$path arguments are strings. The \$path_spec, \$secure, \$discard arguments are boolean values. The \$maxage value is a number indicating number of seconds that this cookie will live. A value of \$maxage <= 0 will delete this cookie. The \$version argument sets the version of the cookie; the default value is 0 (original Netscape spec). Setting \$version to another value indicates the RFC to which the cookie conforms (e.g. version 1 for RFC 2109). %rest defines various other attributes like "Comment" and "CommentURL".

```
$cookie_jar->save
```

```
$cookie_jar->save( $file )
```

```
$cookie_jar->save( file => $file, ignore_discard => $ignore_discard )
```

This method file saves the state of the \$cookie_jar to a file. The state can then be restored later using the load() method. If a filename is not specified we will use the name specified during construction. If the \$ignore_discard value is true (or not specified, but attribute ignore_discard was set at cookie jar construction), then we will even save cookies that are marked to be discarded.

The default is to save a sequence of "Set-Cookie3" lines. "Set-Cookie3" is a proprietary LWP format, not known to be compatible with any browser. The HTTP::Cookies::Netscape sub-class can be used to save in a format compatible with Netscape.

```
$cookie_jar->load
```

```
$cookie_jar->load( $file )
```

This method reads the cookies from the file and adds them to the \$cookie_jar.

The file must be in the format written by the save() method.

`$cookie_jar->revert`

This method empties the `$cookie_jar` and re-loads the `$cookie_jar` from the last save file.

`$cookie_jar->clear`

`$cookie_jar->clear($domain)`

`$cookie_jar->clear($domain, $path)`

`$cookie_jar->clear($domain, $path, $key)`

Invoking this method without arguments will empty the whole `$cookie_jar`. If given a single argument only cookies belonging to that domain will be removed. If given two arguments, cookies belonging to the specified path within that domain are removed. If given three arguments, then the cookie with the specified key, path and domain is removed.

`$cookie_jar->clear_temporary_cookies`

Discard all temporary cookies. Scans for all cookies in the jar with either no expire field or a true "discard" flag. To be called when the user agent shuts down according to RFC 2965.

`$cookie_jar->scan(\&callback)`

The argument is a subroutine that will be invoked for each cookie stored in the `$cookie_jar`. The subroutine will be invoked with the following arguments:

- 0 version
- 1 key
- 2 val
- 3 path
- 4 domain
- 5 port
- 6 path_spec
- 7 secure
- 8 expires

9 discard

10 hash

```
$cookie_jar->as_string
```

```
$cookie_jar->as_string( $skip_discardables )
```

The `as_string()` method will return the state of the `$cookie_jar` represented as a sequence of "Set-Cookie3" header lines separated by "\n". If `$skip_discardables` is TRUE, it will not return lines for cookies with the Discard attribute.

SEE ALSO

[HTTP::Cookies::Netscape](#), [HTTP::Cookies::Microsoft](#)

AUTHOR

Gisle Aas <gisle@activestate.com>

COPYRIGHT AND LICENSE

This software is copyright (c) 2002-2019 by Gisle Aas.

This is free software; you can redistribute it and/or modify it under the same terms as the Perl 5 programming language system itself.

perl v5.30.0

2019-12-06

[HTTP::Cookies\(3pm\)](#)