



Rocky Enterprise Linux 9.2 Manual Pages on command 'Lintian::Processable::Changelog.3'

C:\>man Lintian::Processable::Changelog.3

Lintian::Processable::Changelog(3)Debian Package CheckerLintian::Processable::Changelog(3)

NAME

Lintian::Processable::Changelog - access to collected changelog data

SYNOPSIS

use Lintian::Processable;

my \$processable = Lintian::Processable::Binary->new;

DESCRIPTION

Lintian::Processable::Changelog provides an interface to changelog data.

INSTANCE METHODS

changelog

For binary:

Returns the changelog of the binary package as a Parse::DebianChangelog object, or undef if the changelog doesn't exist. The changelog-file collection script must have been run to create the changelog file, which this method expects to find in changelog.

Needs-Info requirements for using changelog: changelog-file

For source:

Returns the changelog of the source package as a `Parse::DebianChangelog` object, or "undef" if the changelog cannot be resolved safely.

`saved_changelog`

Returns the cached changelog information.

AUTHOR

Originally written by Felix Lechner <felix.lechner@lease-up.com> for Lintian.

SEE ALSO

`lintian(1)`

Lintian v2.62.0ubuntu2.2

2022-11-09

Lintian::Processable::Changelog(3)