



Rocky Enterprise Linux 9.2 Manual Pages on command 'Log::Any::Test.3pm'

C:\>man Log::Any::Test.3pm

Log::Any::Test(3pm) User Contributed Perl Documentation Log::Any::Test(3pm)

NAME

Log::Any::Test - Test what you're logging with Log::Any

VERSION

version 1.708

SYNOPSIS

```
use Test::More;

use Log::Any::Test; # should appear before 'use Log::Any!'

use Log::Any qw($log);

# ...

# call something that logs using Log::Any

# ...

# now test to make sure you logged the right things

$log->contains_ok(qr/good log message/, "good message was logged");

$log->does_not_contain_ok(qr/unexpected log message/, "unexpected message was not logged");

$log->empty_ok("no more logs");

# or

my $msgs = $log->msgs;

cmp_deeply($msgs, [{message => 'msg1', level => 'debug'}, ...]);
```

DESCRIPTION

"Log::Any::Test" is a simple module that allows you to test what has been logged with Log::Any. Most of its API and implementation have been taken from

Log::Any::Dispatch.

Using "Log::Any::Test" signals "Log::Any" to send all subsequent log messages to a single global in-memory buffer and to make the log proxy provide a number of testing functions. To use it, load "Log::Any::Test" before anything that loads "Log::Any". To actually use the test methods, you need to load "Log::Any" and get a log object from it, as shown in the "SYNOPSIS".

METHODS

The test_name is optional in the *_ok methods; a reasonable default will be provided.

msgs ()

Returns the current contents of the global log buffer as an array reference, where each element is a hash containing a category, level, and message key.

e.g.

```
{
  category => 'Foo',
  level => 'error',
  message => 'this is an error'
},
{
  category => 'Bar::Baz',
  level => 'debug',
  message => 'this is a debug'
}
```

contains_ok (\$regex[, \$test_name])

Tests that a message in the log buffer matches \$regex. On success, the message is removed from the log buffer (but any other matches are left untouched).

does_not_contain_ok (\$regex[, \$test_name])

Tests that no message in the log buffer matches \$regex.

category_contains_ok (\$category, \$regex[, \$test_name])

Tests that a message in the log buffer from a specific category matches \$regex.

On success, the message is removed from the log buffer (but any other matches are left untouched).

category_does_not_contain_ok (\$category, \$regex[, \$test_name])

Tests that no message from a specific category in the log buffer matches \$regex.

`empty_ok ([$test_name])`

Tests that there is no log buffer left. On failure, the log buffer is cleared to limit further cascading failures.

`contains_only_ok ($regex[, $test_name])`

Tests that there is a single message in the log buffer and it matches \$regex.

On success, the message is removed.

`clear ()`

Clears the log buffer.

SEE ALSO

`Log::Any`, `Test::Log::Dispatch`

AUTHORS

? Jonathan Swartz <swartz@pobox.com>

? David Golden <dagolden@cpan.org>

? Doug Bell <preaction@cpan.org>

? Daniel Pittman <daniel@rimspace.net>

? Stephen Thirlwall <sdt@cpan.org>

COPYRIGHT AND LICENSE

This software is copyright (c) 2017 by Jonathan Swartz, David Golden, and Doug Bell.

This is free software; you can redistribute it and/or modify it under the same terms as the Perl 5 programming language system itself.

perl v5.30.0

2020-01-24

Log::Any::Test(3pm)