



Rocky Enterprise Linux 9.2 Manual Pages on command 'Test::Lintian::Run.3'

C:\>man Test::Lintian::Run.3

Test::Lintian::Run(3) Debian Package Checker Test::Lintian::Run(3)

NAME

Test::Lintian::Run -- generic runner for all suites

SYNOPSIS

```
use Test::Lintian::Run qw(runner);
```

```
my $runpath = "test working directory";
```

```
runner($runpath);
```

DESCRIPTION

Generic test runner for all Lintian test suites

FUNCTIONS

logged_runner(RUN_PATH)

Starts the generic test runner for the test located in RUN_PATH and logs the output.

runner(RUN_PATH)

This routine provides the basic structure for all runners and runs the test

located in RUN_PATH.

check_literal

check_tags

check_result(DESC, EXPECTED, ACTUAL)

This routine checks if the EXPECTED tags match the calibrated ACTUAL for the test described by DESC. For some additional checks, also need the ORIGINAL tags before calibration. Returns a list of errors, if there are any.

AUTHOR

Originally written by Felix Lechner <felix.lechner@lease-up.com> for Lintian.

SEE ALSO

lintian(1)

Lintian v2.62.0ubuntu2.2

2022-11-09

Test::Lintian::Run(3)